



SLOVENSKI STANDARD
SIST ETS 300 609-2 E1:2003

01-december-2003

8][JhUb]WY] b] hYY_ca i b] UWg] g]ghYa fUhU&L3E GdYW]UcdfYa Yg]ghYa U
VUnb] dchgHf6 GGLE&"XY. 'G][bU]nUWg]j]X]]f] GA "%&8! Ł

Digital cellular telecommunications system (Phase 2) (GSM); Base Station System (BSS) equipment specification; Part 2: Signalling aspects (GSM 11.23)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: SIST ETS 300 609-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/2639fb6b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--


SIST ETS 300 609-2 E1:2003

en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST ETS 300 609-2 E1:2003

<https://standards.iteh.ai/catalog/standards/sist/2639fb3b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>



EUROPEAN TELECOMMUNICATION STANDARD

ETS 300 609-2

June 1997

Source: ETSI TC-SMG

Reference: DE/SMG-081123P

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



**Digital cellular telecommunications system (Phase 2);
Base Station System (BSS) equipment specification;
Part 2: Signalling aspects
(GSM 11.23)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

Page 2

ETS 300 609-2 (GSM 11.23 version 4.6.1): June 1997

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 609-2 E1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/2639fb3b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

Contents

Foreword	11
1 Scope	13
2 Normative references	13
3 Abbreviations.....	15
4 Guide to this ETS	15
4.1 Layer 2 signalling	15
4.2 Layer 3 signalling	15
4.3 Core Specifications.....	15
5 Testing of Layer 2 (LAPDm) functions	16
5.1 Scope.....	16
5.2 Introduction	16
5.3 Layer 2 test frames	16
5.4 General requirements	17
5.5 Establishment of the dedicated physical resource.....	18
5.5.1 MS-originated	18
5.5.1.1 Contention resolution on FACCH or SDCCH	18
5.5.1.2 No Contention resolution on FACCH or SDCCH.....	19
5.5.1.3 No Contention resolution on FACCH (No immediate Assign procedures).....	20
5.5.1.4 No contention resolution on SACCH (Short Message Service).....	21
5.5.2 BSS-originated	21
https://standards.itu.int/catalog/standard/19833-6396-2246-4323-879d-19833-207190/ist-ets-300-609-2-e1-2003	21
5.6 Release of the dedicated physical resource.....	22
5.6.1 MS-originated	22
5.6.2 BSS-originated	22
5.7 LAPDm idle state	22
5.8 Signalling connections (SAPI = 0).....	24
5.8.1 Link establishment.....	24
5.8.1.1 Normal initialization (contention resolution)	24
5.8.1.2 Initialization failure (contention resolution).....	24
5.8.1.2.1 Repeated SABM (loss of UA frame)	24
5.8.1.2.2 SABMs with different information fields.....	25
5.8.1.3 Normal initialization (no contention resolution)	27
5.8.2 Normal information transfer.....	28
5.8.2.1 Sequence counting and I frame acknowledgements.....	28
5.8.2.2 Receipt of an I frame in the timer recovery state.....	31
5.8.2.3 Segmentation and Concatenation	32
5.8.3 Normal Layer 2 release by MS	34
5.8.4 Normal Layer 2 release by BSS	34
5.8.5 Abnormal release	34
5.8.6 Frame loss.....	36
5.8.6.1 I Frame loss (BSS to BSSTE)	36
5.8.6.2 RR Response frame loss (BSSTE to BSS)	36
5.8.6.3 RR response frame loss (BSS to BSSTE)	36
5.8.6.4 UA frame loss (BSS to MS)	37
5.8.7 Reception of REJ frames	38
5.8.7.1 Data link layer not in the timer recovery state.....	38
5.8.7.2 Data link layer in the timer recovery state, reception of a REJ response frame.....	39

	5.8.7.3	Data link layer in the timer recovery state, reception of a REJ command frame	40
5.8.8	Frame transmission with incorrect C/R values	42	
	5.8.8.1	I frame with C bit set to one	42
	5.8.8.2	SABM frame with C bit set to one	43
5.8.9	Link failure	44	
5.8.10	Errors in the Control Field.....	45	
	5.8.10.1	N(S) sequence error	45
	5.8.10.2	N(R) sequence error	47
	5.8.10.3	Improper F bit.....	48
5.8.11	Receipt of invalid frames	50	
5.9	Short Message Services (SMS) (SAPI = 3)	54	
5.9.1	MS-originated link establishment.....	54	
5.9.2	BSS-originated link establishment.....	54	
	5.9.2.1	Normal initialization (no contention resolution)	54
	5.9.2.2	Initialization failure (no contention resolution)	55
	5.9.2.3	Initialization denial (no contention resolution)	56
	5.9.2.4	Total initialization failure (no contention resolution)	57
5.9.3	Normal information transfer	58	
5.9.4	Normal layer 2 release by MS.....	58	
5.9.5	Normal Layer 2 release by BSS.....	59	
5.9.6	Abnormal release.....	59	
5.9.7	Frame loss	61	
5.9.8	Reception of REJ frames.....	61	
	5.9.8.1	Data link layer not in the timer recovery state	61
	5.9.8.2	Data link layer in the timer recovery state, reception of a REJ response frame	62
	5.9.8.3	Data link layer in the timer recovery state, reception of a REJ command frame	63
5.9.9	Frame transmission with incorrect C/R values	65	
	5.9.9.1	I frame with C bit set to one	65
	5.9.9.2	SABM frame with C bit set to one	66
5.9.10	Link failure	67	
5.9.11	Errors in the Control Field.....	68	
5.9.12	Receipt of invalid frames	69	
5.10	Layer 3 functions	69	
5.11	Short Message Service Cell Broadcast (SMSCB)	69	
6	Internal ABIS interfacing	70	
6.1	Layer 1	70	
6.2	Signalling transport mechanism, layer 2	70	
	6.2.1	Base Station Controller	70
	6.2.1.1	Successful TEI allocation - fixed TEI	70
	6.2.1.2	Denied TEI allocation - fixed TEI	71
	6.2.1.3	Successful TEI allocation - additional TEI.....	72
	6.2.1.4	Denied TEI allocation - additional TEI.....	74
	6.2.2	Base Transceiver Station.....	75
	6.2.2.1	Successful TEI allocation - fixed TEI	76
	6.2.2.2	Denied TEI allocation - fixed TEI	77
	6.2.2.3	Successful TEI allocation - additional TEI.....	78
	6.2.2.4	Denied TEI allocation - additional TEI.....	79
6.3	LAYER 3.....	81	
7	Interfacing with the mobile services switching centre	82	
7.1	Physical interface layer 1.....	82	
7.2	Signalling transport mechanism, layer 2	82	
7.3	Layer 3 protocol.....	82	
8	Base station system network aspects	83	
8.1	Base station system network functions	83	
	8.1.1	General	83
	8.1.2	Testing of the DTAP	84
	8.1.2.1	Messages from MSC to MS	84

8.1.3.2	Messages from MS to MSC.....	85
8.1.3	Testing of the BSSMAP and RR functions	85
8.1.3.1	System information.....	87
	8.1.3.1.1 Dedicated resource set up.....	87
	8.1.3.1.2 No dedicated resource established	88
8.1.3.2	Service requests in SABM frames.....	89
	8.1.3.2.1 Allowed messages.....	89
	8.1.3.2.2 Not allowed messages.....	90
8.1.3.3	Random access by MS and immediate assignment	91
	8.1.3.3.1 Normal Case - SDCCH.....	91
	8.1.3.3.2 Normal Case - TCH.....	92
	8.1.3.3.3 T3101 expiry case.....	94
	8.1.3.3.4 No radio resources available	95
	8.1.3.3.5 Immediate assignment extended.....	96
8.1.3.4	Paging.....	97
	8.1.3.4.1 Normal case.....	97
	8.1.3.4.2 Paging reorganization	98
	8.1.3.4.3 Channel needed.....	99
8.1.3.5	Measurement reporting	100
8.1.3.6	Assignment.....	100
	8.1.3.6.1 Normal case.....	100
	8.1.3.6.2 T10 expiry	101
	8.1.3.6.3 Terrestrial resources already allocated	103
	8.1.3.6.4 Reverse to old channel	104
8.1.3.7	External handover as seen from the old BSS.....	105
	8.1.3.7.1 Normal case.....	105
	8.1.3.7.2 T8 expiry	106
	8.1.3.7.3 Reversion to old channel	108
8.1.3.8	External handover as seen from the new BSS.....	109
	8.1.3.8.1 Non-synchronized network	109
	8.1.3.8.1.1 Normal Case	109
	8.1.3.8.1.2 No LAPDm connection	111
	8.1.3.8.1.3 Wrong Handover Reference	113
	8.1.3.8.1.4 Wrong physical channel	114
	8.1.3.8.1.5 No radio resources available	115
	8.1.3.8.1.6 Clear Command from the MSC	116
	8.1.3.8.1.7 No terrestrial resource available	117
	8.1.3.8.1.8 Handover - CLM2.....	118
	8.1.3.8.1.9 Handover - CLM2 and CLM3	119
	8.1.3.8.2 Synchronized network.....	119
8.1.3.9	Internal handover.....	120
	8.1.3.9.1 Internal inter-cell handover	120
	8.1.3.9.1.1 Normal case.....	120
	8.1.3.9.1.2 No LAPDm connection	122
	8.1.3.9.2 Internal intra-cell handover	123
	8.1.3.9.2.1 Intra-cell handover by the assignment procedure.....	123
	8.1.3.9.2.1.1 Normal case.....	123
	8.1.3.9.2.1.2 T10 expiry	125
	8.1.3.9.2.1.3 Revert to old channel	126
	8.1.3.9.2.1.4 CLM2	127
	8.1.3.9.2.2 Intra-cell handover by the handover procedure.....	128
	8.1.3.9.2.2.1 Normal case.....	128
	8.1.3.9.2.2.2 T8 expiry	129
	8.1.3.9.2.2.3 Reverse to old channel	130
8.1.3.10	Frequency redefinition	131
8.1.3.11	Transmission mode change	132
8.1.3.12	Ciphering mode setting.....	133
	8.1.3.12.1 Cipher Mode Complete	133
	8.1.3.12.2 DTAP message.....	135
	8.1.3.12.3 IMEISV request without starting encryption	136

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 609-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/2639fb9b-2206-4723-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

	8.1.3.12.4	IMEISV request with invalid answer ...	137
	8.1.3.12.5	IMEISV not requested with invalid answer.....	138
8.1.3.13		Additional assignment.....	139
8.1.3.14		Partial release	139
8.1.3.15		Classmark.....	140
	8.1.3.15.1	Classmark change	140
	8.1.3.15.2	Classmark Interrogation	140
8.1.3.16		Channel release.....	141
	8.1.3.16.1	Normal case	142
	8.1.3.16.2	T3109 expiry.....	143
	8.1.3.16.3	Radio resources out of service.....	144
8.1.3.17		Radio link failure.....	145
8.1.3.18		Blocking.....	145
	8.1.3.18.1	Single circuit blocking.....	145
	8.1.3.18.1.1	Normal Case	145
	8.1.3.18.1.2	Blocking a terrestrial circuit already used on a call	147
	8.1.3.18.1.3	No response to the Unblocking message.....	148
	8.1.3.18.1.4	Unblocking, Normal case	149
	8.1.3.18.1.5	MSC Reset during Blocking procedure	150
	8.1.3.18.2	Circuit group blocking.....	151
	8.1.3.18.2.1	Circuit group block - Normal case.....	151
	8.1.3.18.2.2	Circuit group unblock - Normal case ..	152
8.1.3.19		Resource indication.....	153
	8.1.3.19.1	Spontaneous indication	153
	8.1.3.19.2	One single indication.....	154
	8.1.3.19.3	Periodic indication	155
	8.1.3.19.4	No indication.....	156
	8.1.3.19.5	Extended resource indicator	157
8.1.3.20		Reset.....	158
	8.1.3.20.1	Global reset	158
	8.1.3.20.1.1	Global reset at the BSS.....	158
	8.1.3.20.1.2	Global reset at the MSC	160
	8.1.3.20.2	Reset circuit	161
	8.1.3.20.2.1	Reset circuit at the BSS	161
	8.1.3.20.2.2	Reset circuit at the MSC	162
8.1.3.21		Handover candidate enquiry	164
	8.1.3.21.1	Handover candidate enquiry for 3 MSs	164
	8.1.3.21.2	Handover candidate enquiry for 1 MS	165
	8.1.3.21.3	Repetition of the Handover candidate enquiry message	166
8.1.3.22		Trace invocation.....	167
	8.1.3.22.1	Trace invoked by the MSC	167
	8.1.3.22.2	Trace invoked by the BSS.....	167
8.1.3.23		Flow control.....	168
	8.1.3.23.1	Overload in the MSC	168
	8.1.3.23.2	Overload in the BSS	168
8.1.3.24		Data link control for SAPI not equal to 0	168
	8.1.3.24.1	MSC-originated transaction.....	168
	8.1.3.24.1.1	Normal case	168
	8.1.3.24.1.2	MS failure	169
	8.1.3.24.1.3	SAPI 3 transactions rejected in the OMC	170
	8.1.3.24.2.1	Normal case	171
8.1.3.25		Queuing indication	172
	8.1.3.25.1	Assignment case.....	173
	8.1.3.25.2	Handover case	174
8.1.3.26		Short Message Service Cell Broadcast (SMSCB)	175
8.1.3.27		Unequipped circuit	175
	8.1.3.27.1	Normal case	175
	8.1.3.27.2	Assignment request message.....	176

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 609-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/263910pb-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

8.1.3.27.3	Handover request message.....	177
8.1.3.27.4	Blocking acknowledge message.....	178
8.1.3.27.5	Unblocking acknowledge message	179
8.1.3.27.6	Reset circuit message	180
8.1.3.27.7	Circuit group blocking acknowledge message	180
8.1.3.27.8	Circuit group unblocking acknowledge message	181
8.1.3.27.9	Unequipped circuit message	182
8.1.3.28	Confusion.....	183
8.1.3.28.1	Reserved element used.....	183
8.1.3.28.2	Zero length value	184
8.1.3.28.3	Inconsistent length value	184
9	Base station controller network aspects.....	186
9.1	Base station controller network functions	186
9.1.1	General.....	186
9.1.2	Transparent messages	187
9.1.3	Non-transparent messages	187
9.1.3.1	Link establishment indication.....	188
9.1.3.2	Link establishment request.....	190
9.1.3.3	Link release indication	191
9.1.3.4	Link release request	192
9.1.3.5	Transmission of transparent L3-message in acknowledged mode.....	194
9.1.3.6	Reception of transparent L3-message in acknowledged mode.....	194
9.1.3.7	Transmission of transparent L3-message in unacknowledged mode.....	195
9.1.3.8	Reception of transparent L3-message in unacknowledged mode.....	195
9.1.3.9	Link error indication	196
9.1.3.10	Channel activation	196
9.1.3.11	Channel mode modify.....	198
9.1.3.12	Handover detection.....	200
9.1.3.13	Encryption.....	201
	9.1.3.13.1 Start of encryption.....	201
	9.1.3.13.2 Stop of encryption	202
	9.1.3.13.3 Failure case	203
9.1.3.14	Measurement reporting	205
	9.1.3.14.1 Basic measurement reporting.....	205
	9.1.3.14.2 Pre-processed measurement reporting (optional).....	205
	9.1.3.14.3 Pre-processing configuration (optional).....	205
9.1.3.15	Deactivate SACCH	206
9.1.3.16	Radio channel release	207
9.1.3.17	MS power control (optional).....	208
9.1.3.18	Transmission power control (optional).....	209
9.1.3.19	Connection failure.....	210
9.1.3.20	Physical context request (optional).....	211
9.1.3.21	SACCH Info modify.....	212
9.1.3.22	Channel request by MS	213
9.1.3.23	Paging.....	213
9.1.3.24	Delete indication	214
9.1.3.25	CCCH load indication	214
9.1.3.26	Broadcast information modify	214
9.1.3.27	Immediate assignment	215
9.1.3.28	Short Message Service Cell Broadcast (SMSCB).....	215
9.1.3.29	Radio resource indication	215
9.1.3.30	SACCH filling information modify	217
9.1.3.31	Flow control	218
9.1.3.32	Error reporting.....	218

10	Base transceiver station network aspects	219
10.1	Base transceiver station network aspects functions	219
10.1.1	General	219
10.1.2	Transparent messages.....	219
10.1.3	Non-transparent messages	219
10.1.3.1	Link establishment indication	220
10.1.3.1.1	SDCCH, Contention Resolution	221
10.1.3.1.2	FACCH, Contention Resolution, Channel Mode modify, Sapi3	222
10.1.3.1.3	No Contention Resolution, Normal Case	223
10.1.3.2	Link establishment request	224
10.1.3.2.1	Normal Case	224
10.1.3.2.2	T200 x (N200 + 1) times expiry	225
10.1.3.3	Link release indication.....	226
10.1.3.4	Link release request.....	227
10.1.3.4.1	Normal Case	227
10.1.3.4.2	T200 x (N200 + 1) times expiry	228
10.1.3.5	Transmission of transparent L3-message in acknowledged mode	230
10.1.3.6	Reception of transparent L3-message in acknowledged mode	231
10.1.3.7	Transmission of transparent L3-message in unacknowledged mode	232
10.1.3.8	Reception of transparent L3-message in unacknowledged mode	232
10.1.3.9	Link error indication.....	232
10.1.3.10	Channel activation.....	232
10.1.3.11	Channel mode modify	233
10.1.3.11.1	Normal Case	234
10.1.3.11.2	Abnormal Case	234
10.1.3.12	Handover detection	235
10.1.3.12.1	Non-synchronized case.....	235
10.1.3.12.2	Synchronized case	237
10.1.3.13	Start of encryption..... https://standards.iteh.ai/catalog/standards/sist/26391000-2206-4323-879d-19f43b301790/sist-ets-300-609-2-e1-2003	238
10.1.3.13.1	Ciphering mode complete	238
10.1.3.13.2	DTAP message	240
10.1.3.13.3	Start of encryption with unavailable algorithm	241
10.1.3.13.4	Stop ciphering	242
10.1.3.13.5	Failure case.....	243
10.1.3.14	Measurement reporting	244
10.1.3.14.1	Basic measurement reporting	244
10.1.3.14.2	Pre-processed measurement reporting (optional)	245
10.1.3.14.3	Pre-processing configuration (optional)	245
10.1.3.15	Deactivate SACCH.....	246
10.1.3.16	Radio channel release	246
10.1.3.17	MS power control	247
10.1.3.18	Transmission power control (optional)	248
10.1.3.19	Connection failure	249
10.1.3.20	Physical context request (optional)	250
10.1.3.21	Channel request by MS.....	250
10.1.3.22	Paging	251
10.1.3.23	Delete indication.....	253
10.1.3.24	CCCH load indication.....	253
10.1.3.25	Broadcast information modify	253
10.1.3.26	Immediate assignment.....	255
10.1.3.26.1	Normal case	255
10.1.3.26.2	Extended immediate assignment procedure	256

10.1.3.26.3	Reject immediate assignment procedure.....	257
10.1.3.27	Short Message Service Cell Broadcast (SMSCB).....	258
10.1.3.27.1	SMS broadcast request	258
10.1.3.27.2	SMS broadcast command	259
10.1.3.28	Radio resource indication	259
10.1.3.29	SACCH filling information modify	260
10.1.3.30	Flow control	261
10.1.3.31	Error reporting.....	262
11	GSM Phases interworking.....	263
11.1	Interworking between phase 1 mobile and phase 2 network.....	263
11.2	Interworking between phase 2 mobile and phase 1 network.....	263
11.2.1	Scope	263
11.2.2	References	263
11.2.3	Radio Interface	263
11.2.3.1	Information Elements.....	263
11.2.3.1.1	Mobile Classmark 1	263
11.2.3.1.1.1	Revision Level.....	263
11.2.3.1.1.1.1	Location updating - revision level 00...	264
11.2.3.1.1.1.2	Location updating - revision level 01...	264
11.2.3.1.1.1.3	Location updating - revision level 10...	265
11.2.3.1.1.1.4	Location updating - revision level 11...	266
11.2.3.1.1.2	Encryption algorithm A5/1	267
11.2.3.1.1.2.1	Location updating - encryption algorithm A5/1	267
11.2.3.1.2	Mobile classmark 2	268
11.2.3.1.2.1	Revision level	268
11.2.3.1.2.1.1	CM Service - revision level 00	268
11.2.3.1.2.1.2	CM Service - revision level 01	269
11.2.3.1.2.1.3	CM Service - revision level 10	269
11.2.3.1.2.1.4	CM Service - revision level 11	270
11.2.3.1.2.2	Encryption algorithm A5/1	271
11.2.3.1.2.2.1	CM Service - encryption algorithm A5/1.....	271
11.2.3.1.2.2.2	CM Service - encryption algorithm A5/1.....	271
11.2.3.1.2.3	Frequency capability	272
11.2.3.1.2.3.1	CM Service	272
11.2.3.1.2.4	SS Screening Indicator	273
11.2.3.1.2.4.1	CM Service - SS Screening Indicator 01	273
11.2.3.1.2.4.2	CM Service - SS Screening Indicator 10	274
11.2.3.1.2.4.3	CM Service - SS Screening Indicator 11	275
11.2.3.1.2.5	PS Capability.....	275
11.2.3.1.2.5.1	CM Service - PS Capability.....	276
11.2.3.1.2.6	Encryption Algorithm A5/2, A5/3	276
11.2.3.1.2.6.1	CM Service - Encryption Algorithm A5/2.....	276
11.2.3.1.2.6.2	CM Service - Encryption Algorithm A5/3.....	277
11.2.3.1.2.6.3	CM Service - Encryption Algorithm A5/2, A5/3	278
11.2.3.1.3	Location Updating Type	279
11.2.3.1.3.1	Location Updating - Location - Updating Type.....	279
11.2.3.2	Radio Resource Procedures	280
11.2.3.2.1	Assignment Procedure	280
11.2.3.2.1.1	Assignment Failure - RR cause 09	280
11.2.3.2.1.2	Assignment Failure - RR cause 0A.....	281
11.2.3.2.2	Handover Procedure.....	282
11.2.3.2.2.1	Handover Failure - RR cause 09	282
11.2.3.2.2.2	Handover Failure - RR cause 0A.....	284

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 609-2 E1:2003](https://standards.iteh.ai/catalog/standards/sist-ets-300-609-2-e1-2003-19f43b307190-sist-ets-300-609-2-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist-ets-300-609-2-e1-2003-19f43b307190-sist-ets-300-609-2-e1-2003>

Page 10**ETS 300 609-2 (GSM 11.23 version 4.6.1): June 1997**

11.2.3.3	Transmission Mode Change	285
11.2.3.3.1	Channel Mode Modify	285
11.2.3.4	Messages.....	286
11.2.3.4.1	Classmark Change.....	286
11.2.3.4.1.1	Mobile Station Classmark 3	286
11.2.4	Abis-interface.....	287
11.2.5	A-interface	287
History.....		288

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 609-2 E1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/2639fb3b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS describes the signalling tests for the Base Station System (BSS) within the digital cellular telecommunications system (Phase 2). This ETS corresponds to GSM technical specification GSM 11.23 version 4.6.1.

Transposition dates	
Date of adoption:	23 May 1997
Date of latest announcement of this ETS (doa):	30 September 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 March 1998
Date of withdrawal of any conflicting National Standard (dow):	31 March 1998

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 609-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/2639fb3b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

Page 12

ETS 300 609-2 (GSM 11.23 version 4.6.1): June 1997

Blank page

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST ETS 300 609-2 E1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/2639fb3b-2206-4323-879d-19f43b307190/sist-ets-300-609-2-e1-2003>

1 Scope

This European Telecommunication Standard (ETS) contains the signalling aspects of the Base Station System for GSM. The set of signalling tests cover major areas of functionality on the air, Abis and A-interfaces, but is not designed to be a complete set of all the possible scenarios.

The tests were designed from the set of core specifications that exist for the GSM network and any changes that occur these specifications will be reflected in the test set documented within.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this specification only when incorporated in it by the amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] ETR 100 (GSM 01.04): "Digital cellular telecommunications system (Phase 2); Abbreviations and acronyms".
- [2] ETS 300 521 (GSM 03.01): "Digital cellular telecommunications system (Phase 2); Network functions".
- [3] ETS 300 555 (GSM 04.06): "Digital cellular telecommunications system (Phase 2); Mobile Station - Base Station System (MS - BSS) interface Data Link (DL) layer specification".
- [4] **iTel STANDARD PREVIEW
(standards.iteh.ai)**
ETS 300 557 (GSM 04.08): "Digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 specification".
<https://standards.iteh.ai/catalog/standards/sist-ets-300-609-2-e1-2003-19f43b307190/sist-ets-300-609-2-e1-2003>
- [5] ETS 300 560 (GSM 04.12): "Digital cellular telecommunications system (Phase 2); Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
[https://standards.iteh.ai/catalog/standards/sist-ets-300-609-2-e1-2003](https://standards.iteh.ai/catalog/standards/sist-ets-300-609-2-e1-2003-19f43b307190/sist-ets-300-609-2-e1-2003)
- [6] ETS 300 574 (GSM 05.02): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [7] ETS 300 577 (GSM 05.05): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] ETS 300 587-2 (GSM 08.02): "Digital cellular telecommunications system (Phase 2); Base Station System - Mobile-services Switching Centre (BSS - MSC) interface Interface principles".
- [9] ETS 300 589 (GSM 08.06): "Digital cellular telecommunications system (Phase 2); Signalling transport mechanism specification for the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [10] ETS 300 590 (GSM 08.08): "Digital cellular telecommunications system (Phase 2); Mobile-services Switching Centre - Base Station System (MSC - BSS) interface Layer 3 specification".
- [11] ETS 300 593 (GSM 08.52): "Digital cellular telecommunications system (Phase 2); Base Station Controller - Base Transceiver Station (BSC - BTS) interface Inerface principles".
- [12] ETS 300 595 (GSM 08.56): "Digital cellular telecommunications system (phase 2); Base Station Controller - Base Transceiver Station (BSC - BTS) interface Layer 2 specification".