

Draft **ETSI EN 301 908-5** V4.1.1 (2009-04)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Base Stations (BS), Repeaters and User Equipment (UE) for
IMT-2000 Third-Generation cellular networks;
Part 5: Harmonized EN for IMT-2000, CDMA Multi-Carrier
(cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile
Broadband (UMB) (BS) covering the essential requirements of
article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e51d8b58-1e26-4f39-8898-8cea296070a3/etsi-en-301-908-5-v4.2.1-2010-03>



Reference

REN/ERM-TFES-005-5

Keywords

3G, 3GPP2, cdma2000, cellular, digital,
IMT-2000, mobile, radio, regulation, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	18
3.3 Abbreviations	22
4 Technical requirements specifications	23
4.1 Environmental profile.....	23
4.2 Conformance requirements	23
4.2.1 Introduction.....	23
4.2.2 Transmitter conducted spurious emissions	23
4.2.2.1 Definition	23
4.2.2.2 Limits	24
4.2.2.3 Conformance.....	26
4.2.3 Maximum output power.....	26
4.2.3.1 Definition	26
4.2.3.2 Limits	26
4.2.3.2.1 Base stations operating in Type 1 cdma2000 systems.....	26
4.2.3.2.2 Base stations operating in Type 2 cdma2000 systems.....	26
4.2.3.3 Conformance	27
4.2.4 Inter-base station transmitter intermodulation	27
4.2.4.1 Definition	27
4.2.4.2 Limits	27
4.2.4.3 Conformance.....	27
4.2.5 Receiver conducted spurious emissions.....	28
4.2.5.1 Definition	28
4.2.5.2 Limits	28
4.2.5.3 Conformance.....	28
4.2.6 Receiver blocking characteristics	28
4.2.6.1 Definition	28
4.2.6.2 Limits	28
4.2.6.2.1 Base stations operating in Type 1 cdma2000 systems.....	28
4.2.6.2.2 Base stations operating in Type 2 cdma2000 systems.....	28
4.2.6.3 Conformance.....	28
4.2.7 Intermodulation spurious response attenuation.....	29
4.2.7.1 Definition	29
4.2.7.2 Limits	29
4.2.7.2.1 Base stations operating in Type 1 cdma2000 systems.....	29
4.2.7.2.2 Base stations operating in Type 2 cdma2000 systems.....	29
4.2.7.3 Conformance.....	29
4.2.8 Adjacent channel selectivity	29
4.2.8.1 Definition	29
4.2.8.2 Limits	29
4.2.8.2.1 Base stations operating in Type 1 cdma2000 systems.....	29
4.2.8.2.2 Base stations operating in Type 2 cdma2000 systems.....	29
4.2.8.3 Conformance.....	29
5 Testing for compliance with technical requirements.....	30
5.1 Conditions for testing	30

5.1.1	Introduction.....	30
5.1.2	Standard equipment under test.....	30
5.1.2.1	Basic equipment.....	30
5.1.2.2	Ancillary equipment.....	30
5.2	Interpretation of the measurement results	30
5.3	Essential radio test suites.....	30
5.3.1	Transmitter conducted spurious emissions	31
5.3.1.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	31
5.3.1.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems.....	31
5.3.2	Maximum output power.....	32
5.3.2.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	32
5.3.2.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems.....	32
5.3.3	Inter-base station transmitter intermodulation	33
5.3.3.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	33
5.3.3.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems 2.....	33
5.3.4	Receiver conducted spurious emissions.....	34
5.3.4.1	Test procedure for base stations supporting operation in Type 1 or Type 2 cdma2000 systems	34
5.3.5	Receiver blocking characteristics	35
5.3.5.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	35
5.3.5.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems.....	36
5.3.6	Intermodulation spurious response attenuation.....	36
5.3.6.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	36
5.3.6.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems.....	37
5.3.7	Adjacent channel selectivity	37
5.3.7.1	Test procedure for base stations supporting operation in Type 1 cdma2000 systems.....	37
5.3.7.2	Test procedure for base stations supporting operation in Type 2 cdma2000 systems.....	38
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	39
Annex B (normative):	Base station Configurations	41
B.1	Receiver diversity.....	41
B.2	Duplexers	41
B.3	Power supply options	41
B.4	Ancillary RF amplifiers.....	42
B.5	BS using antenna arrays	42
B.5.1	Receiver tests.....	43
B.5.2	Transmitter tests	43
Annex C (informative):	Environmental profile and standard test conditions	44
C.1	Introduction	44
C.2	CDMA environmental requirements	44
C.2.1	Temperature and power supply voltage.....	44
C.2.1.1	Definition.....	44
C.2.1.2	Method of measurement	44
C.2.1.3	Minimum standard.....	45
C.2.2	High humidity	45
C.2.2.1	Definition.....	45
C.2.2.2	Method of measurement	45
C.2.2.3	Minimum standard.....	45
C.3	Standard test conditions.....	45
C.3.1	Standard environmental test conditions.....	45
C.3.2	Standard conditions for the primary power supply.....	46
C.3.2.1	General.....	46
C.3.2.2	Standard DC test voltage from accumulator batteries.....	46
C.3.2.3	Standard AC voltage and frequency	46

Annex D (informative):	The EN title in the official languages	47
Annex E (informative):	Bibliography	48
History		49

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e51d8b58-1e26-439-8898-8cea296070a3/etsi-en-301-908-5-v4.2.1-2010-03>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.2] are given in annex A.

The present document is part 5 of a multi-part deliverable covering the Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks, as identified below:

- Part 1: "Harmonized EN for IMT-2000, introduction and common requirements, covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 2: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 4: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 5: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";**
- Part 6: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD and E-UTRA TDD) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 7: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD and E-UTRA TDD) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";

- Part 10: "Harmonized EN for IMT-2000, FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 11: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 12: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 13: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 14: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 15: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (FDD Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 16: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 17: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment types:

- Base stations for IMT-2000 CDMA multi-carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.1.

Table 1.1: CDMA multi-carrier base station operating bands

Band Class (BC)	Direction of transmission	CDMA multi-carrier base station operating bands
6	Transmit	2 110 MHz to 2 170 MHz
	Receive	1 920 MHz to 1 980 MHz
8	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
9	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
13	Transmit	2 620 MHz to 2 690 MHz
	Receive	2 500 MHz to 2 570 MHz

The present document covers requirements for IMT-2000 CDMA multi-carrier (cdma2000) User Equipments and Evolved CDMA Multi-Carrier (UMB) User Equipment.

Base stations for IMT-2000 CDMA multi-carrier (cdma2000) may support:

- 1) operation in cdma2000 spread spectrum systems as defined in 3GPP2 C.S0002-D [2], referred to herein as operation in Type 1 cdma2000 systems; or
- 2) operation in cdma2000 High Rate Packet Data Systems as defined in TIA-856 [7], referred to herein in Type 2 cdma2000 systems.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "[...] radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ANSI/TIA-97-F-1 (June 2006): "Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Base Stations - Addendum 1".
- [2] 3GPP2 C.S0002-D V2.0 (September 2005): "Physical Layer Standard for cdma2000 Spread Spectrum Systems Revision D".

NOTE: Available at: http://www.3gpp2.org/Public_html/Specs/C.S0002-D_v2.0_051006.pdf.

- [3] ANSI/TIA-98-F-1 (June 2006): "Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations - Addendum".
- [4] TIA/EIA-126-D (June 2001): "Loopback Service Options Standard (LSO) for cdma Spread Spectrum Systems".
- [5] TIA-870-A (March 2005): "Test Data Service Option (TDSO) for cdma2000 Spread Spectrum Systems - Revision A".
- [6] TIA/EIA/IS-871 (April 2001): "Markov Service Option (MSO) for cdma2000 Spread Spectrum Systems".
- [7] TIA-856-B-1 (October 2007): "cdma2000 High Rate Packet Data Air Interface Specification".
- [8] 3GPP2 C.S0032-B V1.0 (May 2008): "Recommended Minimum Performance Standards for cdma2000 High Rate Packet Data Access Network".

NOTE: Available at: http://www.3gpp2.org/Public_html/specs/C.S0032-B_v1.0_080519.pdf.

- [9] 3GPP2 C.S0029-B V1.0 (March 2008): "Test Application Specification (TAS) for High Rate Packet Data Air Interface".

NOTE: Available at: http://www.3gpp2.org/Public_html/specs/C.S0029-B_v1.0_080409.pdf.

- [10] ETSI EN 301 908-1 (V4.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 1: Harmonized EN for IMT-2000, introduction and common requirements, covering the essential requirements of article 3.2 of the R&TTE Directive".
- [11] ETSI EN 301 908-17 (V4.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 17: Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

1X: mode of operation of a base station or access network using spreading rate 1

1XDO: mode of operation of a base station or access network using spreading rate 1 in data optimized systems

3X: mode of operation of a base station using spreading rate 3

access attempt: sequence of one or more access probe sequences on the access channel or enhanced access channel containing the same message

NOTE: See also access probe, access probe sequence, and enhanced access probe.

access channel: reverse CDMA channel used by mobile stations for communicating to the base station

NOTE: The access channel is used for short signalling message exchanges, such as call originations, responses to pages, and registrations. The access channel is a slotted random access channel.

access channel preamble: preamble of an access probe consisting of a sequence of all-zero frames that is sent at the 4 800 bit/s rate

access network: network equipment providing data connectivity between a packet switched data network (typically the Internet) and the access terminals in Type 2 cdma2000 systems

NOTE: Connectivity is typically provided at the link layer (PPP). As used in the present document it is synonymous with base station except that HRPD access network always use spreading rate 1.

access probe: one access channel transmission consisting of a preamble and a message

NOTE: The transmission is an integer number of frames in length, and transmits one access channel message. See also access probe sequence and access attempt.

access probe sequence: sequence of one or more access probes on the access channel or enhanced access channel

NOTE: The same access channel or enhanced access channel message is transmitted in every access probe of an access attempt. See also access probe, enhanced access probe, and access attempt.

access terminal: device providing data connectivity to a user in Type 2 cdma2000 systems

NOTE: An access terminal may be connected to a computing device such as a laptop personal computer or may be self-contained data device such as a personal digital assistant or may be a mobile station. Also referred to as HRPD access terminal using spreading rate 1 or UE operating in a Type 2 cdma2000 system.

active frame: frame that contains data and, therefore, is enabled in terms of traffic power

additional preamble: preamble sent after the last fractional preamble on the reverse pilot channel, prior to transmitting on the enhanced access channel or on the reverse common control channel

adjacent channel leakage ratio: ratio of the on-channel transmit power to the power measured in one of the adjacent channels

bad frame: frame classified with insufficient frame quality or for radio configuration 19 600 bit/s primary traffic only, with bit errors

NOTE: See also good frame.

band class: set of frequency channels and a numbering scheme for these channels

NOTE: Band classes are defined in ANSI/TIA-97 [1], clause 3.1, and ANSI/TIA-98 [3], clause 3.1.

base station: fixed station used for communicating with mobile stations

NOTE 1: Base stations for IMT-2000 CDMA multi-carrier (cdma2000) may support, operation in cdma2000 spread spectrum systems as defined in 3GPP2 C.S0002-D [2], referred to herein as operation in Type 1 cdma2000 system, or operation in cdma2000 High Rate Packet Data Systems as defined in TIA-856 [7], referred to herein as operation in Type 2 cdma2000 systems.

NOTE 2: Depending upon the context, the term base station may refer to a cell, a sector within a cell, an MSC, and access network or other part of the wireless system. See also MSC.

basic access mode: mode used on the enhanced access channel where a mobile station transmits an enhanced access channel preamble and enhanced access data in a method similar to that used on the access channel

broadcast control channel: code channel in a forward CDMA channel used for transmission of control information from a base station to a mobile station

candidate frequency: frequency for which the base station specifies a search set, when searching on other frequencies while performing mobile-assisted handoffs

CDMA channel: set of channels transmitted from the base station and the mobile stations on a given frequency

CDMA channel number: 11-bit number corresponding to the centre of the CDMA frequency assignment

CDMA frequency assignment: 1,23 MHz segment of spectrum

NOTE: For band class 0, the channel is centred on one of the 30 kHz channels.
For band classes 1, 4, 6, 7, 8, 9 and 10, the channel is centred on one of the 50 kHz channels.
For band classes 2, 3, 11 and 12, the channel is centred on one of the 25 kHz channels.
For band class 5, the channel is centred on one of the 20 kHz or 25 kHz channels.

CDMA preferred set: set of CDMA channel numbers in a CDMA system corresponding to frequency assignments that a mobile station will normally search to acquire a CDMA pilot channel

chip rate: rate of "chips" (modulated symbols after spreading) per second

code channel: subchannel of a forward CDMA channel or reverse CDMA channel. Each subchannel uses an orthogonal Walsh function or quasi-orthogonal function

Code Division Multiple Access (CDMA): technique for spread-spectrum multiple-access digital communications that creates channels through the use of unique code sequences

code symbol: output of an error-correcting encoder. Information bits are input to the encoder and code symbols are output from the encoder

NOTE: See convolutional code and turbo code.

common assignment channel: forward common channel used by the base station to acknowledge a mobile station accessing the enhanced access channel, and in the case of reservation access mode, to transmit the address of a reverse common control channel and associated common power control subchannel

common power control channel: forward common channel which transmits power control bits (i.e. common power control subchannels) to multiple mobile stations

NOTE: The common power control channel is used by mobile stations operating in the power controlled access mode, reservation access mode, or designated access mode.

common power control subchannel: subchannel on the common power control channel used by the base station to control the power of a mobile station when operating in the power controlled access mode on the enhanced access channel or when operating in the reservation access mode or the designated access mode on the reverse common control channel

continuous transmission: mode of operation in which discontinuous transmission is not permitted

convolutional code: type of error-correcting code

NOTE: A code symbol can be considered as the convolution of the input data sequence with the impulse response of a generator function.

cyclic redundancy code: class of linear error detecting codes which generate parity check bits by finding the remainder of a polynomial division

NOTE: See also frame quality indicator.

discontinuous transmission: mode of operation in which a base station or a mobile station switches its transmitter or a particular code channel on and off autonomously

NOTE: For the case of DTx operation on the forward dedicated control channel, the forward power control subchannel is still transmitted.

down-link: signal path where base station transmits and the mobile receives

NOTE: Also referred to as the forward link.

effective radiated power: product of the power supplied to the antenna and the antenna gain in a direction relative to a half-wave dipole

enhanced access channel: reverse channel used by the mobile for communicating to the base station

NOTE: The enhanced access channel operates in the basic access mode, power controlled access mode, and reservation access mode. It is used for transmission of short messages, such as signalling, MAC messages, response to pages and call originations. It can also be used to transmit moderate-sized data packets.

enhanced access channel preamble: non-data-bearing portion of the enhanced access probe sent by the mobile station to assist the base station in initial acquisition and channel estimation

enhanced access data: data transmitted while in the basic access mode or power controlled access mode on the enhanced access channel or while in the reservation mode on a reverse common control channel

enhanced access header: frame containing access origination information transmitted immediately after the enhanced access channel preamble while in the power controlled access mode or reservation access mode

enhanced access probe: one enhanced access channel transmission consisting of an enhanced access channel preamble, optionally an enhanced access header, and optionally enhanced access data

enhanced access probe sequence: sequence of one or more enhanced access probes on the enhanced access channel

NOTE: See also enhanced access probe.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

forward CDMA channel: CDMA channel from a base station to mobile stations

NOTE: The forward CDMA channel contains one or more code channels that are transmitted on a CDMA frequency assignment using a particular pilot PN offset.

forward common control channel: control channel used for the transmission of digital control information from a base station to one or more mobile stations

forward dedicated control channel: portion of a radio configuration 3 through 9 forward traffic channel used for the transmission of higher-level data, control information, and power control information from a base station to a mobile station