

SLOVENSKI STANDARD SIST EN 300 330-2 V1.5.1:2010

01-april-2010

Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) - Naprave kratkega dosega (SRD) - Radijska oprema v frekvenčnem območju od 9 kHz do 25 MHz in sistemi z indukcijsko zanko v frekvenčnem območju od 9 kHz do 30 MHz - 2. del: Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Short Range Devices (SRD) - Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz. Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

<u>SIST EN 300 330-2 V1.5.1:2010</u> https://standards.iteh.ai/catalog/standards/sist/d80f8854-f781-4e66-b11e-cde0a485ac84/sist-en-300-330-2-v1-5-1-2010

Ta slovenski standard je istoveten z: EN 300 330-2 Version 1.5.1

ICS:

33.060.20 Sprejemna in oddajna Receiving and transmitting

oprema equipment

33.100.01 Elektromagnetna združljivost Electromagnetic compatibility

na splošno in general

SIST EN 300 330-2 V1.5.1:2010 en

SIST EN 300 330-2 V1.5.1:2010

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 330-2 V1.5.1:2010 https://standards.iteh.ai/catalog/standards/sist/d80f8854-f781-4e66-b11e-cde0a485ac84/sist-en-300-330-2-v1-5-1-2010

ETSI EN 300 330-2 V1.5.1 (2010-02)

Harmonized European Standard (Telecommunications series)

Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment in the frequency range
9 kHz to 25 MHz and inductive loop systems
in the frequency range 9 kHz to 30 MHz;
Part 2: Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 330-2 V1.5.1:2010
https://standards.iteh.ai/catalog/standards/sist/d80f8854-f781-4e66-b11e-cde0a485ac84/sist-en-300-330-2-v1-5-1-2010



Reference REN/ERM-TG28-0424-2 Keywords radio, SRD, testing

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Teh Sous-Préfecture de Grasse (06) N° 7803/88 (standards.iteh.ai)

SIST EN 300 330-2 V1.5.1:2010 https://standards.iteh.ai/catalog/standards/sist/d80f8854-f781-4e66-b11ecde0a485ac**Important notice**_v1_5_1_2010

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2010. All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP[™] is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellecti	ual Property Rights		4			
Forewor	d		4			
	Scope					
	•					
2.1 2.2						
3 De 3.1		d abbreviations				
3.2						
3.3						
4 Τ ε	echnical requirements	specifications	7			
4.1	Environmental condition	ons				
4.1.1		file				
4.2		nents				
4.2.1		ments				
4.2.1.1		of operating frequencies				
4.2.1.2	Limits for trans	mitters in the range from 9 kHz to 30 MHz				
4.2.1.3	Limits for the p	ermitted range of modulation bandwidthrous and out-of-band emissions	8			
4.2.1.4 4.2.2	Receiver requireme	ents	c			
4.2.2.1		el selectivity in band (receiver category 1 only)				
4.2.2.2		ensitation (receiver categories 1 or 2 only)				
4.2.2.3		us emissions ST-EN-300-330-2-V1-5-1-2010				
5 Te	esting for compliance	twirth resign and atalogist and arises sist/d80f8854-f781-4e66-b11e-	۶			
5.1	Environmental condition	twith technical requirements/sist/d80f8854-f781-4e66-b11e- ons for lesting ac84/sist-en-300-330-2-v1-5-1-2010	8			
5.2	Essential radio test sui	tes	8			
5.2.1						
5.2.1.1		of operating frequencies				
5.2.1.2		of the modulation bandwidth				
5.2.1.3		for transmitters in the range from 9 kHz to 30 MHz				
5.2.1.4 5.2.2		rious and out-of-band emissions				
5.2.2.1		el selectivity (receiver category 1 only)				
5.2.2.2	Blocking or des	ensitation (receiver categories 1 or 2 only)				
5.2.2.3	Receiver spurio	us emissions	9			
5.3	Interpretation of result	s and measurement uncertainty	9			
Annex A	A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	10			
Annex E	3 (informative):	The EN title in the official languages	12			
Annex (C (informative):	Bibliography	17			
TT: 4	- (1 /			

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [1.2] are given in annex A.

The present document is part 2 of a multi-part deliverse Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive ".

National transposition dates				
Date of adoption of this EN:	8 February 2010			
Date of latest announcement of this EN (doa):	31 May 2010			
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2010			
Date of withdrawal of any conflicting National Standard (dow):	30 November 2011			

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to Short Range Devices (SRDs) transmitters and receivers as described in the scope of EN 300 330-1 [1].

The present document covers transmitters intended to operate in the frequency range as defined in the Commission Decision 2006/771/EC [i.4] on harmonisation of the radio spectrum for use by short-range devices as amended by Commission Decision 2008/432/EC [i.6] and the CEPT/ERC/REC 70-03 [i.5].

The document applies to:

- 1) Generic Short range Devices including transmitters operating in the range from 9 kHz to 25 MHz; and
- 2) inductive loop transmitters operating from 9 kHz to 30 MHz including Radio Frequency Identification (RFID) and EAS equipments;
- 3) receivers operating from 9 kHz to 30 MHz.

These radio equipment types are capable of operating in the permitted frequency bands within the 9 kHz to 30 MHz range as specified in table 1:

- either with a Radio Frequency (RF) output connection and dedicated antenna or with an integral antenna;
- for all types of modulation;
- with or without speech.

Table 1 shows a list of the frequency bands as designated to Short Range Devices by some European Commission Decisions and the CEPT/ERC/REC 70-03 [i,5] as known at the date of publication of the present document.

Table 1: Frequency bands designated to Short Range Devices within 9 kHz to 30 MHz

SIST EN 300 330-2 V1.5.1:2010						
https://sa-Frequency.Bands/frequencies/d8048854_4781_4.Applications						
Transmit and Receive	9 kHz to 90 kHz 200 330 3	Inductive devices, Generic use				
Transmit and Receive	90 kHz to 119 kHz	Inductive devices, Generic use				
Transmit and Receive	119 kHz to 140 kHz	Inductive devices, Generic use				
Transmit and Receive	140 kHz to 148,5 kHz	Inductive devices, Generic use				
Transmit and Receive	148,5 kHz to 5 MHz	Inductive devices, Generic use				
Transmit and Receive	400 kHz to 600 kHz	Inductive devices for RFID only				
Transmit and Receive	5 kHz to 30 MHz	Inductive devices, Generic use				
Transmit and Receive	3 155 kHz to 3 400 kHz	Inductive devices, Generic use				
Transmit and Receive	4 234 kHz	Inductive devices, Railway applications				
Transmit and Receive	4 516 kHz	Inductive devices, Railway applications				
Transmit and Receive	6 765 kHz to 6 795 kHz	Inductive devices, Generic use				
Transmit and Receive	7 400 kHz to 8 800 kHz	Inductive devices, Generic use				
Transmit and Receive	10 200 kHz to 11,000 MHz	Inductive devices, Generic use				
Transmit and Receive	12,5 MHz to 20 MHz	Inductive devices, Wireless healthcare				
Transmit and Receive	13,553 MHz to 13,567 MHz	Inductive devices, Generic use				
Transmit and Receive	26,957 MHz to 27,283 MHz	Inductive devices, Generic use				
Transmit and Receive	27,095 MHz	Inductive devices, Railway applications				

- NOTE 1: It should be noted that table 1 represents the most widely implemented position within the European Union and the CEPT countries, but it should not be assumed that all designated bands are available in all countries.
- NOTE 2: In addition, it should be noted that other frequency bands may be available in a country within the frequency range 9 kHz to 30 MHz covered by the present document.
- NOTE 3: On non-harmonized parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an Individual Rights for use of spectrum or General Authorization, or as a condition for use under "licence exemption" as it is in most cases for Short Range Devices.

6

The present document covers fixed stations, mobile stations and portable stations.

The present document is intended to cover the provisions of article 3.2 of Directive 1999/5/EC [i.2] (R&TTE Directive), which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site http://www.newapproach.org.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference. (standards.iteh.ai)

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

SIST EN 300 330-2 V1.5.1:2010

https://standards.iteh.ai/catalog/standards/sist/d80f8854-f781-4e66-b11e-cde0a485ac84/sist-en-300-330-2-v1-5-1-2010

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

[1] ETSI EN 300 330-1 (V1.7.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz; Part 1: Technical characteristics and test methods".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".

7

- [i.4] Commission Decision 2006/771/EC of 9 November 2006 on harmonisation of the radio spectrum for use by short-range devices as amended by Commission Decision 2008/432/EC.
- [i.5] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.6] Commission Decision 2008/432/EC of 23 May 2008 amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in [i.2] and EN 300 330-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in EN 300 330-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in EN 300 330-1 [1] apply.

iTeh STANDARD PREVIEW

4 Technical requirements specifications

4.1 Environmental conditions 300-2 V1.5.1:2010 Environmental conditions standards/sist/d80f8854-f781-4e66-b11e-

cde0a485ac84/sist-en-300-330-2-v1-5-1-2010

4.1.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the provider. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Transmitter requirements

4.2.1.1 Permitted range of operating frequencies

The permitted range of operating frequencies shall not exceed the limits specified in clause 7.3.3 of EN 300 330-1 [1].

4.2.1.2 Limits for transmitters in the range from 9 kHz to 30 MHz

The maximum radiated field strength and RF carrier current shall not exceed the limits specified in clause 7.2.1.3 of EN 300 330-1 [1].

The maximum RF carrier current shall not exceed the limits specified in clause 7.2.2.3 of EN 300 330-1 [1].