

SLOVENSKI STANDARD SIST-TS CEN/TS 16675:2014

01-november-2014

Karakterizacija odpadkov - Preverjanje statusa monolitnosti odpadkov		
Characterization of waste - Verification of the monolithic status of waste		
Charakterisierung von Abfällen - Nachweis des monolithischen Status von Abfälle	n	
Caractérisation des déchets - Vérification du caractère monolithique d'un déchet		
(standards.iteh.ai) Ta slovenski standard je istoveten z: CEN/TS 16675:2014		
SIST-TS CEN/TS 16675:2014		
https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-		
ICS:		
13.030.10 Trdni odpadki Solid wastes		
SIST-TS CEN/TS 16675:2014 en,fr,de		

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS CEN/TS 16675:2014 https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-46ae473a5e42/sist-ts-cen-ts-16675-2014

SIST-TS CEN/TS 16675:2014

TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

CEN/TS 16675

September 2014

ICS 13.030.10

English Version

Characterisation of waste - Test methods for the determination of the monolithic status of waste

Caractérisation des déchets - Vérification du caractère monolithique d'un déchet

Charakterisierung von Abfällen - Prüfverfahren für die Bestimmung der monolithischen Eigenschaften von Abfällen

This Technical Specification (CEN/TS) was approved by CEN on 18 February 2014 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

SIST-TS CEN/TS 16675:2014 https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-46ae473a5e42/sist-ts-cen-ts-16675-2014



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Ref. No. CEN/TS 16675:2014 E

SIST-TS CEN/TS 16675:2014

CEN/TS 16675:2014 (E)

Contents

Forewo	ord	.3	
Introdu	Introduction4		
1	Scope	.5	
2	Normative references	.5	
3	Terms and definitions	.6	
4	Principle	.7	
5	Equipment and reagents	.8	
6	Sampling and sample preparation	.8	
7 7.1	Procedures	.8 .8	
7.2	Unconfined compressive strength (UCS)	.8	
7.3	Permeability	.8	
7.4		.9	
7.5 7.6	Organic matter	9. 9	
7.7	Freeze/thaw effects	.9	
8	Expression of results	10	
9	Documentation and test report	10	
9.1	General requirements	10	
9.2	General data	10	
9.3	Sample preparation (for each test procedure)	11	
9.4	Result of tests	11	
Bibliog	raphy	12	

Foreword

This document (CEN/TS 16675:2014) has been prepared by Technical Committee CEN/TC 292 "Characterization of waste", the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS CEN/TS 16675:2014 https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-46ae473a5e42/sist-ts-cen-ts-16675-2014 CEN/TS 16675:2014 (E)

Introduction

Disposal of some types of waste requires stabilisation/solidification to reduce the impact and/or comply with regulatory requirements. The characterisation of waste is an essential step for the assessment of a potential final destination, especially in case of landfilling and associated potential hazards. Based on its properties, a stabilised/solidified waste material may be allocated to a landfill for granular waste or a landfill for monolithic waste. Information on certain physical properties of a given stabilised/solidified waste material is required to determine if it can be classified as a monolithic material and to select appropriate leaching test method(s) and landfilling options for that waste. This technical specification describes test methods applicable to assessment of these physical properties.

WARNING – Anyone dealing with waste and sludge analysis should be aware of the typical risks of that kind of material irrespective of the parameter to be determined. Waste and sludge samples may contain hazardous (e.g. toxic, reactive, flammable, infectious) substances, which can be liable to biological and/or chemical reaction. Consequently these samples should be handled with special care. Gases which may be produced by microbiological or chemical activity are potentially flammable and will pressurise sealed bottles. Bursting bottles are likely to result in hazardous shrapnel, dust and/or aerosol. National regulations should be followed with respect to all hazards associated with the methods in this technical specification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS CEN/TS 16675:2014 https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-46ae473a5e42/sist-ts-cen-ts-16675-2014

1 Scope

This Technical Specification provides methods, which can be used to assess the monolithic character of a stabilised/solidified waste, with respect to landfilling. Information on the monolithic character is required to enable the choice of appropriate leaching tests for determination of the release of different substances from stabilised/solidified waste under specified (landfilling) conditions.

This document includes several physical and/or chemical test methods each addressing different aspects of monolithic character. The selection of methods required for an assessment of the monolithic character of a stabilised/solidified waste may vary, depending on the scenario to be addressed or it may be specified in regulation.

Rather than describing the procedures and methods in detail this document refers to existing standards and provides some guidance on their use on stabilised/solidified waste materials.

This Technical Specification does not address issues related to health and safety.

The following procedures and methods are included in this document:

- test to determine unconfined compressive strength;
- test to determine permeability;
- iTeh STANDARD PREVIEW
- test to determine the loss of mass by dissolution or disintegration; (standards.iteh.ai)
- test to determine expansion;
 - SIST-TS CEN/TS 16675:2014
- test to determine the content of organic matter: ds/sist/848e6e1a-967a-4874-ad55-
- 46ae473a5e42/sist-ts-cen-ts-16675-2014
- test to determine freeze/thaw effects.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12390-3, Testing hardened concrete - Part 3: Compressive strength of test specimens

EN 13137, Characterization of waste - Determination of total organic carbon (TOC) in waste, sludges and sediments

EN 15002, Characterization of waste - Preparation of test portions from the laboratory sample

CEN/TR 15177:2006, Testing the freeze-thaw resistance of concrete - Internal structural damage

EN 15216, Characterization of waste - Determination of total dissolved solids (TDS) in water and eluates

CEN/TS 15863, Characterisation of waste - Leaching behaviour test for basic characterisation - Dynamic monolithic leaching test with periodic leachant renewal, under fixed test conditions

CEN/TS 15864, Characterisation of waste - Leaching behaviour test for basic characterisation - Dynamic monolithic leaching test with continuous leachant renewal under conditions relevant for specified scenario(s)

CEN/TS 16675:2014 (E)

CEN ISO/TS 17892-11, Geotechnical investigation and testing - Laboratory testing of soil - Part 11: Determination of permeability by constant and falling head (ISO/TS 17892-11)

Terms and definitions 3

For the purposes of this document, the following terms and definitions apply.

3.1

dry matter

wdm

mass fraction of a sample excluding water expressed as a percentage by mass calculated by determination of dry residue or water content

[SOURCE: EN 14346]

3.2

dry residue wdr remaining mass fraction of a sample after a drying process at 105 °C

[SOURCE: EN 14346]

3.3

eluate

solution recovered from a leaching test

3.4

laboratory sample

sample or subsample (s) sent to or received by the laboratory https://standards.iteh.a/catalog/standards/sist/848e6e1a-967a-4874-ad55-

[SOURCE: IUPAC:1997]

Note 1 to entry: When the laboratory sample is further prepared (reduced) by subdividing, mixing, grinding or by combinations of these operations, the result is the test sample. When no preparation of the laboratory sample is required, the laboratory sample is the test sample. A test portion is removed from the test sample for the performance of the test or for analysis. The laboratory sample is the final sample from the point of view of sample collection but it is the initial sample from the point of view of the laboratory.

STANDARD PREVIEW

(standards.iteh.ai)

46ae473a5e42/sist-ts-cen-ts-16675-2014

Note 2 to entry: Several laboratory samples could be prepared and sent to different laboratories or to the same laboratory for different purposes. When sent to the same laboratory, the set is generally considered as a single laboratory sample and is documented as a single sample.

3.5

leachant liquid used in a leaching test

[SOURCE: EN 12457-1]

3.6

leaching test

test during which a material is put into contact with a leachant and some constituents of the material are extracted

[SOURCE: EN 12457-1]

3.7

monolithic waste

waste prepared with certain minimum dimensions and physical and mechanical properties that ensure its integrity over a certain period of time in the considered scenario

3.8

stabilised/solidified waste

waste stabilised/solidified by chemical and physical means to form a coherent body maintaining its integrity in the landfill over a specified timeframe.

3.9

test portion

quantity of material of proper size for measurement of the concentration or other properties of interest removed from the test sample

[SOURCE: IUPAC:1997]

3.10

test portion of monolithic waste

specimen obtained either by moulding, by cutting or by coring and ready for the performance of a leaching test with a minimum dimension in all directions of 40 mm

Note 1 to entry: The test portion could be taken from the laboratory sample directly if no preparation of sample is required, but usually it is taken from the prepared test sample.

iTeh STANDARD PREVIEW

test sample

3.11

sample, prepared from the laboratory sample, from which test portions are removed for testing or analysis

[SOURCE: IUPAC:1997]

997] <u>SIST-TS CEN/TS 16675:2014</u> https://standards.iteh.ai/catalog/standards/sist/848e6e1a-967a-4874-ad55-46ae473a5e42/sist-ts-cen-ts-16675-2014

water content

ww

3.12

mass fraction of water in a sample determined by Karl-Fischer-titration

[SOURCE: EN 14346]

3.13

waste monolith

waste delivered as bulky forms of specified minimum dimensions retaining its form in the landfill over a specified timeframe

Note 1 to entry: It may generally not be necessary to test a few waste monoliths disposed amongst granular waste, as their contribution to the landfill leachate quality will be marginal.

4 Principle

The selection of methods to be used to assess the monolithic character of a specific waste material provided in this document shall address the conditions imposed by the relevant landfill scenario(s). In general, there is an intention to produce a monolithic waste form which will maintain its integrity under specified conditions over a specified time span for the landfill. The following procedures allow assessment of the monolithic character of a waste sample of regular shape in order to enable selection of appropriate test methods and interpretation models for the determination of the release of substances from the waste under landfilling conditions. Some of the procedures may also be used to determine if the waste material fulfils applicable geotechnical requirements for landfilling. If for some reason one or more of the procedures are not considered necessary for a specific purpose, the justification for that shall be given in the test report.