

ETSI TS 102 636-1 V1.1.1 (2010-03)

Technical Specification

Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 1: Requirements

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/d28beb94-f39e-4502-b4af-b5c741278b6a/etsi-ts-102-636-1-v1.1.1-2010-03>



Reference

DTS/ITS-0030002

Keywords

addressing, ITS, network, point-to-multipoint;
point-to-point, protocol**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp**Copyright Notification**

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	6
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations	6
4 Design guidelines	6
5 Functional requirements	6
5.1 Communication mode	6
5.2 GeoNetworking addressing	7
5.3 Geographical routing	7
5.4 Status information signalling.....	7
5.5 Priority and buffering	7
5.6 Data congestion control.....	7
5.7 Security and privacy.....	8
5.8 Cross-layer signalling.....	8
5.9 GeoNetworking and IPv6.....	8
5.10 Transport layer functions.....	8
6 Performance requirements.....	8
Annex A (informative): Other requirements	9
Annex B (informative): Introduction to GeoNetworking	10
Annex C (informative): Bibliography.....	12
History	13

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport System (ITS).

The present document is part 1 of a multi-part deliverable covering Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking, as identified below:

- Part 1:** " Requirements";
- Part 2: "Scenarios";
- Part 3: "Network architecture";
- Part 4: "Geographical addressing and forwarding for point-to-point and point-to-multipoint communications";
- Part 5: "Transport protocols";
- Part 6: "Internet integration".

1 Scope

The present document specifies the general, functional and performance requirements for ITS network and transport layer at a high level.

The present document is applicable to different types of ITS access technologies.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 302 665: "Intelligent Transport Systems (ITS); Communications Architecture".
- [2] ETSI TS 102 637-1: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 1: Functional Requirements".
- [3] ETSI TS 102 636-2 "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 2: Scenarios".
- [4] ETSI TS 102 636-3 "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 3: Network architecture".
- [5] IETF RFC 4861: "Neighbor Discovery for IP version 6 (IPv6)".
- [6] IETF RFC 4862: "IPv6 Stateless Address Autoconfiguration".
- [7] IETF RFC 3775: "Mobility Support in IPv6".
- [8] IETF RFC 3963: "Network Mobility (NEMO) Basic Support Protocol".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in [4] and the following apply:

ad hoc communication: communication in an ad hoc network

transmission interval control: mechanisms to adjust the rate of sending messages via wireless channel

transmission power control: mechanisms to adjust transmission power on wireless channel

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in [4] and the following apply:

TIC	Transmission Interval Control
TPC	Transmission Power Control
VANET	Vehicular Ad hoc Network

4 Design guidelines

The ITS network and transport layer shall be designed to:

- efficiently disseminate safety and traffic efficiency messages as specified in [2];
- support all communication scenarios specified in [3];
- transparently transport IPv6 packets with minimum changes to IPv6;
- support privacy and security functions;
- support different communication media and interfaces as specified in [1].

5 Functional requirements

5.1 Communication mode

The ITS network and transport layer shall support self-organized communication between ITS vehicle stations without any assistance from the ITS access network, and also allow communication with assistance from the ITS access network. The ITS network and transport layer shall also support self-organized communication ITS vehicle stations and ITS roadside stations.

For safety applications that have stringent requirement on the latency of message delivery, the ITS network and transport layer shall support communication without the need to exchange any signalling messages beforehand.

5.2 GeoNetworking addressing

Each ITS station must have at least one unique address at the ITS network and transport layer in its communication environment. The address may be based on each individual node's identity or geographical position.

The ITS network and transport layer shall support at least circular geographical target areas and may support other types of geographical target areas needed by applications.

The ITS network and transport layer shall support automatic address configuration, which does not require any manual configuration from human beings. The ITS network and transport layer shall also allow manual address configuration.

5.3 Geographical routing

Routing functions must efficiently support all communication scenarios specified in [3].

5.4 Status information signalling

The status information of ITS stations shall include each node's address at the ITS network and transport layer, position, speed, heading, time stamp and their accuracy, and may also include other information such as altitude, etc. Status information shall be maintained in a database and the ITS network and transport layer shall have access to this data.

Exchange of status information shall be carried out by at least one of the following means:

- explicit status information exchange protocol, e.g. location resolution of an ITS station by means of location service;
- implicit status information signalling by sending periodical packets including status information.

The status information signalling shall be carried out in an efficient way that will not cause congestion in the network.

5.5 Priority and buffering

The ITS network and transport layer shall support packets with different priorities with the highest priority for critical safety packets. The ITS network and transport layer shall treat packets with different priorities differently in that high priority packets have easier access to communication channel.

The ITS network and transport layer shall be able to temporarily buffer packets and either drop them or send them to the lower layer at a later time. Such buffering functions are necessary in certain conditions, such as in case the location of the destination is unknown or there is no direct neighbour to forward packets to the destination.

5.6 Data congestion control

The ITS network and transport layer shall support data congestion control functions in order to keep network load at an acceptable level, for example, by means of Transmission Interval Control (TIC), Transmission Power Control (TPC), reducing packet size, efficient routing and forwarding protocol, etc.

NOTE: Data congestion control at the ITS network and transport layer is different from traditional data congestion control mechanisms in TCP in many aspects, e.g. communication type, data traffic characteristics, usage of the end-to-end approach, types of algorithms. Data congestion control at the ITS network and transport layer may take a totally different approach than TCP does.

Depending on the type of packet, one or a combination of several mechanisms shall be applied for data congestion control.

5.7 Security and privacy

The ITS network and transport layer shall support security objectives for both single-hop and multi-hop communication. Security objectives particularly include integrity, privacy and non-repudiation and shall protect the ITS network and transport layer protocol header. The ITS network and transport layer shall also protect privacy, i.e. provide confidentiality to personal data such as node ID and location.

5.8 Cross-layer signalling

The ITS network and transport layer shall support information exchange between different layers, and entities at each layer may select the required information to be received. Information exchange shall be bi-directional, structured and efficient.

5.9 GeoNetworking and IPv6

The ITS network and transport layer shall allow legacy IPv6 applications run on top of the ITS network and transport layer and support transparently routing of IPv6 packets. The following functions shall be supported by the ITS network and transport layer:

- Efficient methods to support IPv6 Neighbor Discovery function [5];
- IPv6 Stateless Address Autoconfiguration [6];
- Interfaces and method to support IPv6 unicast;
- Interfaces and method to support IPv6 multicast;
- IPv6 mobility protocols [7];
- IPv6 Network Mobility (NEMO) Basic Support Protocol [8].

5.10 Transport layer functions

The transport protocol used together with GeoNetworking shall support multiplexing and de-multiplexing of application data.

6 Performance requirements

In general, the ITS network and transport layer shall

- provide low-latency communications;
- provide reliable communications with the highest reliability for safety messages;
- keep signalling, routing and packet forwarding overhead low;
- be fair among different nodes with respect to bandwidth usage considering the type of messages;
- be robust against security attack, mal-function in ITS stations;
- be able to work in scenarios with low and high density of GeoNetworking-enabled nodes.

NOTE: The dissemination of safety messages in VANETs typically have requirements on latency, reliability and dissemination area. The metrics for latency and reliability should be studied and their relationship with message size, ITS station density, and message dissemination range is to be studied with respect to different communication scenarios. Tradeoffs between efficiency and reliability should be studied. A set of rules should be defined to treat packets differently according to their priorities or other criteria.

Annex A (informative): Other requirements

The ITS network and transport layer should have low complexity.

It should also enable have interoperability among:

- different ITS stations;
- different applications;
- different hardware platforms;
- different hardware vendors;
- different software manufacturer.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/d28beb94-f39e-4502-b4af-b5c741278b6a/etsi-ts-102-636-1-v1.1.1-2010-03>