

**Satellite Earth Stations and Systems (SES);  
Harmonized EN for Mobile Earth Stations (MESS),  
including handheld earth stations, for Satellite  
Personal Communications Networks (S-PCN)  
in the 2,0 GHz bands under the Mobile Satellite  
Service (MSS) covering essential requirements  
under article 3.2 of the R&TTE directive**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/18056e22-b985-4d46-96ba-8bea014f510a/etsi-en-301-442-v1.2.1-2010-08>



---

Reference

REN/SES-00308

---

Keywords

satellite, earth station, MES, S-PCN, MSS,  
regulation

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	8
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations .....	10
4 Technical requirements specifications .....	10
4.1 Environmental profile.....	10
4.1.1 General.....	10
4.1.2 Temperature.....	10
4.1.3 Voltage.....	10
4.1.4 Vibration.....	10
4.2 Conformance requirements .....	11
4.2.1 Unwanted emissions outside the band 1 980,1 MHz to 2 009,9 MHz (carrier-on).....	11
4.2.1.1 Justification .....	11
4.2.1.2 Technical Requirement .....	11
4.2.1.3 Conformance Test.....	11
4.2.2 Unwanted emissions within the bands 1 980,1 MHz to 2 009,9 MHz, 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz (carrier-on).....	12
4.2.2.1 Justification .....	12
4.2.2.2 Technical Requirement.....	12
4.2.2.3 Conformance Test .....	12
4.2.3 Unwanted emissions in carrier-off state.....	12
4.2.3.1 Justification .....	12
4.2.3.2 Technical Requirement .....	13
4.2.3.3 Conformance Test.....	13
4.2.4 MES Control and Monitoring Functions (CMF) .....	13
4.2.4.1 Self-monitoring functions / Processor monitoring .....	13
4.2.4.1.1 Justification .....	13
4.2.4.1.2 Technical Requirement.....	13
4.2.4.1.3 Conformance Test .....	13
4.2.4.2 Self-monitoring functions / Transmit frequency generation sub-system monitoring .....	13
4.2.4.2.1 Justification .....	13
4.2.4.2.2 Technical Requirement.....	14
4.2.4.2.3 Conformance Test .....	14
4.2.4.3 Network control authorization .....	14
4.2.4.3.1 Justification .....	14
4.2.4.3.2 Technical Requirement.....	14
4.2.4.3.3 Conformance Test .....	14
4.2.4.4 Network control reception.....	14
4.2.4.4.1 Transmit frequency control .....	14
4.2.4.5 Fellow radio stations in a dual-mode or multi-mode terminal .....	15
4.2.4.5.1 Justification .....	15
4.2.4.5.2 Technical Requirement.....	15
4.2.4.5.3 Conformance Test .....	15
4.2.5 Equipment identity.....	15
4.2.5.1 Justification .....	15
4.2.5.2 Technical Requirement .....	15
4.2.5.3 Conformance Test.....	15

5	Testing for compliance with technical requirements.....	15
5.1	Environmental conditions for testing .....	15
5.1.1	Specification of the environmental test conditions .....	15
5.1.2	Tests under extreme voltage conditions.....	16
5.2	Essential radio test suites.....	16
5.2.1	General.....	16
5.2.1.1	Presentation of equipment for testing purposes.....	16
5.2.1.2	Description of equipment.....	16
5.2.1.3	Testing of host-connected equipment and plug-in modules .....	17
5.2.1.3.1	Alternative approaches .....	17
5.2.1.3.2	Alternative A: combined equipment.....	17
5.2.1.3.3	Alternative B: use of a test jig .....	17
5.2.1.4	CMF / Special Test Equipment (STE) .....	17
5.2.1.5	General test requirements.....	18
5.2.1.5.1	MES test modes .....	18
5.2.1.5.2	Special Test Equipment .....	18
5.2.1.5.3	Laboratory Test Equipment (LTE) .....	19
5.2.1.5.4	Method of test for MES RF emissions according to equipment type .....	20
5.2.1.5.5	Procedures for measurement of MES RF radiated emissions.....	20
5.2.1.5.6	Procedures for measurement of MES RF conducted emissions .....	24
5.2.1.5.7	Interpretation of the measurement results.....	26
5.2.1.5.8	Test report.....	26
5.2.2	Unwanted emissions outside the band 1 980,1 MHz to 2 009,9 MHz (carrier-on).....	26
5.2.2.1	Method of test .....	26
5.2.2.2	Peak measurement.....	26
5.2.2.3	Average measurement .....	27
5.2.2.4	Test requirements .....	27
5.2.3	Unwanted emissions within the bands 1 980,1 MHz to 2 009,9 MHz, 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz (carrier-on) .....	27
5.2.3.1	Method of test .....	27
5.2.3.2	Measurement method .....	28
5.2.3.3	Test requirements .....	28
5.2.4	Unwanted emissions in carrier-off state.....	28
5.2.4.1	Method of test .....	28
5.2.4.2	Measurement method .....	29
5.2.4.3	Test requirements .....	29
5.2.5	MES Control and Monitoring Functions (CMF) .....	29
5.2.5.1	Self-monitoring functions / Processor Monitoring .....	29
5.2.5.2	Self-monitoring functions / Transmit frequency generation sub-system monitoring .....	29
5.2.5.3	Network control authorization .....	29
5.2.5.3.1	Method of test.....	29
5.2.5.3.2	Test procedure .....	30
5.2.5.3.3	Test requirement .....	30
5.2.5.4	Network control reception.....	30
5.2.5.4.1	Transmit frequency control .....	30
5.2.5.5	Fellow radio stations in a dual-mode or multi-mode terminal .....	31
5.2.5.5.1	Method of test.....	31
5.2.5.5.2	Test procedure .....	31
5.2.5.5.3	Test requirements .....	31
5.2.6	Equipment identity.....	31
5.2.6.1	Method of test .....	31
5.2.6.2	Test procedure.....	31
5.2.6.3	Test requirements.....	31
<b>Annex A (normative):</b>	<b>HS Requirements and conformance Test specifications Table (HS-RTT).....</b>	<b>32</b>
<b>Annex B (informative):</b>	<b>Explanation of nominated bandwidth.....</b>	<b>34</b>
B.1	Introduction .....	34
B.2	Interpretation of Parameters $[B_n, f_c, a, b]$ .....	34

B.3	Choice of nominated bandwidth.....	34
B.4	Maximum value for nominated bandwidth .....	36
<b>Annex C (informative):</b>	<b>The EN title in the official languages .....</b>	<b>38</b>
<b>Annex D (informative):</b>	<b>Bibliography.....</b>	<b>39</b>
History .....		40

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/18056e22-b985-4dd6-96ba-8bea014f510a/etsi-en-301-442-v1.2.1-2010-08>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [6] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The requirements relevant to Directive 1999/5/EC [1] are summarised in annex A.

### Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [1]. The modular structure is shown in EG 201 399 [i.1].

# 1 Scope

The present document applies to Mobile Earth Station (MES) radio equipment which have the following characteristics:

- these MES operate in a non-geostationary orbit (NGSO) mobile-satellite system;
- these MES have both transmit and receive capabilities and operate in a Satellite-Personal Communications Network (S-PCN). An S-PCN MES may be handheld, portable, vehicle-mounted, host connected, semi-fixed or fixed equipment, or may be an element in a multi-mode terminal. It may consist of a number of modules with associated connections and user interface, or may be a self contained single unit;
- these LMESs are controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document;
- if the MES is an element in a multi-mode terminal, unless otherwise stated in the present document, its requirements apply only to the S-PCN MES element of the terminal operating in the MSS frequency bands given in table 1;
- these MES are capable in operating in all or part of the frequency bands shown in table 1.

**Table 1: Mobile Satellite Service (MSS) frequency bands**

MES	MSS frequency bands
Transmit (earth to space)	1 980 MHz to 2 010 MHz
Receive (space to earth)	2 170 MHz to 2 200 MHz

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) article 3.2 which states that "...radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [1] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the ETSI web site.

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ITU-T Recommendation O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".

- [3] IEC 60068-2-1 (March 2007): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [4] IEC 60068-2-2 (July 2007): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [5] IEC 60068-2-64 (2008-04) Ed. 2.0: "Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance".
- [6] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

**applicant:** manufacturer or his representative within the European Community or the person responsible for placing the apparatus on the market

**carrier-on state (allocated a channel):** MES is in this state when it is transmitting a signal in a continuous or non-continuous mode

**carrier-off state (idle mode):** MES is in this state when it is powered-on but not transmitting a signal, i.e. not in carrier-on state

**conducted measurement:** measurement of emissions from an antenna port of the MES made by direct wired connection to the port

**Equivalent Isotropically Radiated Power (EIRP):** product of transmitter power and maximum antenna gain, equivalent to an isotropic source radiating uniformly in all directions

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**handheld:** indicates a PE MES which is self-contained and is small enough and light enough to be carried and used during a call with one hand

**host-connected:** indicates an MES for which connection to or integration with host equipment is necessary to offer functionality

**host equipment:** any equipment which has a complete user functionality when not connected to the MES, and to which the MES provides additional functionality, and to which connection is necessary for the MES to offer functionality

**Installable Equipment (IE), Internally Mounted Equipment (IME) and Externally Mounted Equipment (EME):** Installable Equipment (IE) is an equipment which is intended to be installed in a vehicle

NOTE: An IE may consist of one or several interconnected modules. The IE is composed of modules intended to be externally mounted as declared by the applicant, and defined as Externally Mounted Equipment (EME) and the remaining modules(s) as Internally Mounted Equipment (IME).



**Laboratory Test Equipment (LTE):** logical grouping that contains the standard test equipment provided by a test laboratory

**MSS band:** continuous range of frequencies allocated by the ITU to the MSS

**multi-mode:** indicates equipment that accommodates radio stations of different radio networks

**narrow-band system:** narrow band system is one in which the nominal carrier frequency spacing for MESs in the earth-to-space direction is less than 300 kHz

**network control channel:** channel by which an MES receives general control information from the NCF of its S-PCN

**NCF control message:** message, normally originating from a network, to a specified terminal or set of terminals of the network which indicates to the terminal or set of terminals that it/they should carry out some specific action or should enter or maintain some specific state

NOTE: For test purposes NCF control messages may originate from Special Test Equipment (STE).

**nominated bandwidth (Bn):** Bn of the Mobile Earth Station (MES) radio frequency transmission is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified levels of unwanted emissions

NOTE 1: The Bn is defined relative to the MES actual carrier frequency  $f_c$ .

Bn is the width of the frequency interval ( $f_c - a$ ,  $f_c + b$ ), where a and b, which shall be specified by the applicant, may vary with  $f_c$ .

The frequency interval ( $f_c - a$ ,  $f_c + b$ ) shall not encompass more than either:

- i) when  $a = b$ , 4 nominal carrier frequencies for narrow-band systems;
- ii) when  $a \neq b$ , 1 nominal carrier frequency for narrow-band systems; or
- iii) 1 nominal carrier frequency for wide-band systems;

The frequency interval ( $f_c - a$ ,  $f_c + b$ ) shall be within the operational band of the MES.

NOTE 2: Explanation of nominated bandwidth is presented in annex B.

**operational band:** sub-portion of the band 1 980 MHz to 2 010 MHz which has been assigned in the earth-to-space direction to the MSS network, within which the MES is operating

**Portable Equipment (PE):** Portable Equipment (PE) is generally intended to be self-contained, free standing and portable

NOTE: A PE would normally consist of a single module, but may consist of several interconnected modules.

**radiated measurement:** measurement of an actual radiated field

**Special Test Equipment (STE):** equipment which allows a test laboratory to control the MES so that the tests required by the present document can be performed

**test laboratory:** laboratory which performs the conformance testing of the MES against the present document. The test laboratory may be the applicant's laboratory

**test load:** test load is a substantially non-reactive, non-radiating power attenuator which is capable of safely dissipating the power from the transmitter(s)

**unwanted emissions:** unwanted emissions are those falling outside the nominated bandwidth in the carrier-on state and those generated in the carrier-off state

**wide-band system:** wide-band system is one in which the nominal carrier frequency spacing for MESs in the earth-to-space direction is equal or greater than 300 kHz

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

Bn	nominated Bandwidth
CDMA	Code Division Multiple Access
CMF	Control and Monitoring Functions
dBW	decibels relative to 1 Watt
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
EME	Externally Mounted Equipment
IE	Installable Equipment
IME	Internally Mounted Equipment
ITU	International Telecommunications Union
LTE	Laboratory Test Equipment
MES	Mobile Earth Station
MIC	MES unique Identification Code (within its S-PCN)
MSS	Mobile Satellite Service
NCF	Network Control Facility
NGSO	Non GeoStationary Orbit
PE	Portable Equipment
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
S-PCN	Satellite Personal Communications Network
STE	Special Test Equipment
TDMA	Time Division Multiple Access

---

## 4 Technical requirements specifications

### 4.1 Environmental profile

#### 4.1.1 General

The technical requirements of the present document apply under the environmental profile specified below for operation of the equipment. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the specified operational environmental profile.

#### 4.1.2 Temperature

The MES shall fulfil all the requirements in the full temperature ranges of:

-10 °C to +55 °C;

Taken from IEC publications 60068-2-1 [3] and 60068-2-2 [4].

#### 4.1.3 Voltage

The applicant shall declare the nominal, lower and the higher extreme voltages.

The MES shall fulfil all the requirements in the full voltage range between the extreme voltages.

#### 4.1.4 Vibration

The MES shall fulfil all the requirements when vibrated at the frequency/amplitudes given in table 2.

Table 2: Vibration characteristics

Frequency range	ASD (Acceleration Spectral Density) random vibration
5 Hz to 20 Hz	0,96 m <sup>2</sup> /s <sup>3</sup> (+0/-5 %)
20 Hz to 500 Hz	0,96 m <sup>2</sup> /s <sup>3</sup> (+ 0/-5 %) at 20 Hz, thereafter -3 dB/Octave (+0/-5 %) (taken from IEC Publication 60068-2-64 [5])

## 4.2 Conformance requirements

### 4.2.1 Unwanted emissions outside the band 1 980,1 MHz to 2 009,9 MHz (carrier-on)

#### 4.2.1.1 Justification

Protection of other radio services operating outside the band 1 980 MHz to 2 010 MHz from emissions caused by S-PCN MESs operating within the band 1 980,1 MHz to 2 009,9 MHz.

#### 4.2.1.2 Technical Requirement

The maximum EIRP density of the unwanted emissions from the MES outside the band 1 980,1 MHz to 2 009,9 MHz shall not exceed the limits in table 3.

In table 3, whenever a change of limit between adjacent frequency bands occurs, the lower of the two limits shall apply at the transition frequency.

Table 3: Unwanted emissions outside the band 1 980,1 MHz to 2 009,9 MHz

Frequency (MHz)	Carrier - on		
	EIRP (dBW)	Measurement bandwidth	Measurement method
0,1 to 30	-66	10 kHz	Peak hold
30 to 1 000	-66	100 kHz	Peak hold
1 000 to 1 559	-60	3 MHz	Average
1 559 to 1 626,5	-70	1 MHz	Average (over 20 ms)
1 626,5 to 1 950	-60	3 MHz	Average
1 950 to 1 960	-60	1 MHz	Average
1 960 to 1 970	-60	300 kHz	Average
1 970 to 1 975	-60	100 kHz	Average
1 975 to 1 978,1	-60	30 kHz	Average
1 978,1 to 1 980,1	The levels in table 4 for the frequency offset 0 to 2 MHz shall apply from 1 980,1 MHz to 1 978,1 MHz		
1 980,1 to 2 009,9	Not applicable	Not applicable	Not applicable
2 009,9 to 2 011,9	The levels in table 4 for the frequency offset 0 to 2 MHz shall apply from 2 009,9 MHz to 2 011,9 MHz		
2 011,9 to 2 015	-60	30 kHz	Average
2 015 to 2 020	-60	100 kHz	Average
2 020 to 2 030	-60	300 kHz	Average
2 030 to 2 040	-60	1 MHz	Average
2 040 to 2 600	-60	3 MHz	Average
2 600 to 12 750	-60	3 MHz	Peak hold

The conformance requirements apply for the full range of environmental conditions corresponding to the type of equipment as specified in clause 4.1.

#### 4.2.1.3 Conformance Test

Conformance tests shall be carried out in accordance with clause 5.2.2.

## 4.2.2 Unwanted emissions within the bands 1 980,1 MHz to 2 009,9 MHz, 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz (carrier-on)

### 4.2.2.1 Justification

Protection of radio services and systems operating within the frequency band 1 978,1 MHz to 2 011,9 MHz from unwanted emissions caused by S-PCN MESs operating in the band 1 980,1 MHz to 2 009,9 MHz.

### 4.2.2.2 Technical Requirement

The maximum EIRP spectral density of the unwanted emissions from the MES within the band 1 978,1 MHz to 2 011,9 MHz shall not exceed the limits in tables 4 or 5, as applicable.

In tables 4 and 5, whenever a change of limit between adjacent frequency bands occurs, the lower of the two limits shall apply at the transition frequency.

When conflicts between multiple requirements exist, the more stringent requirement applies.

**Table 4: Maximum unwanted emissions within the bands 1 980,1 MHz to 2 009,9 MHz from a TDMA carrier, and maximum unwanted emissions within the bands 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz from any carrier**

Frequency offset (kHz) (note 1)	Carrier - on		
	EIRP (dBW)	Measurement bandwidth (kHz)	Measurement method
0 to 166	0 - (offset × 55/166)	3 kHz	Average
166 to 575	-55	3 kHz	Average
575 to 1 175	-60	3 kHz	Average
1 175 to 1 525	-50 - ((offset - 1 175) × 5/350)	30 kHz (note 2)	Average
1 525 to 32 000	-55	30 kHz (note 2)	Average

NOTE 1: Frequency offset is determined from edge of nominated bandwidth.  
NOTE 2: The measurement bandwidth used may be 3 kHz if the unwanted EIRP limits are reduced correspondingly.

**Table 5: Maximum unwanted emissions within the band 1 980,1 MHz to 2 009,9 MHz from a CDMA carrier**

Frequency offset (kHz) (note)	Carrier - on		
	EIRP (dBW)	Measurement bandwidth (kHz)	Measurement method
0 to 160	-35	30	Average
160 to 2 300	-35 - ((offset - 160) × 21/ 2 140)	30	Average
2 300 to 32 000	-56	30	Average

NOTE: Frequency offset is determined from the edge of nominated bandwidth.

The conformance requirements apply for the full range of environmental conditions corresponding to the type of equipment as specified in clause 4.1.

### 4.2.2.3 Conformance Test

Conformance tests shall be carried out in accordance with clause 5.2.3.

## 4.2.3 Unwanted emissions in carrier-off state

### 4.2.3.1 Justification

Protection of other radio services and systems from unwanted emissions caused by MESs in the carrier-off state.