

ETSI TS 101 376-5-2 V3.1.1 (2009-07)

Technical Specification

**GEO-Mobile Radio Interface Specifications (Release 3);
Third Generation Satellite Packet Radio Service;
Part 5: Radio interface physical layer specifications;
Sub-part 2: Multiplexing and Multiple Access;
Stage 2 Service Description;
GMR-1 3G 45.002**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b01540c3-d6e2-4cfd-94c3-01e9f87082d5/etsi-ts-101-376-5-2-v3.1.1-2009-07>



Reference

RTS/SES-00309-5-2

Keywords3G, GMPRS, GMR, GPRS, GSM, GSO,
interface, MES, mobile, MSS, MUX, radio,
satellite, S-PCN, TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important noticeIndividual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	8
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references	11
3 Definitions and abbreviations.....	11
3.1 Definitions	11
3.2 Abbreviations	11
4 General	11
5 Logical channels.....	11
5.1 General	11
5.2 Traffic channels.....	12
5.2.1 General.....	12
5.2.2 Speech traffic channels	12
5.2.3 Data traffic channels	12
5.2.4 Summary of traffic channel characteristics.....	12
5.2.5 Packet Data Traffic CHannels (PDTCH) (A/Gb mode only).....	12
5.2.5a Packet Data Traffic Channels (PDTCH3) (Iu mode only).....	13
5.2.6 Packet Mode Dedicated Channels (Iu mode only).....	14
5.3 Control channels.....	15
5.3.1 General.....	15
5.3.2 Broadcast channels	15
5.3.2.1 Frequency Correction CHannel (FCCH).....	15
5.3.2.2 GPS Broadcast control CHannel (GBCH)	15
5.3.2.3 Broadcast Control CHannel (BCCH).....	15
5.3.3 Common Control Channel (CCCH).....	15
5.3.4 Dedicated control channels	15
5.3.5 Cell Broadcast CHannel (CBCH)	15
5.3.6 Packet Common Control CHannels (PCCCH)	15
5.3.7 Packet dedicated control channels	16
6 The physical resource.....	16
6.1 General	16
6.2 Radio frequency channels.....	16
6.2.1 Spot beam allocation.....	16
6.2.2 Downlink and uplink	16
6.3 Timeslots and TDMA frames.....	16
6.3.1 General.....	16
6.3.2 Timeslot number	16
6.3.3 TDMA frame number	16
7 Bursts.....	16
7.1 General	16
7.2 Timing	17
7.2.1 Half-symbol period.....	17
7.2.2 Useful duration	17
7.2.3 Guard period	18
7.3 Multiple unique word patterns in bursts	18
7.4 Types of bursts	18
7.4.1 BACH burst	18
7.4.2 BCCH burst	18

7.4.3	CICH burst.....	18
7.4.4	DC2 burst.....	18
7.4.5	DC6 burst.....	18
7.4.6	DKAB bursts	18
7.4.6.1	KAB3 burst	18
7.4.7	FCCH burst.....	19
7.4.7.1	FCCH3 burst	19
7.4.8	NT3 burst.....	20
7.4.8.1	NT3 burst for encoded speech.....	20
7.4.8.2	NT3 burst for FACCH	20
7.4.9	NT6 burst.....	20
7.4.10	NT9 burst.....	20
7.4.11	RACH burst	20
7.4.11.1	RACH3 burst.....	20
7.4.12	SDCCH burst.....	20
7.4.13	Packet Normal Bursts (PNB).....	21
7.4.13.1	Burst header	25
7.4.13.1.1	Guard bits	25
7.4.13.1.2	Unique Word (UW).....	25
7.4.13.1.3	Public Information (PUI) field.....	26
7.4.13.1.4	Transition symbols	26
7.4.13.2	Encoded PRivate Information (PRI).....	26
7.4.13.3	Formats of packet normal burst.....	27
7.4.13.3.1	Void.....	27
7.4.13.3.2	PNB(4,3).....	27
7.4.13.3.3	PNB(5,3).....	27
7.4.13.3.4	PNB(1,6).....	28
7.4.13.3.5	PNB(2,6).....	28
7.4.13.3.6	LDPC coded PNB2(5,12)/Downlink.....	29
7.4.13.3.7	LDPC coded PNB2(5,12)/Uplink.....	30
7.4.13.3.8	LDPC coded PNB2(5,3)/Downlink.....	30
7.4.13.3.9	LDPC coded PNB2(5,3)/Uplink.....	31
7.4.13.3.10	PNB3(5,12)/Uplink	32
7.4.13.3.11	PNB3(5,12)/Downlink.....	32
7.4.13.3.12	PNB3(5,3)/Uplink	34
7.4.13.3.13	PNB3(5,3)/Downlink.....	34
7.4.13.3.14	PNB3(10,3) Downlink.....	35
7.4.13.3.15	PNB3(1,3) Burst.....	36
7.4.13.3.16	PNB3(1,6) burst.....	37
7.4.13.3.17	PNB3(1,8) burst.....	38
7.4.13.3.18	PNB3(2,6).....	39
7.4.14	Packet Access Burst (PAB)	39
7.4.15	Packet Keep-Alive Burst (PKAB)	40
7.4.16	DC12 burst.....	42
8	Logical-physical channel mapping.....	43
8.1	General	43
8.1.1	Frequency-domain description.....	43
8.1.2	Time-domain description.....	43
8.1.2.1	Physical channels	43
8.1.2.2	Logical channels	43
8.2	Physical Channel (PC) types and names	43
8.3	Logical channel parameters.....	43
8.4	Permitted channel configurations	44
8.5	Logical channel frame sequencing concepts	44
8.5.1	Simple frame sequence	44
8.5.1.1	Simple frame sequence subchannels.....	44
8.5.2	Simple paired-frame sequence.....	44
8.5.2.1	Simple paired-frame sequence subchannels.....	44
8.5.3	Configured paired-frame sequence	44
8.5.3.1	CBCH configuration	44
8.5.4	Statistically multiplexed paired-frame sequence	44

8.5.4.1	Pool size	44
8.5.4.2	Statistically multiplexed paired-frame sequence subchannels	44
8.5.4.3	Example using SDCCH.....	45
8.5.5	System information cycle sequencing.....	45
8.5.5.1	Physical-Channel-Relative Timeslot Number (PCRTN)	45
8.5.5.2	System-Information-Relative Frame Number (SIRFN)	45
8.5.5.3	Graphical representation of system information cycle timeslots.....	45
8.6	Mapping of logical channels to BCCH/CCCH.....	45
8.6.1	Fixed reserved-slot logical channels	45
8.6.1.1	FCCH	45
8.6.1.1a	FCCH3	45
8.6.1.2	CICH	45
8.6.1.3	BCCH.....	45
8.6.2	Optional reserved-slot logical channels	46
8.6.2.1	PCH.....	47
8.6.2.2	BACH (A/Gb mode only)	48
8.6.3	Unreserved-slot logical channels	49
8.7	Mapping of logical channels to normal CCCH	49
8.7a	Mapping of logical channels to SI extended/AGCH/CCCH (Iu mode only)	50
8.8	Mapping in time of packet logical channels onto physical channels.....	51
8.8.1	General.....	51
8.8.2	Mapping of the uplink channels.....	52
8.8.2.1	Mapping of uplink packet traffic channel (PDTCH/U) and PACCH/U	52
8.8.2.2	Mapping of the packet timing advance control channel (PTCCH/U),(A/Gb mode only)	52
8.8.2.3	Mapping of the uplink PCCCH, i.e. PRACH (A/Gb mode only)	52
8.8.2.3a	Mapping of the uplink PCCCH, i.e. PRACH3 (Iu mode only)	53
8.8.3	Mapping of the downlink channels.....	53
8.8.3.1	Mapping of the (PDTCH/D) and PACCH/D	53
8.8.3.2	Mapping of the PTCCH/D (A/Gb mode only).....	53
8.8.3.3	Mapping of the PBCCH	54
8.8.3.4	Mapping of the PCCCH	54
8.8.4	Mapping of PBCCH data.....	54
8.8.5	Permitted combination of packet data channels.....	54
8.9	Multislot configurations	54
8.9.1	Multislot configurations for circuit switched connections.....	54
8.9.2	Multislot configurations for packet switched connections.....	54
9	Operation of channels.....	55
9.1	PC6d and PC12u pairing	55
9.1a	PC12d and PC12u pairing	55
9.2	Bidirectional channel timeslot assignments.....	55
9.3	GBCH.....	55
9.3a	GBCH3.....	55
9.4	DKABs.....	55
9.5	FCCH and CICH	56
9.6	TACCH/2	56
9.7	MES monitoring of paging and alerting groups	56
9.7.1	Determination of assigned CCCH	56
9.7.2	Determination of assigned paging group	56
9.7.3	Determination of alerting group.....	56
9.7.4	Determination of PCCCH_GROUP and PAGING_GROUP for MES in GMPRS attached mode	56
9.8	MES selection of PC12U	56
9.9	SDCCH vs. CBCH	57
9.10	MES monitors paired CCCH for AGCH.....	57
9.11	Additional air interface constraints.....	57
10	BCCH parameters	57
10.1	Types of BCCH parameters.....	57
10.2	Information used to obtain synchronization	57
10.3	Channel meta-information.....	57
10.4	Beam-configurable multichannel information.....	57
10.5	Information specific to one instance of a channel	57

Annex A (normative):	Multislot capability	58
A.1	MES classes for multislot capability	58
A.2	Constraints imposed by the service selected	59
A.3	Network requirements for supporting MES multislot classes	59
Annex B (informative):	Asymmetrical pairing of PDCH/D(2,m) with PDCH/U(1,m).....	60
Annex C (normative):	GMR-1 3G Terminal Types	61
Annex D (informative):	Bibliography	69
History		70

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b01540e3-d6e2-4cfd-94c3-01e9f87082d5/etsi-ts-101-376-5-2-v3.1.1-2009-07>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The contents of the present document are subject to continuing work within TC-SES and may change following formal TC-SES approval. Should TC-SES modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 3.m.n

where:

- the third digit (n) is incremented when editorial only changes have been incorporated in the specification;
- the second digit (m) is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The present document is part 5, sub-part 2 of a multi-part deliverable covering the GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service, as identified below:

Part 1: "General specifications";

Part 2: "Service specifications";

Part 3: "Network specifications";

Part 4: "Radio interface protocol specifications";

Part 5: "Radio interface physical layer specifications":

Sub-part 1: "Physical Layer on the Radio Path: General Description";

Sub-part 2: "Multiplexing and Multiple Access; Stage 2 Service Description";

Sub-part 3: "Channel Coding";

Sub-part 4: "Modulation";

Sub-part 5: "Radio Transmission and Reception";

Sub-part 6: "Radio Subsystem Link Control";

Sub-part 7: "Radio Subsystem Synchronization";

Part 6: "Speech coding specifications";

Part 7: "Terminal adaptor specifications".

Introduction

GMR stands for GEO (Geostationary Earth Orbit) Mobile Radio interface, which is used for Mobile Satellite Services (MSS) utilizing geostationary satellite(s). GMR is derived from the terrestrial digital cellular standard GSM and supports access to GSM core networks.

The present document is part of the GMR Release 3 specifications. Release 3 specifications are identified in the title and can also be identified by the version number:

- Release 1 specifications have a GMR 1 prefix in the title and a version number starting with "1" (V1.x.x).
- Release 2 specifications have a GMPRS 1 prefix in the title and a version number starting with "2" (V2.x.x).
- Release 3 specifications have a GMR-1 3G prefix in the title and a version number starting with "3" (V3.x.x).

The GMR release 1 specifications introduce the GEO Mobile Radio interface specifications for circuit mode Mobile Satellite Services (MSS) utilizing geostationary satellite(s). GMR release 1 is derived from the terrestrial digital cellular standard GSM (phase 2) and it supports access to GSM core networks.

The GMR release 2 specifications add packet mode services to GMR release 1. The GMR release 2 specifications introduce the GEO Mobile Packet Radio Service (GMPRS). GMPRS is derived from the terrestrial digital cellular standard GPRS (included in GSM Phase 2+) and it supports access to GSM/GPRS core networks.

The GMR release 3 specifications evolve packet mode services of GMR release 2 to 3rd generation UMTS compatible services. The GMR release 3 specifications introduce the GEO-Mobile Radio Third Generation (GMR-1 3G) service. Where applicable, GMR-1 3G is derived from the terrestrial digital cellular standard 3GPP and it supports access to 3GPP core networks.

Due to the differences between terrestrial and satellite channels, some modifications to the GSM or 3GPP standard are necessary. Some GSM and 3GPP specifications are directly applicable, whereas others are applicable with modifications. Similarly, some GSM and 3GPP specifications do not apply, while some GMR specifications have no corresponding GSM or 3GPP specification.

Since GMR is derived from GSM and 3GPP, the organization of the GMR specifications closely follows that of GSM or 3GPP as appropriate. The GMR numbers have been designed to correspond to the GSM and 3GPP numbering system. All GMR specifications are allocated a unique GMR number. This GMR number has a different prefix for Release 2 and Release 3 specifications as follows:

- Release 1: GMR n xx.zyy.
- Release 2: GMPRS n xx.zyy.
- Release 3: GMR-1 3G xx.zyy

where:

- xx.0yy (z = 0) is used for GMR specifications that have a corresponding GSM or 3GPP specification. In this case, the numbers xx and yy correspond to the GSM or 3GPP numbering scheme.
- xx.2yy (z = 2) is used for GMR specifications that do not correspond to a GSM or 3GPP specification. In this case, only the number xx corresponds to the GSM or 3GPP numbering scheme and the number yy is allocated by GMR.
- n denotes the first (n = 1) or second (n = 2) family of GMR specifications.

A GMR system is defined by the combination of a family of GMR specifications and GSM and 3GPP specifications as follows:

- If a GMR specification exists it takes precedence over the corresponding GSM or 3GPP specification (if any). This precedence rule applies to any references in the corresponding GSM or 3GPP specifications.

NOTE: Any references to GSM or 3GPP specifications within the GMR specifications are not subject to this precedence rule. For example, a GMR specification may contain specific references to the corresponding GSM or 3GPP specification.

- If a GMR specification does not exist, the corresponding GSM or 3GPP specification may or may not apply. The applicability of the GSM or 3GPP specifications is defined in GMR-1 3G 41.201 [2].

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b01540e3-d6e2-4cfd-94c3-01e9f87082d5/etsi-ts-101-376-5-2-v3.1.1-2009-07>

1 Scope

The present document defines the structure of the physical channels for the radio subsystem in the GMR-1 3G Mobile Satellite System. It describes the GMR-1 3G concept of logical channels and the timing concepts of TDMA frames, timeslots, and bursts. It defines the relationship between logical and physical channels, and defines the logical channels in terms of size, structure and timing relationships.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] GMPRS-1 01.004 (ETSI TS 101 376-1-1): "GEO-Mobile Radio Interface Specifications (Release 2) General Packet Radio Service; Part 1: General specifications; Sub-part 1: Abbreviations and acronyms".

NOTE: This is a reference to a GMR-1 Release 2 specification. See the introduction for more details.

- [2] GMR-1 3G 41.201 (ETSI TS 101 376-1-2): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 3: General specifications; Sub-part 2: Introduction to the GMR-1 family".
- [3] GMR-1 3G 44.008 (ETSI TS 101 376-4-8): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 4: Radio interface protocol specifications; Sub-part 8: Mobile Radio Interface Layer 3 Specifications".
- [4] GMR-1 3G 45.003 (ETSI TS 101 376-5-3): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 5: Radio interface physical layer specifications; Sub-part 3: Channel Coding".
- [5] GMR-1 3G 45.004 (ETSI TS 101 376-5-4): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 5: Radio interface physical layer specifications; Sub-part 4: Modulation".
- [6] GMR-1 3G 45.005 (ETSI TS 101 376-5-5): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 5: Radio interface physical layer specifications; Sub-part 5: Radio Transmission and Reception".

- [7] GMR-1 3G 45.010 (ETSI TS 101 376-5-7): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 5: Radio interface physical layer specifications; Sub-part 7: Radio Subsystem Synchronization".
- [8] GMR-1 3G 43.064 (ETSI TS 101 376-3-22): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 3: Network specifications; Sub-part 22: Overall description of the GMPRS radio interface; Stage 2".
- [9] GMR-1 3G 44.060 (ETSI TS 101 376-4-12): "GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service; Part 4: Radio interface protocol specifications; Sub-part 12: Mobile Earth Station (MES) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol".
- [10] GMR-1 05.002 (ETSI TS 101 376-5-2): "GEO-Mobile Radio Interface Specifications; Part 5: Radio interface physical layer specifications; Sub-part 2: Multiplexing and Multiple Access; Stage 2 Service Description".

NOTE: This is a reference to a GMR-1 Release 1 specification. See the introduction for more details.

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in GMR-1 3G 41.201 [2] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in GMPRS-1 01.004 [1] apply.

4 General

Same as clause 4 in GMR-1 05.002 [10].

5 Logical channels

5.1 General

Same as clause 5.1 in GMR-1 05.002 [10].

5.2 Traffic channels

5.2.1 General

TCHs are intended to carry either encoded speech or user data. Three general types of traffic channels are defined:

- 1) TCH3: This channel carries data at a gross rate of 5,20 kbps.
- 2) TCH6: This channel carries data at a gross rate of 10,75 kbps.
- 3) TCH9: This channel carries data at a gross rate of 16,45 kbps.

The data gross rate is defined as the number of encoded bits in NT3, NT6 and NT9 burst, respectively, excluding the number of power control bits, divided by 40 ms frame time.

All traffic channels are bidirectional.

The types of traffic channels capable of speech and user data are identified in the following clauses.

5.2.2 Speech traffic channels

Same as clause 5.2.2 in GMR-1 05.002 [10].

5.2.3 Data traffic channels

Same as clause 5.2.3 in GMR-1 05.002 [10].

5.2.4 Summary of traffic channel characteristics

Table 5.1 summarizes the characteristics of traffic channels, where the gross transmission rate is the channel transmission bit rate (2 times channel transmission symbol rate) multiplied by the duty cycle of the channel.

Table 5.1: Summary of traffic channel characteristics

Channel type	User information capability	Gross transmission rate
TCH3	Encoded speech	5,85 kbps (= 46,8/8)
TCH6	User data: 4,8 kbps Fax: 2 kbps, 4 kbps or 4,8 kbps	11,70 kbps (= 46,8/8 x 2)
TCH9	User data: 9,6 kbps Fax: 2 kbps, 4 kbps, 4,8 kbps, or 9,6 kbps	17,55 kbps (= 46,8/8 x 3)

5.2.5 Packet Data Traffic CHannels (PDTCH) (A/Gb mode only)

The following Packet Data Traffic CHannels (PDTCH) apply to A/Gb mode.

A PDTCH corresponds to the resource allocated to a single MES on one physical channel for user data transmission. Different logical channels may be dynamically multiplexed on to the same PDTCH. The PDTCH uses $\pi/2$ -BPSK, $\pi/4$ -QPSK, 16 APSK, or 32 APSK modulation. All packet data traffic channels are unidirectional, either uplink (PDTCH/U), for a mobile-originated packet transfer or downlink (PDTCH/D) for a mobile-terminated packet transfer. PDTCH and PDTCH2 traffic data channels may be multiplexed on the same physical carrier.

PDTCHs are used to carry packet data traffic. Different PDTCHs are defined by the suffix (m,n) where m indicates the bandwidth of the physical channel in which the PDTCH is mapped, $m \times 31,25$ kHz, and n defines the number of timeslots allocated to this physical channel. Table 5.2 summarizes different types of packet traffic data channels, PDTCH (m, 3), (m = 4 and 5), where the burst duration is 5 ms, PDTCH (m, 6), (m = 1, 2), where the burst duration is 10 ms, and PDTCH (m, 12), (m = 5), where the burst duration is 20 ms

Table 5.2: Packet Traffic Data Channels (Peak Transmission Rates)

Channels	Direction (U: Uplink, D: Downlink)	Transmission symbol rate (ksps)	Channel Coding	Modulation	Peak payload transmission rate (without CRC) (kbps)	Peak payload transmission rate (with CRC) (kbps)
PDTCH(4,3)	U/D	93,6	Conv.	$\pi/4$ -QPSK	113,6	116,8
PDTCH(5,3)	U/D	117,0	Conv.	$\pi/4$ -QPSK	145,6	148,8
PDTCH(1,6)	U	23,4	Conv.	$\pi/4$ -QPSK	27,2	28,8
PDTCH(2,6)	D	46,8	Conv.	$\pi/4$ -QPSK	62,4	64,0
PDTCH2(5,12)	D	117,0	LDPC	$\pi/4$ -QPSK	199,2	199,6
PDTCH2(5,12)	D	117,0	LDPC	16-APSK	354,8	355,2
PDTCH2(5,12)	D	117,0	LDPC	32-APSK	443,6	444,0
PDTCH2(5,12)	U	117,0	LDPC	$\pi/4$ -QPSK	199,2	199,6
PDTCH2(5,12)	U	117,0	LDPC	16-APSK	399,2	399,6
PDTCH2(5,3)	U/D	117,0	LDPC	$\pi/4$ -QPSK	169,6	171,2
PDTCH2(5,3)	U/D	117,0	LDPC	16-APSK	342,4	344,0
PDTCH2(5,3)	U/D	117,0	LDPC	32-APSK	380,8	382,4

The payload is the Private Information (PRI) delivered to the physical layer by the link layer. The PRI includes the MAC header and the other higher layer overhead. The peak payload transmission rate (without CRC) is defined as the maximum attainable PRI data rate with continuous transmission, i.e. using all 24 timeslots in a frame. The above peak-rates are achieved with rate 3/4 coding for PDTCH(4,3) and PDTCH(5,3) and are achieved with rate 4/5 for PDTCH(1,6) and PDTCH(2,6). The peak rates of LDPC coded PDTCH2(5,12) and LDPC coded PDTCH2(5,3) are achieved for different modulation schemes with the following coding rate combinations:

- Downlink: 32 APSK Rate 4/5, 16 APSK Rate 4/5, $\pi/4$ -QPSK Rate 9/10.
- Uplink: 16 APSK Rate 9/10, $\pi/4$ -QPSK Rate 9/10.

NOTE: All the above coding rates are approximate rates. Refer to GMR-1 3G 45.003 [4] for the exact coding rates.

5.2.5a Packet Data Traffic Channels (PDTCH3) (Iu mode only)

The following Packet Data Traffic Channels³ (PDTCH3) apply to Iu mode.

A PDTCH3 corresponds to the resource allocated to a single MES on one physical channel for user data transmission. Different logical channels may be dynamically multiplexed on to the same PDTCH3. The PDTCH3 uses $\pi/2$ -BPSK, $\pi/4$ -QPSK, 16 APSK, or 32 APSK modulation. All packet data traffic channels are unidirectional, either uplink (PDTCH3/U), for a mobile-originated packet transfer or downlink (PDTCH3/D) for a mobile-terminated packet transfer. PDTCH3 may not be multiplexed with PDTCH and PDTCH2 on the same physical carrier.