

**Telecommunications and Internet converged Services and
Protocols for Advanced Networking (TISPAN);
Resource and Admission Control Sub-System (RACS):
Functional Architecture**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/472faa47-db12-4669-8ac4-6077173a896b/etsi-es-282-003-v3.4.1-2009-09>



Reference

RES/TISPAÑ-02072-NGN-R3

Keywords

architecture, control, system

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at www.etsi.org.

<http://portal.etsi.org/th/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

ETSI registered for the benefit of its Members and of the Sector
I T E™ is a Trade Mark of ETSI currently being registered

ETSI is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners

GSM® and the **GSM** logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions and abbreviations.....	12
3.1 Definitions.....	12
3.2 Abbreviations	14
4 General description of RACS.....	16
4.1 Functional overview	16
4.1.1 Global description.....	16
4.1.2 Basic functionalities.....	16
4.1.3 Restrictions applicable to the present document.....	17
4.2 Functional Requirements.....	17
4.2.1 R1 Requirements	17
4.2.1.1 Overall.....	17
4.2.1.2 Transport Control Service Requests.....	17
4.2.1.3 Resource Handling.....	18
4.2.1.4 QoS Management.....	19
4.2.1.5 Traffic Handling.....	19
4.2.1.6 Charging and Overload Control.....	20
4.2.2 R2 Requirements	20
4.2.2.1 Overall.....	20
4.2.2.2 Resource Handling	20
4.2.2.3 QoS Management.....	20
4.2.2.4 e2e QoS Handling	21
4.2.2.5 Multicast/Unicast Handling	21
4.2.2.6 Topology and Resource Information Retrieval	21
4.2.2.7 Network Deployment Scenarios.....	22
4.2.2.8 Charging and Overload Control	22
4.2.3 R3 Requirements	22
4.2.3.1 Interaction with the CPN.....	22
4.2.3.1.1 Direct control by RACS	22
5 RACS functional architecture derivation basis	22
5.1 Resource Control for Unicast and Multicast	23
5.1.1 Resource control scenarios	23
5.1.1.1 Identification of Resources	23
5.1.1.2 Multicast Resource Admission Decision Specifics	24
5.1.1.3 Resource Admission Decision Prerequisites	24
5.1.1.4 Resource Admission Control Approaches	25
5.1.1.5 Multicast Resource Admission Control in the Access Network Domain Transport Nodes	25
5.1.1.6 Unicast/Multicast Resource Reuse in the Access Segment.....	25
5.2 Charging	26
5.3 QoS Management Functions in Fixed Access Networks.....	26
5.4 Resource Control for QoS Downgrading	28
6 RACS functional architecture definition	29
6.1 General	29
6.2 Functional elements.....	31
6.2.1 SPDF.....	31
6.2.1.1 SPDF main functions	31
6.2.1.2 Summary of SPDF Elementary Functions	31
6.2.1.3 Reference points.....	33

6.2.1.4	User profile	33
6.2.1.5	Priority	33
6.2.1.6	Service request	34
6.2.1.7	Coordination function	34
6.2.1.8	Charging	35
6.2.1.9	Deployment considerations	35
6.2.1.10	Overload control	35
6.2.1.11	Discovery mechanism	35
6.2.2	Generic Resource Admission Control Function	35
6.2.2.1	Main functions	35
6.2.2.1.1	Specializations of x-RACF	36
6.2.2.1.2	Reference points applicable to different specializations of x-RACF	36
6.2.2.1.3	Multiple instantiations of x-RACF	36
6.2.2.2	Summary of generic Resource Admission Control Function Elementary Functions	37
6.2.2.3	A-RACF	39
6.2.2.3.1	A-RACF main functions	39
6.2.2.3.2	Reference points	39
6.2.2.4	C-RACF	40
6.2.2.4.1	C-RACF main functions	40
6.2.2.4.2	Reference points	40
6.2.2.5	Admission control process	40
6.2.2.5.1	A-RACF	40
6.2.2.5.2	C-RACF	42
6.2.2.6	Installation of policies	42
6.2.2.7	Charging	43
6.2.2.8	Abnormal condition handling	43
6.2.2.9	Deployment considerations	43
6.2.2.10	Overload control	43
6.2.2.11	Discovery Mechanism	43
6.2.3	BGF	43
6.2.3.1	BGF main functions	43
6.2.3.2	BGF parameters	44
6.2.3.3	Reference points	44
6.2.3.4	Addressing latching	44
6.2.3.5	Abnormal conditions handling	44
6.2.3.6	Overload control	44
6.2.4	RCEF	45
6.2.4.1	RCEF main functions	45
6.2.4.2	Reference points	45
6.2.4.3	RCEF parameters	45
6.2.5	Application Function (AF)	45
6.2.5.1	AF main functions	45
6.2.5.2	Reference points	46
6.2.5.3	Charging	47
6.2.5.4	Abnormal conditions handling	47
6.2.6	BTF	47
6.3	RACS reference points	47
6.3.1	Rq reference point (SPDF - x-RACF)	47
6.3.1.1	Functional requirements	47
6.3.1.1.1	Resource management mechanisms	47
6.3.1.1.2	Service model	48
6.3.1.1.3	Duration semantics	48
6.3.1.1.4	Audit and synchronization support	49
6.3.1.1.5	Report facilities for unsolicited events	49
6.3.1.2	Non-functional requirements	49
6.3.1.2.1	Reliability requirements	49
6.3.1.2.2	Security requirements	49
6.3.1.3	Information exchanged over the Rq Reference Point	49
6.3.1.3.1	Resource Reservation Request	49
6.3.1.3.2	Resource Modification Request	51
6.3.1.3.3	Resource Request/Modification Confirmation	52
6.3.1.3.4	Resource Release Request	52

6.3.1.3.5	Abort Resource Reservation	52
6.3.2	e4 reference point (A-RACF - NASS)	53
6.3.3	Ia Reference Point (SPDF - BGF)	53
6.3.3.1	Functional Requirements	53
6.3.3.1.1	Control of NAT, Hosted NAT traversal and Gating	53
6.3.3.1.2	Transport Protocol Type Policing	53
6.3.3.1.3	Bandwidth control	53
6.3.3.1.4	QoS marking	53
6.3.3.1.5	Usage metering and statistics reporting	53
6.3.3.1.6	Resource state synchronization	54
6.3.3.2	Non-Functional Requirements	54
6.3.3.2.1	Reliability requirements	54
6.3.3.2.2	Security requirements	54
6.3.3.3	Information exchanged over the Ia Reference Point	54
6.3.3.3.1	BGF Service Request	54
6.3.3.3.2	BGF Service Confirmation	57
6.3.3.3.3	BGF Service Modify Request	58
6.3.3.3.4	BGF Service Modify Confirmation	59
6.3.3.3.5	BGF Service Audit Request	60
6.3.3.3.6	BGF Service Audit Response	61
6.3.3.3.7	BGF Service Notify Request	62
6.3.3.3.8	BGF Service Notify Indication	63
6.3.3.3.9	BGF Service Release Request	63
6.3.3.3.10	BGF Service Release Confirmation	64
6.3.4	Gq' Reference Point (AF - SPDF)	65
6.3.4.1	Functional Requirements	65
6.3.4.2	Non-Functional Requirements	65
6.3.4.3	Information exchanged over the Gq' Reference Point	65
6.3.5	Ri' Reference Point (SPDF-SPDF inter-domain)	66
6.3.5.1	Functional Requirements	66
6.3.5.1.1	Resource management mechanisms	66
6.3.5.1.2	Service model	66
6.3.5.1.3	Duration semantics	66
6.3.5.1.4	Audit and Synchronization support	67
6.3.5.1.5	Report facilities for unsolicited events	67
6.3.5.2	Non-Functional Requirements	67
6.3.5.2.1	Reliability requirements	67
6.3.5.2.2	Security requirements	67
6.3.5.3	Information exchanged over the Ri' Reference Point	67
6.3.6	Rd' Reference Point (SPDF-SPDF intra-domain)	67
6.3.6.1	Functional Requirements	67
6.3.6.1.1	Resource management mechanisms	67
6.3.6.1.2	Service model	67
6.3.6.1.3	Duration semantics	68
6.3.6.1.4	Audit and Synchronization support	68
6.3.6.1.5	Report facilities for unsolicited events	68
6.3.6.2	Non-Functional Requirements	68
6.3.6.2.1	Reliability requirements	68
6.3.6.2.2	Security requirements	68
6.3.6.3	Information exchanged over the Rd' Reference Point	68
6.3.7	Re Reference Point (x-RACF - RCEF)	68
6.3.7.1	Functional Requirements	68
6.3.7.1.1	Policy Enforcement Management	68
6.3.7.2	Non-functional requirements	69
6.3.7.2.1	Reliability requirements	69
6.3.7.2.2	Security requirements	69
6.3.7.3	Information exchanged over the Re Reference Point	70
6.3.7.3.1	Information exchanged by using the push mode	70
6.3.7.3.1.1	Policy Enforcement Install Request	70
6.3.7.3.1.2	Policy Enforcement Modification Request	71
6.3.7.3.1.3	Policy Query Request	73
6.3.7.3.1.4	Policy Enforcement Installation/Modification Confirmation	73

6.3.7.3.1.5	Policy Query Confirmation.....	74
6.3.7.3.1.6	Policy Enforcement Release Request.....	75
6.3.7.3.2	Information exchanged by using the pull mode.....	76
6.3.7.3.2.1	Policy Decision Install Request	76
6.3.7.3.2.2	Policy Decision Modification Request.....	77
6.3.7.3.2.3	Policy Decision Deactivation Request	79
6.3.7.3.2.4	Policy Decision Install Response	79
6.3.7.3.2.5	Policy Decision Modification Response	81
6.3.7.3.2.6	Policy Decision Deactivation Response.....	82
6.3.7.3.3	Information exchanged by using both QoS mechanisms.....	83
6.3.7.3.3.1	Event Subscription Request	83
6.3.7.3.3.2	Event Notification Indication.....	84
6.3.8	Rr Reference Point (x-RACF - x-RACF intra-domain).....	84
6.3.8.1	Functional Requirements	84
6.3.8.1.1	Overall features	84
6.3.8.1.2	Resource management mechanisms	85
6.3.8.1.3	Service model.....	86
6.3.8.1.4	Duration semantics	86
6.3.8.1.5	Audit and Synchronization support	86
6.3.8.1.6	Report facilities for unsolicited events	87
6.3.8.2	Non-Functional Requirements	87
6.3.8.2.1	Reliability requirements	87
6.3.8.2.2	Security requirements	87
6.3.8.3	Information exchanged over the Rr Reference Point	87
6.3.8.3.1	Information exchanged over the Rr Reference Point for request model.....	87
6.3.8.3.1.1	Resource Reservation Request.....	87
6.3.8.3.1.2	Resource Modification Request.....	88
6.3.8.3.1.3	Resource Request/Modification Confirmation	89
6.3.8.3.1.4	Resource Release Request	90
6.3.8.3.1.5	Abort Resource Reservation	90
6.3.8.3.2	Information exchanged over the Rr Reference Point for delegated model	90
6.3.8.3.2.1	Resource Delegation Request	90
6.3.8.3.2.2	Resource Delegation Confirmation	91
6.3.8.3.2.3	Resource Delegation Push	92
6.3.8.3.2.4	Resource Delegation Push Response	93
6.3.8.3.2.5	Resource Delegation Query	93
6.3.8.3.2.6	Resource Delegation Query Response	94
6.3.9	Rf Reference Point (SPDF-Charging Functions and x-RACF-Charging Functions).....	94
6.4	RACS Flows: Interaction Procedures.....	94
6.4.1	Subscriber Attaches to the Access Network	95
6.4.2	Request Resource.....	95
6.4.2.1	Request Resource by using the push mode	95
6.4.2.1.1	Admission control using push mode when only one x-RACF is involved	95
6.4.2.1.2	Admission control using push mode when multiple x-RACFs are involved	97
6.4.2.1.2.1	Use of request bulk resources	97
6.4.2.1.2.2	Use of Rr request model	98
6.4.2.2	Request Resource by using the pull mode	100
6.4.2.2.1	Admission control using pull mode when only one x-RACF is involved	100
6.4.2.2.2	Admission control using pull mode when multiple x-RACFs are involved	101
6.4.2.3	Request resource by combining push and pull mode	102
6.4.3	Request Resource Wholesale/Retail Scenario	105
6.4.3.1	Request Resource with access to the A-RACF in the retail domain	105
6.4.3.2	Request Resource without access to the A-RACF in the retail domain	107
6.4.4	Release Resource	109
6.4.4.1	Release Resource Request by using the push mode	109
6.4.4.2	Release Resource Request by using the pull mode	110
6.4.4.2.1	Resource Release using pull mode when only one x-RACF is involved.....	110
6.4.4.2.2	Resource release using pull mode when multiple x-RACFs are involved.....	111
6.4.5	Commit Resources procedure	112
6.4.6	Resource Modification Request.....	113
6.4.6.1	Resource Modification Request by using the push mode.....	113
6.4.6.2	Resource Modification Request by using the pull mode	114

6.4.7	RACS Retrieves Access Profile from NASS	115
6.4.8	Subscriber Detaches from the access network	115
6.4.9	Abnormal event from the RCEF	117
6.4.10	Report of BGF Events.....	117
6.4.11	Indication of a BGF Service Failure (Autonomous Release of BGF).....	118
Annex A (informative):	Binding Information in RACS, NASS and AF	120
Annex B (informative):	Policy nomenclature for RACS	121
B.1	Overview	121
B.2	Policy Terminology	121
B.2.1	Policy.....	121
B.2.2	Conditions	121
B.2.3	Actions	121
B.2.4	Events	121
B.3	Types of Policy.....	122
B.3.1	Authorization Policy.....	122
B.3.2	Obligation Policy.....	122
B.3.3	Traffic Policy.....	122
B.3.4	Control Policy	122
Annex C (informative):	Admission control scenarios	123
C.1	Example of the handling of Connection Oriented network in the aggregation segment	123
Annex D (informative):	Network deployment scenarios.....	124
D.1	Resource control scenarios according to distribution of Service-based Policy Decision and Admission Control Functions	124
D.1.1	Single NGN operator performs Service-based Policy Decision and Admission Control Functions	124
D.1.1.1	Scenario Overview.....	124
D.1.1.2	Business Need.....	124
D.1.1.3	Mapping to TISPAN Architecture: RACS requirements.....	125
D.1.1.4	Technical Analysis.....	125
D.1.1.4.1	Functional Element Analysis	125
D.1.1.4.2	Elementary Functions Analysis.....	125
D.1.1.4.3	Reference Point Analysis	125
D.1.2	Service-based Policy Decision function handled in two domains	125
D.1.2.1	Scenario Overview.....	125
D.1.2.2	Business Need.....	126
D.1.2.3	Mapping to TISPAN Architecture: RACS requirements.....	126
D.1.2.4	Technical Analysis.....	126
D.1.2.4.1	Functional Element Analysis	126
D.1.2.4.2	Elementary Functions Analysis.....	126
D.1.2.4.3	Reference Point Analysis	126
D.1.3	Service-based Policy Decision and Admission Control functions distributed across two domains	127
D.1.3.1	Scenario Overview.....	127
D.1.3.2	Business Need.....	127
D.1.3.3	Mapping to TISPAN Architecture: RACS requirements.....	127
D.1.3.4	Technical Analysis.....	128
D.1.3.4.1	Functional Element Analysis	128
D.1.3.4.2	Elementary Functions Analysis.....	128
D.1.3.4.3	Reference Point Analysis	128
D.2	Resource control scenarios for Multicast and Unicast	128
D.2.1	Independent scenario - Unicast and Multicast admission control are separated.....	128
D.2.1.1	Scenario Overview.....	128
D.2.1.2	Business Need.....	128
D.2.1.3	Mapping to TISPAN Architecture: RACS requirements.....	128
D.2.1.4	Technical Analysis.....	129
D.2.1.4.1	Functional Element Analysis	129

D.2.1.4.2	Elementary Functions Analysis.....	129
D.2.1.4.3	Reference Point Analysis	129
D.2.2	Synchronized Scenario	129
D.2.2.1	Scenario Overview.....	129
D.2.2.2	Business Need.....	129
D.2.2.3	Mapping to TISPAN Architecture: RACS requirements.....	129
D.2.2.4	Technical Analysis.....	129
D.2.2.4.1	Functional Element Analysis	129
D.2.2.4.2	Elementary Functions Analysis.....	129
D.2.2.4.3	Reference Point Analysis	130
D.2.3	Integrated scenario - Integrated Unicast and Multicast Admission Control.....	130
D.2.3.1	Scenario Overview.....	130
D.2.3.2	Business Need.....	130
D.2.3.3	Mapping to TISPAN Architecture: RACS requirements.....	130
D.2.3.4	Technical Analysis.....	130
D.2.3.4.1	Functional Element Analysis	130
D.2.3.4.2	Elementary Functions Analysis.....	130
D.2.3.4.3	Reference Point Analysis	130
D.3	Resource control scenario for Metro Network	131
D.3.1	Scenario Overview	131
D.3.2	Business Need	131
D.3.3	Mapping to TISPAN Architecture: RACS requirements	131
D.3.4	Technical Analysis	131
D.3.4.1	Functional Element Analysis	131
D.3.4.2	Elementary Functions Analysis	131
D.3.4.3	Reference Point Analysis	132
D.4	Resource control scenario for CPNs.....	132
D.4.1	Scenario Overview.....	132
D.4.2	Business Need.....	132
D.4.3	Mapping to TISPAN Architecture: RACS requirements.....	133
D.4.4	Technical Analysis.....	133
D.4.4.1	Functional Element Analysis	133
D.4.4.2	Elementary Functions Analysis.....	133
D.4.4.3	Reference Point Analysis	133

Annex E (informative): Topology and Resource Management Use Cases and Elementary Functions 134

E.1	Topology and Resource Management Use Cases	134
E.1.1	Initial RACS Startup	134
E.1.2	Network Auto-Discovery	135
E.1.3	Managing Network Elements	135
E.1.4	Managing Network Topology	136
E.1.5	Real-Time Monitoring.....	136
E.1.5.1	Real-time Monitoring (Network Integration)	136
E.1.5.2	Real-time Monitoring (OSS Integration)	137
E.1.5.3	OSS-based Monitoring	138
E.1.6	Just-In-Time Information Pull	138
E.2	Topology and Resource Management Elementary Functions	139
E.2.1	Provisioning Elementary Function	139
E.2.2	Discovery Elementary Function	139
E.2.3	Partitioning Elementary Function.....	139
E.2.4	Monitoring Elementary Function	139
E.3	Topology and Resource Management Architectural Models	140
E.3.1	Centralized Model	140
E.3.2	Distributed Model.....	141

Annex F (informative): Architectural scenarios for supporting unicast and multicast..... 143

F.1	Example of an NGN Access Network Architecture for support of Multicast Resource Admission Control.....	143
-----	--	-----

F.2	Scenario for supporting multicast in push mode	144
F.3	Scenario for supporting multicast with UE requested QoS policy-pull mode	145
F.4	Scenario for supporting service authorization control when multicast uses the pull mode.....	145

Annex G (informative): Information flows for supporting unicast and multicast.....147

G.1	Information flows for enabling and disabling the multicast service	147
G.1.1	Control flow for enabling multicast service	147
G.1.2	Control flow for disabling multicast service	149
G.2	Information flows for supporting multicast in pull mode	150
G.2.1	Request Resource in the pull mode	150
G.2.2	Multicast stream in pull mode when a A-RACF is present in the AN	151
G.2.3	Multicast stream in pull mode when a A-RACF is not present in the AN and the content is in the IP_Edge	153
G.2.4	Multicast stream in pull mode when a A-RACF is not present in the AN and the content is in the AN	154
G.2.5	Multicast Admission Control for the Access Segment only.....	156
G.2.6	Multicast Admission Control when the maximum bandwidth associated with Multicast service is over-provisioned in the aggregation segment and beyond.....	157
G.3	Information flows for supporting multicast in mixed push and pull mode	159
G.3.1	Multicast stream in mixed push and pull mode when a A-RACF is present in the AN	159
G.3.2	Multicast stream in mixed push and pull mode when a A-RACF is not present in the AN and the content is in the IP_Edge	161
G.3.3	Multicast stream in mixed push and pull mode when a A-RACF is not present in the AN and the content is in the AN	163
G.4	Information flows for supporting combined unicast and multicast together with resource handling ..	165
G.4.1	Unicast and multicast services do NOT share resources on the Access Segment	165
G.4.2	Unicast and multicast applications share resources on the Access Segment	167
G.4.3	Unicast and multicast applications share resources on the Access Segment	169

Annex H (informative): Session modification procedures174

H.1	The status of the connection during the session modification	174
H.2	The session modification procedure.....	174

Annex I (informative): Change history.....179

History	181
---------------	-----

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN), and is now submitted for the ETSI standards Membership Approval Procedure.

The present document describes the architecture of the Resource and Admission Control Sub-System (RACS) identified in the overall TISPAN NGN architecture.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/472faa47-db12-4669-8ac4-6077173a896b/etsi-es-282-003-v3.4.1-2009-09>

1 Scope

The present document describes the functional architecture of the Resource and Admission Control Sub-System (RACS), for TISPAN NGN Release 3, in line with the service requirements described in TS 181 005 [1], in line with the QoS Requirements described in TS 181 018 [13] and its role in the TISPAN NGN architecture as defined in ES 282 001 [2]. It specifies as well high level stage 2 requirements that are also considered when describing its functional operation.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TS 181 005: "Telecommunications and Internet Converged Services and Protocols for Advanced Networking (TISPAN); Service and Capability Requirements".
- [2] ETSI ES 282 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture".
- [3] IETF RFC 3312: "Integration of Resource Management and Session Initiation Protocol (SIP)".
- [4] IETF RFC 2475: "An Architecture for Differentiated Services".
- [5] ETSI ES 282 004: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture; Network Attachment Sub-System (NASS)".
- [6] ETSI TR 180 000: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Terminology".
- [7] ETSI TS 123 107: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Quality of Service (QoS) concept and architecture (3GPP TS 23.107)".
- [8] ITU-T Recommendation Y.1541: "Network performance objectives for IP-based services".
- [9] IETF RFC 3198: "Terminology for Policy-Based Management".

- [10] IETF RFC 2753: "A Framework for Policy-based Admission Control".
- [11] Broadband Forum: "Policy Control Framework for DSL", Draft Working Text WT-134.
- [12] Damianou, N. et. al.: "The Ponder policy based Management toolkit", August 2002.
- [13] ETSI TS 181 018: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Requirements for QoS in a NGN".
- [14] ETSI TS 187 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN SECurity (SEC); Requirements".
- [15] ETSI TS 185 005: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Services requirements and capabilities for customer networks connected to TISPAN NGN".
- [16] ETSI TS 123 228: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IMS Multimedia Subsystem (IMS); Functional Architecture".
- [17] IETF RFC 2474: "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI TS 182 027: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IPTV Architecture; IPTV functions supported by the IMS subsystem".
- [i.2] ETSI ES 283 026: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control; Protocol for QoS reservation information exchange between the Service Policy Decision Function (SPDF) and the Access-Resource and Admission Control Function (A-RACF) in the Resource and Protocol specification".
- [i.3] ETSI TS 183 017: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control: DIAMETER protocol for session based policy set-up information exchange between the Application Function (AF) and the Service Policy Decision Function (SPDF); Protocol specification".
- [i.4] ETSI TS 185 003: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Customer Network Gateway (CNG) Architecture and Reference Points".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 180 000 [6] and the following apply:

access network policies: policies which are used to make decisions for resource admission control and are designed to derive the traffic policies to be enforced by the A-RACF

NOTE: Access network policies are constructed using Conditions and Actions that are specifically supported by A-RACFs. An example would be a policy which checks the condition that resources are available and the action to reserve the resource.

Application Function (AF): functional entity that offers applications the control of IP bearer resources when required

NOTE: The AF is capable of communicating with the RACS to transfer dynamic QoS-related service information.

application session: end-to-end user session, which is setup by an AF (using SIP or another protocol) and requires one or more resource reservations to take place

NOTE: An application session may involve one, two or more end users.

BGF service: traffic flow function performed by the BGF Functional Entity on media flows and/or the allocation of BGF resources

DiffServ: DiffService networks classify packets into one of a small number of aggregated flows or "classes", based on the DiffService code point (DSCP) in the packet's IP header

gate: operates on a unidirectional flow of packets, i.e. in either the upstream or downstream direction

NOTE: A gate consists of a packet classifier, and a gate status (open/closed). When a gate is open, the packets in the flow are accepted. When a gate is closed, all of the packets in the flow are dropped.

"Last mile" access network segment: comprises the functional elements that enable communication between a CPN and an Access Node

local A-RACF policies: specific Access network policies that are currently active on an A-RACF (may be a subset of all access network policies)

NOTE: Local A-RACF policies are instances of Access network policies.

local SPDF policies: specific Service based policies that are currently active on an SPDF (may be a subset of all service based policies)

NOTE: Local SPDF policies are instances of Service based policies.

media flow: uni-directional media stream of a particular type, which is specified by two endpoint identifiers, bandwidth and class of service

NAT: generic term for Network Address Translation that includes NAT-PT and NA(P)T

overbooking admission control: situation whereby the A-RACF considers that different AF-sessions can reserve the same resources bearing in mind that these resources cannot be committed to more than one AF-session at a time

NOTE: This enables optimal resource management in certain service conditions (e.g. Call Hold, Communication waiting).

path-coupled signalling: mode of signalling where the signalling messages follow a path that is tied to the data packets

NOTE: Signalling messages are routed only through the nodes that are in the data path.

policy: set of rules which govern the choices in behaviour of a system and that comprises conditions and actions, where conditions are evaluated when triggered by an event

NOTE 1: See annex B for further details.

NOTE 2: The content of policies is outside of the scope of the present document.

QoS classes: As defined in ITU-T Recommendation Y.1541 [8] and TS 123 107 [7].

QoS "Push" model: model where the RACS "pushes" traffic policies to the transport functions to enforce its policy decisions

NOTE: In this model, the CPN does not itself support native application independent QoS procedures.