
**Durum wheat semolinas — Determination
of the undersize fraction**

Semoules de blé dur — Détermination du taux d'affleurement

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 15793:2000](https://standards.iteh.ai/catalog/standards/sist/96fe9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000)

<https://standards.iteh.ai/catalog/standards/sist/96fe9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15793:2000

<https://standards.iteh.ai/catalog/standards/sist/96fe9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000>

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 15793 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 4, *Cereals and pulses*.

Annex A of this International Standard is for information only.

Full STANDARD PREVIEW
(standards.iteh.ai)

[ISO 15793:2000](https://standards.iteh.ai/catalog/standards/sist/96fef9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000)

<https://standards.iteh.ai/catalog/standards/sist/96fef9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15793:2000

<https://standards.iteh.ai/catalog/standards/sist/96fef9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000>

Durum wheat semolinas — Determination of the undersize fraction

1 Scope

This International Standard specifies a method for the determination of the undersize fraction of durum wheat semolinas, which is an important characteristic.

It is applicable to samples of at least 1 kg of durum wheat semolina obtained solely by comminution, without subsequent combination, having a moisture content higher than 10 % and packaged in fully filled airtight packaging.

It is not applicable to determinations carried out using sieves of aperture size below 160 μm .

NOTE Determination of the undersize fraction is sometimes termed "granulation of semolinas".

2 Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 712, *Cereals and cereal products — Determination of moisture content — Routine reference method*.

3 Term and definition

For the purposes of this International Standard, the following term and definition applies.

3.1

undersize fraction of semolina

by convention, the percentage of semolina which passes through the sieve specified for the semolina in question, under the operating conditions described in this International Standard

4 Principle

The semolina under test is sieved using a chosen sieve of specified aperture size, in accordance with the procedure described in this International Standard.

5 Apparatus

Usual laboratory equipment and, in particular, the following.

5.1 Laboratory sieving machine¹⁾, capable of being set at 200 r/min \pm 5 r/min as well as at sieving amplitudes of 30 mm \pm 2 mm and 60 mm \pm 2 mm, and equipped with a sieve blocking system.

5.2 Circular sieve, with sieving medium, cover and receiver, in stainless steel or similar material, having the following characteristics:

- a) frame diameter: 200 mm;
- b) useful diameter of sieving medium: 185 mm \pm 5 mm, corresponding to a sieving surface area of approximately 270 cm²;
- c) height: 20 mm minimum;
- d) aperture size (or void): the following list gives examples of aperture sizes²⁾ of sieving media currently used in European and international transactions:
 - 160 μ m \pm 6,9 μ m,
 - 180 μ m \pm 7,6 μ m,
 - 200 μ m \pm 8,3 μ m,
 - 250 μ m \pm 9,9 μ m,
 - 300 μ m \pm 11 μ m,
 - 315 μ m \pm 12 μ m,
 - 425 μ m \pm 15 μ m,
 - 500 μ m \pm 18 μ m.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/96fe9a2-4673-4337-a364-62bae4fb9ddc/iso-15793-2000>

5.3 Rubber balls (eight), having a diameter of 18 mm \pm 1 mm and a mass of 5 g \pm 0,5 g.

5.4 Spatula.

5.5 Soft-haired brush.

5.6 Flat container, having a capacity of approximately 2 litres, made of a non-electrostatic material.

5.7 Dishes (two), of suitable dimensions, made of a non-electrostatic material.

5.8 Analytical balance, capable of being read to the nearest 0,001 g.

5.9 Chronometer, capable of being read to the nearest 1 s.

6 Sampling

Sampling is not a part of the method specified in this International Standard. A recommended sampling method is given in ISO 13690 [2].

1) ROTACHOC is an example of a suitable apparatus and is supplied by Tripette et Renaud (France). This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this apparatus. Equivalent apparatus may be used if it can be shown to give the same results.

2) The tolerances are as given in ISO 3310-1 [1].

It is important that the laboratory receive a sample which is truly representative and has not been damaged or changed during transport or storage.

7 Preparation of test sample

Pour the entire contents of a package of approximately 1 kg of semolina into the container (5.6). Mix it carefully in order to make it as homogeneous as possible. The homogenization may be carried out by a mixing device if its container is made of non-electrostatic material.

8 Determination of moisture content of the sample

Determine separately the moisture content of the prepared test sample (clause 7) in accordance with ISO 712.

The moisture content shall be between 10 % and 15,50 %.

If this is not the case, the procedure described in clause 9 is not applicable (in accordance with clause 1).

9 Procedure

9.1 General

The operations described in 9.2 to 9.3.8 inclusive shall be carried out in less than 15 min.

9.2 Test portion

From the test sample prepared according to clause 7, immediately take, using a spatula (5.4), a test portion of $50 \text{ g} \pm 0,5 \text{ g}$, weighed to the nearest $0,01 \text{ g}$ (m).

9.3 Determination

9.3.1 Place the sieve, appropriate for the type of semolina to be tested, on the receiver (5.2) and put eight rubber balls (5.3) in the sieve.

9.3.2 Pour the test portion (9.2) into the sieve and put on the cover. Place the assembly on the sieving machine (5.1) which is set at an amplitude of 60 mm. Block using the tightening system and disengage the sieve cleaning system if the appliance is equipped with one.

9.3.3 Start the chronometer (5.9) and the sieving machine (5.1) simultaneously. Sieve the test portion for $5 \text{ min} \pm 5 \text{ s}$.

9.3.4 As soon as the sieving machine stops, release the tightening system and remove the assembly.

9.3.5 Remove the cover. Brush off (5.5) the particles of semolina adhering to the underside of the sieve into the receiver to avoid loss.

9.3.6 Discard the semolina remaining on the sieve.

9.3.7 Transfer quantitatively the contents of the receiver (the undersize fraction) into a dish (5.7), then weigh to the nearest $0,01 \text{ g}$ (m).

9.3.8 Conduct a new determination by sampling another test portion (9.2) and proceeding as described in 9.3.1 to 9.3.7.

9.4 Calculation

Calculate the undersize fraction (T) of each test portion of the semolina according to the following equation:

$$T = \frac{m}{m_0} \times 100 \%$$

where

m is the mass, in grams, of the undersize fraction obtained;

m_0 is the mass, in grams, of the test portion.

Calculate the arithmetic mean of the two determinations and express the results to the nearest 0,01 %.

10 Expression of results

10.1 Examine the repeatability of the measurements by taking the following criteria into consideration.

a) If the mean value is higher than 15 %

Accept the result only if both values do not differ by more than $\pm 1,0 \%$ (i.e. $\pm 0,50$ g).

b) If the mean value is lower than 15 %

Accept the result only if both values do not differ by more than $\pm 0,5 \%$ (i.e. $\pm 0,25$ g).

If the result does not meet the criteria given in a) and b), repeat all of the operations with two other test portions.

10.2 If the repeatability conditions are fulfilled, examine whether the mean value obtained is higher or lower than 15 % (i.e. 7,5 g).

a) If the mean value is higher than 15 %

Accept this value as the final result of the test and express it to the nearest 0,1 %.

b) If the mean value is lower than 15 %

Repeat the operations with two other test portions following the same procedure as previously described (see 9.2 to 9.4), but modifying the operating conditions as follows:

- in 9.2: using a spatula (5.4), take a test portion of $100 \text{ g} \pm 0,50 \text{ g}$, weighed to the nearest 0,01 g;
- in 9.3.1: put four rubber balls (5.3) into the sieve;
- in 9.3.2: set the sieving machine (5.1) at an amplitude of $30 \text{ mm} \pm 2 \text{ mm}$.

Proceed as before on two test portions. Calculate the arithmetical mean of the two results and express it to the nearest 0,01 %.

Examine the repeatability of the measurements taking the following criteria into consideration.

- 1) **If the mean value is higher than 15 %:** accept the result only if both values do not differ by more than $\pm 1,0 \%$ (i.e. $\pm 1,0$ g).

- 2) **If the mean value is lower than 15 %:** accept the result only if both values do not differ by more than $\pm 0,5 \%$ (i.e. $\pm 0,50 \text{ g}$).

10.3 If the result does not meet these criteria, repeat all of the operations with two other test portions proceeding as described in 10.2 b). Otherwise, take the arithmetical mean as the final result and express it to the nearest 0,01 %.

11 Precision

11.1 Interlaboratory test

Details of an interlaboratory test on the precision of the method are summarized in annex A. The values derived from this interlaboratory test may not be applicable to concentration ranges and matrices other than those given.

11.2 Repeatability

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will in not more than 5 % of cases be greater than the values specified, as appropriate, in 10.1 or 10.2 b).

11.3 Reproducibility

The absolute difference between two single test results, obtained using the same method on identical test material in different laboratories with different operators using different equipment, will in not more than 5 % of cases be greater than 25 % of the arithmetic mean of the two results, with minimum and maximum tolerances of 2 g and 10 g respectively.

NOTE These values correspond to what can be currently obtained, account being taken of the "rules of the game". Indeed, if a certain scattering of results is observed, it is not solely due to the method, but also results from the tolerances authorized for the sieve aperture sizes.

12 Test report

The test report shall specify:

- all information necessary for the complete identification of the sample;
- the sampling method used, if known;
- the test method used and the aperture size chosen, with reference to this International Standard;
- all operating details not specified in this International Standard, or regarded as optional, together with details or any incidents which may have influenced the test result(s);
- the test result(s) obtained or, if the repeatability has been checked, the final quoted result obtained.