

---

---

**Identification cards — Contactless  
integrated circuit(s) cards — Proximity  
cards —**

Part 2:

**Radio frequency power and signal interface**

iTeh STANDARD PREVIEW

*Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact —  
Cartes de proximité*

*Partie 2: Puissance de la fréquence radio et interface du signal*

[ISO/IEC 14443-2:2001](https://standards.iso.org/standards/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001)

[https://standards.itih.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-  
f953079f9a6/iso-iec-14443-2-2001](https://standards.itih.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 14443-2:2001

<https://standards.iteh.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001>

© ISO/IEC 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

# Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions .....	1
4 Symbols and abbreviated terms .....	2
5 Initial dialogue for proximity cards.....	3
6 Power transfer.....	3
6.1 Frequency.....	3
6.2 Operating field.....	3
7 Signal interface .....	3
8 Communication signal interface Type A.....	4
8.1 Communication PCD to PICC.....	4
8.1.1 Bit rate.....	4
8.1.2 Modulation.....	4
8.1.3 Bit representation and coding.....	6
8.2 Communication PICC to PCD.....	7
8.2.1 Bit rate.....	7
8.2.2 Load modulation.....	7
8.2.3 Subcarrier.....	7
8.2.4 Subcarrier modulation .....	7
8.2.5 Bit representation and coding.....	7
9 Communication signal interface Type B.....	8
9.1 Communication PCD to PICC.....	8
9.1.1 Bit rate.....	8
9.1.2 Modulation.....	8
9.1.3 Bit representation and coding.....	8
9.2 Communication PICC to PCD.....	9
9.2.1 Bit rate.....	9
9.2.2 Load modulation.....	9
9.2.3 Subcarrier.....	9
9.2.4 Subcarrier modulation .....	9
9.2.5 Bit representation and coding.....	9
10 PICC minimal coupling zone .....	10
Annex A (informative) Compatibility with other card standards.....	11

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 14443-2 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Identification cards and related devices*.

ISO/IEC 14443 consists of the following parts, under the general title *Identification cards — Contactless integrated circuit(s) cards — Proximity cards*:

— Part 1: *Physical characteristics*

— Part 2: *Radio frequency power and signal interface*

— Part 3: *Initialization and anticollision*

— Part 4: *Transmission protocol*

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14443-2:2001](https://standards.iteh.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001)

<https://standards.iteh.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001>

Annex A of this part of ISO/IEC 14443 is for information only.

## Introduction

ISO/IEC 14443 is one of a series of International Standards describing the parameters for identification cards as defined in ISO/IEC 7810 and the use of such cards for international interchange.

This part of ISO/IEC 14443 describes the electrical characteristics of two types of contactless interface between a proximity card and a proximity coupling device. The interface includes both power and bi-directional communication.

This part of ISO/IEC 14443 does not preclude the incorporation of other standard technologies on the card, such as those referenced in Annex A.

Contactless card standards cover a variety of types as embodied in ISO/IEC 10536 (close-coupled cards), ISO/IEC 14443 (proximity cards), ISO/IEC 15693 (vicinity cards). These are intended for operation when very near, nearby and at a longer distance from associated coupling devices respectively.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this part of ISO/IEC 14443 may involve the use of patents.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holders of these patent rights have assured ISO and IEC that they are willing to negotiate licences under reasonable and non discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of patent rights are registered with ISO and IEC. Information may be obtained from:

US Patent US5359323

<https://standards.iteh.ai/en/standards/iec/66879dbd-10a4-43d1-a9a9-f9538798a6/iso-iec-14443-2-2001>

FRANCE TELECOM

Centre National d'Etudes des  
Télécommunications  
38-40 rue de Général Leclerc  
92794 Issy-les-Molineaux  
Cedex 9  
France

WO 98/26370

Clause 9.1.2 (Type B) Modulation

WO 98/26370 A1 (pending)

US Patent US 5613159 (Type B)

Europe 0 901 670

French Patent App 96.15163

Int Pat App

PCT/FR97/02229

Innovatron Electronique / RATP

sub clause 9.1.2 and 9.1.3.

INNOVOTRON

Director of International Operations

Innovotrol

1 Rue Danton

75006 Paris

France

MOTOROLA

Motorola ESG

207 route de Ferney

P O Box 15

1218 Grand-Saconnex

Geneva

Switzerland

## ISO/IEC 14443-2:2001(E)

OMRON  
Intellectual Property Department  
Law & Intellectual Property H.Q.  
20, Igadera Shimokaiinji  
Nagaokakyo City  
Kyoto 617-8510  
Japan

Patent EP 0 492 569 B1

A system and method for the non-contact transmission of data.

ON-TRACK INNOVATIONS  
Z.H.R. Industrial Zone  
P O Box 32  
Rosh-Pina 12000  
Israel

PHO 90.508  
EP-PS 047 35 69  
(CH,DE,FR,GB,NL)  
JP-A 91-211035  
US-PS 5 345 231  
AT-PS 395 224

Relates to "radio interference interface" as specified in ISO/IEC 14443-2

PHILIPS  
Director  
Koninklijke Philips Electronics N.V.  
P. O. Box 220  
5600 AE Eindhoven  
The Netherlands

Japan patent: 2705076  
Japan Utility: 2137036  
Europe patent: 324564  
Europe patent: 435137

Describing the methods of returning signals from PICC, and related to the load switching technology. Both Type A and Type B are using this technology

SONY CORPORATION  
Intellectual Property Department  
Communications Systems Solutions  
Network Co.  
6-7-37 Kitashinagawa  
Shinagawa-ku  
Tokyo, 141-0001  
Japan

iTeh STANDARD PREVIEW  
(standards.itteh.ai)

<https://standards.itteh.ai/catalog/standards/sist/66879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001>

The following companies may hold patents relating to this part of ISO/IEC 14443 but have not provided details of the patents or agreed to provide licences.

US 4 650 981

WAYNE S FOLETTA  
CA 95129, USA  
4760 Castlewood Drive  
San Jose, California CA 9512  
USA

US Patent No. 4, 661,691

JOHN W HALPERN  
C/O Vincent M DeLuca  
Rothwell, Figg, Ernst & Kurz, p.c.  
555 Thirteenth Street, N.W.  
Suite 701 East Tower  
Washington, D.C. 20004

WO 89 05549 A

MAGELLAN CORPORATION  
8717 Research Drive  
Irvine  
CA 92618  
USA

Attention is drawn to the possibility that some of the elements of this part of ISO/IEC 14443 may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

# Identification cards — Contactless integrated circuit(s) cards — Proximity cards —

## Part 2: Radio frequency power and signal interface

### 1 Scope

This part of ISO/IEC 14443 specifies the characteristics of the fields to be provided for power and bi-directional communication between proximity coupling devices (PCDs) and proximity cards (PICCs).

This part of ISO/IEC 14443 is intended to be used in conjunction with other parts of ISO/IEC 14443.

This part of ISO/IEC 14443 does not specify the means of generating coupling fields, nor the means of compliance with electromagnetic radiation and human exposure regulations which can vary according to country.

### 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 14443. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/IEC 14443 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to apply. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/IEC 7816-2, *Information technology – Identification cards – Integrated circuit(s) cards with contacts – Part 2: Dimensions and location of the contacts*

ISO/IEC 10373-6, *Identification cards – Test methods – Proximity cards*

ISO/IEC 14443-1, *Identification cards – Contactless integrated circuit(s) cards – Proximity cards – Part 1: Physical characteristics*

ISO/IEC 14443-3, *Identification cards – Contactless integrated circuit(s) cards – Proximity cards – Part 3: Initialization and anticollision*

### 3 Terms and definitions

For the purposes of this part of ISO/IEC 14443, the following terms and definitions apply.

#### 3.1

##### **bit duration**

time during which a logic level is defined, at the end of which a new bit starts

**3.2**  
**binary phase shift keying**

phase shift keying where the phase shift is 180°, resulting in two phase state possibilities

**3.3**  
**modulation index**

defined as  $[a-b]/[a+b]$  where  $a$  and  $b$  are the peak and minimum signal amplitude respectively. The value of the index may be expressed as a percentage

**3.4**  
**NRZ-L**

method of bit coding whereby a logic level during a bit duration is represented by one of two defined physical states of a communication medium

**3.5**  
**subcarrier**

signal of frequency  $f_s$  used to modulate a carrier of frequency  $f_c$

**3.6**  
**Manchester**

method of bit coding whereby a logic level during a bit duration is represented by a sequence of two defined physical states of a communication medium. The order of the physical states within the sequence defines the logical state

**3.7**  
**TR0**

guard time between the end of a PCD transmission and the start of the PICC subcarrier generation

**3.8**  
**TR1**

synchronization time between the start of the PICC subcarrier generation and the start of the PICC subcarrier modulation

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO/IEC 14443-2:2001  
<https://standards.iteh.ai/catalog/standards/sist/68879dbd-10a4-43d1-a9a9-f953079f9a6/iso-iec-14443-2-2001>

**4 Symbols and abbreviated terms**

- ASK Amplitude Shift Keying
- BPSK Binary Phase Shift Keying
- $f_c$  Frequency of operating field (carrier frequency)
- $f_s$  Frequency of subcarrier modulation
- NRZ-L Non-Return to Zero (L for level)
- OOK On/Off Keying
- PCD Proximity Coupling Device
- PICC Proximity Card
- RF Radio Frequency



## 5 Initial dialogue for proximity cards

The initial dialogue between the PCD and the PICC shall be conducted through the following consecutive operations:

- activation of the PICC by the RF operating field of the PCD;
- the PICC shall wait silently for a command from the PCD;
- transmission of a command by the PCD;
- transmission of a response by the PICC.

These operations shall use the RF power and signal interface specified in the following clauses.

## 6 Power transfer

The PCD shall produce an energizing RF field which couples to the PICC to transfer power and which shall be modulated for communication.

### 6.1 Frequency

The frequency  $f_c$  of the RF operating field shall be 13,56 MHz  $\pm$ 7 kHz.

### 6.2 Operating field

The minimum unmodulated operating field shall be  $H_{min}$  and has a value of 1,5 A/m rms.

The maximum unmodulated operating field shall be  $H_{max}$  and has a value of 7,5 A/m rms.

A PICC shall operate as intended continuously between  $H_{min}$  and  $H_{max}$ .

A PCD shall generate a field of at least  $H_{min}$  and not exceeding  $H_{max}$  at manufacturer specified positions (operating volume).

In addition the PCD shall be capable of powering any single reference PICC (defined in ISO/IEC 10373-6) at manufacturer specified positions (operating volume).

The PCD shall not generate a field higher than the value specified in ISO/IEC 14443-1 (alternating magnetic field) in any possible PICC position.

Test methods for the PCD operating field are defined in ISO/IEC 10373-6.

## 7 Signal interface

Two communication signal interfaces, Type A and Type B, are described in the following clauses.

The PCD shall alternate between modulation methods when idling before detecting the presence of a PICC of Type A or Type B.

Only one communication signal interface may be active during a communication session until deactivation by the PCD or removal of the PICC. Subsequent session(s) may then proceed with either modulation method.

Figure 1 is an illustration of the concepts described in the following clauses.