



SLOVENSKI STANDARD

SIST ISO 15739:2011

01-julij-2011

Fotografija - Digitalno upodabljanje mirujočih slik - Meritve slikovnega šuma

Photography - Electronic still-picture imaging - Noise measurements

Photographie - Imagerie des prises de vue électroniques - Mesurages du bruit

Ta slovenski standard je istoveten z: **ISO 15739:2003**

[SIST ISO 15739:2011](https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011)

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>

ICS:

37.040.99

Drugi standardi v zvezi s
fotografijo

Other standards related to
photography

SIST ISO 15739:2011

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15739:2011

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>

INTERNATIONAL STANDARD

**ISO
15739**

First edition
2003-05-01

Photography — Electronic still-picture imaging — Noise measurements

*Photographie — Imagerie des prises de vue électroniques —
Mesurages du bruit*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 15739:2011](https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011)

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>



Reference number
ISO 15739:2003(E)

© ISO 2003

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 15739:2011](https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011)

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	3
4.1 General	3
4.2 Illumination	3
4.3 Temperature and relative humidity	4
4.4 White balance	4
4.5 Infrared (IR) blocking filter	4
4.6 Photosite integration time	4
4.7 Colour noise weighting	4
4.8 Compression	4
5 Noise measurement procedures	5
5.1 General	5
5.2 Uniform field noise measurement methods	5
5.3 Cameras with removable lenses	5
5.4 Whole camera	6
5.5 Density measurements for methods 5.3 and 5.4	7
5.6 Test chart noise measurements	7
6 Calculation and reporting of results	8
6.1 General	8
6.2 Signal-to-noise ratios — large area	9
6.3 ISO DSC dynamic range	10
6.4 Visual noise measurements	11
6.5 Evaluation of noise measurements with software	11
Annex A (normative) Test chart	12
Annex B (normative) Noise component analysis	15
Annex C (informative) Visual noise measurements	18
Annex D (informative) Method for measuring edge noise	22
Annex E (informative) Incremental gain calculation	24
Bibliography	26

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15739 was prepared by Technical Committee ISO/TC 42, *Photography*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15739:2011

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>

Introduction

Noise is an important attribute of electronic photographic systems. Standardization assists users and manufacturers in determining the quality of images that may be obtained from an electronic still-picture camera. The camera noise measurements described in this International Standard are performed in the digital domain, using digital analysis techniques. For electronic cameras that include only analogue outputs, the analogue signal has to be digitized, so that the digital measurement can be performed. The digitizing equipment has to be characterized, so that the effects of the digitization can be removed from the measurement results. When this is not possible, the type of digitizing equipment used is to be reported along with the measurement results.

Since the noise performance of an image sensor may vary significantly with exposure time and operating temperature, these operating conditions are specified. The visibility of noise to human observers depends on the magnitude of the noise, the apparent tone of the area containing the noise and the spatial frequency of the noise. The magnitude of the noise present in an output representation depends on the noise present in the stored image data and the contrast amplification or gain applied to the data in producing the output. The noise visibility is different for the luminance (or monochrome) channel and the colour (or colour difference) channels. Therefore, this International Standard accounts for these factors in measuring and reporting the camera noise measurements. Annex A gives the construction of an ISO standard camera noise test chart. Annex B specifies the method for determining the components of the digital camera noise from a number of samples. Annex C describes a procedure using a human visual model as a method for weighting the spectral components of the noise.

Many electronic still-picture cameras use extensive signal processing to reduce noise in uniform areas, and the noise levels measured in the large area test defined in this International Standard may not be representative of the noise levels found in the pictures taken by the camera. Therefore, new methods of measuring edge noise have been investigated. One method is described in Annex D. The incremental gain calculation is given in Annex E.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15739:2011

<https://standards.iteh.ai/catalog/standards/sist/9da55709-be5d-4fe2-ab55-772af590230d/sist-iso-15739-2011>

Photography — Electronic still-picture imaging — Noise measurements

1 Scope

This International Standard specifies methods for measuring and reporting the noise versus signal level and dynamic range of electronic still-picture cameras. It applies to both monochrome and colour electronic still-picture cameras.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7589:2002, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 12232:1998, *Photography — Electronic still-picture cameras — Determination of ISO speed*

ISO 14524:1999, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

ITU-R BT.709-5, *Parameter values for the HDTV Standards for production and International programme exchange*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

camera opto-electronic conversion function

camera OECF

opto-electronic conversion function

focal plane opto-electronic conversion function

relationship between the input scene log luminances and the digital output levels for an opto-electronic digital capture system

NOTE The units of measurement for this function are \log_{10} candelas per square metre.

3.2

digital output level

digital code value

numerical value assigned to a particular output level

3.3

digital still camera

DSC

camera incorporating an image sensor which outputs a digital signal representing a still picture, or records a digital signal representing a still picture on a removable medium, such as a memory card or magnetic disk

ISO 15739:2003(E)

3.4

electronic still-picture camera

camera incorporating an image sensor which outputs an analogue or digital signal representing a still picture, and/or records an analogue or digital signal representing a still picture on a removable medium, such as a memory card or magnetic disk

3.5

image sensor

electronic device which converts incident electromagnetic radiation into an electronic signal

NOTE A charge coupled device (CCD) array is an example of an electronic signal.

3.6

incremental gain function

change in the output level (digital code value) divided by the change in the input level (luminance or exposure) as a function of the light level

NOTE 1 For the determination of incremental gain values, log input values are not used.

NOTE 2 If the input exposure points are very finely spaced and the output noise is small compared to the quantization interval, the incremental gain function can have a jagged shape. Such behaviour is an artefact of the quantization process and is removed by using an appropriate smoothing algorithm, or by fitting a smooth curve to the data. In some cases, it may be desirable to fit a curve to the input-output data and then determine the incremental gain function by taking the first derivative of the function used for the curve fit.

3.7

incremental output signal

input level (luminance or exposure, not logged) multiplied by the system incremental gain at that level

3.8

incremental signal-to-noise ratio

ratio of the incremental output signal to the root mean square (rms) noise level at a particular signal level

NOTE This is typically expressed as a graph or table showing the rms noise level versus output signal level for the full range of output signal levels.

3.9

ISO DSC dynamic range

ratio of the maximum luminance level which appears unclipped to the minimum luminance level which can be reproduced with an incremental signal-to-temporal-noise ratio of at least 1, as determined in accordance with ISO 15739

3.10

noise

unwanted variations in the response of an imaging system

3.10.1

total noise

all the unwanted variations captured by a single exposure

3.10.2

fixed pattern noise

unwanted variations which are consistent for every exposure

3.10.3

temporally varying noise

random noise due to sensor dark current, photon shot noise, analogue processing and quantization, which varies from one image to the next

3.11**noise spectral power distribution**

curve or equation which expresses the camera output noise as a function of two-dimensional image spatial frequencies

3.12**photosite integration time**

total time period during which the photosites of an image sensor are able to integrate the light from the scene to form an image

3.13**signal processing**

operations performed by electronic circuits or algorithms which convert or modify the output of an image sensor

3.14**video signal-to-noise ratio**

ratio of the maximum (peak) output signal level to the root mean square (rms) noise level in video systems

NOTE 1 This value is typically expressed in decibels (dB).

NOTE 2 This term is not used to express the noise in an electronic still-picture imaging system.

4 Test conditions**4.1 General**

The following measurement conditions should be used as nominal conditions when measuring the noise of an electronic still-picture camera. If it is not possible or appropriate to achieve these nominal operating conditions, the actual operating conditions shall be listed along with the reported results.

4.2 Illumination**4.2.1 Characteristics**

The noise measurements shall indicate whether a source conforming to the daylight or tungsten illuminant was used. ISO 7589 describes the procedures for determining if the characteristics of the illumination used in a specific speed rating determination test are an acceptable match to the daylight and tungsten sensitometric illuminants.

4.2.2 Daylight illumination

For daylight measurements without the camera lens, a source conforming to the ISO sensitometric daylight illuminant specified in Table 1 of ISO 7589:2002 shall be used. This illuminant is defined as the product of the spectral power distribution of CIE illuminant D55 and the spectral transmittance of the ISO standard camera lens. For measurements with the camera lens in place, the spectral characteristics of the illuminant shall be equivalent to CIE illuminant D55.

4.2.3 Tungsten illumination

For tungsten measurements without the camera lens, a source conforming to the ISO sensitometric tungsten illuminant specified in Table 2 of ISO 7589:2002 shall be used. This illuminant is defined as the product of the average spectral power distribution of experimentally measured sources having a colour temperature of approximately 3 050 K and the spectral transmittance of the ISO standard camera lens. For measurements with the camera lens in place, the spectral characteristics of the illuminant shall be equivalent to the product of the average spectral power distribution of experimentally measured sources having a colour temperature of approximately 3 050 K.

ISO 15739:2003(E)

4.2.4 Reflection illumination

For measurements using a reflection test chart, the illumination should meet the uniformity requirements of the measurement procedures described in Clause 5. The sources are positioned so that the angular distribution of influx radiation is at its maximum at 45° to the test chart normal, and is negligible at angles of less than 40° or more than 50° to the normal, at any point on the test chart.

4.3 Temperature and relative humidity

The ambient room temperature during the acquisition of the test data shall be $23\text{ °C} \pm 2\text{ °C}$, as specified in ISO 554, and the relative humidity shall be $50\% \pm 20\%$. Additional measurements at 0 °C and 40 °C are recommended. The normal camera operating temperature (internal rise above ambient) shall be achieved before beginning the tests. If the ambient temperature varies throughout the room, for example as a result of heat generated by light sources, the ambient room temperature shall be measured at a distance of between 0,1 m and 0,2 m from the camera under test.

4.4 White balance

For a colour camera, the camera white balance shall be adjusted, if possible, to provide proper white balance (equal RGB signal levels) for the illumination light source, as specified in ISO 14524.

4.5 Infrared (IR) blocking filter

If required, an infrared blocking filter shall be used, as specified in ISO 14524.

4.6 Photosite integration time

The photosite integration time should not be longer than 1/30 s.

4.7 Colour noise weighting

For colour cameras using a single exposure process, the camera noise may be determined using a weighted sum of the colour outputs to derive the luminance. If the proper luminance weighting values for the RGB channel spectral sensitivities are known, they shall be used to calculate the luminance channel data. If these values are not known, the following weighting, given in ITU-R BT.709, shall be used:

$$Y = 0,2125 R + 0,7154 G + 0,0721 B \quad (1)$$

For colour cameras with luminance and colour-difference outputs, the standard deviation of the camera noise may be computed from the luminance channel standard deviation $\sigma(Y)$, the red minus luminance channel standard deviation $\sigma(R-Y)$ and the blue minus luminance channel standard deviation $\sigma(B-Y)$. The following Equation (2), as specified in 6.2.3 of ISO 12232:1998 shall be used:

$$\sigma(D_H) \text{ or } \sigma(D_L) = [\sigma(Y)^2 + 0,64 \sigma(R-Y)^2 + 0,16 \sigma(B-Y)^2]^{1/2} \quad (2)$$

4.8 Compression

If the electronic still-picture camera includes any form of lossy compression, the compression shall be disabled, if possible, during the noise measurements. If the compression cannot be turned off, then measurements should be taken and the compression level reported with the noise measurement result, for example, the actual camera switch setting (fine, standard, etc.) and the approximate average number of bits per pixel.