

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Maritime mobile transmitters and receivers
for use in the MF and HF bands;
Part 3: Harmonized EN covering essential requirements
under article 3.3(e) of the R&TTE Directive;
Equipment with integrated or associated equipment for
Class E Digital Selective Calling (DSC)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9ac2e60a-0929-4dca-a094-3d28627fadae/etsi-en-300-373-3-v1.1.2-2009-12>



Reference

REN/ERM-TG26-081-3

Keywordsmaritime, mobile, radio, regulation, selcall,
telephony**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Technical requirements specifications	11
4.1 Environmental profile.....	11
4.2 General, operational and technical requirements.....	11
4.2.1 General.....	11
4.2.2 General requirements	11
4.2.2.1 Composition	11
4.2.2.1.1 Audio frequencies interfaces	11
4.2.2.1.2 DSC Interface	11
4.2.2.1.3 Digital input panels.....	12
4.2.2.2 Construction	12
4.2.2.3 Controls and indicators	12
4.2.2.3.1 General	12
4.2.2.3.2 Illumination	12
4.2.2.4 Labelling	13
4.2.2.4.1 General	13
4.2.2.4.2 Distress frequencies	13
4.2.2.5 Protection against mishandling	13
4.2.3 Operational requirements.....	13
4.2.3.1 Frequency bands	13
4.2.3.1.1 MF band	13
4.2.3.1.2 HF bands.....	13
4.2.3.2 Classes of emission	14
4.2.4 Warming up period	14
4.2.4.1 Time	14
4.2.4.2 Heaters	14
4.2.4.3 Heating circuits	14
4.2.4.4 Delay.....	14
4.2.5 Technical requirements.....	14
4.2.5.1 Distress controls.....	14
4.2.5.2 Telephony transmit control	14
4.2.5.3 Misuse	14
4.2.5.4 Control panel priority.....	15
4.2.5.5 Manual gain control and Automatic Gain Control (AGC).....	15
4.2.5.6 Output indication.....	15
4.2.5.7 DSC operation.....	15
4.3 Environmental requirements	15
4.3.1 Vibration test	15
4.3.1.1 Definition	15
4.3.1.2 Requirement	15
4.3.1.3 Conformance.....	15
4.3.2 Temperature tests.....	15
4.3.2.1 Definition	15
4.3.2.2 Dry heat.....	15
4.3.2.2.1 Definition.....	15
4.3.2.2.2 Requirement	16

4.3.2.2.3	Conformance	16
4.3.2.3	Damp heat	16
4.3.2.3.1	Definition.....	16
4.3.2.3.2	Requirement	16
4.3.2.3.3	Conformance	16
4.3.2.4	Low temperature cycle.....	16
4.3.2.4.1	Definition.....	16
4.3.2.4.2	Requirement	16
4.3.2.4.3	Conformance	16
4.3.3	Corrosion test.....	16
4.3.3.1	Definition	16
4.3.3.2	Requirement	17
4.3.3.3	Conformance	17
4.3.4	Rain test	17
4.3.4.1	Definition	17
4.3.4.2	Requirement	17
4.3.4.3	Conformance.....	17
4.4	Conformance requirements	17
4.4.1	Unwanted frequency modulation	17
4.4.1.1	Definition	17
4.4.1.2	Limit.....	17
4.4.1.3	Conformance.....	17
4.4.2	Sensitivity of the microphone and the 600 Ω line inputs for SSB telephony.....	17
4.4.2.1	Definition	17
4.4.2.2	Limits	18
4.4.2.3	Conformance	18
4.4.3	Automatic level control and/or limiter for SSB telephony	18
4.4.3.1	Definition	18
4.4.3.2	Limits	18
4.4.3.3	Conformance.....	18
4.4.4	Audio frequency response of SSB telephony	18
4.4.4.1	Definition	18
4.4.4.2	Limits	19
4.4.4.3	Conformance.....	19
4.4.5	Residual hum and noise power for telephony.....	19
4.4.5.1	Definition	19
4.4.5.2	Limits	19
4.4.5.3	Conformance.....	19
4.4.6	Residual frequency modulation on DSC.....	20
4.4.6.1	Definition	20
4.4.6.2	Limits	20
4.4.6.3	Conformance.....	20
4.4.7	Continuous operation on telephony	20
4.4.7.1	Definition	20
4.4.7.2	Limits	20
4.4.7.3	Conformance.....	20
4.4.8	Protection of transmitter	20
4.4.8.1	Definition	20
4.4.8.2	Limits	20
4.4.8.3	Conformance.....	20
4.4.9	Receiver frequency error	20
4.4.9.1	Definition	20
4.4.9.2	Limits	21
4.4.9.3	Conformance.....	21
4.4.10	Unwanted frequency modulation	21
4.4.10.1	Definition	21
4.4.10.2	Limits	21
4.4.10.3	Conformance.....	21
4.4.11	Pass band	21
4.4.11.1	Definition	21
4.4.11.2	Limits	21
4.4.11.3	Conformance.....	21

4.4.12	Reciprocal mixing.....	21
4.4.12.1	Definition	21
4.4.12.2	Limits	21
4.4.12.3	Conformance.....	21
4.4.13	Harmonic content in output	22
4.4.13.1	Definition	22
4.4.13.2	Limits	22
4.4.13.3	Conformance.....	22
4.4.14	Audio frequency intermodulation.....	22
4.4.14.1	Definition	22
4.4.14.2	Limits	22
4.4.14.3	Conformance.....	22
4.4.15	Internally generated spurious signals.....	22
4.4.15.1	Definition	22
4.4.15.2	Limit.....	22
4.4.15.3	Conformance.....	22
4.4.16	AGC efficiency	22
4.4.16.1	Definition	22
4.4.16.2	Limits	23
4.4.16.3	Conformance.....	23
4.4.17	AGC time constants (attack and recovery time)	23
4.4.17.1	Definitions.....	23
4.4.17.2	Limits	23
4.4.17.3	Conformance.....	23
4.4.18	Protection of input circuits.....	23
4.4.18.1	Definition	23
4.4.18.2	Limits	23
4.4.18.3	Conformance.....	23
5	Testing for compliance with technical requirements.....	24
5.1	Test conditions, power supply and ambient temperatures.....	24
5.1.1	General.....	24
5.1.2	Test power source	24
5.1.3	Normal test conditions	24
5.1.3.1	Normal temperature and humidity	24
5.1.3.2	Normal test power source.....	24
5.1.3.2.1	Mains voltage and frequency	24
5.1.3.2.2	Secondary battery power sources	24
5.1.3.2.3	Other power sources.....	24
5.1.4	Extreme test conditions.....	25
5.1.4.1	Extreme temperature tests	25
5.1.4.2	Extreme values of test power source.....	25
5.1.4.2.1	Mains voltage and mains frequency	25
5.1.4.2.2	Secondary battery power sources	25
5.1.4.2.3	Other power sources	25
5.1.5	Artificial antennas.....	25
5.1.5.1	Transmitters	25
5.1.5.2	Receivers.....	25
5.1.6	Standard test signals.....	26
5.1.6.1	Test signals applied to the receiver input	26
5.1.6.1.1	Sources	26
5.1.6.1.2	Levels	26
5.1.6.2	Normal test signals.....	26
5.1.6.2.1	Class of emission J3E.....	26
5.1.6.2.2	Class of emission F1B	26
5.1.6.3	Choice of testing frequencies	26
5.1.7	Warming up period	26
5.1.7.1	Time	26
5.1.7.2	Heaters	26
5.2	Interpretation of the measurement results	27
5.3	Essential radio test suites.....	27
5.3.1	Environmental tests.....	27

5.3.1.1	Introduction	27
5.3.1.2	Procedure	27
5.3.1.3	Performance check	28
5.3.1.4	Vibration test.....	28
5.3.1.5	Temperature tests	29
5.3.1.5.1	Dry heat	29
5.3.1.5.2	Damp heat.....	29
5.3.1.5.3	Low temperature cycle	30
5.3.1.6	Corrosion test	30
5.3.1.6.1	General	30
5.3.1.6.2	Method of measurement	30
5.3.1.7	Rain test	31
5.3.1.7.1	General	31
5.3.1.7.2	Method of measurement	31
5.3.2	Conformance tests	31
5.3.2.1	Unwanted frequency modulation	31
5.3.2.2	Sensitivity of the microphone and the 600 Ω line inputs for SSB telephony	32
5.3.2.3	Automatic level control and/or limiter for SSB telephony	32
5.3.2.4	Audio frequency response of SSB telephony	32
5.3.2.5	Residual hum and noise power for telephony	33
5.3.2.6	Residual frequency modulation on DSC	33
5.3.2.7	Continuous operation on telephony.....	33
5.3.2.8	Protection of transmitter.....	33
5.4	Other test specifications	34
5.4.1	General.....	34
5.4.2	Receiver frequency error	34
5.4.3	Unwanted frequency modulation.....	34
5.4.4	Pass band	34
5.4.4.1	Class of emission J3E.....	34
5.4.5	Reciprocal mixing.....	35
5.4.6	Harmonic content in output	35
5.4.7	Audio frequency intermodulation	35
5.4.8	Internally generated spurious signals.....	35
5.4.9	AGC efficiency	36
5.4.9.1	Settings.....	36
5.4.9.2	Increase in Signal-to-Noise Ratio (SNR)	36
5.4.10	AGC time constants (attack and recovery time)	36
5.4.11	Protection of input circuits.....	36
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	37
Annex B (informative):	The EN title in the official languages	40
Annex C (informative):	Bibliography	41
History		42

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) [i.2] laying down a procedure for the provision of information in the field of technical standards and regulations and following the Commission Decision 2004/71/EC [i.5] of 4 September 2003.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.1] are given in annex A.

The present document is part 3 of a multi-part deliverable covering Maritime mobile transmitters and receivers for use in the MF and HF bands, as identified below:

- Part 1: "Technical characteristics and methods of measurement";
- Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN covering essential requirements under article 3.3(e) of the R&TTE Directive; Equipment with integrated or associated equipment for Class E Digital Selective Calling (DSC)".**

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

1 Scope

The present document applies to radio transmitters and receivers, for use on vessels operating in either the Medium Frequency (MF) 1 606,5 kHz to 4 000 kHz bands only, or in the Medium and High Frequency (MF/HF) 1 606,5 kHz to 27,5 MHz bands allocated in the International Telecommunications Union (ITU) Radio Regulations [1], to the Maritime Mobile Service (MMS).

The present document refers to equipment for one or more of the following:

- Single SideBand (SSB) modulation for telephony transmission and reception (J3E);
- Frequency Shift Keying (FSK) or SSB modulation of a keyed sub-carrier to transmit and receive Digital Selective Calling (DSC) signals.

The present document refers to radio equipment, which is either fitted with an integrated DSC controller or fitted with a dedicated interface for a DSC controller.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) article 3.3 e), which states that radio equipment within the scope of the present document shall be so constructed that: "it supports certain features ensuring access to emergency services".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.1] will apply to equipment within the scope of the present document.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ITU Radio Regulations (2008).
- [2] ETSI EN 300 373-2 (V1.1.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Maritime mobile transmitters and receivers for use in the MF and HF bands; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- [3] ISO 3791 (1976): "Office machines and data processing equipment - Keyboard layouts for numeric applications".

- [4] ETSI EN 300 338-4 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 4: Class E DSC".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.3] ITU-T Recommendation E.161 (2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [i.4] ETSI TR 100 028: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.5] Commission Decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS).
- [i.6] CENELEC EN 60945 (2002): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

assigned frequency: centre of the frequency band assigned to a station

carrier frequency: frequency to which the transmitter or receiver is tuned

environmental profile: range of environmental conditions under which equipment complies with the provisions of the present document

rated output power: (of the receiver) rated output power of the receiver is the output power of the receiver as declared by the manufacturer that complies with both the minimum audio power and maximum total harmonic distortion at the same time

standard output power: (of the receiver) is defined as:

- a) 1 mW for earphone reception;
- b) 500 mW for loudspeaker reception;
- c) 0 dBm into 600 Ω for the audio line outputs;

measured across a resistor equal to the nominal value of the load impedance as declared by the manufacturer

3.2 Symbols

For the purposes of the present document, the symbols given in the ITU Radio Regulations [1] and the following apply:

dB	decibel
dBm	dBmilliwatt
dB μ V	dBmicrovolt
F1B	frequency modulation, single channel containing quantized or digital information without the use of a modulating sub-carrier, telegraphy for automatic reception
g	gram
h	hour
Hz	hertz
J2B	SSB, suppressed carrier, single channel containing quantized or digital information with the use of a modulating sub-carrier, telegraphy for automatic reception
J3E	SSB, suppressed carrier, single channel containing analogue information, telephony
k	kilo
kHz	kilohertz
kPa	kilopascal
l	litre
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
mW	milliwatt
NaCl	sodium chloride
Ω	ohm
pF	picofarad
s	second
V	volt
W	watt

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AGC	Automatic Gain Control
DC	Direct Current
DSC	Digital Selective Calling
EMC	ElectroMagnetic Compatibility
emf	electromotive force
EUT	Equipment Under Test
FSK	Frequency Shift Keying
ISO	International Standards Organization
ITU	International Telecommunications Union
MF	Medium Frequency
MF/HF	Medium and High Frequency
MMS	Maritime Mobile Service
PEP	Peak Envelope Power
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
RMS	Root Mean Square
SINAD	Signal plus Noise plus Distortion to Noise plus Distortion
SNR	Signal-to-Noise Ratio
SSB	Single Side Band

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be determined by the environmental class of the equipment. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

4.2 General, operational and technical requirements

4.2.1 General

There are no essential test suites for the requirements in clause 4.2. The availability of the specified controls shall be verified by visual inspection.

4.2.2 General requirements

4.2.2.1 Composition

The equipment shall contain either:

- a dedicated watchkeeping receiver for the DSC decoder;
- a DSC encoder; and
- a DSC decoder.

Or:

- a dedicated DSC controller interface.

4.2.2.1.1 Audio frequencies interfaces

The following inputs and outputs applicable to the type of equipment shall be provided:

- a) transmitters:
 - SSB Telephony:
 - 600 Ω earth free audio input;
 - microphone input;
- b) receivers:
 - SSB Telephony:
 - 600 Ω earth free audio output;
 - earphone output;
 - speaker output.

4.2.2.1.2 DSC Interface

If the equipment does not have an integrated DSC controller then, the equipment shall have a dedicated interface for an external DSC controller compliant with EN 300 338-4 [4].

4.2.2.1.3 Digital input panels

Where a digital input panel with the digits "0" to "9" is provided, the digits shall be arranged to conform to ITU-T Recommendation E.161 [i.3]. However, where an alphanumeric keyboard layout is provided, the digits "0" to "9" may, alternatively, be arranged to conform to ISO 3791 [3].

4.2.2.2 Construction

The attention of the manufacturer is drawn to EN 60945 [i.6] which offers guidelines on the construction and ergonomic details for equipment intended to be used on board vessels.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

Adequately detailed operating instructions shall be provided with the equipment.

The equipment shall be capable of operating on single-frequency and two-frequency channels with manual control (simplex).

4.2.2.3 Controls and indicators

4.2.2.3.1 General

All controls shall be easily identified from the position at which the operator operates the equipment.

The number of operational controls, their design and manner of functioning, location, arrangement and size should provide for simple, quick and efficient operation. Controls which are not necessary for normal operation shall not be readily accessible to the operator.

The controls should be arranged in a manner which minimizes the risk of inadvertent operation.

For transmitters it shall be possible to change the transmitter from any class of emission to another for which it is designed to operate by means of not more than one control.

For receivers the class of emission shall be selectable by not more than one control.

Facilities shall be provided to enable the loudspeaker to be switched off when reception is by headphones or telephone handset. Automatic facilities shall be provided to turn off the loudspeaker during duplex operation.

If a device is provided in the receiver to reduce the effects of impulsive noise, a switch shall be provided to disable its function.

4.2.2.3.2 Illumination

Equipment intended to be installed on the navigating bridge of a ship shall be provided with adequate illumination to enable identification of controls and facilitate reading of indicators at all times. Means shall be provided for reducing continuously, to extinction, the output of any light source on the equipment which is capable of interfering with navigation.

All adjustments and controls necessary for switching the transmitter and receiver to operate on the distress and safety channels covered by the equipment shall be clearly marked in order that this operation can be easily performed.

If the accessible controls are located on a separate control panel and if there are two or more control panels, one of the control panels shall have priority over the others. If there are two or more control panels, when any control panel is in use, this shall be clearly indicated on all of the other control panels.