
**Ships and marine technology —
Drainage systems on ships and
marine structures —**

Part 5:

**Drainage of decks, cargo spaces and
swimming pools**

*Navires et technologie maritime — Installations de drainage sur navires
et structures maritimes —*

Partie 5: Drainage des ponts, des cales et des piscines

ISO 15749-5:2004

<https://standards.iteh.ai/catalog/standards/iso/084292dc-ced5-4b49-8f4e-c77a55e422f1/iso-15749-5-2004>



Reference number
ISO 15749-5:2004(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 15749-5:2004](https://standards.iteh.ai/catalog/standards/iso/084292dc-ced5-4b49-8f4e-c77a55e422f1/iso-15749-5-2004)

<https://standards.iteh.ai/catalog/standards/iso/084292dc-ced5-4b49-8f4e-c77a55e422f1/iso-15749-5-2004>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Drainage of exposed decks and non-weathertight spaces	2
5 Drainage of cargo holds on bulkhead decks of passenger ships and on freeboard decks, respectively, and on vehicle decks of cargo ships	3
6 Drainage of swimming pools	3
7 Wastewater discharges	4
8 Shut-off fittings (closing devices)	4
9 Piping	4
Annex A (informative) Diagram for the calculation of the amount of drainage	7

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 15749-5:2004](https://standards.iteh.ai/catalog/standards/iso/084292dc-ced5-4b49-8f4e-c77a55e422f1/iso-15749-5-2004)

<https://standards.iteh.ai/catalog/standards/iso/084292dc-ced5-4b49-8f4e-c77a55e422f1/iso-15749-5-2004>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15749-5 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 3, *Piping and machinery*.

ISO 15749 consists of the following parts, under the general title *Ships and marine technology — Drainage systems on ships and marine structures*:

- *Part 1: Sanitary drainage-system design*
- *Part 2: Sanitary drainage, drain piping for gravity systems*
- *Part 3: Sanitary drainage, drain piping for vacuum systems*
- *Part 4: Sanitary drainage, sewage disposal pipes*
- *Part 5: Drainage of decks, cargo spaces and swimming pools*

Ships and marine technology — Drainage systems on ships and marine structures —

Part 5: Drainage of decks, cargo spaces and swimming pools

1 Scope

This part of ISO 15749 applies to the planning and design of drain lines for gravity-operated conveyance of grey water from

- weather decks and non-weathertight spaces on ships and marine structures,
- ro-ro spaces,
- cargo spaces, and
- swimming pools.

NOTE Wastewater from spaces in which live animals are accommodated is classified as sewage water and shall be discharged in accordance with MARPOL regulations. For drainage of sewage, see ISO 15749-2 and ISO 15749-3.

For planning and basic requirements, see ISO 15749-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 65, *Carbon steel tubes suitable for screwing in accordance with ISO 7-1*

ISO 4200, *Plain end steel tubes, welded and seamless — General tables of dimensions and masses per unit length*

ISO 9329-1, *Seamless steel tubes for pressure purposes — Technical delivery conditions — Part 1: Unalloyed steels with specified room temperature properties*

ISO 9330-1, *Welded steel tubes for pressure purposes — Technical delivery conditions — Part 1: Unalloyed steel tubes with specified room temperature properties*

ISO 15749-1, *Ships and marine technology — Drainage systems on ships and marine structures — Part 1: Sanitary drainage-system design*

ISO 15749-4, *Ships and marine technology — Drainage systems on ships and marine structures — Part 4: Sanitary drainage, sewage disposal pipes*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15749-1 and the following definition apply.

3.1
drain line
pipeline which serves to carry wastewater from drains directly overboard or into the bilge using the gravity principle without a collector tank or sewage treatment plant being connected in between

4 Drainage of exposed decks and non-weathertight spaces

4.1 Basic considerations

4.1.1 Wastewater from exposed decks and superstructure or deckhouses, without weathertight doors, shall be discharged overboard.

4.1.2 Open superstructure decks may be drained directly overboard or via pipes leading from one deck to the next lower deck.

4.1.3 The weather deck shall be drained overboard mainly via openings in the bulwark. Residual wastewater that cannot be drained via these openings has to be discharged overboard via drain lines.

4.1.4 The drain line from the funnel or stack top should not terminate on an exposed deck owing to the soot that may be contained in the wastewater.

This line may, taking the quantity of wastewater occurring into consideration, be connected to other lines draining exposed decks and leading directly overboard.

4.2 Drains

Drains shall be fitted with water discharges without odour seals.

4.3 Piping

4.3.1 Types of pipes

For deck drainage, the following pipes may be used:

- steel pipes in accordance with 9.1;
- spigot and socket steel pipes, but only in the exposed superstructure deck area.

Plastic pipes may be used only with the approval of the classification society.

4.3.2 Nominal bore

The nominal bores of the above-mentioned pipes usually range from NB 40 to NB 150.

Table 1 gives information about the possible amount of drainage, depending on the nominal bore and assuming gravity delivery lines.