

SLOVENSKI STANDARD SIST EN ISO 11463:2008

01-julij-2008

?cfcn]'U_cj]b']b'n']h]b'!'JfYXbchYb'Y''Ua] UghY'_cfcn]'Y'flGC'%'(*'.%-)L

Corrosion of metals and alloys - Evaluation of pitting corrosion (ISO 11463:1995)

Corrosion des métaux et alliages - Évaluation de la corrosion par piqures (ISO 11463:1995)

(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN ISO 11463:2008

https://standards.iteh.ai/catalog/standards/sist/9df68426-3fa2-4aca-85e4-

d5be6ff7678d/sist-en-iso-11463-2008

ICS:

77.060 Korozija kovin Corrosion of metals

SIST EN ISO 11463:2008 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD

EN ISO 11463

NORME EUROPÉENNE EUROPÄISCHE NORM

April 2008

ICS 77.060

English Version

Corrosion of metals and alloys - Evaluation of pitting corrosion (ISO 11463:1995)

Corrosion des métaux et alliages - Évaluation de la corrosion par piqûres (ISO 11463:1995)

Korrosion von Metallen und Legierungen - Bewertung der Lochkorrosion (ISO 11463:1995)

This European Standard was approved by CEN on 21 March 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Iteland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

SIST EN ISO 11463:2008 https://standards.iteh.ai/catalog/standards/sist/9df68426-3fa2-4aca-85e4-d5be6ff7678d/sist-en-iso-11463-2008



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

EN ISO 11463:2008 (E)

Contents	Page
Foreword	3

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

The text of ISO 11463:1995 has been prepared by Technical Committee ISO/TC 156 "Corrosion of metals and alloys" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 11463:2008 by Technical Committee CEN/TC 262 "Metallic and other inorganic coatings" the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2008, and conflicting national standards shall be withdrawn at the latest by October 2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

iTeh STANDARD PREVIEW
Endorsement notice

The text of ISO 11463:1995 has been approved by CEN as a EN ISO 11463:2008 without any modification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

INTERNATIONAL STANDARD

ISO 11463

> First edition 1995-12-15

Corrosion of metals and alloys — Evaluation of pitting corrosion

iTeh STANDARD PREVIEW

Corrosion des métaux et alliages — Évaluation de la corrosion par piqûres (Standards.iteh.al)



ISO 11463:1995(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11463 was prepared by Technical Committee VIEW ISO/TC 156, Corrosion of metals and alloys. standards.iteh.ai)

Annexes A and B of this International Standard are for information only.

SIST EN ISO 11463:2008 https://standards.iteh.ai/catalog/standards/sist/9df68426-3fa2-4aca-85e4-d5be6ff7678d/sist-en-iso-11463-2008

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

It is important to be able to determine the extent of pitting, either in a service application where it is necessary to estimate the remaining life in a metal structure, or in laboratory test programmes that are used to select pitting-resistant materials for a particular service (see [1] in annex B).

The application of the materials to be tested will determine the minimum pit size to be evaluated and whether total area covered, average pit depth, maximum pit depth or another criterion is the most important to measure.

iTeh STANDARD PREVIEW (standards.iteh.ai)

iTeh STANDARD PREVIEW This page intentionally left blank (standards.iteh.ai)

SIST EN ISO 11463:2008

Corrosion of metals and alloys — Evaluation of pitting corrosion

1 Scope

This International Standard gives guidance on the selection of procedures that can be used in the identification and examination of pits and in the evaluation of pitting corrosion.

2 Normative reference Teh STANDARI

The following standard contains provisions which, ds. the pit of through reference in this text, constitute provisions of products this International Standard. At the time of publication, on the edition indicated was valid. All standards are sub-indards standards are sub-indards standards are sub-indards standards. Standards are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8407:1991, Corrosion of metals and alloys - Removal of corrosion products from corrosion test specimens.

3 Identification and examination of pits

3.1 Visual inspection

A visual examination of the corroded metal surface with or without the use of a low-power magnifying glass may be used to determine the extent of corrosion and the apparent location of pits. It is often advisable to photograph the corroded surface so that it can be compared with the clean surface after the removal of corrosion products.

3.1.1 If the metal specimen has been exposed to an unknown environment, the composition of the corrosion products may be of value in determining the cause of corrosion. Recommended procedures in the

removal of particulate corrosion products should be followed and reserved for future identification.

- **3.1.2** To expose the pits fully, it is recommended that cleaning procedures should be used to remove the corrosion products and avoid solutions that attack the base metal excessively (see ISO 8407). It may be advisable during cleaning to probe the pits with a pointed tool to determine the extent of undercutting or subsurface corrosion (see figure 1). However, scrubbing with a stiff-bristle brush will often enlarge the pit openings sufficiently by removal of corrosion products or undercut metal to make the pits easier to evaluate.
- **3.1.3** Examine the cleaned metal surface to determine the approximate size and distribution of pits. Follow this procedure by a more detailed examination through a microscope using low magnification (approximately × 20).
- **3.1.4** Determine the size, shape and density of pits.
- **3.1.4.1** Pits may have various sizes and shapes. A visual examination of the metal surface may show a round, elongated or irregular opening, but it seldom provides an accurate indication of corrosion beneath the surface. Thus it is often necessary to cross-section the pit to see its actual shape and to determine its true depth. Several variations in the cross-sectioned shape of pits are shown in figure 1.
- **3.1.4.2** It is difficult to determine pit density by counting pits through a microscope eyepiece, but the task may be made easier by the use of a plastic grid. Place the grid, containing 3 mm to 6 mm squares, on the metal surface. Count and record the number of pits in each square, and move across the grid in a systematic manner until all the surface has been covered. This approach minimizes eye-strain because the eyes can be taken from the field of view without fear of losing the area of interest. Enlarged photographs of the area of interest may also be used to reduce eyestrain.