

SLOVENSKI STANDARD SIST ISO 3019-1:2002

01-julij-2002

: `i]XbU'hY\ b]_U'!'<]XfUj `]_U'!'A YfY`]b`cnbU VY'df][fUXb]\ `df]fcVb]WhYf'[fYX]` fdU_]b`a chcf^Yj '!'%"XY'. '7 c`g_Y'j fghY'j 'a Yhfg_]\ `YbchU\

Hydraulic fluid power -- Dimensions and identification code for mounting flanges and shaft ends of displacement pumps and motors -- Part 1: Inch series shown in metric units

iTeh STANDARD PREVIEW

Transmissions hydrauliques -- Dimensions et code d'identification des flasques de montage et des bouts d'arbres des pompes volumétriques et moteurs -- Partie 1: Conversion en unités métriques de la série en inches

3c5a01234960/sist-iso-3019-1-2002
Ta slovenski standard je istoveten z: ISO 3019-1:2001

ICS:

23.100.10 Paalae[a] ^Á| aal ^Áa Á [d la Pumps and motors

SIST ISO 3019-1:2002 en

SIST ISO 3019-1:2002

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3019-1:2002</u> https://standards.iteh.ai/catalog/standards/sist/f800f549-30d6-4103-81c3-3c5a01234960/sist-iso-3019-1-2002 SIST ISO 3019-1:2002

INTERNATIONAL STANDARD

ISO 3019-1

Second edition 2001-06-01

Hydraulic fluid power — Dimensions and identification code for mounting flanges and shaft ends of displacement pumps and motors —

Part 1:

Teh Inch series shown in metric units

Transmissions hydrauliques Dimensions et code d'identification des flasques de montage et des bouts d'arbres des pompes volumétriques et moteurs 371SO 3019-12002

https://standards.iphai/catal Conversion en unités métriques de la série en inches 3c5a01234960/sist-iso-3019-1-2002



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3019-1:2002</u> https://standards.iteh.ai/catalog/standards/sist/f800f549-30d6-4103-81c3-3c5a01234960/sist-iso-3019-1-2002

© ISO 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 3019 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 3019-1 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 2, *Pumps, motors and integral transmissions*.

This second edition cancels and replaces the first edition (ISO 3019-1:1975), which has been technically revised.

ISO 3019 consists of the following parts under the general title Hydraulic fluid power — Dimensions and identification code for mounting flanges and shaft ends of displacement pumps and motors:

- Part 1: Inch series shown in metric units SIST ISO 3019-1:2002 https://standards.iteh.a/catalog/standards/sist/f800f549-30d6-4103-81c3-
- 3c5a01234960/sist-iso-3019-1-2002

— Part 2: Metric series

Annex A forms a normative part of this part of ISO 3019.

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Pumps convert mechanical power into hydraulic fluid power, while motors convert hydraulic fluid power into mechanical power.

This part of ISO 3019 provides composite dimension reference and identification codes for both pumps and motors, simplified dimensional interchangeability for their flanges and shafts, and preferred sizes and dimensions for new designs.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3019-1:2002</u> https://standards.iteh.ai/catalog/standards/sist/f800f549-30d6-4103-81c3-3c5a01234960/sist-iso-3019-1-2002

Hydraulic fluid power — Dimensions and identification code for mounting flanges and shaft ends of displacement pumps and motors —

Part 1:

Inch series shown in metric units

Scope

This part of ISO 3019 specifies sizes and dimensions and establishes an identification code for the two- and fourbolt mounting flanges and the shaft ends of positive-displacement, rotary hydraulic fluid power pumps and motors. It is applicable to cylindrical keyed shaft ends with an external thread, as well as to those without a thread, to conical keyed shaft ends with an external thread and to 30° involute spline shaft ends.

NOTE

Involute spline is in accordance with SAE J744 [1]. RD PREVIEW

(standards.iteh.ai)

Normative references 2

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 3019. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 3019 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 68-2, ISO general purpose screw threads — Basic profile — Part 2: Inch screw threads.

ISO 1101:—1), Geometrical Product Specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out.

ISO 5598, Fluid power systems and components — Vocabulary.

3 Terms and definitions

For the purposes of this part of ISO 3019, the terms and definitions given in ISO 5598 apply.

1) To be published. (Revision of ISO 1101:1983)

Dimensions

Tolerances 4.1

Dimensions shown without tolerances are nominal.

Tolerances of form and position are shown in accordance with ISO 1101.

Selection of mounting flanges and shaft ends

Select flange and shaft dimensions for pumps and motors manufactured in accordance with this part of ISO 3019 from Figures 1 to 6 and Tables 1 to 6, inclusive.

Shaft ends according to Figure 3 and Figure 6 may be provided with a tapped hole.

Mating components 4.3

The dimensions and related tolerances of the mating components shall be compatible with the dimensions and tolerances specified in this part of ISO 3019, thus avoiding undue body strain as well as transverse loads on shafts in excess of those permitted by the pump or motor manufacturer.

Identification code 5

iTeh STANDARD PREVIEW

Mounting flanges

Use the mounting flange identification code given in Table 1 and Table 2.

The number preceding the hyphen (-) is an approximation, in millimetres, of the mounting flange pilot diameter.

The number following the hyphen is the number of mounting bolt holes in the flange.

5.2 Shaft ends

Use the shaft end identification codes shown in Tables 3 to 6.

The number preceding the hyphen is an approximation, in millimetres, of the shaft major diameter.

The number following the hyphen is arbitrarily assigned as follows:

- cylindrical keyed shaft ends without thread, -1;
- cylindrical keyed shaft ends with external thread, -2;
- conical keyed shaft ends with external thread, -3;
- 30° involute spline shaft ends, -4.

Flange/shaft end combinations

Use the preferred flange or shaft end combinations given in Table 7. Use other combinations only when necessary, by agreement between the purchaser and the supplier.

7 Flange/shaft end concentricity and perpendicularity

Maintain flange or shaft end concentricity within 0,25 mm and perpendicularity within 0,002/1, in accordance with Figures 3 to 6.

NOTE Rigid couplings may require closer tolerances.

8 Identification statement (Reference to this part of ISO 3019)

It is strongly recommended that manufacturers use the following statement in test reports, catalogues and sales literature when electing to comply with this part of ISO 3019:

"Dimensions and identification code for mounting flanges and shaft ends in accordance with ISO 3019-1:2001, Hydraulic fluid power — Dimensions and identification code for mounting flanges and shaft ends of displacement pumps and motors — Part 1: Inch series shown in metric units."

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3019-1:2002</u> https://standards.iteh.ai/catalog/standards/sist/f800f549-30d6-4103-81c3-3c5a01234960/sist-iso-3019-1-2002

© ISO 2001 – All rights reserved