

**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 3: Medium Access Control (MAC) layer**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/86b739d3-178c-42d7-8e91-0ad350efd393/etsi-en-300-175-3-v2.3.1-2010-06>



Reference

REN/DECT-000254-3

Keywords

DECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
1 Scope	14
2 References	14
2.1 Normative references	15
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	16
4 Description of the MAC layer	19
4.1 MAC layer reference model	19
4.1.1 General.....	20
4.1.2 Cluster Control Function (CCF)	20
4.1.3 Cell Site Functions (CSF).....	20
4.1.4 Relationship to physical layer elements.....	20
4.2 Frame and multiframe structures.....	21
4.2.1 General.....	21
4.2.2 Frame structure	21
4.2.3 Multiframe structure	23
4.3 State definitions.....	23
4.3.1 PP states.....	23
4.3.2 RFP states	24
5 Overview of MAC layer services	25
5.1 General	25
5.1.1 Broadcast Message Control (BMC).....	25
5.1.2 Connectionless Message Control (CMC).....	25
5.1.3 Multi-Bearer Control	25
5.2 Service descriptions.....	25
5.2.1 Common functions.....	25
5.2.2 BMC service	26
5.2.3 CMC service	26
5.2.4 MBC services.....	26
5.3 Logical channels.....	27
5.3.1 MBC connection endpoints (MC-SAP logical channels)	27
5.3.1.1 The higher layer C-plane channels, C	27
5.3.1.2 The higher layer U-Plane channels, I	27
5.3.1.3 The higher layer U-Plane control channel, G _F	28
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	28
5.3.2 CMC endpoints (MB-SAP logical channels).....	28
5.3.2.1 The connectionless C-Plane channels, CL	28
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	29
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	29
5.3.3 BMC endpoint (MA-SAP logical channel).....	29
5.3.3.1 The slow broadcast channel, B _S	29
5.3.4 Internal MAC control channels.....	29
5.3.4.1 The system information channel, Q	29
5.3.4.2 Identities channel, N.....	30
5.3.4.3 The MAC control channel, M	30
5.3.4.4 MAC paging channel, P	30
5.4 SAP definitions	30
5.4.1 MA SAP	30
5.4.2 MB SAP.....	31
5.4.3 MC SAP.....	31

5.4.4	ME SAP	32
5.4.5	Order of transmission.....	32
5.5	Bearer.....	32
5.5.1	Bearer types	32
5.5.2	Bearer operation.....	33
5.6	Connection oriented services.....	33
5.6.1	Connection types	33
5.6.1.1	Basic connections.....	33
5.6.1.2	Advanced connections	34
5.6.1.2.1	Rules for ECN selection in advanced connections	34
5.6.1.3	Connection identifiers	34
5.6.1.4	Complementary connections	35
5.6.2	Symmetric and asymmetric connections.....	35
5.6.2.1	Symmetric connections	35
5.6.2.2	Asymmetric connections	40
5.7	Broadcast and connectionless services	48
5.7.1	The broadcast services	49
5.7.1.1	The continuous broadcast service	49
5.7.1.2	The non-continuous broadcast service	49
5.7.2	The connectionless services	50
5.7.2.1	Connectionless downlink services	50
5.7.2.2	Connectionless uplink services	50
6	Multiplexing.....	51
6.1	CCF multiplexing functions	51
6.2	CSF multiplexing functions.....	51
6.2.1	Bit Mappings (MAP)	56
6.2.1.1	D-field mapping (D-MAP).....	56
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	57
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	57
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	58
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	58
6.2.1.2	A-field Mapping (A-MAP)	59
6.2.1.3	B-field Mapping (B-MAP).....	60
6.2.1.3.1	Unprotected format.....	60
6.2.1.3.2	Encoded protected format.....	62
6.2.1.3.3	Multisubfield protected format.....	62
6.2.1.3.4	Singlesubfield protected format.....	64
6.2.2	Time multiplexers	66
6.2.2.1	Tail MULTipleXer (T-MUX)	66
6.2.2.1.1	T-MUX algorithm for RFP transmissions	66
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	67
6.2.2.2	B-field control multiplexer (E/U-MUX)	68
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes	70
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield	70
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation	84
6.2.2.4	Priority scheme in E or E+U mode	84
6.2.3	Encryption.....	85
6.2.4	Scrambling.....	86
6.2.5	Error control.....	88
6.2.5.1	R-CRC overview	88
6.2.5.2	R-CRC generation and checking.....	88
6.2.5.3	X-CRC overview.....	89
6.2.5.4	X-CRC generation and checking.....	89
6.2.5.5	B-CRC generation and checking.....	91
6.2.6	Broadcast controller.....	92
7	Medium access layer messages	92
7.1	Header field	92
7.1.1	Overview/formatting.....	92
7.1.2	Tail identification, TA, bits a_0 to a_2	93
7.1.3	The "Q1/BCK" bit, bit a_3	93

7.1.4	B-field identification, BA, bits a_4 to a_6	94
7.1.5	The "Q2" bit, bit a_7	95
7.2	Messages in the tail field	95
7.2.1	Overview	95
7.2.2	Identities information (N_T).....	95
7.2.3	System information and multiframe marker (Q_T)	96
7.2.3.1	General	96
7.2.3.2	Static system information.....	97
7.2.3.2.1	General, $Q_H = 0, 1$ (hex)	97
7.2.3.2.2	Q_H and Normal-Reverse (NR)	97
7.2.3.2.3	Slot Number (SN).....	97
7.2.3.2.4	Start Position (SP)	98
7.2.3.2.5	ESCAPE bit (ESC).....	98
7.2.3.2.6	Number of transceivers.....	98
7.2.3.2.7	Extended RF carrier information available (M_c).....	98
7.2.3.2.8	RF carriers available (RF-cars).....	99
7.2.3.2.9	Spare bits (SPR)	99
7.2.3.2.10	Carrier number.....	99
7.2.3.2.11	Spare bits (SPR)	99
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	100
7.2.3.3	Extended RF carrier information part 1	100
7.2.3.3.1	General, $Q_H = 2$ (hex).....	100
7.2.3.3.2	Further RF carrier extensions	101
7.2.3.3.3	Number of RF carriers.....	101
7.2.3.4	Fixed part capabilities	101
7.2.3.4.1	General, $Q_H = 3$ (hex)	101
7.2.3.4.2	Standard capabilities.....	101
7.2.3.5	Extended fixed part capabilities	102
7.2.3.5.1	General, $Q_H = 4$ (hex).....	102
7.2.3.5.2	Extended Physical and MAC layer capabilities.....	103
7.2.3.5.3	Extended higher layer capabilities.....	104
7.2.3.6	Secondary access rights identities	104
7.2.3.6.1	General, $Q_H = 5$ (hex).....	104
7.2.3.6.2	SARI message	104
7.2.3.7	Multiframe number	104
7.2.3.7.1	General, $Q_H = 6$ (hex).....	104
7.2.3.7.2	Multiframe number.....	104
7.2.3.8	Escape	105
7.2.3.8.1	General, $Q_H = 7$ (hex).....	105
7.2.3.8.2	Escape information.....	105
7.2.3.9	Extended RF carrier information part 2	105
7.2.3.9.1	General, $Q_H = 9$ (hex).....	105
7.2.3.10	Transmit information	105
7.2.3.10.1	General, $Q_H = B$ (hex)	105
7.2.3.11	Extended fixed part capabilities (part 2)	106
7.2.3.11.1	General, $Q_H = C$ (hex)	106
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2).....	106
7.2.3.11.3	Extended higher layer capabilities (part 2).....	107
7.2.4	Paging Tail (P_T)	107
7.2.4.1	General format	107
7.2.4.1.1	P_T format for full and long page messages	107
7.2.4.1.2	P_T format for short page messages	108
7.2.4.1.3	P_T format for zero length page messages.....	108
7.2.4.1.4	P_T format for MAC_Resume_and_Control_page message	108
7.2.4.2	P_T header format.....	109
7.2.4.2.1	General format.....	109
7.2.4.2.2	Bit a_8 is the extend flag.....	109
7.2.4.2.3	B_S SDU length indication	109
7.2.4.3	MAC layer information for PT.....	110
7.2.4.3.1	Information type	110
7.2.4.3.2	Fill bits / Blind long slot ($j=640$ / $j=672$) information.....	110
7.2.4.3.3	Blind full slot information	111

7.2.4.3.4	Bearer description.....	111
7.2.4.3.5	Escape.....	112
7.2.4.3.6	Dummy or connectionless downlink bearer marker	112
7.2.4.3.7	Bearer handover/replacement information	112
7.2.4.3.8	RFP status and modulation types.....	113
7.2.4.3.9	Active carriers	114
7.2.4.3.10	RFP power level	114
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	115
7.2.4.3.12	Extended modulation types	115
7.2.5	MAC control (M_T)	116
7.2.5.1	General format and contents	116
7.2.5.2	Basic connection control	116
7.2.5.2.1	General	116
7.2.5.2.2	Format for most messages	117
7.2.5.2.3	WAIT	117
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}	117
7.2.5.3	Advanced connection control.....	118
7.2.5.3.1	General	118
7.2.5.3.2	ACCESS_REQUEST	118
7.2.5.3.3	BEARER_HANDOVER_REQUEST	118
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST	118
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST	119
7.2.5.3.6	BEARER_CONFIRM	119
7.2.5.3.7	WAIT	119
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}	119
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}	122
7.2.5.3.10	Channel_list.....	122
7.2.5.3.11	Unconfirmed_dummy.....	123
7.2.5.3.12	Unconfirmed_handover.....	123
7.2.5.3.13	RELEASE	123
7.2.5.4	MAC layer test messages	124
7.2.5.4.1	Basic format	124
7.2.5.4.2	FORCE_TRANSMIT	125
7.2.5.4.3	LOOPBACK_DATA	125
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	126
7.2.5.4.5	ESCAPE	127
7.2.5.4.6	NETWORK_TEST.....	127
7.2.5.4.7	CLEAR_TEST_MODES.....	127
7.2.5.4.8	CHANGE_MODULATION_SCHEME	127
7.2.5.5	Quality control	128
7.2.5.5.1	Prolonged preamble diversity	129
7.2.5.6	Broadcast and connectionless services.....	130
7.2.5.7	Encryption control.....	130
7.2.5.8	B-field setup, first PT transmission.....	131
7.2.5.9	Escape	132
7.2.5.10	TARI message.....	132
7.2.5.11	REP connection control.....	132
7.2.5.11.1	General	132
7.2.5.11.2	Format for most messages	132
7.2.5.11.3	REP CHANNEL MAP REQUEST	133
7.2.5.11.4	REP CHANNEL MAP CONFIRM.....	133
7.3	Messages in the B-field	133
7.3.1	Overview	133
7.3.2	Advanced connection control	134
7.3.2.1	General format	134
7.3.2.2	BEARER_REQUEST	135
7.3.2.3	BEARER_CONFIRM.....	135
7.3.2.4	WAIT	136
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}	136
7.3.2.6	BANDWIDTH_B_{Req;Cfm}	137
7.3.2.7	CHANNEL_LIST	137
7.3.2.8	UNCONFIRMED_DUMMY.....	137

7.3.2.9	UNCONFIRMED_HANDOVER	138
7.3.2.10	RELEASE	138
7.3.3	Null or I _{PF} segmentation info	139
7.3.3.1	Spare or I _{PF} segmentation info	140
7.3.3.2	Extended NCF bits	141
7.3.4	Quality control	141
7.3.4.1	General format	141
7.3.4.2	Bearer and connection control.....	141
7.3.4.3	RESET	143
7.3.4.4	Bearer quality in an asymmetric connection	143
7.3.5	Extended system information	144
7.3.5.1	General format	144
7.3.5.2	TARI messages	144
7.3.5.3	"no-emission" mode sync information	144
7.3.6	G _F channel data packet.....	145
7.3.7	Escape.....	145
8	Medium access layer primitives	145
8.1	Connection oriented service primitives	146
8.1.1	Connection setup: MAC_CON {req;ind;cfm}	146
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}	147
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}	148
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}	149
8.1.5	Restart DLC: MAC_RES_DLC {ind}	149
8.1.6	Connection release: MAC_DIS {req;ind}	149
8.1.7	MAC bandwidth: MAC_BW {ind;res}	150
8.1.8	Encryption.....	150
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}.....	150
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}	150
8.1.9	C-plane switching procedure	151
8.1.9.1	C-plane switching procedure: MAC_C _S C _F {req, cfm, ind, res}.....	151
8.1.9.2	C-plane switching procedure: MAC_C _S C _F _END {ind}	151
8.2	Connectionless and broadcast service primitives.....	152
8.2.1	Paging: MAC_PAGE {req;ind}.....	152
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}	152
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}	153
8.2.4	"no-emission" mode.....	153
8.3	Management primitives	153
8.3.1	Connection control.....	153
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	153
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}	153
8.3.1.3	Bearer release: MAC_ME_REL {req}	153
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind}	154
8.3.2	System information and identities	154
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}	154
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}	154
8.3.2.3	System information output: MAC_ME_INFO {ind;res}	154
8.3.2.4	Extended system info: MAC_ME_EXT.{req;ind;res;cfm}	154
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	154
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}	155
8.3.5	Error reports: MAC_ME_ERROR {ind;res}	155
8.4	Flow control	155
8.4.1	MA SAP flow control.....	155
8.4.2	MB SAP flow control	155
8.4.3	MC SAP flow control	155
9	Broadcast and connectionless procedures	157
9.1	Downlink broadcast and connectionless procedures	157
9.1.1	Downlink broadcast procedure	158
9.1.1.1	Broadcast information.....	158
9.1.1.2	Channel selection for downlink broadcast services.....	158
9.1.1.3	Downlink broadcast procedure description.....	159

9.1.2	Downlink connectionless procedure	160
9.1.2.1	Channel selection at the RFP	160
9.1.2.2	Downlink connectionless procedure description	160
9.1.3	Paging broadcast procedure	160
9.1.3.1	RFP paging broadcasts	160
9.1.3.2	PP paging procedures	163
9.1.3.2.1	PP paging detection	163
9.1.3.2.2	PP paging processing	163
9.2	Uplink connectionless procedures	163
9.2.1	General	163
9.2.2	Bearer selection for the connectionless uplink	164
9.2.3	Procedure for the connectionless uplink	164
9.2.3.1	Predicates	164
9.2.3.2	PT D-field construction	164
9.2.3.3	PT transmission sequence	165
9.2.3.4	FT procedure	165
9.3	Non-continuous broadcast procedure	166
9.3.1	Request for specific Q channel information	166
9.3.1.1	A-field procedure	166
9.3.1.2	B-field procedure	166
9.3.2	Request for a new dummy bearer	167
9.4	"No-emission" mode procedures	167
9.4.1	Initiation of the "no-emission" mode	167
9.4.1.1	Successful activation (countdown to zero)	167
9.4.1.2	Multiframe countdown stopped by FT	168
9.4.1.3	Multiframe countdown stopped by PT	168
9.4.1.4	PT does not receive multiframe countdown "zero"	169
9.4.2	Behaviour during power-down-mode	169
9.4.3	Waking up, FT initiated	169
9.4.4	Waking up, PT initiated	173
10	Connection oriented service procedures	174
10.1	Overview	174
10.2	C/O connection setup	175
10.2.1	General	175
10.2.2	Initiation of a basic and a normal connection setup	175
10.2.3	Initiation of a fast connection setup	175
10.2.4	Connection setup procedure description	176
10.2.4.1	Creation of MBCs	176
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	178
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation	179
10.2.4.3.1	Symmetric connection	181
10.2.4.3.2	Asymmetric uplink connection	181
10.2.4.3.3	Asymmetric downlink connection	181
10.2.4.3.4	Connection established	181
10.3	C/O connection modification	182
10.3.1	Advanced connection: bandwidth modification	182
10.3.1.1	Suspend and resume	184
10.3.1.2	MAC resume paging	184
10.3.2	Advanced connection: service type or slot type modification	184
10.3.2.1	Procedure for service type modification	184
10.3.2.2	Procedures for slot type modification	185
10.3.2.2.1	Procedure for slot type modification full to double	185
10.3.2.2.2	Procedure for slot type modification double to full	186
10.3.2.2.3	Procedures for slot type modification to/from long	186
10.3.2.2.4	Procedure for slot type modification in multibearer connections	187
10.3.2.3	Procedure for ECN number modification in an advanced connection	187
10.3.3	Connection type modification	187
10.3.3.1	Procedure for connection type modification basic to advanced	188
10.3.3.1.1	General procedure	188
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	188

10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	189
10.3.3.2	Procedure for connection type modification advanced to basic	189
10.3.4	Modulation type modification.....	189
10.3.4.1	Adaptive code rate.....	191
10.4	C/O connection release.....	191
10.4.1	General.....	191
10.4.2	Procedure description	192
10.5	C/O bearer setup.....	192
10.5.1	Single bearer setup procedures	192
10.5.1.1	Basic bearer setup procedure.....	192
10.5.1.2	A-field advanced single bearer setup procedure	194
10.5.1.2.1	PT initiated	195
10.5.1.2.2	FT initiated	197
10.5.1.3	B-field single bearer setup procedure.....	198
10.5.1.3.1	PT initiated	199
10.5.1.3.2	FT initiated	201
10.5.1.4	Double simplex setup procedure	201
10.5.1.4.1	Terminology and Predicates	201
10.5.1.4.2	General description.....	202
10.5.1.4.3	Channel selection procedure for circuit mode connections	202
10.5.1.4.4	Channel selection procedure for packet mode connections	203
10.5.1.4.5	Indirect setup procedure	204
10.5.1.4.6	Direct setup procedure.....	204
10.5.1.4.7	Handling of encrypted connections	207
10.5.1.5	Complementary connection bearer setup	209
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	209
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	210
10.5.1.7.1	Default rules for TA code "111"	211
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	211
10.5.2	Channel list procedures.....	212
10.5.2.1	General	212
10.5.2.2	Description of the channel list messages.....	212
10.5.2.3	Usage of the channel list messages	213
10.6	C/O bearer handover	214
10.6.1	General.....	214
10.6.2	Duplex bearer handover procedure	215
10.6.3	Double simplex bearer handover.....	216
10.6.4	Bearer replacement	216
10.6.4.1	General bearer replacement.....	216
10.6.4.2	Frequency replacement	217
10.7	C/O bearer release	218
10.7.1	General.....	218
10.7.2	Bearer release procedure description	218
10.7.2.1	Unacknowledged release procedure	218
10.7.2.1.1	Crossed bearer release procedure	219
10.7.2.2	Acknowledged release procedure.....	219
10.7.2.3	Fast release procedure	219
10.7.2.4	REP relayed bearer release.....	220
10.8	C/O data transfer	220
10.8.1	Higher layer associated signalling (C)	220
10.8.1.1	C _S channel data	220
10.8.1.1.1	Transmission principle	221
10.8.1.1.2	Numbering principle.....	221
10.8.1.2	C _F channel data	221
10.8.1.2.1	Transmission principle	221
10.8.1.2.2	Numbering principle.....	222
10.8.1.3	Q1 and Q2 bit settings for I _N and I _{P_error_detection} services	222
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I _N	222
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I _{P_error_detect}	222
10.8.1.3.3	Q2 bit settings.....	223
10.8.1.3.4	Q1 bit settings.....	224

10.8.2	MOD-2 protected I channel operation (I_P).....	225
10.8.2.1	General.....	225
10.8.2.2	Limiting the lifetime of packets.....	225
10.8.2.3	A-field shall always be correct.....	225
10.8.2.4	Use of the acknowledge bits.....	225
10.8.2.4.1	Q2 and BCK bit setting for I_P _error_correction services.....	226
10.8.2.4.2	BCK bit setting.....	226
10.8.2.5	Data jump procedures.....	226
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement.....	227
10.8.2.5.2	Unilateral jump.....	227
10.8.2.5.3	MAC I_P bearer reset.....	228
10.8.2.6	Bearer handover and bearer replacement procedures.....	229
10.8.2.6.1	General.....	229
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	229
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel.....	229
10.8.2.7	Exchange of data from/to higher layers.....	230
10.8.2.7.1	Operation if I_{PF} channel is supported.....	230
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_P).....	231
10.8.3.1	I_N _minimum_delay service.....	231
10.8.3.2	I_N _normal_delay service.....	231
10.8.3.3	I_P _error_detection service.....	231
10.8.3.3.1	Operation if I_{PF} channel is supported.....	232
10.8.3.4	I_P _encodec_protected service (I_{PX}).....	232
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux.....	232
10.8.4.1	Purpose of the I_{PF} channel.....	232
10.8.4.2	Activation of the E+U type mux mode.....	232
10.8.4.3	I_{PF} procedures.....	233
10.8.4.3.1	I_{PF} basic procedures.....	233
10.8.4.3.2	I_{PF} advanced procedures.....	234
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	234
10.8.4.4	I_{PF} Mod-2 protected operation.....	234
10.8.4.5	I_{PF} _error_detect operation.....	235
10.8.4.6	I_{PF} _operation with I_N service.....	235
10.8.4.7	Backcompatibility rule.....	235
10.9	C/O procedures for FT connections with CRFP.....	235
10.9.1	Dual C/O bearer setup.....	235
10.9.2	C/O connection release of connection with CRFP.....	236
10.9.3	C/O connection suspend and resume.....	236
11	Medium access layer management procedures.....	236
11.1	Broadcasting.....	236
11.1.1	RFP transmission.....	236
11.1.2	PP reception.....	236
11.2	Extended system information.....	237
11.2.1	PP requests.....	237
11.2.2	RFP response.....	237
11.3	PP states and state transitions.....	237
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	237
11.3.2	Entry into the Idle_Locked state.....	237
11.3.3	Actions in the Idle_Locked state.....	238
11.3.3.1	Page detection in Idle_Locked state.....	238
11.3.3.2	Setup detection in Idle_Locked state.....	238
11.3.4	Idle_Locked and Active_Locked state transitions.....	239
11.4	Physical channel selection.....	239
11.4.1	The channel selection lists.....	239
11.4.2	Physical channel and RFP selection at the PP.....	241
11.4.3	Physical channel selection at the RFP.....	243
11.4.4	Hand over criteria due to in-connection base identification.....	244
11.4.5	Handover criteria due to interference.....	245
11.5	In-connection quality control.....	245
11.5.1	RFPI handshake.....	245
11.5.2	Frequency control.....	245

11.5.2.1	RFP measurement of frequency error	245
11.5.2.2	PT frequency correction	245
11.6	Maximum allowed system load at RFPs	246
11.7	PMID and FMID definitions	246
11.7.1	FMID definition	246
11.7.2	PMID definition	246
11.8	RFP idle receiver scan sequence	246
11.9	PT receiver scan sequence	247
11.10	Management of connections associated with Broadband data links	247
11.11	Management procedures for "no-emission" mode	248
11.11.1	Behaviour during "no-emission" mode	248
12	Medium access layer test message procedure	248
12.1	Introduction	248
12.2	General	248
12.2.1	Portable part testing	250
12.2.2	Fixed part testing	250
12.2.3	Applicability of test messages	250
12.3	FORCE_TRANSMIT	250
12.3.1	Portable part	250
12.3.2	Fixed part	251
12.4	LOOPBACK_DATA	251
12.4.1	Portable part	252
12.4.2	Fixed Part	252
12.4.2.1	IUTs implementing the DECT scrambler	252
12.4.2.2	IUTs implementing a proprietary scrambler	252
12.5	DEFEAT_ANTENNA_DIVERSITY	252
12.6	NETWORK_TEST	252
12.7	ESCAPE	252
12.8	CLEAR_TEST_MODES	252
12.9	CHANGE_MODULATION_SCHEME	252
Annex A (normative):	MAC layer timers and constants	253
A.1	Timers and Time Windows	253
A.2	Constants	253
Annex B (informative):	Construction of the CRC polynomial and error detecting performance	255
Annex C (informative):	MAC relationship to other layers	256
Annex D (informative):	Synchronization	257
Annex E (normative):	Scrambling patterns	258
Annex F (informative):	Seamless handover operation	259
F.1	I channel data flow for I _N _minimum_delay service	259
Annex G (normative):	Requirements for PPs with direct PP to PP communication mode	260
G.1	Description of operation in direct PP to PP communication mode	260
G.2	Requirements	260
G.2.1	Setting the PP in direct communications mode	261
G.2.2	Specific Alternative 1 requirements	261
G.2.2.1	When the PP has not initiated a call	261
G.2.2.2	When the PP initiates a call	261
G.2.3	Specific Alternative 2 Requirements	262
Annex H (normative):	Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode	263

H.1	Introduction	263
H.2	Description of operation in W-FT2FT communication mode	264
Annex I (normative):	Channel coding and Modulation	265
I.1	Channel coding	265
I.1.1	The parallel Turbo Code Principle	266
I.1.2	The FOCTC implementation	266
I.1.2.1	The FOCTC concept	266
I.1.2.2	The FOCTC structure and the component code	267
I.1.2.3	The FOCTC Inner interleaving algorithm	269
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats	270
I.2	Adaptive coding and Modulation Embodiment	272
I.2.1	Adaptive code rates	272
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80)	273
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32)	274
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80)	274
I.2.2	Puncturing patterns	275
I.2.3	Channel Capacity for the B-field map configurations	276
I.2.3.1	Double Slot Structure	276
I.2.3.2	Full Slot Structure	277
I.2.3.3	Half Slot Structure	278
I.3	Change Modulation Scheme	278
Annex J (informative):	Channel decoding	279
Annex K (informative):	Additional information on MAC messages	280
K.1	Historic use of some MAC service codes	280
Annex L (informative):	Bibliography	281
Annex M (informative):	Change history	282
History		283

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa