

ETSI EN 300 175-3 V2.3.1 (2010-06)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/86b739d3-178c-42d7-8e91-0ad350efd393/etsi-en-300-175-3-v2.3.1-2010-06>



Reference

REN/DECT-000254-3

Keywords

DECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|--|----|
| Intellectual Property Rights | 13 |
| Foreword..... | 13 |
| 1 Scope | 14 |
| 2 References | 14 |
| 2.1 Normative references | 14 |
| 2.2 Informative references..... | 15 |
| 3 Definitions, symbols and abbreviations | 15 |
| 3.1 Definitions..... | 15 |
| 3.2 Symbols and abbreviations..... | 16 |
| 4 Description of the MAC layer | 18 |
| 4.1 MAC layer reference model | 18 |
| 4.1.1 General..... | 19 |
| 4.1.2 Cluster Control Function (CCF) | 19 |
| 4.1.3 Cell Site Functions (CSF)..... | 19 |
| 4.1.4 Relationship to physical layer elements..... | 19 |
| 4.2 Frame and multiframe structures..... | 20 |
| 4.2.1 General..... | 20 |
| 4.2.2 Frame structure | 20 |
| 4.2.3 Multiframe structure | 22 |
| 4.3 State definitions..... | 22 |
| 4.3.1 PP states | 22 |
| 4.3.2 RFP states | 23 |
| 5 Overview of MAC layer services | 24 |
| 5.1 General | 24 |
| 5.1.1 Broadcast Message Control (BMC)..... | 24 |
| 5.1.2 Connectionless Message Control (CMC)..... | 24 |
| 5.1.3 Multi-Bearer Control | 24 |
| 5.2 Service descriptions..... | 24 |
| 5.2.1 Common functions..... | 24 |
| 5.2.2 BMC service | 25 |
| 5.2.3 CMC service | 25 |
| 5.2.4 MBC services..... | 25 |
| 5.3 Logical channels..... | 26 |
| 5.3.1 MBC connection endpoints (MC-SAP logical channels) | 26 |
| 5.3.1.1 The higher layer C-plane channels, C | 26 |
| 5.3.1.2 The higher layer U-Plane channels, I | 26 |
| 5.3.1.3 The higher layer U-Plane control channel, G _F | 27 |
| 5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF} | 27 |
| 5.3.2 CMC endpoints (MB-SAP logical channels)..... | 28 |
| 5.3.2.1 The connectionless C-Plane channels, CL | 28 |
| 5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P | 28 |
| 5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF} | 28 |
| 5.3.3 BMC endpoint (MA-SAP logical channel)..... | 28 |
| 5.3.3.1 The slow broadcast channel, B _S | 28 |
| 5.3.4 Internal MAC control channels..... | 29 |
| 5.3.4.1 The system information channel, Q | 29 |
| 5.3.4.2 Identities channel, N..... | 29 |
| 5.3.4.3 The MAC control channel, M | 29 |
| 5.3.4.4 MAC paging channel, P | 29 |
| 5.4 SAP definitions | 30 |
| 5.4.1 MA SAP | 30 |
| 5.4.2 MB SAP..... | 30 |
| 5.4.3 MC SAP..... | 30 |

| | | |
|-----------|--|----|
| 5.4.4 | ME SAP | 31 |
| 5.4.5 | Order of transmission..... | 31 |
| 5.5 | Bearers..... | 31 |
| 5.5.1 | Bearer types | 31 |
| 5.5.2 | Bearer operation..... | 32 |
| 5.6 | Connection oriented services..... | 32 |
| 5.6.1 | Connection types | 32 |
| 5.6.1.1 | Basic connections..... | 33 |
| 5.6.1.2 | Advanced connections | 33 |
| 5.6.1.2.1 | Rules for ECN selection in advanced connections | 33 |
| 5.6.1.3 | Connection identifiers | 34 |
| 5.6.1.4 | Complementary connections | 34 |
| 5.6.2 | Symmetric and asymmetric connections..... | 34 |
| 5.6.2.1 | Symmetric connections | 35 |
| 5.6.2.2 | Asymmetric connections | 40 |
| 5.7 | Broadcast and connectionless services | 48 |
| 5.7.1 | The broadcast services | 49 |
| 5.7.1.1 | The continuous broadcast service | 49 |
| 5.7.1.2 | The non-continuous broadcast service | 49 |
| 5.7.2 | The connectionless services | 50 |
| 5.7.2.1 | Connectionless downlink services | 50 |
| 5.7.2.2 | Connectionless uplink services | 50 |
| 6 | Multiplexing..... | 51 |
| 6.1 | CCF multiplexing functions | 51 |
| 6.2 | CSF multiplexing functions..... | 51 |
| 6.2.1 | Bit Mappings (MAP) | 56 |
| 6.2.1.1 | D-field mapping (D-MAP)..... | 56 |
| 6.2.1.1.1 | D-field mapping for the double slot structure (physical packet P80) | 57 |
| 6.2.1.1.2 | D-field mapping for the full slot structure (physical packet P32)..... | 57 |
| 6.2.1.1.3 | D-field mapping for the short slot structure (physical packet P00) | 58 |
| 6.2.1.1.4 | D-field mapping for the variable slot structure (physical packet P00j) | 58 |
| 6.2.1.2 | A-field Mapping (A-MAP) | 59 |
| 6.2.1.3 | B-field Mapping (B-MAP)..... | 60 |
| 6.2.1.3.1 | Unprotected format..... | 60 |
| 6.2.1.3.2 | Encoded protected format..... | 62 |
| 6.2.1.3.3 | Multisubfield protected format..... | 62 |
| 6.2.1.3.4 | Singlesubfield protected format..... | 64 |
| 6.2.2 | Time multiplexers | 66 |
| 6.2.2.1 | Tail MULTipleXer (T-MUX) | 66 |
| 6.2.2.1.1 | T-MUX algorithm for RFP transmissions | 67 |
| 6.2.2.1.2 | T-MUX algorithm for PT transmissions..... | 68 |
| 6.2.2.2 | B-field control multiplexer (E/U-MUX) | 68 |
| 6.2.2.3 | B-field mode multiplexer E-type and E+U-type modes | 70 |
| 6.2.2.3.1 | E-type and E+U-type modes for slots with more than one subfield | 70 |
| 6.2.2.3.2 | Half slot (j=80) modes for 2-level modulation | 84 |
| 6.2.2.4 | Priority scheme in E or E+U mode | 85 |
| 6.2.3 | Encryption..... | 86 |
| 6.2.4 | Scrambling..... | 86 |
| 6.2.5 | Error control..... | 88 |
| 6.2.5.1 | R-CRC overview | 88 |
| 6.2.5.2 | R-CRC generation and checking..... | 89 |
| 6.2.5.3 | X-CRC overview..... | 89 |
| 6.2.5.4 | X-CRC generation and checking..... | 89 |
| 6.2.5.5 | B-CRC generation and checking..... | 91 |
| 6.2.6 | Broadcast controller..... | 92 |
| 7 | Medium access layer messages | 92 |
| 7.1 | Header field | 93 |
| 7.1.1 | Overview/formatting..... | 93 |
| 7.1.2 | Tail identification, TA, bits a_0 to a_2 | 93 |
| 7.1.3 | The "Q1/BCK" bit, bit a_3 | 93 |

| | | |
|------------|--|-----|
| 7.1.4 | B-field identification, BA, bits a_4 to a_6 | 94 |
| 7.1.5 | The "Q2" bit, bit a_7 | 95 |
| 7.2 | Messages in the tail field | 95 |
| 7.2.1 | Overview | 95 |
| 7.2.2 | Identities information (N_T)..... | 95 |
| 7.2.3 | System information and multiframe marker (Q_T) | 96 |
| 7.2.3.1 | General | 96 |
| 7.2.3.2 | Static system information..... | 97 |
| 7.2.3.2.1 | General, $Q_H = 0, 1$ (hex) | 97 |
| 7.2.3.2.2 | Q_H and Normal-Reverse (NR) | 97 |
| 7.2.3.2.3 | Slot Number (SN)..... | 97 |
| 7.2.3.2.4 | Start Position (SP) | 98 |
| 7.2.3.2.5 | ESCAPE bit (ESC)..... | 98 |
| 7.2.3.2.6 | Number of transceivers..... | 98 |
| 7.2.3.2.7 | Extended RF carrier information available (M_c)..... | 98 |
| 7.2.3.2.8 | RF carriers available (RF-cars)..... | 99 |
| 7.2.3.2.9 | Spare bits (SPR) | 99 |
| 7.2.3.2.10 | Carrier number..... | 99 |
| 7.2.3.2.11 | Spare bits (SPR) | 99 |
| 7.2.3.2.12 | Primary receiver Scan Carrier Number (PSCN)..... | 100 |
| 7.2.3.3 | Extended RF carrier information part 1 | 100 |
| 7.2.3.3.1 | General, $Q_H = 2$ (hex)..... | 100 |
| 7.2.3.3.2 | Further RF carrier extensions | 101 |
| 7.2.3.3.3 | Number of RF carriers..... | 101 |
| 7.2.3.4 | Fixed part capabilities | 101 |
| 7.2.3.4.1 | General, $Q_H = 3$ (hex) | 101 |
| 7.2.3.4.2 | Standard capabilities..... | 101 |
| 7.2.3.5 | Extended fixed part capabilities | 102 |
| 7.2.3.5.1 | General, $Q_H = 4$ (hex)..... | 102 |
| 7.2.3.5.2 | Extended Physical and MAC layer capabilities..... | 103 |
| 7.2.3.5.3 | Extended higher layer capabilities..... | 104 |
| 7.2.3.6 | Secondary access rights identities | 104 |
| 7.2.3.6.1 | General, $Q_H = 5$ (hex)..... | 104 |
| 7.2.3.6.2 | SARI message | 104 |
| 7.2.3.7 | Multiframe number | 104 |
| 7.2.3.7.1 | General, $Q_H = 6$ (hex)..... | 104 |
| 7.2.3.7.2 | Multiframe number..... | 104 |
| 7.2.3.8 | Escape | 105 |
| 7.2.3.8.1 | General, $Q_H = 7$ (hex)..... | 105 |
| 7.2.3.8.2 | Escape information..... | 105 |
| 7.2.3.9 | Extended RF carrier information part 2 | 105 |
| 7.2.3.9.1 | General, $Q_H = 9$ (hex)..... | 105 |
| 7.2.3.10 | Transmit information | 105 |
| 7.2.3.10.1 | General, $Q_H = B$ (hex) | 105 |
| 7.2.3.11 | Extended fixed part capabilities (part 2) | 106 |
| 7.2.3.11.1 | General, $Q_H = C$ (hex) | 106 |
| 7.2.3.11.2 | Extended Physical and MAC layer capabilities (part 2)..... | 106 |
| 7.2.3.11.3 | Extended higher layer capabilities (part 2)..... | 107 |
| 7.2.4 | Paging Tail (P_T) | 107 |
| 7.2.4.1 | General format | 107 |
| 7.2.4.1.1 | P_T format for full and long page messages | 107 |
| 7.2.4.1.2 | P_T format for short page messages | 108 |
| 7.2.4.1.3 | P_T format for zero length page messages..... | 108 |
| 7.2.4.1.4 | P_T format for MAC_Resume_and_Control_page message | 108 |
| 7.2.4.2 | P_T header format..... | 109 |
| 7.2.4.2.1 | General format..... | 109 |
| 7.2.4.2.2 | Bit a_8 is the extend flag..... | 109 |
| 7.2.4.2.3 | B_S SDU length indication | 109 |
| 7.2.4.3 | MAC layer information for PT..... | 110 |
| 7.2.4.3.1 | Information type | 110 |
| 7.2.4.3.2 | Fill bits / Blind long slot ($j=640$ / $j=672$) information..... | 110 |
| 7.2.4.3.3 | Blind full slot information | 111 |

| | | |
|------------|--|-----|
| 7.2.4.3.4 | Bearer description..... | 111 |
| 7.2.4.3.5 | Escape..... | 112 |
| 7.2.4.3.6 | Dummy or connectionless downlink bearer marker | 112 |
| 7.2.4.3.7 | Bearer handover/replacement information | 112 |
| 7.2.4.3.8 | RFP status and modulation types..... | 113 |
| 7.2.4.3.9 | Active carriers | 114 |
| 7.2.4.3.10 | RFP power level | 114 |
| 7.2.4.3.11 | Blind double slot/RFP-FP interface resource information..... | 115 |
| 7.2.4.3.12 | Extended modulation types | 115 |
| 7.2.5 | MAC control (M_T) | 116 |
| 7.2.5.1 | General format and contents | 116 |
| 7.2.5.2 | Basic connection control | 116 |
| 7.2.5.2.1 | General | 116 |
| 7.2.5.2.2 | Format for most messages | 117 |
| 7.2.5.2.3 | WAIT | 117 |
| 7.2.5.2.4 | ATTRIBUTES_T_{Req;Cfm} | 117 |
| 7.2.5.3 | Advanced connection control..... | 118 |
| 7.2.5.3.1 | General | 118 |
| 7.2.5.3.2 | ACCESS_REQUEST | 118 |
| 7.2.5.3.3 | BEARER_HANDOVER_REQUEST | 118 |
| 7.2.5.3.4 | CONNECTION_HANDOVER_REQUEST | 118 |
| 7.2.5.3.5 | UNCONFIRMED_ACCESS_REQUEST | 119 |
| 7.2.5.3.6 | BEARER_CONFIRM | 119 |
| 7.2.5.3.7 | WAIT | 119 |
| 7.2.5.3.8 | ATTRIBUTES_T_{Req;Cfm} | 119 |
| 7.2.5.3.9 | BANDWIDTH_T_{Req;Cfm} | 122 |
| 7.2.5.3.10 | Channel_list..... | 122 |
| 7.2.5.3.11 | Unconfirmed_dummy..... | 123 |
| 7.2.5.3.12 | Unconfirmed_handover..... | 123 |
| 7.2.5.3.13 | RELEASE | 123 |
| 7.2.5.4 | MAC layer test messages | 124 |
| 7.2.5.4.1 | Basic format | 124 |
| 7.2.5.4.2 | FORCE_TRANSMIT | 125 |
| 7.2.5.4.3 | LOOPBACK_DATA | 125 |
| 7.2.5.4.4 | DEFEAT_ANTENNA_DIVERSITY..... | 126 |
| 7.2.5.4.5 | ESCAPE | 127 |
| 7.2.5.4.6 | NETWORK_TEST..... | 127 |
| 7.2.5.4.7 | CLEAR_TEST_MODES..... | 127 |
| 7.2.5.4.8 | CHANGE_MODULATION_SCHEME | 127 |
| 7.2.5.5 | Quality control | 128 |
| 7.2.5.5.1 | Prolonged preamble diversity | 129 |
| 7.2.5.6 | Broadcast and connectionless services..... | 130 |
| 7.2.5.7 | Encryption control..... | 130 |
| 7.2.5.8 | B-field setup, first PT transmission..... | 131 |
| 7.2.5.9 | Escape | 132 |
| 7.2.5.10 | TARI message..... | 132 |
| 7.2.5.11 | REP connection control..... | 132 |
| 7.2.5.11.1 | General | 132 |
| 7.2.5.11.2 | Format for most messages | 132 |
| 7.2.5.11.3 | REP CHANNEL MAP REQUEST | 133 |
| 7.2.5.11.4 | REP CHANNEL MAP CONFIRM..... | 133 |
| 7.3 | Messages in the B-field | 133 |
| 7.3.1 | Overview | 133 |
| 7.3.2 | Advanced connection control | 134 |
| 7.3.2.1 | General format | 134 |
| 7.3.2.2 | BEARER_REQUEST | 135 |
| 7.3.2.3 | BEARER_CONFIRM..... | 135 |
| 7.3.2.4 | WAIT | 136 |
| 7.3.2.5 | ATTRIBUTES_B_{Req;Cfm} | 136 |
| 7.3.2.6 | BANDWIDTH_B_{Req;Cfm} | 137 |
| 7.3.2.7 | CHANNEL_LIST | 137 |
| 7.3.2.8 | UNCONFIRMED_DUMMY..... | 137 |

| | | |
|----------|--|-----|
| 7.3.2.9 | UNCONFIRMED_HANDOVER | 138 |
| 7.3.2.10 | RELEASE | 138 |
| 7.3.3 | Null or I _{PF} segmentation info | 139 |
| 7.3.3.1 | Spare or I _{PF} segmentation info | 140 |
| 7.3.3.2 | Extended NCF bits | 141 |
| 7.3.4 | Quality control | 141 |
| 7.3.4.1 | General format | 141 |
| 7.3.4.2 | Bearer and connection control..... | 141 |
| 7.3.4.3 | RESET | 143 |
| 7.3.4.4 | Bearer quality in an asymmetric connection | 143 |
| 7.3.5 | Extended system information | 144 |
| 7.3.5.1 | General format | 144 |
| 7.3.5.2 | TARI messages | 144 |
| 7.3.5.3 | "no-emission" mode sync information | 144 |
| 7.3.6 | G _F channel data packet..... | 145 |
| 7.3.7 | Escape..... | 145 |
| 8 | Medium access layer primitives | 145 |
| 8.1 | Connection oriented service primitives | 146 |
| 8.1.1 | Connection setup: MAC_CON {req;ind;cfm} | 146 |
| 8.1.2 | Connection modification: MAC_MOD {req;ind;cfm} | 147 |
| 8.1.3 | CO data transmit ready: MAC_CO_DTR {ind} | 148 |
| 8.1.4 | CO data transfer: MAC_CO_DATA {req;ind} | 149 |
| 8.1.5 | Restart DLC: MAC_RES_DLC {ind} | 149 |
| 8.1.6 | Connection release: MAC_DIS {req;ind} | 149 |
| 8.1.7 | MAC bandwidth: MAC_BW {ind;res} | 150 |
| 8.1.8 | Encryption..... | 150 |
| 8.1.8.1 | Load encryption key: MAC_ENC_KEY {req}..... | 150 |
| 8.1.8.2 | Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm} | 150 |
| 8.1.9 | C-plane switching procedure | 151 |
| 8.1.9.1 | C-plane switching procedure: MAC_C _S C _F {req, cfm, ind, res}..... | 151 |
| 8.1.9.2 | C-plane switching procedure: MAC_C _S C _F _END {ind} | 151 |
| 8.2 | Connectionless and broadcast service primitives..... | 152 |
| 8.2.1 | Paging: MAC_PAGE {req;ind}..... | 152 |
| 8.2.2 | Downlink connectionless: MAC_DOWN_CON {req;ind} | 152 |
| 8.2.3 | Uplink connectionless: MAC_UP_CON {req;ind;cfm} | 153 |
| 8.2.4 | "no-emission" mode..... | 153 |
| 8.3 | Management primitives | 153 |
| 8.3.1 | Connection control..... | 153 |
| 8.3.1.1 | Connection setup: MAC_ME_CON {ind}..... | 153 |
| 8.3.1.2 | Connection setup allowed: MAC_ME_CON_ALL {req} | 153 |
| 8.3.1.3 | Bearer release: MAC_ME_REL {req} | 153 |
| 8.3.1.4 | MBC release report: MAC_ME_REL_REP {ind} | 154 |
| 8.3.2 | System information and identities | 154 |
| 8.3.2.1 | FP information preloading: MAC_ME_RFP_PRELOAD {req} | 154 |
| 8.3.2.2 | PT information preloading: MAC_ME_PT_PRELOAD {req} | 154 |
| 8.3.2.3 | System information output: MAC_ME_INFO {ind;res} | 154 |
| 8.3.2.4 | Extended system info: MAC_ME_EXT.{req;ind;res;cfm} | 154 |
| 8.3.3 | Channel map: MAC_ME_CHANMAP {ind;res}..... | 154 |
| 8.3.4 | Status reports: MAC_ME_STATUS {req;ind;res;cfm} | 155 |
| 8.3.5 | Error reports: MAC_ME_ERROR {ind;res} | 155 |
| 8.4 | Flow control | 155 |
| 8.4.1 | MA SAP flow control..... | 155 |
| 8.4.2 | MB SAP flow control | 155 |
| 8.4.3 | MC SAP flow control | 155 |
| 9 | Broadcast and connectionless procedures | 158 |
| 9.1 | Downlink broadcast and connectionless procedures | 158 |
| 9.1.1 | Downlink broadcast procedure | 158 |
| 9.1.1.1 | Broadcast information..... | 158 |
| 9.1.1.2 | Channel selection for downlink broadcast services..... | 158 |
| 9.1.1.3 | Downlink broadcast procedure description..... | 160 |

| | | |
|------------|---|-----|
| 9.1.2 | Downlink connectionless procedure | 160 |
| 9.1.2.1 | Channel selection at the RFP | 160 |
| 9.1.2.2 | Downlink connectionless procedure description | 160 |
| 9.1.3 | Paging broadcast procedure | 160 |
| 9.1.3.1 | RFP paging broadcasts | 161 |
| 9.1.3.2 | PP paging procedures | 163 |
| 9.1.3.2.1 | PP paging detection | 163 |
| 9.1.3.2.2 | PP paging processing | 163 |
| 9.2 | Uplink connectionless procedures | 163 |
| 9.2.1 | General | 163 |
| 9.2.2 | Bearer selection for the connectionless uplink | 164 |
| 9.2.3 | Procedure for the connectionless uplink | 164 |
| 9.2.3.1 | Predicates | 164 |
| 9.2.3.2 | PT D-field construction | 164 |
| 9.2.3.3 | PT transmission sequence | 165 |
| 9.2.3.4 | FT procedure | 165 |
| 9.3 | Non-continuous broadcast procedure | 166 |
| 9.3.1 | Request for specific Q channel information | 166 |
| 9.3.1.1 | A-field procedure | 166 |
| 9.3.1.2 | B-field procedure | 166 |
| 9.3.2 | Request for a new dummy bearer | 167 |
| 9.4 | "No-emission" mode procedures | 167 |
| 9.4.1 | Initiation of the "no-emission" mode | 167 |
| 9.4.1.1 | Successful activation (countdown to zero) | 167 |
| 9.4.1.2 | Multiframe countdown stopped by FT | 168 |
| 9.4.1.3 | Multiframe countdown stopped by PT | 168 |
| 9.4.1.4 | PT does not receive multiframe countdown "zero" | 169 |
| 9.4.2 | Behaviour during power-down-mode | 169 |
| 9.4.3 | Waking up, FT initiated | 169 |
| 9.4.4 | Waking up, PT initiated | 173 |
| 10 | Connection oriented service procedures | 174 |
| 10.1 | Overview | 174 |
| 10.2 | C/O connection setup | 175 |
| 10.2.1 | General | 175 |
| 10.2.2 | Initiation of a basic and a normal connection setup | 175 |
| 10.2.3 | Initiation of a fast connection setup | 175 |
| 10.2.4 | Connection setup procedure description | 176 |
| 10.2.4.1 | Creation of MBCs | 176 |
| 10.2.4.2 | Establishment of a single bearer duplex connection of a known service type | 178 |
| 10.2.4.3 | Establishment of multi-bearer connections and connections needing service negotiation | 179 |
| 10.2.4.3.1 | Symmetric connection | 181 |
| 10.2.4.3.2 | Asymmetric uplink connection | 181 |
| 10.2.4.3.3 | Asymmetric downlink connection | 181 |
| 10.2.4.3.4 | Connection established | 181 |
| 10.3 | C/O connection modification | 182 |
| 10.3.1 | Advanced connection: bandwidth modification | 182 |
| 10.3.1.1 | Suspend and resume | 184 |
| 10.3.1.2 | MAC resume paging | 184 |
| 10.3.2 | Advanced connection: service type or slot type modification | 184 |
| 10.3.2.1 | Procedure for service type modification | 184 |
| 10.3.2.2 | Procedures for slot type modification | 185 |
| 10.3.2.2.1 | Procedure for slot type modification full to double | 185 |
| 10.3.2.2.2 | Procedure for slot type modification double to full | 186 |
| 10.3.2.2.3 | Procedures for slot type modification to/from long | 186 |
| 10.3.2.2.4 | Procedure for slot type modification in multibearer connections | 187 |
| 10.3.2.3 | Procedure for ECN number modification in an advanced connection | 187 |
| 10.3.3 | Connection type modification | 187 |
| 10.3.3.1 | Procedure for connection type modification basic to advanced | 188 |
| 10.3.3.1.1 | General procedure | 188 |
| 10.3.3.1.2 | Procedure for connection type modification basic to advanced plus slot type modification full to double | 188 |

| | | |
|------------|--|-----|
| 10.3.3.1.3 | Procedure for connection type modification basic to advanced plus slot type modification full to long..... | 189 |
| 10.3.3.2 | Procedure for connection type modification advanced to basic | 189 |
| 10.3.4 | Modulation type modification..... | 189 |
| 10.3.4.1 | Adaptive code rate..... | 191 |
| 10.4 | C/O connection release..... | 191 |
| 10.4.1 | General..... | 191 |
| 10.4.2 | Procedure description | 192 |
| 10.5 | C/O bearer setup..... | 192 |
| 10.5.1 | Single bearer setup procedures | 192 |
| 10.5.1.1 | Basic bearer setup procedure..... | 192 |
| 10.5.1.2 | A-field advanced single bearer setup procedure | 194 |
| 10.5.1.2.1 | PT initiated | 195 |
| 10.5.1.2.2 | FT initiated | 197 |
| 10.5.1.3 | B-field single bearer setup procedure..... | 198 |
| 10.5.1.3.1 | PT initiated | 199 |
| 10.5.1.3.2 | FT initiated | 201 |
| 10.5.1.4 | Double simplex setup procedure | 201 |
| 10.5.1.4.1 | Terminology and Predicates | 201 |
| 10.5.1.4.2 | General description..... | 202 |
| 10.5.1.4.3 | Channel selection procedure for circuit mode connections | 202 |
| 10.5.1.4.4 | Channel selection procedure for packet mode connections | 203 |
| 10.5.1.4.5 | Indirect setup procedure | 204 |
| 10.5.1.4.6 | Direct setup procedure..... | 204 |
| 10.5.1.4.7 | Handling of encrypted connections | 207 |
| 10.5.1.5 | Complementary connection bearer setup | 209 |
| 10.5.1.6 | Double duplex bearer setup procedure: Mapping procedure..... | 209 |
| 10.5.1.7 | Usage of TA special code "111" and M _T message "B-field setup, first PT transmission" | 210 |
| 10.5.1.7.1 | Default rules for TA code "111" | 211 |
| 10.5.1.7.2 | Default rules for M _T message "B-field setup, first transmission" | 211 |
| 10.5.2 | Channel list procedures..... | 212 |
| 10.5.2.1 | General | 212 |
| 10.5.2.2 | Description of the channel list messages..... | 212 |
| 10.5.2.3 | Usage of the channel list messages | 213 |
| 10.6 | C/O bearer handover | 214 |
| 10.6.1 | General..... | 214 |
| 10.6.2 | Duplex bearer handover procedure | 215 |
| 10.6.3 | Double simplex bearer handover..... | 216 |
| 10.6.4 | Bearer replacement | 216 |
| 10.6.4.1 | General bearer replacement..... | 216 |
| 10.6.4.2 | Frequency replacement | 217 |
| 10.7 | C/O bearer release | 218 |
| 10.7.1 | General..... | 218 |
| 10.7.2 | Bearer release procedure description | 218 |
| 10.7.2.1 | Unacknowledged release procedure | 218 |
| 10.7.2.1.1 | Crossed bearer release procedure | 219 |
| 10.7.2.2 | Acknowledged release procedure..... | 219 |
| 10.7.2.3 | Fast release procedure | 219 |
| 10.7.2.4 | REP relayed bearer release..... | 220 |
| 10.8 | C/O data transfer | 220 |
| 10.8.1 | Higher layer associated signalling (C) | 220 |
| 10.8.1.1 | C _S channel data | 220 |
| 10.8.1.1.1 | Transmission principle | 221 |
| 10.8.1.1.2 | Numbering principle..... | 221 |
| 10.8.1.2 | C _F channel data | 221 |
| 10.8.1.2.1 | Transmission principle | 221 |
| 10.8.1.2.2 | Numbering principle..... | 222 |
| 10.8.1.3 | Q1 and Q2 bit settings for I _N and I _{P_error_detection} services | 222 |
| 10.8.1.3.1 | Q1 and Q2 bit settings for MAC service I _N | 222 |
| 10.8.1.3.2 | Q1 and Q2 bit settings for MAC service I _{P_error_detect} | 222 |
| 10.8.1.3.3 | Q2 bit settings..... | 223 |
| 10.8.1.3.4 | Q1 bit settings..... | 224 |

| | | |
|------------|--|-----|
| 10.8.2 | MOD-2 protected I channel operation (I_P)..... | 225 |
| 10.8.2.1 | General..... | 225 |
| 10.8.2.2 | Limiting the lifetime of packets..... | 225 |
| 10.8.2.3 | A-field shall always be correct..... | 225 |
| 10.8.2.4 | Use of the acknowledge bits..... | 225 |
| 10.8.2.4.1 | Q2 and BCK bit setting for I_P _error_correction services..... | 226 |
| 10.8.2.4.2 | BCK bit setting..... | 226 |
| 10.8.2.5 | Data jump procedures..... | 226 |
| 10.8.2.5.1 | New MOD-2 numbering in case of Bearer replacement..... | 227 |
| 10.8.2.5.2 | Unilateral jump..... | 227 |
| 10.8.2.5.3 | MAC I_P bearer reset..... | 228 |
| 10.8.2.6 | Bearer handover and bearer replacement procedures..... | 229 |
| 10.8.2.6.1 | General..... | 229 |
| 10.8.2.6.2 | Bearer handover in a MOD-2 protected I channel..... | 229 |
| 10.8.2.6.3 | Bearer replacement in a MOD-2 protected I channel..... | 229 |
| 10.8.2.7 | Exchange of data from/to higher layers..... | 230 |
| 10.8.2.7.1 | Operation if I_{PF} channel is supported..... | 230 |
| 10.8.3 | Higher layer unprotected information (I_N) and MAC_error_detection services (I_P)..... | 231 |
| 10.8.3.1 | I_N _minimum_delay service..... | 231 |
| 10.8.3.2 | I_N _normal_delay service..... | 231 |
| 10.8.3.3 | I_P _error_detection service..... | 231 |
| 10.8.3.3.1 | Operation if I_{PF} channel is supported..... | 232 |
| 10.8.3.4 | I_P _encodec_protected service (I_{PX})..... | 232 |
| 10.8.4 | Higher layer U-plane channel (I_{PF}) in E+U type mux..... | 232 |
| 10.8.4.1 | Purpose of the I_{PF} channel..... | 232 |
| 10.8.4.2 | Activation of the E+U type mux mode..... | 232 |
| 10.8.4.3 | I_{PF} procedures..... | 233 |
| 10.8.4.3.1 | I_{PF} basic procedures..... | 233 |
| 10.8.4.3.2 | I_{PF} advanced procedures..... | 234 |
| 10.8.4.3.3 | Special case: slots not multiple of 64 bits..... | 234 |
| 10.8.4.4 | I_{PF} Mod-2 protected operation..... | 234 |
| 10.8.4.5 | I_{PF} _error_detect operation..... | 235 |
| 10.8.4.6 | I_{PF} _operation with I_N service..... | 235 |
| 10.8.4.7 | Backcompatibility rule..... | 235 |
| 10.9 | C/O procedures for FT connections with CRFP..... | 235 |
| 10.9.1 | Dual C/O bearer setup..... | 235 |
| 10.9.2 | C/O connection release of connection with CRFP..... | 236 |
| 10.9.3 | C/O connection suspend and resume..... | 236 |
| 11 | Medium access layer management procedures..... | 236 |
| 11.1 | Broadcasting..... | 236 |
| 11.1.1 | RFP transmission..... | 236 |
| 11.1.2 | PP reception..... | 236 |
| 11.2 | Extended system information..... | 237 |
| 11.2.1 | PP requests..... | 237 |
| 11.2.2 | RFP response..... | 237 |
| 11.3 | PP states and state transitions..... | 237 |
| 11.3.1 | Actions in Idle_Unlocked and Active_Unlocked states..... | 237 |
| 11.3.2 | Entry into the Idle_Locked state..... | 237 |
| 11.3.3 | Actions in the Idle_Locked state..... | 238 |
| 11.3.3.1 | Page detection in Idle_Locked state..... | 238 |
| 11.3.3.2 | Setup detection in Idle_Locked state..... | 238 |
| 11.3.4 | Idle_Locked and Active_Locked state transitions..... | 239 |
| 11.4 | Physical channel selection..... | 239 |
| 11.4.1 | The channel selection lists..... | 240 |
| 11.4.2 | Physical channel and RFP selection at the PP..... | 242 |
| 11.4.3 | Physical channel selection at the RFP..... | 243 |
| 11.4.4 | Hand over criteria due to in-connection base identification..... | 245 |
| 11.4.5 | Handover criteria due to interference..... | 245 |
| 11.5 | In-connection quality control..... | 245 |
| 11.5.1 | RFPI handshake..... | 245 |
| 11.5.2 | Frequency control..... | 246 |

| | | |
|-------------------------------|---|------------|
| 11.5.2.1 | RFP measurement of frequency error | 246 |
| 11.5.2.2 | PT frequency correction | 246 |
| 11.6 | Maximum allowed system load at RFPs | 246 |
| 11.7 | PMID and FMID definitions | 246 |
| 11.7.1 | FMID definition | 246 |
| 11.7.2 | PMID definition | 246 |
| 11.8 | RFP idle receiver scan sequence | 246 |
| 11.9 | PT receiver scan sequence | 247 |
| 11.10 | Management of connections associated with Broadband data links | 248 |
| 11.11 | Management procedures for "no-emission" mode | 248 |
| 11.11.1 | Behaviour during "no-emission" mode | 248 |
| 12 | Medium access layer test message procedure | 248 |
| 12.1 | Introduction | 248 |
| 12.2 | General | 249 |
| 12.2.1 | Portable part testing | 250 |
| 12.2.2 | Fixed part testing | 250 |
| 12.2.3 | Applicability of test messages | 250 |
| 12.3 | FORCE_TRANSMIT | 251 |
| 12.3.1 | Portable part | 251 |
| 12.3.2 | Fixed part | 251 |
| 12.4 | LOOPBACK_DATA | 252 |
| 12.4.1 | Portable part | 252 |
| 12.4.2 | Fixed Part | 252 |
| 12.4.2.1 | IUTs implementing the DECT scrambler | 252 |
| 12.4.2.2 | IUTs implementing a proprietary scrambler | 252 |
| 12.5 | DEFEAT_ANTENNA_DIVERSITY | 252 |
| 12.6 | NETWORK_TEST | 253 |
| 12.7 | ESCAPE | 253 |
| 12.8 | CLEAR_TEST_MODES | 253 |
| 12.9 | CHANGE_MODULATION_SCHEME | 253 |
| Annex A (normative): | MAC layer timers and constants | 254 |
| A.1 | Timers and Time Windows | 254 |
| A.2 | Constants | 254 |
| Annex B (informative): | Construction of the CRC polynomial and error detecting performance | 256 |
| Annex C (informative): | MAC relationship to other layers | 257 |
| Annex D (informative): | Synchronization | 258 |
| Annex E (normative): | Scrambling patterns | 259 |
| Annex F (informative): | Seamless handover operation | 260 |
| F.1 | I channel data flow for I _N _minimum_delay service | 260 |
| Annex G (normative): | Requirements for PPs with direct PP to PP communication mode | 261 |
| G.1 | Description of operation in direct PP to PP communication mode | 261 |
| G.2 | Requirements | 262 |
| G.2.1 | Setting the PP in direct communications mode | 262 |
| G.2.2 | Specific Alternative 1 requirements | 262 |
| G.2.2.1 | When the PP has not initiated a call | 262 |
| G.2.2.2 | When the PP initiates a call | 262 |
| G.2.3 | Specific Alternative 2 Requirements | 263 |
| Annex H (normative): | Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode | 264 |

| | | |
|-------------------------------|--|------------|
| H.1 | Introduction | 264 |
| H.2 | Description of operation in W-FT2FT communication mode | 265 |
| Annex I (normative): | Channel coding and Modulation | 266 |
| I.1 | Channel coding | 266 |
| I.1.1 | The parallel Turbo Code Principle | 267 |
| I.1.2 | The FOCTC implementation | 267 |
| I.1.2.1 | The FOCTC concept | 267 |
| I.1.2.2 | The FOCTC structure and the component code | 268 |
| I.1.2.3 | The FOCTC Inner interleaving algorithm | 270 |
| I.1.2.4 | FOCTC Inner interleaving size adaptation to all Physical Packet Formats | 271 |
| I.2 | Adaptive coding and Modulation Embodiment | 273 |
| I.2.1 | Adaptive code rates | 273 |
| I.2.1.1 | Adaptive code rates for the double slot structure (physical packet P80) | 274 |
| I.2.1.2 | Adaptive code rates for the full slot structure (physical packet P32) | 275 |
| I.2.1.3 | Adaptive code rates for the half slot structure (physical packet P00j with j=80) | 275 |
| I.2.2 | Puncturing patterns | 276 |
| I.2.3 | Channel Capacity for the B-field map configurations | 277 |
| I.2.3.1 | Double Slot Structure | 277 |
| I.2.3.2 | Full Slot Structure | 278 |
| I.2.3.3 | Half Slot Structure | 279 |
| I.3 | Change Modulation Scheme | 279 |
| Annex J (informative): | Channel decoding | 280 |
| Annex K (informative): | Additional information on MAC messages | 281 |
| K.1 | Historic use of some MAC service codes | 281 |
| Annex L (informative): | Bibliography | 282 |
| Annex M (informative): | Change history | 283 |
| History | | 284 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

| National transposition dates | |
|--|-------------------|
| Date of adoption of this EN: | 7 June 2010 |
| Date of latest announcement of this EN (doa): | 30 September 2010 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 March 2011 |
| Date of withdrawal of any conflicting National Standard (dow): | 31 March 2011 |