



SLOVENSKI STANDARD
SIST EN 300 175-3 V2.3.1:2010

01-oktober-2010

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 3.
del: Plast krmiljenja dostopa do prenosnega medija (MAC)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST EN 300 175-3 V2.3.1:2010](https://standards.iteh.ai/catalog/standards/sist/c66a8ee4-fae5-419c-b8ab-faa55957bb9d/sist-en-300-175-3-v2-3-1-2010)
<https://standards.iteh.ai/catalog/standards/sist/c66a8ee4-fae5-419c-b8ab-faa55957bb9d/sist-en-300-175-3-v2-3-1-2010>

ICS:

33.070.30 Digitalne izboljšane Digital Enhanced Cordless
 brezvrvične telekomunikacije Telecommunications (DECT)
 (DECT)

SIST EN 300 175-3 V2.3.1:2010 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 300 175-3 V2.3.1:2010

<https://standards.iteh.ai/catalog/standards/sist/c66a8eea-fae5-419c-b8ab-faa55957bb9d/sist-en-300-175-3-v2-3-1-2010>

ETSI EN 300 175-3 V2.3.1 (2010-06)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-3 V2.3.1:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/c66a8eea-fae5-419c-b8ab-faa55957bb9d/sist-en-300-175-3-v2-3-1-2010>



Reference
REN/DECT-000254-3

Keywords
DECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse N° 780388

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-3 V2.3.1:2010

<https://standards.iteh.ai/catalog/standards/sist/c66a8eea-fae5-419c-b8ab-faa55957bb30> - 2023-05-23 10:23:10

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at www.etsi.org.

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

ETSI registered for the benefit of its Members and of the Sector
I TIE™ is a Trade Mark of ETSI currently being registered

ETSI is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners

GSM® and the **GSM** logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols and abbreviations.....	16
4 Description of the MAC layer	18
4.1 MAC layer reference model	18
4.1.1 General.....	19
4.1.2 Cluster Control Function (CCF)	19
4.1.3 Cell Site Functions (CSF)	19
4.1.4 Relationship to physical layer elements.....	19
4.2 Frame and multiframe structures.....	20
4.2.1 General.....	20
4.2.2 Frame structure	20
4.2.3 Multiframe structure.....	22
4.3 State definitions	22
4.3.1 PP states.....	22
4.3.2 RFP states	23
5 Overview of MAC layer services.....	24
5.1 General	24
5.1.1 Broadcast Message Control (BMC).....	24
5.1.2 Connectionless Message Control (CMC)	24
5.1.3 Multi-Bearer Control	24
5.2 Service descriptions.....	24
5.2.1 Common functions.....	24
5.2.2 BMC service	25
5.2.3 CMC service	25
5.2.4 MBC services.....	25
5.3 Logical channels.....	26
5.3.1 MBC connection endpoints (MC-SAP logical channels)	26
5.3.1.1 The higher layer C-plane channels, C	26
5.3.1.2 The higher layer U-Plane channels, I	26
5.3.1.3 The higher layer U-Plane control channel, G _F	27
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	27
5.3.2 CMC endpoints (MB-SAP logical channels).....	28
5.3.2.1 The connectionless C-Plane channels, CL	28
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	28
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	28
5.3.3 BMC endpoint (MA-SAP logical channel).....	28
5.3.3.1 The slow broadcast channel, B _S	28
5.3.4 Internal MAC control channels.....	29
5.3.4.1 The system information channel, Q	29
5.3.4.2 Identities channel, N.....	29
5.3.4.3 The MAC control channel, M	29
5.3.4.4 MAC paging channel, P	29
5.4 SAP definitions	30
5.4.1 MA SAP	30
5.4.2 MB SAP.....	30
5.4.3 MC SAP	30

5.4.4	ME SAP	31
5.4.5	Order of transmission.....	31
5.5	Bearers.....	31
5.5.1	Bearer types	31
5.5.2	Bearer operation.....	32
5.6	Connection oriented services.....	32
5.6.1	Connection types	32
5.6.1.1	Basic connections.....	33
5.6.1.2	Advanced connections	33
5.6.1.2.1	Rules for ECN selection in advanced connections	33
5.6.1.3	Connection identifiers	34
5.6.1.4	Complementary connections	34
5.6.2	Symmetric and asymmetric connections.....	34
5.6.2.1	Symmetric connections	35
5.6.2.2	Asymmetric connections	40
5.7	Broadcast and connectionless services	48
5.7.1	The broadcast services	49
5.7.1.1	The continuous broadcast service	49
5.7.1.2	The non-continuous broadcast service	49
5.7.2	The connectionless services	50
5.7.2.1	Connectionless downlink services	50
5.7.2.2	Connectionless uplink services	50
6	Multiplexing	51
6.1	CCF multiplexing functions	51
6.2	CSF multiplexing functions	51
6.2.1	Bit Mappings (MAP)	56
6.2.1.1	D-field mapping (D-MAP)	56
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	57
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	57
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	58
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	58
6.2.1.2	A-field Mapping (A-MAP)	59
6.2.1.3	B-field Mapping (B-MAP)	60
6.2.1.3.1	Unprotected format.....	60
6.2.1.3.2	Encoded protected format.....	62
6.2.1.3.3	Multisubfield protected format	62
6.2.1.3.4	Singlesubfield protected format.....	64
6.2.2	Time multiplexers	66
6.2.2.1	Tail MULTipleXer (T-MUX)	66
6.2.2.1.1	T-MUX algorithm for RFP transmissions	67
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	68
6.2.2.2	B-field control multiplexer (E/U-MUX)	68
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes	70
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield	70
6.2.2.3.2	Half slot ($j=80$) modes for 2-level modulation	84
6.2.2.4	Priority scheme in E or E+U mode	85
6.2.3	Encryption.....	86
6.2.4	Scrambling	86
6.2.5	Error control.....	88
6.2.5.1	R-CRC overview	88
6.2.5.2	R-CRC generation and checking	89
6.2.5.3	X-CRC overview	89
6.2.5.4	X-CRC generation and checking	89
6.2.5.5	B-CRC generation and checking	91
6.2.6	Broadcast controller	92
7	Medium access layer messages	92
7.1	Header field	93
7.1.1	Overview/formatting.....	93
7.1.2	Tail identification, TA, bits a_0 to a_2	93
7.1.3	The "Q1/BCK" bit, bit a_3	93

7.1.4	B-field identification, BA, bits a ₄ to a ₆	94
7.1.5	The "Q2" bit, bit a ₇	95
7.2	Messages in the tail field	95
7.2.1	Overview	95
7.2.2	Identities information (N _T)	95
7.2.3	System information and multiframe marker (Q _T)	96
7.2.3.1	General	96
7.2.3.2	Static system information	97
7.2.3.2.1	General, Q _H = 0, 1 (hex)	97
7.2.3.2.2	Q _H and Normal-Reverse (NR)	97
7.2.3.2.3	Slot Number (SN)	97
7.2.3.2.4	Start Position (SP)	98
7.2.3.2.5	ESCAPE bit (ESC)	98
7.2.3.2.6	Number of transceivers	98
7.2.3.2.7	Extended RF carrier information available (Mc)	98
7.2.3.2.8	RF carriers available (RF-cars)	99
7.2.3.2.9	Spare bits (SPR)	99
7.2.3.2.10	Carrier number	99
7.2.3.2.11	Spare bits (SPR)	99
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN)	100
7.2.3.3	Extended RF carrier information part 1	100
7.2.3.3.1	General, Q _H = 2 (hex)	100
7.2.3.3.2	Further RF carrier extensions	101
7.2.3.3.3	Number of RF carriers	101
7.2.3.4	Fixed part capabilities	101
7.2.3.4.1	General, Q _H = 3 (hex)	101
7.2.3.4.2	Standard capabilities	101
7.2.3.5	Extended fixed part capabilities	102
7.2.3.5.1	General, Q _H = 4 (hex)	102
7.2.3.5.2	Extended Physical and MAC layer capabilities	103
7.2.3.5.3	Extended higher layer capabilities	104
7.2.3.6	Secondary access rights identities	104
7.2.3.6.1	General, Q _H = 5 (hex)	104
7.2.3.6.2	SARI message	104
7.2.3.7	Multiframe number	104
7.2.3.7.1	General, Q _H = 6 (hex)	104
7.2.3.7.2	Multiframe number	104
7.2.3.8	Escape	105
7.2.3.8.1	General, Q _H = 7 (hex)	105
7.2.3.8.2	Escape information	105
7.2.3.9	Extended RF carrier information part 2	105
7.2.3.9.1	General, Q _H = 9 (hex)	105
7.2.3.10	Transmit information	105
7.2.3.10.1	General, Q _H = B (hex)	105
7.2.3.11	Extended fixed part capabilities (part 2)	106
7.2.3.11.1	General, Q _H = C (hex)	106
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2)	106
7.2.3.11.3	Extended higher layer capabilities (part 2)	107
7.2.4	Paging Tail (P _T)	107
7.2.4.1	General format	107
7.2.4.1.1	P _T format for full and long page messages	107
7.2.4.1.2	P _T format for short page messages	108
7.2.4.1.3	P _T format for zero length page messages	108
7.2.4.1.4	P _T format for MAC_Resume_and_Control_page message	108
7.2.4.2	P _T header format	109
7.2.4.2.1	General format	109
7.2.4.2.2	Bit a ₈ is the extend flag	109
7.2.4.2.3	B _S SDU length indication	109
7.2.4.3	MAC layer information for PT	110
7.2.4.3.1	Information type	110
7.2.4.3.2	Fill bits / Blind long slot (j=640 / j=672) information	110
7.2.4.3.3	Blind full slot information	111

7.2.4.3.4	Bearer description.....	111
7.2.4.3.5	Escape.....	112
7.2.4.3.6	Dummy or connectionless downlink bearer marker.....	112
7.2.4.3.7	Bearer handover/replacement information	112
7.2.4.3.8	RFP status and modulation types.....	113
7.2.4.3.9	Active carriers	114
7.2.4.3.10	RFP power level	114
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	115
7.2.4.3.12	Extended modulation types	115
7.2.5	MAC control (M_T)	116
7.2.5.1	General format and contents	116
7.2.5.2	Basic connection control	116
7.2.5.2.1	General	116
7.2.5.2.2	Format for most messages	117
7.2.5.2.3	WAIT	117
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}	117
7.2.5.3	Advanced connection control.....	118
7.2.5.3.1	General	118
7.2.5.3.2	ACCESS_REQUEST	118
7.2.5.3.3	BEARER_HANDOVER_REQUEST	118
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST	118
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST	119
7.2.5.3.6	BEARER_CONFIRM	119
7.2.5.3.7	WAIT	119
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}	119
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}.....	122
7.2.5.3.10	Channel_list.....	122
7.2.5.3.11	Unconfirmed_dummy.....	123
7.2.5.3.12	Unconfirmed_handover.....	123
7.2.5.3.13	RELEASE	123
7.2.5.4	MAC layer test messages	124
7.2.5.4.1	Basic format	124
7.2.5.4.2	FORCE_TRANSMIT.....	125
7.2.5.4.3	LOOPBACK_DATA.....	125
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	126
7.2.5.4.5	ESCAPE	127
7.2.5.4.6	NETWORK_TEST.....	127
7.2.5.4.7	CLEAR_TEST_MODES.....	127
7.2.5.4.8	CHANGE_MODULATION_SCHEME	127
7.2.5.5	Quality control	128
7.2.5.5.1	Prolonged preamble diversity	129
7.2.5.6	Broadcast and connectionless services.....	130
7.2.5.7	Encryption control.....	130
7.2.5.8	B-field setup, first PT transmission.....	131
7.2.5.9	Escape	132
7.2.5.10	TARI message.....	132
7.2.5.11	REP connection control.....	132
7.2.5.11.1	General	132
7.2.5.11.2	Format for most messages	132
7.2.5.11.3	REP CHANNEL MAP REQUEST	133
7.2.5.11.4	REP CHANNEL MAP CONFIRM	133
7.3	Messages in the B-field	133
7.3.1	Overview	133
7.3.2	Advanced connection control	134
7.3.2.1	General format	134
7.3.2.2	BEARER_REQUEST	135
7.3.2.3	BEARER_CONFIRM	135
7.3.2.4	WAIT	136
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}	136
7.3.2.6	BANDWIDTH_B_{Req;Cfm}	137
7.3.2.7	CHANNEL_LIST	137
7.3.2.8	UNCONFIRMED_DUMMY.....	137

7.3.2.9	UNCONFIRMED_HANDOVER	138
7.3.2.10	RELEASE	138
7.3.3	Null or I _{PF} segmentation info	139
7.3.3.1	Spare or I _{PF} segmentation info	140
7.3.3.2	Extended NCF bits	141
7.3.4	Quality control	141
7.3.4.1	General format	141
7.3.4.2	Bearer and connection control	141
7.3.4.3	RESET	143
7.3.4.4	Bearer quality in an asymmetric connection	143
7.3.5	Extended system information	144
7.3.5.1	General format	144
7.3.5.2	TARI messages	144
7.3.5.3	"no-emission" mode sync information	144
7.3.6	G _F channel data packet	145
7.3.7	Escape	145
8	Medium access layer primitives	145
8.1	Connection oriented service primitives	146
8.1.1	Connection setup: MAC_CON {req;ind;cfm}	146
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}	147
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}	148
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}	149
8.1.5	Restart DLC: MAC_RES_DLC {ind}	149
8.1.6	Connection release: MAC_DIS {req;ind}	149
8.1.7	MAC bandwidth: MAC_BW {ind;res}	150
8.1.8	Encryption.....	150
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}	150
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}	150
8.1.9	C-plane switching procedure	151
8.1.9.1	C-plane switching procedure: MAC_C _S _C _F {req, cfm, ind, res}	151
8.1.9.2	C-plane switching procedure: MAC_C _S C _F END {ind}	151
8.2	Connectionless and broadcast service primitives	152
8.2.1	Paging: MAC_PAGE {req;ind}	152
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}	152
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}	153
8.2.4	"no-emission" mode.....	153
8.3	Management primitives	153
8.3.1	Connection control.....	153
8.3.1.1	Connection setup: MAC_ME_CON {ind}	153
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}	153
8.3.1.3	Bearer release: MAC_ME_REL {req}	153
8.3.1.4	MBC release report: MAC_ME_REL REP {ind}	154
8.3.2	System information and identities	154
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}	154
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}	154
8.3.2.3	System information output: MAC_ME_INFO {ind;res}	154
8.3.2.4	Extended system info: MAC_ME_EXT.{req;ind;res;cfm}	154
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}	154
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}	155
8.3.5	Error reports: MAC_ME_ERROR {ind;res}	155
8.4	Flow control	155
8.4.1	MA SAP flow control	155
8.4.2	MB SAP flow control	155
8.4.3	MC SAP flow control	155
9	Broadcast and connectionless procedures	158
9.1	Downlink broadcast and connectionless procedures	158
9.1.1	Downlink broadcast procedure	158
9.1.1.1	Broadcast information	158
9.1.1.2	Channel selection for downlink broadcast services	158
9.1.1.3	Downlink broadcast procedure description	160

9.1.2	Downlink connectionless procedure	160
9.1.2.1	Channel selection at the RFP	160
9.1.2.2	Downlink connectionless procedure description.....	160
9.1.3	Paging broadcast procedure	160
9.1.3.1	RFP paging broadcasts	161
9.1.3.2	PP paging procedures.....	163
9.1.3.2.1	PP paging detection	163
9.1.3.2.2	PP paging processing.....	163
9.2	Uplink connectionless procedures	163
9.2.1	General.....	163
9.2.2	Bearer selection for the connectionless uplink.....	164
9.2.3	Procedure for the connectionless uplink	164
9.2.3.1	Predicates	164
9.2.3.2	PT D-field construction.....	164
9.2.3.3	PT transmission sequence	165
9.2.3.4	FT procedure	165
9.3	Non-continuous broadcast procedure	166
9.3.1	Request for specific Q channel information.....	166
9.3.1.1	A-field procedure	166
9.3.1.2	B-field procedure	166
9.3.2	Request for a new dummy bearer	167
9.4	"No-emission" mode procedures	167
9.4.1	Initiation of the "no-emission" mode	167
9.4.1.1	Successful activation (countdown to zero).....	167
9.4.1.2	Multiframe countdown stopped by FT	168
9.4.1.3	Multiframe countdown stopped by PT	168
9.4.1.4	PT does not receive multiframe countdown "zero".....	169
9.4.2	Behaviour during power-down-mode	169
9.4.3	Waking up, FT initiated	169
9.4.4	Waking up, PT initiated	173
10	Connection oriented service procedures.....	174
10.1	Overview	174
10.2	C/O connection setup	175
10.2.1	General.....	175
10.2.2	Initiation of a basic and a normal connection setup.....	175
10.2.3	Initiation of a fast connection setup	175
10.2.4	Connection setup procedure description	176
10.2.4.1	Creation of MBCs	176
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	178
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation.....	179
10.2.4.3.1	Symmetric connection	181
10.2.4.3.2	Asymmetric uplink connection.....	181
10.2.4.3.3	Asymmetric downlink connection.....	181
10.2.4.3.4	Connection established.....	181
10.3	C/O connection modification	182
10.3.1	Advanced connection: bandwidth modification.....	182
10.3.1.1	Suspend and resume	184
10.3.1.2	MAC resume paging	184
10.3.2	Advanced connection: service type or slot type modification	184
10.3.2.1	Procedure for service type modification	184
10.3.2.2	Procedures for slot type modification	185
10.3.2.2.1	Procedure for slot type modification full to double	185
10.3.2.2.2	Procedure for slot type modification double to full	186
10.3.2.2.3	Procedures for slot type modification to/from long	186
10.3.2.2.4	Procedure for slot type modification in multibearer connections	187
10.3.2.3	Procedure for ECN number modification in an advanced connection	187
10.3.3	Connection type modification.....	187
10.3.3.1	Procedure for connection type modification basic to advanced	188
10.3.3.1.1	General procedure	188
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	188

10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	189
10.3.3.2	Procedure for connection type modification advanced to basic	189
10.3.4	Modulation type modification.....	189
10.3.4.1	Adaptive code rate.....	191
10.4	C/O connection release.....	191
10.4.1	General.....	191
10.4.2	Procedure description	192
10.5	C/O bearer setup.....	192
10.5.1	Single bearer setup procedures	192
10.5.1.1	Basic bearer setup procedure.....	192
10.5.1.2	A-field advanced single bearer setup procedure	194
10.5.1.2.1	PT initiated	195
10.5.1.2.2	FT initiated	197
10.5.1.3	B-field single bearer setup procedure.....	198
10.5.1.3.1	PT initiated	199
10.5.1.3.2	FT initiated	201
10.5.1.4	Double simplex setup procedure	201
10.5.1.4.1	Terminology and Predicates	201
10.5.1.4.2	General description.....	202
10.5.1.4.3	Channel selection procedure for circuit mode connections	202
10.5.1.4.4	Channel selection procedure for packet mode connections	203
10.5.1.4.5	Indirect setup procedure	204
10.5.1.4.6	Direct setup procedure.....	204
10.5.1.4.7	Handling of encrypted connections	207
10.5.1.5	Complementary connection bearer setup	209
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	209
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	210
10.5.1.7.1	Default rules for TA code "111".....	211
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	211
10.5.2	Channel list procedures	212
10.5.2.1	General	212
10.5.2.2	Description of the channel list messages	212
10.5.2.3	Usage of the channel list messages	213
10.6	C/O bearer handover	214
10.6.1	General.....	214
10.6.2	Duplex bearer handover procedure.....	215
10.6.3	Double simplex bearer handover	216
10.6.4	Bearer replacement	216
10.6.4.1	General bearer replacement.....	216
10.6.4.2	Frequency replacement	217
10.7	C/O bearer release	218
10.7.1	General.....	218
10.7.2	Bearer release procedure description	218
10.7.2.1	Unacknowledged release procedure	218
10.7.2.1.1	Crossed bearer release procedure	219
10.7.2.2	Acknowledged release procedure.....	219
10.7.2.3	Fast release procedure	219
10.7.2.4	REP relayed bearer release.....	220
10.8	C/O data transfer	220
10.8.1	Higher layer associated signalling (C)	220
10.8.1.1	C _S channel data	220
10.8.1.1.1	Transmission principle	221
10.8.1.1.2	Numbering principle.....	221
10.8.1.2	C _F channel data	221
10.8.1.2.1	Transmission principle	221
10.8.1.2.2	Numbering principle.....	222
10.8.1.3	Q1 and Q2 bit settings for I _N and I _{P_error_detection} services	222
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I _N	222
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I _{P_error_detect}	222
10.8.1.3.3	Q2 bit settings.....	223
10.8.1.3.4	Q1 bit settings.....	224

10.8.2	MOD-2 protected I channel operation (I_P).....	225
10.8.2.1	General.....	225
10.8.2.2	Limiting the lifetime of packets	225
10.8.2.3	A-field shall always be correct.....	225
10.8.2.4	Use of the acknowledge bits.....	225
10.8.2.4.1	Q2 and BCK bit setting for I_P _error_correction services	226
10.8.2.4.2	BCK bit setting.....	226
10.8.2.5	Data jump procedures	226
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement	227
10.8.2.5.2	Unilateral jump.....	227
10.8.2.5.3	MAC I_P bearer reset.....	228
10.8.2.6	Bearer handover and bearer replacement procedures.....	229
10.8.2.6.1	General	229
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	229
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel	229
10.8.2.7	Exchange of data from/to higher layers	230
10.8.2.7.1	Operation if I_{PF} channel is supported.....	230
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_P).....	231
10.8.3.1	I_N _minimum_delay service	231
10.8.3.2	I_N _normal_delay service	231
10.8.3.3	I_P _error_detection service	231
10.8.3.3.1	Operation if I_{PF} channel is supported.....	232
10.8.3.4	I_P _encoder_protected service (I_{PX})	232
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux.....	232
10.8.4.1	Purpose of the I_{PF} channel	232
10.8.4.2	Activation of the E+U type mux mode	232
10.8.4.3	I_{PF} procedures.....	233
10.8.4.3.1	I_{PF} basic procedures	233
10.8.4.3.2	I_{PF} advanced procedures	234
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	234
10.8.4.4	I_{PF} Mod-2 protected operation.....	234
10.8.4.5	I_{PF} _error_detect operation SIST EN 300 175-3 V2.3.1:2010	235
10.8.4.6	I_{PF} _operation with I_N service ai/catalog/standards/sist/c66a8eea-fa5-419c-b8ab- 55957bh9d/sist-en-300-175-3-v2-3-1-2010	235
10.8.4.7	Backcompatibility rule 55957bh9d/sist-en-300-175-3-v2-3-1-2010	235
10.9	C/O procedures for FT connections with CRFP.....	235
10.9.1	Dual C/O bearer setup.....	235
10.9.2	C/O connection release of connection with CRFP.....	236
10.9.3	C/O connection suspend and resume	236
11	Medium access layer management procedures	236
11.1	Broadcasting.....	236
11.1.1	RFP transmission	236
11.1.2	PP reception.....	236
11.2	Extended system information	237
11.2.1	PP requests.....	237
11.2.2	RFP response	237
11.3	PP states and state transitions	237
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	237
11.3.2	Entry into the Idle_Locked state	237
11.3.3	Actions in the Idle_Locked state.....	238
11.3.3.1	Page detection in Idle_Locked state	238
11.3.3.2	Setup detection in Idle_Locked state.....	238
11.3.4	Idle_Locked and Active_Locked state transitions	239
11.4	Physical channel selection.....	239
11.4.1	The channel selection lists	240
11.4.2	Physical channel and RFP selection at the PP	242
11.4.3	Physical channel selection at the RFP.....	243
11.4.4	Hand over criteria due to in-connection base identification	245
11.4.5	Handover criteria due to interference.....	245
11.5	In-connection quality control	245
11.5.1	RFPI handshake	245
11.5.2	Frequency control	246

11.5.2.1	RFP measurement of frequency error	246
11.5.2.2	PT frequency correction	246
11.6	Maximum allowed system load at RFPs	246
11.7	PMID and FMID definitions	246
11.7.1	FMID definition	246
11.7.2	PMID definition	246
11.8	RFP idle receiver scan sequence	246
11.9	PT receiver scan sequence	247
11.10	Management of connections associated with Broadband data links	248
11.11	Management procedures for "no-emission" mode	248
11.11.1	Behaviour during "no-emission" mode	248
12	Medium access layer test message procedure	248
12.1	Introduction	248
12.2	General	249
12.2.1	Portable part testing	250
12.2.2	Fixed part testing	250
12.2.3	Applicability of test messages	250
12.3	FORCE_TRANSMIT	251
12.3.1	Portable part	251
12.3.2	Fixed part	251
12.4	LOOPBACK_DATA	252
12.4.1	Portable part	252
12.4.2	Fixed Part	252
12.4.2.1	IUTs implementing the DECT scrambler	252
12.4.2.2	IUTs implementing a proprietary scrambler	252
12.5	DEFEAT_ANTENNA_DIVERSITY	252
12.6	NETWORK_TEST	253
12.7	ESCAPE	253
12.8	CLEAR_TEST_MODES	253
12.9	CHANGE_MODULATION_SCHEME	253
Annex A (normative):	SIST EN 300 175-3 V2.3.1:2010 MAC layer timers and constants	254
A.1	Timers and Time Windows	254
A.2	Constants	254
Annex B (informative):	Construction of the CRC polynomial and error detecting performance	256
Annex C (informative):	MAC relationship to other layers	257
Annex D (informative):	Synchronization	258
Annex E (normative):	Scrambling patterns	259
Annex F (informative):	Seamless handover operation	260
F.1	I channel data flow for I _N _minimum_delay service	260
Annex G (normative):	Requirements for PPs with direct PP to PP communication mode	261
G.1	Description of operation in direct PP to PP communication mode	261
G.2	Requirements	262
G.2.1	Setting the PP in direct communications mode	262
G.2.2	Specific Alternative 1 requirements	262
G.2.2.1	When the PP has not initiated a call	262
G.2.2.2	When the PP initiates a call	262
G.2.3	Specific Alternative 2 Requirements	263
Annex H (normative):	Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode	264

H.1	Introduction	264
H.2	Description of operation in W-FT2FT communication mode.....	265
Annex I (normative):	Channel coding and Modulation	266
I.1	Channel coding.....	266
I.1.1	The parallel Turbo Code Principle	267
I.1.2	The FOCTC implementation.....	267
I.1.2.1	The FOCTC concept.....	267
I.1.2.2	The FOCTC structure and the component code.....	268
I.1.2.3	The FOCTC Inner interleaving algorithm	270
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats	271
I.2	Adaptive coding and Modulation Embodiment.....	273
I.2.1	Adaptive code rates	273
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80)	274
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32).....	275
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80).....	275
I.2.2	Puncturing patterns.....	276
I.2.3	Channel Capacity for the B-field map configurations	277
I.2.3.1	Double Slot Structure.....	277
I.2.3.2	Full Slot Structure.....	278
I.2.3.3	Half Slot Structure	279
I.3	Change Modulation Scheme	279
Annex J (informative):	Channel decoding.....	280
Annex K (informative):	iTeh STANDARD PREVIEW Additional information on MAC messages.....	281
K.1	Historic use of some MAC service codes.....	281
Annex L (informative):	Bibliography EN 300 175-3 V2.3.1:2010.....	282
Annex M (informative):	Change history.....	283
	History	284

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

National transposition dates iTeh STANDARD PREVIEW (standards.iteh.ai)	
Date of adoption of this EN:	7 June 2010
Date of latest announcement of this EN (doa):	30 September 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e): https://standards.iteh.ai/catalog/standards/sist/c66a8eea-fae5-419c-b8ab-055957119d/sist-en-300-175-3-v2-3-1-2010	31 March 2011
Date of withdrawal of any conflicting National Standard (dow):	31 March 2011