

# ETSI EN 300 175-4 V2.3.1 (2010-06)

---

European Standard (Telecommunications series)

## Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/3708f68e-94e5-482e-a1ea-c81e377a0f00/etsi-en-300-175-4-v2.3.1-2010-06>



## Reference

REN/DECT-000254-4

## Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

|  |    |
|--|----|
| Intellectual Property Rights .....   | 11 |
| Foreword.....  | 11 |
| 1 Scope .....  | 12 |
| 2 References .....   | 13 |
| 2.1 Normative references .....   | 13 |
| 2.2 Informative references.....  | 14 |
| 3 Definitions, symbols and abbreviations .....   | 14 |
| 3.1 Definitions.....   | 14 |
| 3.2 Symbols and abbreviations.....   | 14 |
| 4 Data Link Control (DLC) layer overview .....   | 16 |
| 4.1 General .....  | 16 |
| 4.2 C-plane services .....   | 17 |
| 4.3 U-plane services .....   | 18 |
| 4.4 Lower Layer Management Entity (LLME) .....   | 20 |
| 5 C-plane service characteristics .....  | 20 |
| 5.1 Data link service (LAPC+Lc).....   | 20 |
| 5.1.1 General.....   | 20 |
| 5.1.2 LAPC types of operation .....  | 21 |
| 5.1.3 Establishment of information transfer modes .....                                    | 21 |
| 5.1.3.1 Data Link Identifier (DLI) .....   | 21 |
| 5.1.3.2 LAPC states.....   | 21 |
| 5.2 Broadcast service (Lb).....  | 22 |
| 6 Frame structures for C-plane services.....   | 23 |
| 6.1 Data link service frame structure.....   | 23 |
| 6.1.1 General frame structure .....  | 23 |
| 6.1.2 Lc frame delimiting and transparency .....   | 24 |
| 6.1.3 Transmission order .....   | 24 |
| 6.1.4 Routing to logical channels.....   | 24 |
| 6.1.4.1 C <sub>F</sub> /CL <sub>F</sub> logical channel.....                               | 24 |
| 6.1.4.2 C <sub>S</sub> /CL <sub>S</sub> logical channel.....                               | 25 |
| 6.1.5 Invalid frames .....   | 25 |
| 6.2 Broadcast service frame structure.....   | 26 |
| 6.2.1 Standard frame structure .....   | 26 |
| 6.2.2 Extended frame structure .....   | 26 |
| 7 Elements of procedures and formats of fields for C-plane peer-to-peer communication..... | 27 |
| 7.1 General .....  | 27 |
| 7.2 Address field formats .....  | 27 |
| 7.3 Address field parameters .....   | 27 |
| 7.3.1 REServed bit (RES).....  | 27 |
| 7.3.2 Command Response (C/R) bit .....   | 27 |
| 7.3.3 SAPI field .....   | 27 |
| 7.3.4 New Link Flag (NLF) bit.....   | 28 |
| 7.3.5 LLN-field.....   | 28 |
| 7.3.6 Data Link Identifiers (DLI).....   | 28 |
| 7.4 Control field formats .....  | 29 |
| 7.5 Control field parameters .....   | 29 |
| 7.5.1 Poll/Final (P/F) bit .....   | 29 |
| 7.5.2 Multiple frame operation variables and sequence numbers .....                        | 29 |
| 7.5.2.1 Modulus .....  | 29 |
| 7.5.2.2 Send state Variable V(S).....  | 29 |
| 7.5.2.3 Acknowledge state Variable V(A) .....  | 30 |
| 7.5.2.4 Send sequence Number N(S) .....  | 30 |

|         |   |    |
|---------|---|----|
| 7.5.2.5 | Receive state Variable V(R).....                                      | 30 |
| 7.5.2.6 | Receive sequence Number N(R).....                                     | 30 |
| 7.5.3   | Unacknowledged operation variables and sequence numbers.....          | 30 |
| 7.5.4   | Supervisory and Unnumbered function bits S and U.....                 | 30 |
| 7.6     | Length indicator field format.....                                    | 30 |
| 7.7     | Length indicator field parameters.....                                | 31 |
| 7.7.1   | Length indicator field extension bit (N).....                         | 31 |
| 7.7.2   | More data bit (M).....  | 31 |
| 7.7.3   | Length parameter (L <sub>I</sub> ).....                               | 31 |
| 7.7.4   | Extended length parameter (L <sub>II</sub> ).....                     | 32 |
| 7.7.5   | Reserved bit (RES).....   | 32 |
| 7.8     | Fill field format.....  | 32 |
| 7.9     | Checksum field format.....  | 32 |
| 7.10    | Checksum field parameters.....  | 32 |
| 7.11    | Commands and responses.....   | 34 |
| 7.11.1  | Information (I) command.....  | 34 |
| 7.11.2  | Receive Ready (RR) command/response.....                              | 34 |
| 7.11.3  | Receive Not Ready (RNR) command/response.....                         | 35 |
| 7.11.4  | REJect (REJ) command/response.....                                    | 35 |
| 7.11.5  | Set Asynchronous Balanced Mode (SABM) command.....                    | 35 |
| 7.11.6  | Disconnect Mode (DM) response.....                                    | 35 |
| 7.11.7  | Unnumbered Information (UI) command.....                              | 35 |
| 7.11.8  | DISConnect (DISC) command.....  | 36 |
| 7.11.9  | Unnumbered ACK (UA) response.....                                     | 36 |
| 8       | Primitives.....   | 36 |
| 8.1     | Primitive types.....  | 36 |
| 8.2     | Primitives to the MAC layer (lower layer).....                        | 36 |
| 8.3     | Primitives to the NWK layer (higher layer).....                       | 36 |
| 8.3.1   | Parameter definitions.....  | 37 |
| 8.3.2   | S-SAP primitives.....   | 38 |
| 8.3.2.1 | DL_ESTABLISH primitive.....   | 38 |
| 8.3.2.2 | DL_RELEASE primitive.....   | 38 |
| 8.3.2.3 | DL_DATA primitive.....  | 39 |
| 8.3.2.4 | DL_UNIT_DATA primitive.....   | 39 |
| 8.3.2.5 | DL_SUSPEND primitive.....   | 39 |
| 8.3.2.6 | DL_RESUME primitive.....  | 39 |
| 8.3.2.7 | DL_ENC_KEY primitive.....   | 40 |
| 8.3.2.8 | DL_ENCRYPT primitive.....   | 40 |
| 8.3.2.9 | DL_SERVICE_MOD primitive.....   | 40 |
| 8.3.3   | B-SAP primitives.....   | 40 |
| 8.3.3.1 | DL_BROADCAST primitive.....   | 41 |
| 8.3.3.2 | DL_EXPEDITED primitive.....   | 41 |
| 8.4     | Primitives to the interworking unit.....                              | 41 |
| 8.4.1   | Parameter definitions.....  | 41 |
| 8.4.2   | LU <sub>X</sub> -SAP primitives.....                                  | 42 |
| 8.4.2.1 | DL_U_DATA primitive.....  | 42 |
| 8.4.2.2 | DL_U_UNIT_DATA primitive.....   | 42 |
| 8.4.2.3 | DL_U_ERROR primitive.....   | 42 |
| 9       | C-plane peer-to-peer procedures.....                                  | 43 |
| 9.1     | General.....  | 43 |
| 9.2     | Point to point acknowledged operation.....                            | 43 |
| 9.2.1   | Procedure for the use of the P/F bit.....                             | 43 |
| 9.2.1.1 | Class A acknowledged information transfer.....                        | 43 |
| 9.2.1.2 | Class B acknowledged information transfer.....                        | 44 |
| 9.2.2   | Use of LLN.....   | 44 |
| 9.2.2.1 | Class A operation.....  | 44 |
| 9.2.2.2 | Class B operation.....  | 44 |
| 9.2.3   | Link establishment and information transfer in class A operation..... | 44 |
| 9.2.3.1 | Establishing class A operation.....                                   | 44 |
| 9.2.3.2 | Class A acknowledged information transfer.....                        | 45 |

|           |   |    |
|-----------|---|----|
| 9.2.3.3   | Transmission of class A I-frames .....  | 45 |
| 9.2.3.4   | Reception of class A I-frames .....   | 46 |
| 9.2.3.5   | Receiving acknowledgements .....  | 46 |
| 9.2.3.6   | Waiting for acknowledgement .....   | 46 |
| 9.2.3.7   | Release of class A operation .....  | 47 |
| 9.2.3.8   | Re-establishment of class A operation .....   | 47 |
| 9.2.4     | Establishing class B multiple frame operation .....                                 | 47 |
| 9.2.4.1   | Overview .....  | 47 |
| 9.2.4.2   | Class B multiple frame establishment procedures .....                               | 48 |
| 9.2.4.3   | Class B LLN assignment procedures .....   | 49 |
| 9.2.4.3.1 | PT establishment .....  | 49 |
| 9.2.4.3.2 | FT establishment .....  | 50 |
| 9.2.5     | Link maintenance and information transfer in class B multiple frame operation ..... | 50 |
| 9.2.5.1   | Transmitting I-frames .....   | 50 |
| 9.2.5.2   | Receiving I-frames .....  | 51 |
| 9.2.5.2.1 | P bit set to 1 .....  | 51 |
| 9.2.5.2.2 | P bit set to 0 .....  | 51 |
| 9.2.5.3   | Sending and receiving acknowledgements .....  | 51 |
| 9.2.5.3.1 | Sending acknowledgements .....  | 51 |
| 9.2.5.3.2 | Receiving acknowledgements .....  | 51 |
| 9.2.5.4   | Receiving REJ-frames .....  | 52 |
| 9.2.5.5   | Receiving RNR-frames .....  | 53 |
| 9.2.5.6   | LAPC own receiver busy condition .....  | 54 |
| 9.2.5.7   | Waiting acknowledgement .....   | 54 |
| 9.2.5.8   | Appropriate supervisory frame .....   | 55 |
| 9.2.6     | Release of class B multiple frame operation .....                                   | 55 |
| 9.2.7     | Link suspension and resumption .....  | 56 |
| 9.2.7.1   | Link suspension .....   | 56 |
| 9.2.7.1.1 | Class B acknowledged suspend .....  | 56 |
| 9.2.7.1.2 | Unacknowledged suspend .....  | 57 |
| 9.2.7.2   | Class B link resumption .....   | 58 |
| 9.2.7.3   | Connection handover .....   | 59 |
| 9.2.7.3.1 | Class A connection handover .....   | 60 |
| 9.2.7.3.2 | Class B connection handover .....   | 61 |
| 9.2.7.3.3 | Expiry of connection handover timer .....   | 61 |
| 9.2.8     | Re-establishment of class B multi-frame operation .....                             | 61 |
| 9.2.8.1   | Criteria for re-establishment .....   | 61 |
| 9.2.8.2   | Procedure .....   | 62 |
| 9.2.9     | Exception handling .....  | 62 |
| 9.2.9.1   | General .....   | 62 |
| 9.2.9.2   | Class B exception condition reporting and recovery .....                            | 63 |
| 9.2.9.2.1 | N(S) sequence error .....   | 63 |
| 9.2.9.2.2 | N(R) sequence error .....   | 63 |
| 9.2.9.2.3 | Timer recovery condition .....  | 63 |
| 9.2.9.2.4 | Collision of identical transmitted and received commands .....                      | 63 |
| 9.3       | Unacknowledged operation .....  | 64 |
| 9.3.1     | Use of LLN for unacknowledged information transfer .....                            | 64 |
| 9.3.2     | Class U link establishment .....  | 64 |
| 9.3.3     | Unacknowledged information transfer .....   | 64 |
| 9.3.3.1   | Transmission of unacknowledged information .....                                    | 64 |
| 9.3.3.2   | Reception of unacknowledged information .....                                       | 64 |
| 9.3.4     | Unacknowledged release .....  | 64 |
| 9.4       | Broadcast operation .....   | 65 |
| 9.4.1     | Normal operation .....  | 65 |
| 9.4.1.1   | Procedure in the Fixed radio Termination (FT) .....                                 | 65 |
| 9.4.1.2   | Procedure in the Portable radio Termination (PT) .....                              | 65 |
| 9.4.2     | Expedited operation .....   | 65 |
| 9.4.2.1   | Procedure in the Fixed radio Termination (FT) .....                                 | 65 |
| 9.4.2.2   | Procedure in the Portable radio Termination (PT) .....                              | 65 |
| 9.5       | MAC layer interfaces .....  | 66 |
| 9.5.1     | MC-SAP .....  | 66 |
| 9.5.1.1   | C-plane overview .....  | 66 |

|          |  |    |
|----------|--|----|
| 9.5.1.2  | C-plane service data procedures.....   | 66 |
| 9.5.1.3  | U-plane service data.....  | 67 |
| 9.5.2    | MB-SAP.....  | 67 |
| 9.5.2.1  | C-plane service data procedures.....   | 67 |
| 9.5.2.2  | U-plane service data.....  | 67 |
| 9.5.3    | MA-SAP.....  | 68 |
| 9.5.3.1  | Overview.....  | 68 |
| 9.5.3.2  | Service data procedures.....   | 68 |
| 10       | Management procedures.....   | 68 |
| 10.1     | Lower Layer Management Entity (LLME).....  | 68 |
| 10.2     | MAC connection management.....   | 69 |
| 10.2.1   | MAC connection set-up.....   | 69 |
| 10.2.2   | MAC connection release.....  | 69 |
| 10.2.3   | MAC connection modification.....   | 69 |
| 10.2.4   | MAC connection identifiers.....  | 70 |
| 10.2.4.1 | Overview.....  | 70 |
| 10.2.4.2 | Advanced MAC Connection Identifiers (AMCI).....  | 70 |
| 10.2.4.3 | Basic MAC Connection Identifiers (BMCI).....   | 71 |
| 10.2.4.4 | MAC Connection Endpoint Identifier (MCEI).....   | 71 |
| 10.2.5   | Selection of logical channel ( $C_S$ or $C_F$ ).....   | 71 |
| 10.3     | DLC C-plane (LAPC) management.....   | 72 |
| 10.3.1   | Provision of link signature.....   | 72 |
| 10.3.2   | Routing of connection oriented links.....  | 72 |
| 10.3.3   | Routing of connectionless links.....   | 73 |
| 10.4     | DLC U-plane (LUX) management.....  | 73 |
| 10.4.1   | U-plane establishment.....   | 73 |
| 10.4.2   | U-plane release.....   | 73 |
| 10.4.3   | U-plane suspend and resume.....  | 73 |
| 10.5     | Connection handover management.....  | 74 |
| 10.6     | Ciphering management.....  | 74 |
| 10.6.1   | Ciphering management in cases where the NWK layer executes the ciphering related MM procedure.....         | 74 |
| 10.6.1.1 | Providing a key to the MAC layer.....  | 74 |
| 10.6.1.2 | Starting and stopping the ciphering.....   | 75 |
| 10.6.1.3 | Connection handover.....   | 75 |
| 10.6.2   | Ciphering management in cases where the NWK layer does not execute the ciphering related MM procedure..... | 75 |
| 10.7     | Broadband data link management.....  | 75 |
| 11       | U-plane service characteristics.....   | 76 |
| 11.1     | General.....   | 76 |
| 11.2     | LU1 TRansparent UnProtected service (TRUP).....  | 76 |
| 11.3     | LU2 Frame RELay service (FREL).....  | 77 |
| 11.3.1   | General.....   | 77 |
| 11.3.2   | Checksum operation.....  | 78 |
| 11.3.3   | Segmentation and transmission class.....   | 78 |
| 11.3.4   | Data transmission.....   | 79 |
| 11.3.4.1 | Send side procedure.....   | 79 |
| 11.3.4.2 | Receive side procedure.....  | 79 |
| 11.4     | LU3 Frame SWItching service (FSWI).....  | 80 |
| 11.5     | LU4 Forward Error Correction (FEC) service.....  | 80 |
| 11.6     | LU5 Basic RATE adaption service (BRAT).....  | 81 |
| 11.6.1   | Overview.....  | 81 |
| 11.6.2   | Protected service operation.....   | 82 |
| 11.6.2.1 | General.....   | 82 |
| 11.6.2.2 | Data buffering and initial rate adaptation.....  | 82 |
| 11.6.2.3 | Multi-channel set multiplexing.....  | 83 |
| 11.6.2.4 | Segmentation of Multiplexed Data Units (MDU).....  | 84 |
| 11.6.2.5 | Frame sequencing and addition of control and fill octets.....  | 85 |
| 11.6.2.6 | Frame transmission.....  | 86 |
| 11.6.3   | Unprotected service operation.....   | 87 |
| 11.6.3.1 | General.....   | 87 |

|             |   |     |
|-------------|---|-----|
| 11.6.3.2    | Data buffering and initial rate adaption.....                               | 87  |
| 11.6.3.3    | Multi-channel set multiplexing .....  | 87  |
| 11.6.3.4    | Segmentation of MDUs.....   | 89  |
| 11.6.3.5    | Frame transmission .....  | 89  |
| 11.7        | LU6 Secondary RATE adaption (SRAT) service .....                            | 89  |
| 11.7.1      | General.....  | 89  |
| 11.8        | LU16 ESCape Service (ESC).....  | 90  |
| 11.8.1      | General.....  | 90  |
| 11.9        | LU7 64 kbit/s data bearer service .....                                     | 91  |
| 11.9.1      | General.....  | 91  |
| 11.9.2      | Physical layer service.....   | 91  |
| 11.9.3      | MAC layer service .....   | 91  |
| 11.9.4      | DLC layer service .....   | 91  |
| 11.9.4.1    | Architectural model.....  | 91  |
| 11.9.4.1.1  | Transmit (Tx) frame buffering .....   | 92  |
| 11.9.4.1.2  | Receive (Rx) frame buffering .....  | 92  |
| 11.9.4.2    | Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....         | 92  |
| 11.9.4.2.1  | Control field .....   | 93  |
| 11.9.4.2.2  | Information field.....  | 95  |
| 11.9.4.2.3  | ARQ checksum.....   | 96  |
| 11.9.4.3    | Procedures for normal operation .....                                       | 96  |
| 11.9.4.3.1  | Establishment and synchronization procedures .....                          | 96  |
| 11.9.4.3.2  | Active phase .....  | 98  |
| 11.9.4.3.3  | Release.....  | 100 |
| 11.9.4.4    | Exceptional procedures .....  | 100 |
| 11.9.4.4.1  | Invalid frame condition .....   | 100 |
| 11.9.4.4.2  | Establishment .....   | 100 |
| 11.9.4.4.3  | Transmitting frames.....  | 100 |
| 11.9.4.4.4  | Receiving frames .....  | 100 |
| 11.9.4.4.5  | Sending acknowledgements .....  | 101 |
| 11.9.4.4.6  | Forwarding of received data .....   | 101 |
| 11.9.4.4.7  | N(R) sequence error .....   | 101 |
| 11.9.4.4.8  | N(O) sequence error .....   | 101 |
| 11.9.4.4.9  | N(S) sequence error .....   | 102 |
| 11.9.4.4.10 | Format error.....   | 102 |
| 11.9.4.4.11 | Abnormal release.....   | 102 |
| 11.9.4.4.12 | Implicit reset.....   | 102 |
| 11.9.5      | Network layer service .....   | 102 |
| 11.9.5.1    | LCE service.....  | 102 |
| 11.9.5.2    | CC service.....   | 102 |
| 11.10       | LU8 service .....   | 103 |
| 11.10.1     | Physical layer service.....   | 103 |
| 11.10.2     | MAC layer service .....   | 103 |
| 11.10.3     | DLC layer service .....   | 103 |
| 11.11       | LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service ..... | 103 |
| 11.11.1     | Overview .....  | 103 |
| 11.11.1.1   | FU9 frame structure .....   | 104 |
| 11.11.1.1.1 | General frame structure .....   | 104 |
| 11.11.1.1.2 | FU9 buffering procedures.....   | 104 |
| 11.11.1.1.3 | Connection handover.....  | 104 |
| 11.11.1.1.4 | Transmission order .....  | 105 |
| 11.11.2     | Alignment signal management .....   | 105 |
| 11.11.2.1   | General .....   | 105 |
| 11.11.2.2   | Procedures.....   | 105 |
| 11.11.3     | V.24 Signalling .....   | 106 |
| 11.11.3.1   | General .....   | 106 |
| 11.11.3.2   | Transmitter procedures.....   | 107 |
| 11.11.3.3   | Receiver procedures .....   | 107 |
| 11.11.4     | Rate Coding .....   | 107 |
| 11.11.4.1   | General .....   | 107 |
| 11.11.4.2   | Transmitter procedures.....   | 108 |
| 11.11.4.3   | Receiver procedures .....   | 108 |



|             |   |     |
|-------------|---|-----|
| 11.11.5     | DECT Independent Clocking (DIC) .....           | 109 |
| 11.11.5.1   | General .....                                   | 109 |
| 11.11.5.2   | Measurement of phase differences .....          | 109 |
| 11.11.5.3   | Compensation control rules .....                | 110 |
| 11.11.5.3.1 | General .....                                   | 110 |
| 11.11.5.3.2 | Optimizing error resilience .....               | 110 |
| 11.11.6     | Information field .....                         | 111 |
| 11.11.6.1   | General .....                                   | 111 |
| 11.11.6.2   | User data rates .....                           | 111 |
| 11.11.6.3   | Information field filling rule .....            | 111 |
| 11.11.7     | Primitives .....                                | 112 |
| 11.12       | LU10 Enhanced Frame RELay (EFREL) service ..... | 113 |
| 11.12.1     | General .....                                   | 113 |
| 11.12.2     | Segmentation and transmission class .....       | 114 |
| 11.12.3     | Data transmission .....                         | 114 |
| 11.12.3.1   | Send side procedures .....                      | 114 |
| 11.12.3.1.1 | "Early transmission" option .....               | 114 |
| 11.12.3.2   | Receive side procedure .....                    | 115 |
| 11.12.3.2.1 | Standard SDU delivery mode .....                | 115 |
| 11.12.3.2.2 | In-sequence SDU delivery mode .....             | 115 |
| 11.12.3.2.3 | PDU-in-sequence delivery mode .....             | 116 |
| 11.12.3.2.4 | PDU-as-received delivery mode .....             | 116 |
| 11.12.4     | SDU boundaries definition .....                 | 116 |
| 11.12.4.1   | Infinite SDU mode .....                         | 116 |
| 11.13       | LU11 service .....                              | 116 |
| 11.13.1     | Physical layer service .....                    | 117 |
| 11.13.2     | MAC layer service .....                         | 117 |
| 11.13.3     | DLC layer service .....                         | 117 |
| 11.14       | LU12 UNprotected Framed service (UNF) .....     | 117 |
| 11.14.1     | General .....                                   | 117 |
| 11.14.2     | DLC layer service .....                         | 117 |
| 11.14.2.1   | Segmentation .....                              | 118 |
| 11.14.2.2   | Data transmission .....                         | 119 |
| 11.14.2.2.1 | Send side procedure .....                       | 119 |
| 11.14.2.2.2 | Receive side procedure .....                    | 119 |
| 12          | Frame structures for U-plane services .....     | 120 |
| 12.1        | General .....                                   | 120 |
| 12.2        | FU1 frame structure .....                       | 120 |
| 12.2.1      | General frame structure .....                   | 120 |
| 12.2.2      | FU1 buffering procedures .....                  | 121 |
| 12.2.3      | Minimum delay (speech) operation .....          | 122 |
| 12.2.4      | Connection handover .....                       | 122 |
| 12.2.5      | Transmission order .....                        | 122 |
| 12.3        | FU2 frame structure .....                       | 123 |
| 12.3.1      | General frame structure .....                   | 123 |
| 12.3.2      | FU2 buffering procedures .....                  | 123 |
| 12.3.3      | Connection handover .....                       | 123 |
| 12.3.4      | Transmission order .....                        | 124 |
| 12.4        | FU3 frame structure .....                       | 124 |
| 12.4.1      | General frame structure .....                   | 124 |
| 12.4.2      | FU3 buffering procedures .....                  | 125 |
| 12.4.3      | Connection handover .....                       | 125 |
| 12.4.4      | Transmission order .....                        | 125 |
| 12.5        | FU4 frame structure .....                       | 125 |
| 12.5.1      | General frame structure .....                   | 125 |
| 12.5.2      | FU4 buffering procedures .....                  | 126 |
| 12.5.3      | Connection handover .....                       | 126 |
| 12.5.4      | Transmission order .....                        | 126 |
| 12.6        | FU5 frame structure .....                       | 127 |
| 12.6.1      | General frame structure .....                   | 127 |
| 12.6.2      | FU5 buffering procedures .....                  | 128 |



|            |   |     |
|------------|---|-----|
| 12.6.3     | Connection handover .....   | 128 |
| 12.6.4     | Transmission order .....  | 128 |
| 12.7       | FU6 frame structure.....  | 128 |
| 12.7.1     | General frame structure .....   | 128 |
| 12.7.2     | FU6 buffering procedures.....   | 129 |
| 12.7.3     | Connection handover .....   | 129 |
| 12.7.4     | Transmission order .....  | 129 |
| 12.8       | FU7 frame structure.....  | 129 |
| 12.9       | FU8 frame structure.....  | 130 |
| 12.10      | FU9 frame structure.....  | 130 |
| 12.11      | FU10 frame structure.....   | 130 |
| 12.11.1    | General frame structure .....   | 130 |
| 12.11.2    | Transmission of FU10c frames.....   | 131 |
| 12.11.2.1  | Insertion of the FU10c frame in an FU10a frame of the opposite link.....                  | 132 |
| 12.11.2.2  | Transmission of the F10c frame using the $G_F$ channel.....                               | 132 |
| 12.11.3    | FU10 buffering procedures.....  | 132 |
| 12.11.4    | Connection handover .....   | 132 |
| 12.11.5    | Transmission order .....  | 133 |
| 12.12      | FU12 frame structure.....   | 133 |
| 12.12.1    | General frame structure .....   | 133 |
| 12.12.2    | FU12 buffering procedures.....  | 133 |
| 12.12.3    | Connection handover .....   | 134 |
| 12.12.4    | Transmission order .....  | 134 |
| 13         | Elements of procedures and formats of fields for U-plane peer-to-peer communication ..... | 134 |
| 13.1       | General .....   | 134 |
| 13.2       | Address elements.....   | 134 |
| 13.2.1     | Address field format .....  | 134 |
| 13.2.2     | Address field parameters .....  | 135 |
| 13.3       | Length indicator elements .....   | 135 |
| 13.3.1     | Length indicator field format.....  | 135 |
| 13.3.1.1   | Length indicator field format for all services except LU10 .....                          | 135 |
| 13.3.1.2   | Length indicator field format for service LU10.....                                       | 136 |
| 13.3.2     | Length indicator field parameters .....   | 136 |
| 13.3.2.1   | Length indicator field parameters for all services except LU10.....                       | 136 |
| 13.3.2.2   | Length indicator field parameters for LU10 service .....                                  | 137 |
| 13.3.2.2.1 | Meaning of the more (M) bit .....   | 139 |
| 13.4       | Sequence number elements .....  | 139 |
| 13.4.1     | Send sequence number format .....   | 139 |
| 13.4.2     | Send sequence number parameters .....   | 140 |
| 13.4.3     | Receive sequence number format.....   | 140 |
| 13.4.4     | Receive sequence number parameters .....  | 140 |
| 13.5       | Fill elements - Fill field format .....   | 141 |
| 14         | U-plane peer-to-peer procedures .....   | 141 |
| 14.1       | General .....   | 141 |
| 14.2       | Frame transmission principles.....  | 141 |
| 14.2.1     | Sequence numbering.....   | 141 |
| 14.2.2     | Acknowledgements.....   | 141 |
| 14.2.2.1   | Sending acknowledgements .....  | 141 |
| 14.2.2.2   | Receiving acknowledgements .....  | 142 |
| 14.2.3     | Transmission classes.....   | 142 |
| 14.2.3.1   | Class 0: No $LU_X$ retransmission or sequencing.....                                      | 142 |
| 14.2.3.2   | Class 1: no $LU_X$ retransmission.....  | 143 |
| 14.2.3.3   | Class 2: variable throughput, limited delay $LU_X$ retransmission.....                    | 143 |
| 14.2.3.4   | Class 3: fixed throughput $LU_X$ retransmission .....                                     | 143 |
| 14.2.4     | Operation parameter negotiation.....  | 144 |
| 14.3       | Frame transmission procedures .....   | 144 |
| 14.3.1     | General.....  | 144 |
| 14.3.2     | Class 0 procedures .....  | 144 |
| 14.3.2.1   | Sending side procedure .....  | 144 |
| 14.3.2.2   | Receiving side procedure .....  | 144 |

|  |  |            |
|--|--|------------|
| 14.3.3   | Class 1 procedures .....   | 145        |
| 14.3.3.1   | Sending side procedure .....                                       | 145        |
| 14.3.3.2   | Receiving side procedure .....                                     | 145        |
| 14.3.4   | Class 2 procedures .....   | 146        |
| 14.3.4.1   | Sending side procedure .....                                       | 146        |
| 14.3.4.1.1   | Synchronization message sending side procedure (LU10) .....        | 147        |
| 14.3.4.1.2   | Tx side end-of-activity rule .....                                 | 148        |
| 14.3.4.1.3   | Abnormal SDU termination/abort signal (LU10 only) .....            | 148        |
| 14.3.4.2   | Receiving side procedure .....                                     | 149        |
| 14.3.4.2.1   | Acknowledgement procedure .....                                    | 149        |
| 14.3.4.2.2   | Rx side end-of-activity rule .....                                 | 150        |
| 14.3.4.2.3   | Retransmission request procedure .....                             | 150        |
| 14.3.4.2.4   | SDU delivery procedure .....                                       | 151        |
| 14.3.4.2.5   | Synchronization message receiver side procedure (LU10) .....       | 151        |
| 14.3.4.2.6   | Reception of an abnormal SDU termination/abort signal (LU10) ..... | 152        |
| 14.3.5   | Class 3 procedures .....   | 152        |
| 14.3.5.1   | Sending side procedure .....                                       | 152        |
| 14.3.5.2   | Receiving side procedure .....                                     | 153        |
| <b>Annex A (normative): System parameters.....</b>                             |  | <b>154</b> |
| A.1  | LAPC timer values .....  | 154        |
| A.2  | U-plane timer values .....   | 155        |
| A.3  | Constants .....  | 155        |
| A.3.1  | Retransmission counter (N250) .....                                | 155        |
| A.3.2  | Maximum number of CHO attempts (N251) .....                        | 155        |
| <b>Annex B (normative): Checksum algorithms.....</b>                           |  | <b>156</b> |
| B.1  | Arithmetic conventions .....                                       | 156        |
| B.2  | Coding algorithm.....  | 156        |
| B.3  | Decoding algorithm.....  | 156        |
| B.4  | Some examples.....   | 157        |
| <b>Annex C (informative): MAC connection states.....</b>                       |  | <b>158</b> |
| <b>Annex D (normative): Mapping of agreed channel rates to MCS sizes .....</b> |  | <b>159</b> |
| D.1  | Protected class operation .....                                    | 159        |
| D.2  | Unprotected class operation .....                                  | 160        |
| <b>Annex E (normative): LU12 applications .....</b>                            |  | <b>161</b> |
| E.1  | G.729.1 over 32 kb/s channel.....                                  | 161        |
| E.1.1  | G.729.1 payload format.....  | 161        |
| E.1.1.1  | G.729.1 payload header coding .....                                | 161        |
| E.1.2  | Operations .....   | 163        |
| E.1.2.1  | Encoder bit rate.....  | 163        |
| E.1.2.2  | Protection against random errors .....                             | 164        |
| <b>Annex F (informative): Bibliography.....</b>                                |  | <b>165</b> |
| <b>Annex G (informative): Change history .....</b>                             |  | <b>166</b> |
| History .....  |  | 167        |

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 4 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

| <b>National transposition dates</b>  |                   |
|--|-------------------|
| Date of adoption of this EN:   | 7 June 2010       |
| Date of latest announcement of this EN (doa):  | 30 September 2010 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 March 2011     |
| Date of withdrawal of any conflicting National Standard (dow):                         | 31 March 2011     |

# 1 Scope

The present document is one of the parts of the specification of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

The present document specifies the Data Link Control (DLC) layer. The DLC layer is part 4 of the DECT CI standard and layer 2b of the DECT protocol stack.

|                                 |                          |
|---------------------------------|--------------------------|
| Network layer<br>C-plane<br>(3) | Network layer<br>U-plane |
| DLC layer<br>C-plane<br>(2b)    | DLC layer<br>U-plane     |
| MAC layer<br>(2a)               |                          |
| Physical layer<br>(1)           |                          |

**Figure 1.1**

Two planes of operation are specified for this DLC (sub)layer. These planes are called the Control plane (C-plane) and the User plane (U-plane).

The C-plane is mostly concerned with the DECT signalling aspects. It provides a reliable point-to-point service that uses a link access protocol to offer error protected transmission of Network (NWK) layer messages. The C-plane also provides a separate point-to-multipoint (broadcast) service (Lb).

The U-plane is only concerned with end-to-end user information. This plane contains most of the application dependent procedures of DECT. Several alternative services (both circuit-mode and packet-mode) are defined as a family of independent entities. Each service provides one or more point-to-point U-plane data links, where the detailed characteristics of those links are determined by the particular needs of each service. The defined services cover a wide range of performance, from "unprotected with low delay" for speech applications to "highly protected with variable delay", for local area network applications.

**NOTE:** The performance of the DLC services need not be tight to any particular application. For example the "unprotected with low delay" service could also be used for data applications, e.g. if some data protection is provided outside the DECT protocol.

The present document uses the layered model principles and terminology as described in ITU-T Recommendations X.200 [14] and X.210 [15].

The present document includes New Generation DECT, a further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] Void.
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] Void.
- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [9] ETSI TS 144 006: "Digital cellular telecommunications system (Phase 2+); Mobile Station - Base Stations System (MS -BSS) interface Data Link (DL) layer specification (3GPP TS 44.006)".
- [10] ITU-T Recommendation Q.920: "ISDN user-network interface data link layer - General aspects".
- [11] ITU-T Recommendation Q.921: "ISDN user-network interface - Data link layer specification".
- [12] ITU-T Recommendation V.42: "Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion".
- [13] ITU-T Recommendation V.110: "Support by an ISDN of data terminal equipments with V-Series type interfaces".
- [14] ITU-T Recommendation X.200: "Information technology - Open Systems Interconnection - Basic Reference Model: The basic model".
- [15] ITU-T Recommendation X.210: "Information technology - Open Systems Interconnection - Basic Reference Model: Conventions for the definition of OSI services".
- [16] ISO/IEC 8073: "Information technology - Open Systems Interconnection - Protocol for providing the connection-mode transport service".
- [17] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".