



SLOVENSKI STANDARD

SIST EN 300 175-5 V2.3.1:2010

01-oktober-2010

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 5.
del: Omrežna plast (NWK)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
5: Network (NWK) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 175-5 Version 2.3.1**

SIST EN 300 175-5 V2.3.1:2010
<https://standards.iteh.ai/catalog/standards/sist/fd4bc7b-0d42-4783-880e-40fa72dff3f8/sist-en-300-175-5-v2-3-1-2010>

ICS:

| | | |
|-----------|--|---|
| 33.070.30 | Digitalne izboljšane brezvrvične telekomunikacije (DECT) | Digital Enhanced Cordless Telecommunications (DECT) |
|-----------|--|---|

| | | |
|-----------|--------------|---------------|
| 35.100.30 | Omrežni sloj | Network layer |
|-----------|--------------|---------------|

| | |
|--------------------------------------|-----------|
| SIST EN 300 175-5 V2.3.1:2010 | en |
|--------------------------------------|-----------|

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-5 V2.3.1:2010

<https://standards.iteh.ai/catalog/standards/sist/ffd4be7b-0d42-4783-880e-40fa72df3f8/sist-en-300-175-5-v2-3-1-2010>

ETSI EN 300 175-5 V2.3.1 (2010-06)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-5 V2.3.1:2010](https://standards.iteh.ai/catalog/standards/sist/ffd4be7b-0d42-4783-880e-40fa72df3f8/sist-en-300-175-5-v2-3-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/ffd4be7b-0d42-4783-880e-40fa72df3f8/sist-en-300-175-5-v2-3-1-2010>



Reference

REN/DECT-000254-5

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-5 V2.3.1:2010<https://standards.iteh.ai/catalog/standards/sist/ff44be7b-0d42-4783-880e-406a72dff33b/etsi-en-300-175-5-v2-3-1-2010>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|----|
| Intellectual Property Rights | 16 |
| Foreword..... | 16 |
| 1 Scope | 17 |
| 2 References | 17 |
| 2.1 Normative references | 18 |
| 2.2 Informative references..... | 21 |
| 3 Definitions, symbols and abbreviations | 22 |
| 3.1 Definitions..... | 22 |
| 3.2 Symbols and abbreviations..... | 23 |
| 4 Overview of the NWK layer | 26 |
| 5 Overview of procedures | 28 |
| 5.1 General | 28 |
| 5.2 Overview of Call Control (CC)..... | 28 |
| 5.2.1 General..... | 28 |
| 5.2.2 Call establishment..... | 28 |
| 5.2.2.1 Call setup | 28 |
| 5.2.2.2 Service negotiation..... | 29 |
| 5.2.3 Call connect | 29 |
| 5.2.4 Call information..... | 29 |
| 5.2.5 Service change..... | 30 |
| 5.2.6 Call release..... | 30 |
| 5.3 Overview of Supplementary Services (SS) | 30 |
| 5.3.1 General..... | 30 |
| 5.3.2 Keypad protocol..... | 31 |
| 5.3.3 Feature key management protocol..... | 31 |
| 5.3.4 Functional protocol..... | 31 |
| 5.4 Overview of Connection Oriented Message Service (COMS)..... | 31 |
| 5.4.1 General..... | 31 |
| 5.4.2 COMS establishment | 32 |
| 5.4.3 Service negotiation | 32 |
| 5.4.4 COMS connect..... | 32 |
| 5.4.5 COMS data transfer | 32 |
| 5.4.6 COMS suspend and resume | 32 |
| 5.4.7 COMS release | 33 |
| 5.5 Overview of ConnectionLess Message Service (CLMS) | 33 |
| 5.5.1 Fixed length message service..... | 33 |
| 5.5.2 Variable length message service..... | 33 |
| 5.6 Overview of Mobility Management (MM) | 33 |
| 5.6.1 General..... | 33 |
| 5.6.2 Identity procedures | 34 |
| 5.6.3 Authentication procedures | 34 |
| 5.6.4 Location procedures..... | 35 |
| 5.6.5 Access rights procedures | 35 |
| 5.6.6 Key allocation procedure | 35 |
| 5.6.7 Parameter retrieval procedure | 35 |
| 5.6.8 Cipherring related procedure..... | 36 |
| 5.6.9 External protocol information procedure..... | 36 |
| 5.7 Overview of Link Control Entity (LCE) | 36 |
| 5.7.1 General..... | 36 |
| 5.7.2 Data Link Endpoint Identifier (DLEI) | 36 |
| 5.7.3 Data link establishment..... | 37 |
| 5.7.4 Data link re-establishment | 37 |
| 5.7.5 Data link release | 37 |

| | | |
|----------|--|----|
| 5.7.6 | Data link suspend and resume..... | 37 |
| 5.7.7 | Queuing of messages | 38 |
| 5.7.8 | Request paging..... | 38 |
| 6 | Message functional definitions..... | 38 |
| 6.1 | Overview of message structures | 38 |
| 6.1.1 | Messages..... | 38 |
| 6.1.2 | Information elements | 39 |
| 6.2 | Message summaries..... | 39 |
| 6.2.1 | Summary of CC messages | 39 |
| 6.2.2 | Summary of CISS messages | 40 |
| 6.2.3 | Summary of COMS messages | 40 |
| 6.2.4 | Summary of CLMS messages..... | 40 |
| 6.2.5 | Summary of MM messages | 41 |
| 6.2.6 | Summary of LCE messages | 41 |
| 6.3 | S-FORMAT message functional contents..... | 42 |
| 6.3.1 | S-FORMAT message overview..... | 42 |
| 6.3.2 | CC-messages..... | 42 |
| 6.3.2.1 | {CC-SETUP}..... | 42 |
| 6.3.2.2 | {CC-INFO}..... | 44 |
| 6.3.2.3 | {CC-SETUP-ACK} | 45 |
| 6.3.2.4 | {CC-CALL-PROC} | 46 |
| 6.3.2.5 | {CC-ALERTING} | 47 |
| 6.3.2.6 | {CC-CONNECT} | 48 |
| 6.3.2.7 | {CC-CONNECT-ACK}..... | 49 |
| 6.3.2.8 | {CC-RELEASE}..... | 49 |
| 6.3.2.9 | {CC-RELEASE-COM}..... | 50 |
| 6.3.2.10 | {CC-SERVICE-CHANGE}..... | 51 |
| 6.3.2.11 | {CC-SERVICE-ACCEPT}..... | 52 |
| 6.3.2.12 | {CC-SERVICE-REJECT}..... | 52 |
| 6.3.2.13 | {CC-NOTIFY}..... | 53 |
| 6.3.2.14 | {IWU-INFO} | 53 |
| 6.3.3 | SS-messages (call related and call independent)..... | 54 |
| 6.3.3.1 | {FACILITY}..... | 54 |
| 6.3.3.2 | {HOLD}..... | 54 |
| 6.3.3.3 | {HOLD-ACK} | 55 |
| 6.3.3.4 | {HOLD-REJECT} | 55 |
| 6.3.3.5 | {RETRIEVE} | 55 |
| 6.3.3.6 | {RETRIEVE-ACK} | 56 |
| 6.3.3.7 | {RETRIEVE-REJECT} | 56 |
| 6.3.3.8 | {CISS-REGISTER} | 57 |
| 6.3.3.9 | {CISS-RELEASE-COM} | 57 |
| 6.3.4 | COMS-messages..... | 58 |
| 6.3.4.1 | {COMS-SETUP} | 58 |
| 6.3.4.2 | {COMS-INFO} | 58 |
| 6.3.4.3 | {COMS-ACK}..... | 59 |
| 6.3.4.4 | {COMS-CONNECT} | 59 |
| 6.3.4.5 | {COMS-RELEASE}..... | 60 |
| 6.3.4.6 | {COMS-RELEASE-COM} | 60 |
| 6.3.4.7 | {COMS-NOTIFY}..... | 61 |
| 6.3.5 | CLMS-message..... | 61 |
| 6.3.5.1 | {CLMS-VARIABLE} | 61 |
| 6.3.6 | MM-messages..... | 62 |
| 6.3.6.1 | {ACCESS-RIGHTS-ACCEPT} | 62 |
| 6.3.6.2 | {ACCESS-RIGHTS-REJECT}..... | 62 |
| 6.3.6.3 | {ACCESS-RIGHTS-REQUEST} | 63 |
| 6.3.6.4 | {ACCESS-RIGHTS-TERMINATE-ACCEPT} | 63 |
| 6.3.6.5 | {ACCESS-RIGHTS-TERMINATE-REJECT} | 64 |
| 6.3.6.6 | {ACCESS-RIGHTS-TERMINATE-REQUEST}..... | 64 |
| 6.3.6.7 | {AUTHENTICATION-REJECT} | 65 |
| 6.3.6.8 | {AUTHENTICATION-REPLY}..... | 65 |
| 6.3.6.9 | {AUTHENTICATION-REQUEST} | 66 |

| | | |
|----------|--|----|
| 6.3.6.10 | { CIPHER-REJECT } | 66 |
| 6.3.6.11 | { CIPHER-REQUEST } | 67 |
| 6.3.6.12 | { CIPHER-SUGGEST } | 67 |
| 6.3.6.13 | { DETACH } | 67 |
| 6.3.6.14 | { IDENTITY-REPLY } | 68 |
| 6.3.6.15 | { IDENTITY-REQUEST } | 69 |
| 6.3.6.16 | { KEY-ALLOCATE } | 69 |
| 6.3.6.17 | { LOCATE-ACCEPT } | 70 |
| 6.3.6.18 | { LOCATE-REJECT } | 70 |
| 6.3.6.19 | { LOCATE-REQUEST } | 71 |
| 6.3.6.20 | { MM-INFO-ACCEPT } | 72 |
| 6.3.6.21 | { MM-INFO-REJECT } | 72 |
| 6.3.6.22 | { MM-INFO-REQUEST } | 73 |
| 6.3.6.23 | { MM-INFO-SUGGEST } | 74 |
| 6.3.6.24 | { TEMPORARY-IDENTITY-ASSIGN } | 74 |
| 6.3.6.25 | { TEMPORARY-IDENTITY-ASSIGN-ACK } | 75 |
| 6.3.6.26 | { TEMPORARY-IDENTITY-ASSIGN-REJ } | 75 |
| 6.3.6.27 | { MM-IWU } | 76 |
| 6.3.6.28 | { MM-NOTIFY } | 76 |
| 6.3.7 | LCE-messages | 77 |
| 6.3.7.1 | { LCE-PAGE-RESPONSE } | 77 |
| 6.3.7.2 | { LCE-PAGE-REJECT } | 77 |
| 6.4 | B-FORMAT message functional contents | 78 |
| 6.4.1 | B-FORMAT message overview | 78 |
| 6.4.2 | { LCE-REQUEST-PAGE } | 78 |
| 6.4.3 | { CLMS-FIXED } | 79 |
| 7 | S-FORMAT message structures | 79 |
| 7.1 | Overview | 79 |
| 7.2 | Protocol Discrimination (PD) element | 80 |
| 7.3 | Transaction Identifier (TI) element | 80 |
| 7.4 | Message type element | 81 |
| 7.4.1 | Messages for CC | 82 |
| 7.4.2 | Messages for SS | 82 |
| 7.4.3 | Messages for COMS | 82 |
| 7.4.4 | Messages for CLMS | 83 |
| 7.4.5 | Messages for MM | 83 |
| 7.4.6 | Messages for LCE | 83 |
| 7.5 | Other information elements | 84 |
| 7.5.1 | Coding rules | 84 |
| 7.5.2 | Extensions of codesets | 86 |
| 7.5.3 | Locking shift procedure | 86 |
| 7.5.4 | Non-locking shift procedure | 87 |
| 7.5.5 | Display and keypad elements | 87 |
| 7.5.6 | Repeated elements | 87 |
| 7.6 | Fixed length information elements | 88 |
| 7.6.1 | Summary | 88 |
| 7.6.2 | Sending complete, delimiter request and use TPUI | 88 |
| 7.6.3 | Repeat indicator | 89 |
| 7.6.4 | Basic service | 89 |
| 7.6.5 | Single display | 90 |
| 7.6.6 | Single keypad | 90 |
| 7.6.7 | Release reason | 90 |
| 7.6.8 | Signal | 92 |
| 7.6.9 | Timer restart | 93 |
| 7.6.10 | Test hook control | 93 |
| 7.7 | Variable length information elements | 93 |
| 7.7.1 | Summary | 93 |
| 7.7.2 | Allocation type | 95 |
| 7.7.3 | Alphanumeric | 95 |
| 7.7.4 | Auth type | 96 |
| 7.7.5 | Call attributes | 98 |

iTech STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 300 175-5 V2.3.1:2010

[https://standards.iteh.ai/catalog/standards/sist/fd4be7b-0d42-4783-880c-](https://standards.iteh.ai/catalog/standards/sist/fd4be7b-0d42-4783-880c-40fa72df3f8/sist-en-300-175-5-v2-3-1-2010)[40fa72df3f8/sist-en-300-175-5-v2-3-1-2010](https://standards.iteh.ai/catalog/standards/sist/fd4be7b-0d42-4783-880c-40fa72df3f8/sist-en-300-175-5-v2-3-1-2010)

| | | |
|---------|--|-----|
| 7.7.6 | Call identity | 101 |
| 7.7.7 | Called party number..... | 101 |
| 7.7.8 | Called party subaddress | 102 |
| 7.7.9 | Calling party number | 103 |
| 7.7.10 | Cipher info | 104 |
| 7.7.11 | Connection attributes | 105 |
| 7.7.12 | Connection identity | 108 |
| 7.7.13 | Duration | 109 |
| 7.7.14 | End-to-end compatibility | 110 |
| 7.7.15 | Facility | 113 |
| 7.7.16 | Feature activate | 113 |
| 7.7.17 | Feature indicate..... | 115 |
| 7.7.18 | Fixed identity | 117 |
| 7.7.19 | Identity type | 118 |
| 7.7.20 | Info type..... | 119 |
| 7.7.21 | InterWorking Unit (IWU) attributes | 120 |
| 7.7.22 | IWU packet | 125 |
| 7.7.23 | IWU to IWU | 126 |
| 7.7.24 | Key..... | 128 |
| 7.7.25 | Location area | 128 |
| 7.7.26 | Multi-display..... | 129 |
| 7.7.27 | Multi-keypad..... | 130 |
| 7.7.28 | NetWorK (NWK) assigned identity..... | 130 |
| 7.7.29 | Network parameter | 131 |
| 7.7.30 | Portable identity | 133 |
| 7.7.31 | Progress indicator | 137 |
| 7.7.32 | RAND | 137 |
| 7.7.33 | Rate parameters | 138 |
| 7.7.34 | Reject reason..... | 139 |
| 7.7.35 | RES | 140 |
| 7.7.36 | RS | 141 |
| 7.7.37 | Segmented info | 141 |
| 7.7.38 | Service change info | 142 |
| 7.7.39 | Service class..... | 143 |
| 7.7.40 | Setup capability | 144 |
| 7.7.41 | Terminal capability | 145 |
| 7.7.42 | Transit delay | 150 |
| 7.7.43 | Window size | 151 |
| 7.7.44 | ZAP field | 151 |
| 7.7.45 | Escape to proprietary | 152 |
| 7.7.46 | Model identifier | 152 |
| 7.7.47 | MMS Generic Header..... | 153 |
| 7.7.48 | MMS Object Header..... | 153 |
| 7.7.49 | MMS Extended header | 154 |
| 7.7.50 | Time-Date | 154 |
| 7.7.51 | Ext h/o indicator | 156 |
| 7.7.52 | Authentication Reject Parameter | 157 |
| 7.7.53 | Calling party Name | 157 |
| 7.7.54 | Codec List..... | 158 |
| 7.7.55 | Events notification | 159 |
| 7.7.56 | Call information..... | 163 |
| 8 | B-FORMAT message structures | 166 |
| 8.1 | General | 166 |
| 8.2 | LCE request paging messages | 166 |
| 8.2.1 | Short format message..... | 167 |
| 8.2.2 | Full format message..... | 168 |
| 8.2.3 | Long format message..... | 169 |
| 8.2.4 | Message elements | 170 |
| 8.2.4.1 | LCE paging header..... | 170 |
| 8.2.4.2 | Info fields (Full format) | 171 |
| 8.2.4.3 | Default setup behaviour | 172 |

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 300 175-5 V2.3.1:2010
<http://standards.itech.ai/catalog/standards/sist/ff14be7b-0d42-4783-880e-40672dff3f8/sist-en-300-175-5-v2-3-1-2010>

| | | |
|----------|---|-----|
| 8.2.4.4 | Address elements in collective or group ringing..... | 174 |
| 8.3 | CLMS-FIXED messages..... | 174 |
| 8.3.1 | General message structure..... | 174 |
| 8.3.2 | Message elements..... | 175 |
| 8.3.3 | Standard message structures..... | 177 |
| 8.3.3.1 | General..... | 177 |
| 8.3.3.2 | Messages using 4-bit characters..... | 177 |
| 8.3.3.3 | Messages using 8-bit characters..... | 177 |
| 9 | Call Control (CC) procedures..... | 177 |
| 9.1 | General..... | 177 |
| 9.2 | Call Control (CC) states..... | 180 |
| 9.2.1 | States at PT..... | 180 |
| 9.2.1.1 | State T-00: "NULL"..... | 180 |
| 9.2.1.2 | State T-19: "RELEASE PENDING"..... | 180 |
| 9.2.1.3 | State T-10: "ACTIVE"..... | 180 |
| 9.2.1.4 | State T-01: "CALL INITIATED"..... | 180 |
| 9.2.1.5 | State T-02: "OVERLAP SENDING"..... | 180 |
| 9.2.1.6 | State T-03: "CALL PROCEEDING"..... | 180 |
| 9.2.1.7 | State T-04: "CALL DELIVERED"..... | 180 |
| 9.2.1.8 | State T-06: "CALL PRESENT"..... | 180 |
| 9.2.1.9 | State T-07: "CALL RECEIVED"..... | 180 |
| 9.2.1.10 | State T-08: "CONNECT PENDING"..... | 180 |
| 9.2.2 | States at FT..... | 181 |
| 9.2.2.1 | State F-00: "NULL"..... | 181 |
| 9.2.2.2 | State F-19: "RELEASE PENDING"..... | 181 |
| 9.2.2.3 | State F-10: "ACTIVE"..... | 181 |
| 9.2.2.4 | State F-01: "CALL INITIATED"..... | 181 |
| 9.2.2.5 | State F-02: "OVERLAP SENDING"..... | 181 |
| 9.2.2.6 | State F-03: "CALL PROCEEDING"..... | 181 |
| 9.2.2.7 | State F-04: "CALL DELIVERED"..... | 181 |
| 9.2.2.8 | State F-06: "CALL PRESENT"..... | 181 |
| 9.2.2.9 | State F-07: "CALL RECEIVED"..... | 181 |
| 9.2.3 | Optional states (PT and FT)..... | 182 |
| 9.2.3.1 | States T-22 and F-22: "OVERLAP RECEIVING"..... | 182 |
| 9.2.3.2 | States T-23 and F-23: "INCOMING CALL PROCEEDING"..... | 182 |
| 9.3 | Call establishment procedures..... | 182 |
| 9.3.1 | PT initiated call establishment (outgoing call)..... | 182 |
| 9.3.1.1 | Call request..... | 182 |
| 9.3.1.2 | Call accept or reject..... | 183 |
| 9.3.1.3 | Selection of lower layer resources..... | 183 |
| 9.3.1.4 | Connection of U-plane..... | 184 |
| 9.3.1.5 | Overlap sending..... | 184 |
| 9.3.1.6 | Call proceeding..... | 185 |
| 9.3.1.7 | Call confirmation..... | 185 |
| 9.3.1.8 | Call connection..... | 186 |
| 9.3.1.9 | Expiry of timer <CC.04>..... | 186 |
| 9.3.2 | FT initiated call establishment (incoming call)..... | 186 |
| 9.3.2.1 | Call request..... | 186 |
| 9.3.2.2 | Call accept or reject..... | 187 |
| 9.3.2.3 | Selection of lower layer resources..... | 187 |
| 9.3.2.4 | Connection of U-plane..... | 188 |
| 9.3.2.5 | Overlap receiving..... | 188 |
| 9.3.2.6 | Call proceeding..... | 188 |
| 9.3.2.7 | Call confirmation..... | 188 |
| 9.3.2.8 | Call connection..... | 188 |
| 9.3.2.9 | Sending of <<TERMINAL-CAPABILITY>>..... | 189 |
| 9.3.2.10 | Expiry of timer <CC.04>..... | 189 |
| 9.4 | Call information procedures..... | 189 |
| 9.5 | Call release procedures..... | 189 |
| 9.5.1 | Normal call release..... | 189 |
| 9.5.2 | Abnormal call release..... | 190 |

| | | |
|------------|---|-----|
| 9.5.3 | Release collisions..... | 191 |
| 9.6 | Service change procedures | 191 |
| 9.6.1 | General..... | 191 |
| 9.6.2 | Change of Bandwidth parameters (including changes in connection type) | 192 |
| 9.6.3 | Service rerouting..... | 192 |
| 9.6.4 | NWK layer service suspension and resumption..... | 192 |
| 9.6.5 | Modulation scheme change..... | 193 |
| 9.7 | NWK layer Packet mode procedures..... | 193 |
| 9.7.1 | General..... | 193 |
| 9.7.2 | PT initiated access | 194 |
| 9.7.3 | FT initiated access | 194 |
| 9.7.4 | NWK layer suspend and resume..... | 194 |
| 9.7.4.1 | General | 194 |
| 9.7.4.2 | C-plane NWK layer suspend and resume..... | 195 |
| 9.7.4.3 | U-plane NWK layer suspend and resume | 195 |
| 9.8 | Emergency call procedure | 195 |
| 9.9 | Segmentation of information in CC procedures | 196 |
| 10 | Supplementary Services procedures..... | 197 |
| 10.1 | General | 197 |
| 10.2 | Keypad protocol | 198 |
| 10.3 | Feature key management protocol..... | 198 |
| 10.4 | Functional protocol..... | 199 |
| 10.4.1 | Separate messages approach | 199 |
| 10.4.1.1 | Hold procedures | 199 |
| 10.4.1.2 | Retrieve procedures..... | 199 |
| 10.4.1.3 | Auxiliary states for hold and retrieve..... | 200 |
| 10.4.2 | Common information element approach..... | 200 |
| 10.4.2.1 | Call Related Supplementary Services (CRSS) procedures..... | 200 |
| 10.4.2.2 | Call Independent Supplementary Services (CISS) procedures | 200 |
| 10.4.2.2.1 | Transport of CISS..... | 200 |
| 10.4.2.3 | Connectionless Supplementary Service (CLSS) procedure | 201 |
| 10.5 | Co-existence of multiple protocols..... | 201 |
| 10.6 | Application protocols | 202 |
| 10.6.1 | DECT standard functional supplementary services | 202 |
| 10.6.2 | DECT specific supplementary services | 203 |
| 10.6.2.1 | Queue management..... | 203 |
| 10.6.2.2 | Indication of subscriber number..... | 203 |
| 10.6.2.3 | Control of echo control functions..... | 204 |
| 10.6.2.4 | Cost information | 204 |
| 11 | Connection Oriented Message Service (COMS)..... | 205 |
| 11.1 | General | 205 |
| 11.2 | COMS states..... | 205 |
| 11.2.1 | States at PT | 205 |
| 11.2.1.1 | State TS-0: "NULL" | 205 |
| 11.2.1.2 | State TS-1: "CONNECT PENDING" | 205 |
| 11.2.1.3 | State TS-2: "RELEASE PENDING" | 205 |
| 11.2.1.4 | State TS-3: "ACTIVE" | 205 |
| 11.2.2 | States at FT | 205 |
| 11.2.2.1 | State FS-0: "NULL" | 205 |
| 11.2.2.2 | State FS-1: "CONNECT PENDING" | 205 |
| 11.2.2.3 | State FS-2: "RELEASE PENDING" | 205 |
| 11.2.2.4 | State FS-3: "ACTIVE" | 206 |
| 11.3 | COMS establishment procedures | 206 |
| 11.3.1 | PT initiated COMS establishment | 206 |
| 11.3.1.1 | COMS request..... | 206 |
| 11.3.1.2 | COMS connection..... | 206 |
| 11.3.2 | FT initiated COMS establishment | 207 |
| 11.3.2.1 | COMS request..... | 207 |
| 11.3.2.2 | COMS connection..... | 207 |
| 11.4 | COMS data transfer procedures | 207 |

| | | |
|----------|---|-----|
| 11.4.1 | Procedure at the sending side..... | 207 |
| 11.4.2 | Procedure at the receiving side | 208 |
| 11.5 | COMS NWK layer suspend and resume procedures..... | 209 |
| 11.6 | COMS release procedures | 209 |
| 11.6.1 | Normal COMS release..... | 209 |
| 11.6.2 | Release collisions..... | 209 |
| 12 | ConnectionLess Message Service (CLMS)..... | 210 |
| 12.1 | General | 210 |
| 12.2 | CLMS states | 210 |
| 12.3 | CLMS message transmission procedures | 210 |
| 12.3.1 | Fixed length messages | 210 |
| 12.3.1.1 | Procedure in the Fixed radio Termination (FT) | 210 |
| 12.3.1.2 | Procedure in the Portable radio Termination (PT) | 211 |
| 12.3.2 | Variable length messages..... | 211 |
| 12.3.2.1 | Procedure at the sending side | 211 |
| 12.3.2.2 | Procedure at the receiving side..... | 211 |
| 12.3.2.3 | Restrictions for portable side initiated messages..... | 212 |
| 13 | Mobility Management (MM) procedures..... | 212 |
| 13.1 | General | 212 |
| 13.2 | Identity procedures | 213 |
| 13.2.1 | Procedure for identification of PT | 213 |
| 13.2.2 | Procedure for temporary identity assignment | 214 |
| 13.3 | Authentication procedures..... | 215 |
| 13.3.1 | Authentication of a PT..... | 215 |
| 13.3.2 | Authentication of the user..... | 217 |
| 13.3.3 | Authentication of a FT..... | 217 |
| 13.4 | Location procedures | 218 |
| 13.4.1 | Location registration | 218 |
| 13.4.2 | Detach..... | 220 |
| 13.4.3 | Location update | 220 |
| 13.5 | Access rights procedure..... | 221 |
| 13.5.1 | Obtaining the access rights..... | 221 |
| 13.5.2 | Termination of access rights..... | 222 |
| 13.5.3 | Modification of access rights..... | 224 |
| 13.6 | Key allocation procedure..... | 224 |
| 13.7 | Parameter retrieval procedure..... | 225 |
| 13.8 | Ciphering related procedure | 227 |
| 13.9 | External protocol information procedure | 229 |
| 13.9.1 | Procedure for external protocol information initiated by the FT | 229 |
| 13.9.2 | Procedure for external protocol information initiated by the PT | 230 |
| 13.9.3 | Segmentation of information in MM procedures..... | 230 |
| 14 | Link Control Entity (LCE) procedures..... | 231 |
| 14.1 | General | 231 |
| 14.2 | Connection oriented link control procedures..... | 232 |
| 14.2.1 | Link establishment..... | 232 |
| 14.2.2 | Direct PT initiated link establishment..... | 232 |
| 14.2.3 | Indirect (paged) FT initiated link establishment | 233 |
| 14.2.4 | Direct FT initiated link establishment..... | 234 |
| 14.2.5 | Link maintenance..... | 235 |
| 14.2.6 | Link suspend and resume..... | 235 |
| 14.2.6.1 | Link suspend | 235 |
| 14.2.6.2 | Link resume..... | 236 |
| 14.2.7 | Link release..... | 236 |
| 14.2.7.1 | NLR notification without "partial release" as release reason | 236 |
| 14.2.7.2 | NLR notification with "partial release" as release reason | 237 |
| 14.3 | Connectionless link control procedures..... | 237 |
| 14.3.1 | Message routing..... | 237 |
| 14.3.2 | Broadcast announce procedure | 237 |
| 14.3.3 | LCE paging codes for connectionless service..... | 238 |
| 14.4 | Procedure for collective and group ringing | 238 |

| | | |
|----------|--|-----|
| 14.5 | LCE paging procedures for DPRS | 239 |
| 14.5.1 | DPRS initial setup paging..... | 239 |
| 14.5.1.1 | Assumptions for Short paging format or for Full format with IPUI..... | 239 |
| 14.5.1.2 | Coding for Full paging format with TPUI..... | 239 |
| 14.5.2 | DPRS Resume paging..... | 240 |
| 14.5.2.1 | Assumptions for Short paging format or for Full format with IPUI..... | 240 |
| 14.5.2.2 | Coding for Full paging format with TPUI..... | 240 |
| 14.5.2.3 | LCE Resume Procedure description..... | 240 |
| 14.5.3 | Special cases | 241 |
| 14.5.3.1 | Rule for DPRS Class 1 devices..... | 241 |
| 14.5.3.2 | Rule for backcompatibility with former A/B 1 devices | 241 |
| 15 | Management procedures..... | 241 |
| 15.1 | Lower Layer Management Entity (LLME) | 241 |
| 15.2 | Service mapping and negotiation | 242 |
| 15.2.1 | General..... | 242 |
| 15.2.2 | Prioritized list negotiation..... | 242 |
| 15.2.3 | Exchanged attribute negotiation | 242 |
| 15.2.4 | Operating parameter negotiation..... | 243 |
| 15.2.5 | Peer attribute negotiation | 243 |
| 15.3 | Service modification procedures | 244 |
| 15.4 | Resource management..... | 244 |
| 15.5 | Management of MM procedures | 244 |
| 15.6 | Call ciphering management..... | 245 |
| 15.7 | External Handover..... | 246 |
| 15.7.1 | Handover candidate procedures..... | 246 |
| 15.7.1.1 | General..... | 246 |
| 15.7.1.2 | Handover candidate indication..... | 246 |
| 15.7.1.3 | Handover candidate retrieval | 247 |
| 15.7.1.4 | Target FP selection..... | 247 |
| 15.7.2 | Handover reference procedure..... | 248 |
| 15.7.2.1 | General..... | 248 |
| 15.7.2.2 | Handover reference indication..... | 248 |
| 15.7.2.3 | Handover reference retrieval..... | 248 |
| 15.7.3 | External handover suggested by FP | 248 |
| 15.7.4 | NWK layer set up procedure..... | 249 |
| 15.7.4.1 | Handover request | 249 |
| 15.7.4.2 | Handover confirm | 249 |
| 15.7.4.3 | Handover accept..... | 249 |
| 15.7.4.4 | Handover reject..... | 249 |
| 15.7.4.5 | Release of old connection | 249 |
| 15.7.4.6 | Handover Fall Back..... | 250 |
| 15.7.5 | U-plane handling | 250 |
| 15.7.6 | Ciphering procedure | 251 |
| 15.7.7 | Interaction with location registration | 251 |
| 15.8 | Test management procedures | 251 |
| 15.8.1 | Test call back procedure | 252 |
| 15.8.2 | Test hook control procedures..... | 252 |
| 15.8.3 | Upper tester procedure..... | 252 |
| 15.9 | Application assistance procedures..... | 253 |
| 15.9.1 | DECT Identity Resolution (Retrieval) Procedure..... | 253 |
| 15.9.1.1 | FT (or HyP) initiated Connectionless Identity Resolution procedure | 253 |
| 15.9.1.2 | PT initiated Connectionless Identity Resolution procedure | 254 |
| 15.9.1.3 | Connection oriented Identity Resolution procedure..... | 254 |
| 15.9.2 | Application Address Resolution (Retrieval) Procedure..... | 254 |
| 15.9.3 | Application Parameter Allocation Procedure..... | 254 |
| 15.9.3.1 | FT initiated application parameter allocation procedure..... | 254 |
| 15.9.3.2 | PT initiated application parameter allocation procedure..... | 255 |
| 15.9.4 | Application parameter information procedure | 255 |
| 15.9.4.1 | FT initiated connection oriented Application parameter information procedure | 255 |
| 15.9.4.2 | PT initiated connection oriented Application parameter information procedure | 255 |
| 15.9.4.3 | FT initiated connectionless Application parameter information procedure | 256 |

| | | |
|-----------|---|-----|
| 15.9.4.4 | PT initiated connectionless Application parameter information procedure | 256 |
| 15.9.5 | Application Parameter Indication procedure | 256 |
| 16 | Primitives | 257 |
| 16.1 | Primitive types..... | 257 |
| 16.2 | Primitives to lower layer (DLC layer)..... | 257 |
| 16.3 | Primitives to IWU | 257 |
| 16.3.1 | Parameter definitions | 257 |
| 16.3.2 | MNCC primitives | 258 |
| 16.3.2.1 | MNCC_SETUP primitive | 259 |
| 16.3.2.2 | MNCC_SETUP_ACK primitive..... | 259 |
| 16.3.2.3 | MNCC_REJECT primitive | 260 |
| 16.3.2.4 | MNCC_CALL_PROC primitive..... | 260 |
| 16.3.2.5 | MNCC_ALERT primitive | 261 |
| 16.3.2.6 | MNCC_CONNECT primitive..... | 261 |
| 16.3.2.7 | MNCC_RELEASE primitive | 262 |
| 16.3.2.8 | MNCC_FACILITY primitive | 262 |
| 16.3.2.9 | MNCC_INFO primitive | 263 |
| 16.3.2.10 | MNCC_MODIFY primitive..... | 263 |
| 16.3.2.11 | MNCC_HOLD primitive | 263 |
| 16.3.2.12 | MNCC_RETRIEVE primitive | 264 |
| 16.3.2.13 | MNCC_IWU_INFO primitive | 264 |
| 16.3.3 | MNSS primitives | 264 |
| 16.3.3.1 | MNSS_SETUP primitive | 264 |
| 16.3.3.2 | MNSS_FACILITY primitive | 265 |
| 16.3.3.3 | MNSS_RELEASE primitive..... | 265 |
| 16.3.4 | MNCO primitives | 265 |
| 16.3.4.1 | MNCO_SETUP primitive | 266 |
| 16.3.4.2 | MNCO_CONNECT primitive | 266 |
| 16.3.4.3 | MNCO_INFO primitive..... | 266 |
| 16.3.4.4 | MNCO_ACK primitive..... | 266 |
| 16.3.4.5 | MNCO_RELEASE primitive..... | 267 |
| 16.3.4.6 | MNCO_REJECT primitive..... | 267 |
| 16.3.5 | MNCL primitives..... | 267 |
| 16.3.5.1 | MNCL_UNITDATA primitive..... | 267 |
| 16.3.6 | MM primitives | 268 |
| 16.3.6.1 | MM_IDENTITY primitive | 268 |
| 16.3.6.2 | MM_IDENTITY_ASSIGN primitive | 268 |
| 16.3.6.3 | MM_AUTHENTICATE primitive | 269 |
| 16.3.6.4 | MM_LOCATE primitive | 269 |
| 16.3.6.5 | MM_DETACH primitive..... | 269 |
| 16.3.6.6 | MM_ACCESS_RIGHTS primitive..... | 270 |
| 16.3.6.7 | MM_ACCESS_RIGHTS_TERMINATE primitive..... | 270 |
| 16.3.6.8 | MM_KEY_ALLOCATE primitive..... | 270 |
| 16.3.6.9 | MM_INFO primitive..... | 271 |
| 16.3.6.10 | MM_CIPHER primitive..... | 271 |
| 16.3.6.11 | MM_IWU primitive | 271 |
| 17 | Handling of error and exception conditions | 272 |
| 17.1 | Protocol discrimination error..... | 272 |
| 17.2 | Message too short..... | 272 |
| 17.3 | Transaction identifier error..... | 272 |
| 17.3.1 | Illegal and unsupported transaction identifier value | 272 |
| 17.3.2 | Transaction identifier procedural errors and exception conditions | 272 |
| 17.3.2.1 | Unknown active CC call | 272 |
| 17.3.2.2 | Unknown active CISS call | 273 |
| 17.3.2.3 | Unknown active COMS call | 273 |
| 17.3.2.4 | Unknown active CLMS call..... | 273 |
| 17.3.2.5 | Unknown active MM transaction..... | 273 |
| 17.3.2.6 | Unknown active LCE transaction | 273 |
| 17.3.3 | Call Resource Contention | 273 |
| 17.4 | Message type or message sequence errors | 274 |

| | | |
|---|--|------------|
| 17.4.1 | CC message error..... | 274 |
| 17.4.2 | CISS message error..... | 274 |
| 17.4.3 | COMS or CLMS message error..... | 274 |
| 17.4.4 | MM message error..... | 274 |
| 17.4.5 | LCE message error..... | 274 |
| 17.5 | General information element errors..... | 274 |
| 17.5.1 | Information element out of sequence..... | 274 |
| 17.5.2 | Duplicated information elements..... | 275 |
| 17.6 | Mandatory information element errors..... | 275 |
| 17.6.1 | Mandatory information element missing in CC messages..... | 275 |
| 17.6.2 | Mandatory information element content error in CC messages..... | 275 |
| 17.6.3 | Mandatory information element error in COMS or CLMS messages..... | 275 |
| 17.6.4 | Mandatory information element error in MM messages..... | 276 |
| 17.6.5 | Mandatory information element error in LCE messages..... | 276 |
| 17.7 | Non-mandatory information element errors..... | 276 |
| 17.7.1 | Unrecognized information element..... | 276 |
| 17.7.2 | Non-mandatory information element content error..... | 276 |
| 17.8 | Data link reset..... | 277 |
| 17.9 | Data link failure..... | 277 |
| Annex A (normative): System parameters..... | | 278 |
| A.1 | CC timers..... | 278 |
| A.2 | SS timers..... | 279 |
| A.3 | COMS timers..... | 279 |
| A.4 | CLMS timer..... | 280 |
| A.5 | MM timers..... | 280 |
| A.6 | LCE timers..... | 283 |
| A.7 | NWK layer constants..... | 284 |
| A.8 | Restart..... | 284 |
| Annex B (normative): CC state transition tables..... | | 285 |
| B.1 | CC state transitions at PT side..... | 285 |
| B.1.1 | CC state table at PT side..... | 285 |
| B.1.2 | CC transition procedures at PT side..... | 286 |
| B.2 | CC state transitions at FT side..... | 288 |
| B.2.1 | CC state table at FT side..... | 288 |
| B.2.2 | CC transition procedures at FT side..... | 288 |
| Annex C (informative): DLC states as viewed by the LCE..... | | 291 |
| Annex D (normative): DECT standard character sets..... | | 292 |
| D.1 | General..... | 292 |
| D.2 | DECT standard 8-bit characters..... | 292 |
| D.2.1 | General..... | 292 |
| D.2.2 | Control codes..... | 293 |
| D.2.3 | Standard IA5 codes..... | 294 |
| D.2.4 | extended codes and escape to alternative character sets..... | 294 |
| D.3 | DECT standard 4-bit characters..... | 294 |
| Annex E (normative): Default coding of information elements..... | | 295 |
| E.1 | Default coding of <<IWU-ATTRIBUTES>> and <CALL-ATTRIBUTES>> information elements for basic speech..... | 295 |

| | | |
|---|--|------------|
| E.2 | Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES>> and <<CONNECTION-ATTRIBUTES>> information elements for wideband speech | 295 |
| E.2.1 | Default setup attributes for basic service wideband speech | 296 |
| Annex F (normative): Broadcast attributes coding | | 297 |
| F.1 | Higher layer capabilities..... | 297 |
| F.2 | Extended higher layer capabilities | 298 |
| F.3 | Extended higher layer capabilities (part 2)..... | 298 |
| Annex G (normative): Use of <<IWU-PACKET>> and <<IWU-TO-IWU>> information elements | | 300 |
| G.1 | General | 300 |
| G.2 | Sending of <<IWU-PACKET>> elements..... | 300 |
| G.2.1 | CC and MM use of <<IWU-PACKET>> | 300 |
| G.2.2 | COMS and CLMS use of <<IWU-PACKET>>..... | 300 |
| G.2.3 | Rejection of <<IWU-PACKET>> elements | 300 |
| G.3 | Use of <<IWU-TO-IWU>> elements | 301 |
| G.3.1 | Sending of <<IWU-TO-IWU>> elements..... | 301 |
| G.3.2 | Rejection of <<IWU-TO-IWU>> elements | 301 |
| Annex H (normative): Transaction identifier flags (TIF) assignment in MM procedures..... | | 302 |
| H.1 | General | 302 |
| H.2 | Nested procedures | 302 |
| H.3 | Stand alone procedures..... | 303 |
| H.3.1 | Location update procedure | 303 |
| H.3.2 | Location registration procedure with temporary identity assignment | 303 |
| H.3.3 | PT initiated cipher switching | 304 |
| H.3.4 | Key allocation | 304 |
| H.4 | External protocol information procedure | 305 |
| Annex I (normative): Distributed communications..... | | 306 |
| I.1 | Introduction | 306 |
| I.2 | General requirements | 306 |
| I.2.1 | DCDL-net..... | 306 |
| I.2.2 | Subscription..... | 306 |
| I.2.3 | Communication | 307 |
| I.3 | Procedure description..... | 308 |
| I.3.1 | HyP Identities | 308 |
| I.3.2 | Membership Access Rights Allocation | 308 |
| I.3.3 | Re-initialization of membership access rights | 309 |
| I.3.4 | Members Data Transfer | 309 |
| I.3.5 | Presence/Absence Indication..... | 311 |
| I.3.6 | Bandwidth management | 311 |
| I.3.7 | Direct Link Establishment..... | 312 |
| I.3.8 | Indirect Link Establishment | 313 |
| I.3.9 | MASTER management | 314 |
| I.3.9.1 | MASTER assign | 314 |
| I.3.9.2 | MASTER Change | 314 |
| I.3.9.3 | DCDL-net System bearer management | 314 |
| I.3.10 | Common Subscription Database management | 315 |
| I.3.10.1 | IdN..... | 315 |
| I.3.10.2 | RFPI, PARK and PLI..... | 315 |
| I.3.10.3 | IPUI | 316 |
| I.3.10.4 | TPUI and LAL..... | 316 |