

**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 5: Network (NWK) layer**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b84e80e5-396a-427f-bbbe-7227a3597df1/etsi-en-300-175-5-v2.3.1-2010-06>



Reference

REN/DECT-000254-5

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
1 Scope	17
2 References	17
2.1 Normative references	18
2.2 Informative references.....	22
3 Definitions, symbols and abbreviations	22
3.1 Definitions.....	22
3.2 Symbols and abbreviations.....	23
4 Overview of the NWK layer	26
5 Overview of procedures	28
5.1 General	28
5.2 Overview of Call Control (CC).....	28
5.2.1 General.....	28
5.2.2 Call establishment.....	28
5.2.2.1 Call setup	28
5.2.2.2 Service negotiation.....	29
5.2.3 Call connect	29
5.2.4 Call information.....	29
5.2.5 Service change	30
5.2.6 Call release.....	30
5.3 Overview of Supplementary Services (SS)	30
5.3.1 General.....	30
5.3.2 Keypad protocol.....	31
5.3.3 Feature key management protocol	31
5.3.4 Functional protocol.....	31
5.4 Overview of Connection Oriented Message Service (COMS).....	31
5.4.1 General.....	31
5.4.2 COMS establishment	32
5.4.3 Service negotiation	32
5.4.4 COMS connect.....	32
5.4.5 COMS data transfer	32
5.4.6 COMS suspend and resume	32
5.4.7 COMS release	33
5.5 Overview of ConnectionLess Message Service (CLMS)	33
5.5.1 Fixed length message service.....	33
5.5.2 Variable length message service.....	33
5.6 Overview of Mobility Management (MM)	33
5.6.1 General.....	33
5.6.2 Identity procedures	34
5.6.3 Authentication procedures	34
5.6.4 Location procedures.....	35
5.6.5 Access rights procedures	35
5.6.6 Key allocation procedure	35
5.6.7 Parameter retrieval procedure	35
5.6.8 Cipherring related procedure.....	36
5.6.9 External protocol information procedure.....	36
5.7 Overview of Link Control Entity (LCE)	36
5.7.1 General.....	36
5.7.2 Data Link Endpoint Identifier (DLEI)	36
5.7.3 Data link establishment.....	37
5.7.4 Data link re-establishment	37
5.7.5 Data link release	37

5.7.6	Data link suspend and resume.....	37
5.7.7	Queuing of messages	38
5.7.8	Request paging.....	38
6	Message functional definitions.....	38
6.1	Overview of message structures	38
6.1.1	Messages.....	38
6.1.2	Information elements	39
6.2	Message summaries.....	39
6.2.1	Summary of CC messages	39
6.2.2	Summary of CISS messages	40
6.2.3	Summary of COMS messages	40
6.2.4	Summary of CLMS messages.....	40
6.2.5	Summary of MM messages	41
6.2.6	Summary of LCE messages	41
6.3	S-FORMAT message functional contents.....	42
6.3.1	S-FORMAT message overview.....	42
6.3.2	CC-messages.....	42
6.3.2.1	{CC-SETUP}	42
6.3.2.2	{CC-INFO}	44
6.3.2.3	{CC-SETUP-ACK}	45
6.3.2.4	{CC-CALL-PROC}	46
6.3.2.5	{CC-ALERTING}	47
6.3.2.6	{CC-CONNECT}	48
6.3.2.7	{CC-CONNECT-ACK}	49
6.3.2.8	{CC-RELEASE}.....	49
6.3.2.9	{CC-RELEASE-COM}	50
6.3.2.10	{CC-SERVICE-CHANGE}	51
6.3.2.11	{CC-SERVICE-ACCEPT}	52
6.3.2.12	{CC-SERVICE-REJECT}	52
6.3.2.13	{CC-NOTIFY}.....	53
6.3.2.14	{IWU-INFO}	53
6.3.3	SS-messages (call related and call independent)	54
6.3.3.1	{FACILITY}.....	54
6.3.3.2	{HOLD}	54
6.3.3.3	{HOLD-ACK}	55
6.3.3.4	{HOLD-REJECT}	55
6.3.3.5	{RETRIEVE}	55
6.3.3.6	{RETRIEVE-ACK}	56
6.3.3.7	{RETRIEVE-REJECT}	56
6.3.3.8	{CISS-REGISTER}	57
6.3.3.9	{CISS-RELEASE-COM}	57
6.3.4	COMS-messages.....	58
6.3.4.1	{COMS-SETUP}	58
6.3.4.2	{COMS-INFO}	58
6.3.4.3	{COMS-ACK}	59
6.3.4.4	{COMS-CONNECT}	59
6.3.4.5	{COMS-RELEASE}	60
6.3.4.6	{COMS-RELEASE-COM}	60
6.3.4.7	{COMS-NOTIFY}.....	61
6.3.5	CLMS-message.....	61
6.3.5.1	{CLMS-VARIABLE}	61
6.3.6	MM-messages	62
6.3.6.1	{ACCESS-RIGHTS-ACCEPT}	62
6.3.6.2	{ACCESS-RIGHTS-REJECT}	62
6.3.6.3	{ACCESS-RIGHTS-REQUEST}	63
6.3.6.4	{ACCESS-RIGHTS-TERMINATE-ACCEPT}	63
6.3.6.5	{ACCESS-RIGHTS-TERMINATE-REJECT}	64
6.3.6.6	{ACCESS-RIGHTS-TERMINATE-REQUEST}	64
6.3.6.7	{AUTHENTICATION-REJECT}	65
6.3.6.8	{AUTHENTICATION-REPLY}	65
6.3.6.9	{AUTHENTICATION-REQUEST}	66

6.3.6.10	{ CIPHER-REJECT }	66
6.3.6.11	{ CIPHER-REQUEST }	67
6.3.6.12	{ CIPHER-SUGGEST }	67
6.3.6.13	{ DETACH }	67
6.3.6.14	{ IDENTITY-REPLY }	68
6.3.6.15	{ IDENTITY-REQUEST }	69
6.3.6.16	{ KEY-ALLOCATE }	69
6.3.6.17	{ LOCATE-ACCEPT }	70
6.3.6.18	{ LOCATE-REJECT }	70
6.3.6.19	{ LOCATE-REQUEST }	71
6.3.6.20	{ MM-INFO-ACCEPT }	72
6.3.6.21	{ MM-INFO-REJECT }	72
6.3.6.22	{ MM-INFO-REQUEST }	73
6.3.6.23	{ MM-INFO-SUGGEST }	74
6.3.6.24	{ TEMPORARY-IDENTITY-ASSIGN }	74
6.3.6.25	{ TEMPORARY-IDENTITY-ASSIGN-ACK }	75
6.3.6.26	{ TEMPORARY-IDENTITY-ASSIGN-REJ }	75
6.3.6.27	{ MM-IWU }	76
6.3.6.28	{ MM-NOTIFY }	76
6.3.7	LCE-messages	77
6.3.7.1	{ LCE-PAGE-RESPONSE }	77
6.3.7.2	{ LCE-PAGE-REJECT }	77
6.4	B-FORMAT message functional contents	78
6.4.1	B-FORMAT message overview	78
6.4.2	{ LCE-REQUEST-PAGE }	78
6.4.3	{ CLMS-FIXED }	79
7	S-FORMAT message structures	79
7.1	Overview	79
7.2	Protocol Discrimination (PD) element	80
7.3	Transaction Identifier (TI) element	80
7.4	Message type element	81
7.4.1	Messages for CC	82
7.4.2	Messages for SS	82
7.4.3	Messages for COMS	82
7.4.4	Messages for CLMS	83
7.4.5	Messages for MM	83
7.4.6	Messages for LCE	83
7.5	Other information elements	84
7.5.1	Coding rules	84
7.5.2	Extensions of codesets	86
7.5.3	Locking shift procedure	86
7.5.4	Non-locking shift procedure	87
7.5.5	Display and keypad elements	87
7.5.6	Repeated elements	87
7.6	Fixed length information elements	88
7.6.1	Summary	88
7.6.2	Sending complete, delimiter request and use TPUI	88
7.6.3	Repeat indicator	89
7.6.4	Basic service	89
7.6.5	Single display	90
7.6.6	Single keypad	90
7.6.7	Release reason	90
7.6.8	Signal	92
7.6.9	Timer restart	93
7.6.10	Test hook control	93
7.7	Variable length information elements	93
7.7.1	Summary	93
7.7.2	Allocation type	95
7.7.3	Alphanumeric	95
7.7.4	Auth type	96
7.7.5	Call attributes	98

7.7.6	Call identity	101
7.7.7	Called party number.....	101
7.7.8	Called party subaddress	102
7.7.9	Calling party number	103
7.7.10	Cipher info	104
7.7.11	Connection attributes	105
7.7.12	Connection identity	108
7.7.13	Duration	109
7.7.14	End-to-end compatibility	110
7.7.15	Facility	113
7.7.16	Feature activate	113
7.7.17	Feature indicate.....	115
7.7.18	Fixed identity	117
7.7.19	Identity type	118
7.7.20	Info type.....	119
7.7.21	InterWorking Unit (IWU) attributes	120
7.7.22	IWU packet	125
7.7.23	IWU to IWU	126
7.7.24	Key.....	128
7.7.25	Location area	128
7.7.26	Multi-display.....	129
7.7.27	Multi-keypad.....	130
7.7.28	NetWoRK (NWK) assigned identity.....	130
7.7.29	Network parameter	131
7.7.30	Portable identity	133
7.7.31	Progress indicator	137
7.7.32	RAND	137
7.7.33	Rate parameters	138
7.7.34	Reject reason.....	139
7.7.35	RES	140
7.7.36	RS	141
7.7.37	Segmented info	141
7.7.38	Service change info.....	142
7.7.39	Service class.....	143
7.7.40	Setup capability	144
7.7.41	Terminal capability	145
7.7.42	Transit delay	150
7.7.43	Window size	151
7.7.44	ZAP field	151
7.7.45	Escape to proprietary	152
7.7.46	Model identifier	152
7.7.47	MMS Generic Header.....	153
7.7.48	MMS Object Header.....	153
7.7.49	MMS Extended header	154
7.7.50	Time-Date	154
7.7.51	Ext h/o indicator	156
7.7.52	Authentication Reject Parameter	157
7.7.53	Calling party Name	157
7.7.54	Codec List.....	158
7.7.55	Events notification	159
7.7.56	Call information.....	163
8	B-FORMAT message structures	166
8.1	General	166
8.2	LCE request paging messages	166
8.2.1	Short format message.....	167
8.2.2	Full format message.....	168
8.2.3	Long format message.....	169
8.2.4	Message elements	170
8.2.4.1	LCE paging header.....	170
8.2.4.2	Info fields (Full format)	171
8.2.4.3	Default setup behaviour	172

8.2.4.4	Address elements in collective or group ringing.....	174
8.3	CLMS-FIXED messages	174
8.3.1	General message structure	174
8.3.2	Message elements	175
8.3.3	Standard message structures	177
8.3.3.1	General	177
8.3.3.2	Messages using 4-bit characters	177
8.3.3.3	Messages using 8-bit characters	177
9	Call Control (CC) procedures.....	177
9.1	General	177
9.2	Call Control (CC) states	180
9.2.1	States at PT	180
9.2.1.1	State T-00: "NULL"	180
9.2.1.2	State T-19: "RELEASE PENDING"	180
9.2.1.3	State T-10: "ACTIVE"	180
9.2.1.4	State T-01: "CALL INITIATED"	180
9.2.1.5	State T-02: "OVERLAP SENDING"	180
9.2.1.6	State T-03: "CALL PROCEEDING"	180
9.2.1.7	State T-04: "CALL DELIVERED"	180
9.2.1.8	State T-06: "CALL PRESENT"	180
9.2.1.9	State T-07: "CALL RECEIVED"	180
9.2.1.10	State T-08: "CONNECT PENDING"	180
9.2.2	States at FT	181
9.2.2.1	State F-00: "NULL"	181
9.2.2.2	State F-19: "RELEASE PENDING"	181
9.2.2.3	State F-10: "ACTIVE"	181
9.2.2.4	State F-01: "CALL-INITIATED"	181
9.2.2.5	State F-02: "OVERLAP SENDING"	181
9.2.2.6	State F-03: "CALL PROCEEDING"	181
9.2.2.7	State F-04: "CALL DELIVERED"	181
9.2.2.8	State F-06: "CALL PRESENT"	181
9.2.2.9	State F-07: "CALL RECEIVED"	181
9.2.3	Optional states (PT and FT).....	182
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING"	182
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING"	182
9.3	Call establishment procedures.....	182
9.3.1	PT initiated call establishment (outgoing call).....	182
9.3.1.1	Call request	182
9.3.1.2	Call accept or reject.....	183
9.3.1.3	Selection of lower layer resources	183
9.3.1.4	Connection of U-plane	184
9.3.1.5	Overlap sending	184
9.3.1.6	Call proceeding	185
9.3.1.7	Call confirmation	185
9.3.1.8	Call connection	186
9.3.1.9	Expiry of timer <CC.04>	186
9.3.2	FT initiated call establishment (incoming call).....	186
9.3.2.1	Call request	186
9.3.2.2	Call accept or reject.....	187
9.3.2.3	Selection of lower layer resources	187
9.3.2.4	Connection of U-plane	188
9.3.2.5	Overlap receiving	188
9.3.2.6	Call proceeding	188
9.3.2.7	Call confirmation	188
9.3.2.8	Call connection	188
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>.....	189
9.3.2.10	Expiry of timer <CC.04>	189
9.4	Call information procedures	189
9.5	Call release procedures.....	189
9.5.1	Normal call release	189
9.5.2	Abnormal call release	190

9.5.3	Release collisions.....	191
9.6	Service change procedures	191
9.6.1	General.....	191
9.6.2	Change of Bandwidth parameters (including changes in connection type)	192
9.6.3	Service rerouting.....	192
9.6.4	NWK layer service suspension and resumption.....	192
9.6.5	Modulation scheme change.....	193
9.7	NWK layer Packet mode procedures.....	193
9.7.1	General.....	193
9.7.2	PT initiated access	194
9.7.3	FT initiated access	194
9.7.4	NWK layer suspend and resume.....	194
9.7.4.1	General.....	194
9.7.4.2	C-plane NWK layer suspend and resume.....	195
9.7.4.3	U-plane NWK layer suspend and resume	195
9.8	Emergency call procedure.....	195
9.9	Segmentation of information in CC procedures	196
10	Supplementary Services procedures.....	197
10.1	General	197
10.2	Keypad protocol	198
10.3	Feature key management protocol.....	198
10.4	Functional protocol.....	199
10.4.1	Separate messages approach	199
10.4.1.1	Hold procedures	199
10.4.1.2	Retrieve procedures.....	199
10.4.1.3	Auxiliary states for hold and retrieve	200
10.4.2	Common information element approach	200
10.4.2.1	Call Related Supplementary Services (CRSS) procedures.....	200
10.4.2.2	Call Independent Supplementary Services (CISS) procedures	200
10.4.2.2.1	Transport of CISS.....	200
10.4.2.3	Connectionless Supplementary Service (CLSS) procedure	201
10.5	Co-existence of multiple protocols.....	201
10.6	Application protocols	202
10.6.1	DECT standard functional supplementary services	202
10.6.2	DECT specific supplementary services	203
10.6.2.1	Queue management.....	203
10.6.2.2	Indication of subscriber number.....	203
10.6.2.3	Control of echo control functions.....	204
10.6.2.4	Cost information	204
11	Connection Oriented Message Service (COMS).....	205
11.1	General	205
11.2	COMS states.....	205
11.2.1	States at PT	205
11.2.1.1	State TS-0: "NULL"	205
11.2.1.2	State TS-1: "CONNECT PENDING"	205
11.2.1.3	State TS-2: "RELEASE PENDING"	205
11.2.1.4	State TS-3: "ACTIVE"	205
11.2.2	States at FT	205
11.2.2.1	State FS-0: "NULL"	205
11.2.2.2	State FS-1: "CONNECT PENDING"	205
11.2.2.3	State FS-2: "RELEASE PENDING"	205
11.2.2.4	State FS-3: "ACTIVE"	206
11.3	COMS establishment procedures	206
11.3.1	PT initiated COMS establishment	206
11.3.1.1	COMS request.....	206
11.3.1.2	COMS connection.....	206
11.3.2	FT initiated COMS establishment	207
11.3.2.1	COMS request.....	207
11.3.2.2	COMS connection.....	207
11.4	COMS data transfer procedures	207

11.4.1	Procedure at the sending side.....	207
11.4.2	Procedure at the receiving side	208
11.5	COMS NWK layer suspend and resume procedures.....	209
11.6	COMS release procedures	209
11.6.1	Normal COMS release.....	209
11.6.2	Release collisions.....	209
12	ConnectionLess Message Service (CLMS).....	210
12.1	General	210
12.2	CLMS states	210
12.3	CLMS message transmission procedures	210
12.3.1	Fixed length messages	210
12.3.1.1	Procedure in the Fixed radio Termination (FT)	210
12.3.1.2	Procedure in the Portable radio Termination (PT)	211
12.3.2	Variable length messages.....	211
12.3.2.1	Procedure at the sending side	211
12.3.2.2	Procedure at the receiving side.....	211
12.3.2.3	Restrictions for portable side initiated messages.....	212
13	Mobility Management (MM) procedures.....	212
13.1	General	212
13.2	Identity procedures	213
13.2.1	Procedure for identification of PT	213
13.2.2	Procedure for temporary identity assignment	214
13.3	Authentication procedures.....	215
13.3.1	Authentication of a PT.....	215
13.3.2	Authentication of the user.....	217
13.3.3	Authentication of a FT.....	217
13.4	Location procedures	218
13.4.1	Location registration	218
13.4.2	Detach.....	220
13.4.3	Location update	220
13.5	Access rights procedure.....	221
13.5.1	Obtaining the access rights	221
13.5.2	Termination of access rights	222
13.5.3	Modification of access rights	224
13.6	Key allocation procedure.....	224
13.7	Parameter retrieval procedure.....	225
13.8	Ciphering related procedure	227
13.9	External protocol information procedure	229
13.9.1	Procedure for external protocol information initiated by the FT	229
13.9.2	Procedure for external protocol information initiated by the PT	230
13.9.3	Segmentation of information in MM procedures.....	230
14	Link Control Entity (LCE) procedures.....	231
14.1	General	231
14.2	Connection oriented link control procedures.....	232
14.2.1	Link establishment.....	232
14.2.2	Direct PT initiated link establishment.....	232
14.2.3	Indirect (paged) FT initiated link establishment	233
14.2.4	Direct FT initiated link establishment.....	234
14.2.5	Link maintenance.....	235
14.2.6	Link suspend and resume.....	235
14.2.6.1	Link suspend	235
14.2.6.2	Link resume.....	236
14.2.7	Link release.....	236
14.2.7.1	NLR notification without "partial release" as release reason	236
14.2.7.2	NLR notification with "partial release" as release reason	237
14.3	Connectionless link control procedures.....	237
14.3.1	Message routing.....	237
14.3.2	Broadcast announce procedure	237
14.3.3	LCE paging codes for connectionless service.....	238
14.4	Procedure for collective and group ringing	238

14.5	LCE paging procedures for DPRS	239
14.5.1	DPRS initial setup paging.....	239
14.5.1.1	Assumptions for Short paging format or for Full format with IPUI.....	239
14.5.1.2	Coding for Full paging format with TPUI.....	239
14.5.2	DPRS Resume paging.....	240
14.5.2.1	Assumptions for Short paging format or for Full format with IPUI.....	240
14.5.2.2	Coding for Full paging format with TPUI.....	240
14.5.2.3	LCE Resume Procedure description.....	240
14.5.3	Special cases	241
14.5.3.1	Rule for DPRS Class 1 devices.....	241
14.5.3.2	Rule for backcompatibility with former A/B 1 devices	241
15	Management procedures.....	241
15.1	Lower Layer Management Entity (LLME)	241
15.2	Service mapping and negotiation	242
15.2.1	General.....	242
15.2.2	Prioritized list negotiation.....	242
15.2.3	Exchanged attribute negotiation	242
15.2.4	Operating parameter negotiation.....	243
15.2.5	Peer attribute negotiation	243
15.3	Service modification procedures	244
15.4	Resource management.....	244
15.5	Management of MM procedures	244
15.6	Call ciphering management.....	245
15.7	External Handover.....	246
15.7.1	Handover candidate procedures	246
15.7.1.1	General.....	246
15.7.1.2	Handover candidate indication.....	246
15.7.1.3	Handover candidate retrieval	247
15.7.1.4	Target FP selection.....	247
15.7.2	Handover reference procedure.....	248
15.7.2.1	General.....	248
15.7.2.2	Handover reference indication	248
15.7.2.3	Handover reference retrieval.....	248
15.7.3	External handover suggested by FP.....	248
15.7.4	NWK layer set up procedure.....	249
15.7.4.1	Handover request	249
15.7.4.2	Handover confirm	249
15.7.4.3	Handover accept.....	249
15.7.4.4	Handover reject.....	249
15.7.4.5	Release of old connection	249
15.7.4.6	Handover Fall Back.....	250
15.7.5	U-plane handling	250
15.7.6	Ciphering procedure	251
15.7.7	Interaction with location registration	251
15.8	Test management procedures	251
15.8.1	Test call back procedure	252
15.8.2	Test hook control procedures.....	252
15.8.3	Upper tester procedure.....	252
15.9	Application assistance procedures.....	253
15.9.1	DECT Identity Resolution (Retrieval) Procedure	253
15.9.1.1	FT (or HyP) initiated Connectionless Identity Resolution procedure	253
15.9.1.2	PT initiated Connectionless Identity Resolution procedure	254
15.9.1.3	Connection oriented Identity Resolution procedure.....	254
15.9.2	Application Address Resolution (Retrieval) Procedure.....	254
15.9.3	Application Parameter Allocation Procedure.....	254
15.9.3.1	FT initiated application parameter allocation procedure.....	254
15.9.3.2	PT initiated application parameter allocation procedure.....	255
15.9.4	Application parameter information procedure	255
15.9.4.1	FT initiated connection oriented Application parameter information procedure	255
15.9.4.2	PT initiated connection oriented Application parameter information procedure	255
15.9.4.3	FT initiated connectionless Application parameter information procedure	256

15.9.4.4	PT initiated connectionless Application parameter information procedure	256
15.9.5	Application Parameter Indication procedure	256
16	Primitives	257
16.1	Primitive types.....	257
16.2	Primitives to lower layer (DLC layer).....	257
16.3	Primitives to IWU	257
16.3.1	Parameter definitions	257
16.3.2	MNCC primitives	258
16.3.2.1	MNCC_SETUP primitive	259
16.3.2.2	MNCC_SETUP_ACK primitive.....	259
16.3.2.3	MNCC_REJECT primitive	260
16.3.2.4	MNCC_CALL_PROC primitive.....	260
16.3.2.5	MNCC_ALERT primitive	261
16.3.2.6	MNCC_CONNECT primitive.....	261
16.3.2.7	MNCC_RELEASE primitive.....	262
16.3.2.8	MNCC_FACILITY primitive	262
16.3.2.9	MNCC_INFO primitive	263
16.3.2.10	MNCC_MODIFY primitive.....	263
16.3.2.11	MNCC_HOLD primitive	263
16.3.2.12	MNCC_RETRIEVE primitive	264
16.3.2.13	MNCC_IWU_INFO primitive	264
16.3.3	MNSS primitives	264
16.3.3.1	MNSS_SETUP primitive	264
16.3.3.2	MNSS_FACILITY primitive	265
16.3.3.3	MNSS_RELEASE primitive.....	265
16.3.4	MNCO primitives	265
16.3.4.1	MNCO_SETUP primitive	266
16.3.4.2	MNCO_CONNECT primitive	266
16.3.4.3	MNCO_INFO primitive.....	266
16.3.4.4	MNCO_ACK primitive.....	266
16.3.4.5	MNCO_RELEASE primitive.....	267
16.3.4.6	MNCO_REJECT primitive.....	267
16.3.5	MNCL primitives.....	267
16.3.5.1	MNCL_UNITDATA primitive.....	267
16.3.6	MM primitives	268
16.3.6.1	MM_IDENTITY primitive	268
16.3.6.2	MM_IDENTITY_ASSIGN primitive	268
16.3.6.3	MM_AUTHENTICATE primitive	269
16.3.6.4	MM_LOCATE primitive.....	269
16.3.6.5	MM_DETACH primitive.....	269
16.3.6.6	MM_ACCESS_RIGHTS primitive.....	270
16.3.6.7	MM_ACCESS_RIGHTS_TERMINATE primitive.....	270
16.3.6.8	MM_KEY_ALLOCATE primitive.....	270
16.3.6.9	MM_INFO primitive.....	271
16.3.6.10	MM_CIPHER primitive.....	271
16.3.6.11	MM_IWU primitive	271
17	Handling of error and exception conditions	272
17.1	Protocol discrimination error.....	272
17.2	Message too short.....	272
17.3	Transaction identifier error.....	272
17.3.1	Illegal and unsupported transaction identifier value	272
17.3.2	Transaction identifier procedural errors and exception conditions	272
17.3.2.1	Unknown active CC call	272
17.3.2.2	Unknown active CISS call	273
17.3.2.3	Unknown active COMS call	273
17.3.2.4	Unknown active CLMS call.....	273
17.3.2.5	Unknown active MM transaction.....	273
17.3.2.6	Unknown active LCE transaction	273
17.3.3	Call Resource Contention	273
17.4	Message type or message sequence errors	274

17.4.1	CC message error.....	274
17.4.2	CISS message error.....	274
17.4.3	COMS or CLMS message error.....	274
17.4.4	MM message error.....	274
17.4.5	LCE message error.....	274
17.5	General information element errors.....	274
17.5.1	Information element out of sequence.....	274
17.5.2	Duplicated information elements.....	275
17.6	Mandatory information element errors.....	275
17.6.1	Mandatory information element missing in CC messages.....	275
17.6.2	Mandatory information element content error in CC messages.....	275
17.6.3	Mandatory information element error in COMS or CLMS messages.....	275
17.6.4	Mandatory information element error in MM messages.....	276
17.6.5	Mandatory information element error in LCE messages.....	276
17.7	Non-mandatory information element errors.....	276
17.7.1	Unrecognized information element.....	276
17.7.2	Non-mandatory information element content error.....	276
17.8	Data link reset.....	277
17.9	Data link failure.....	277
Annex A (normative): System parameters.....		278
A.1	CC timers.....	278
A.2	SS timers.....	279
A.3	COMS timers.....	279
A.4	CLMS timer.....	280
A.5	MM timers.....	280
A.6	LCE timers.....	283
A.7	NWK layer constants.....	284
A.8	Restart.....	284
Annex B (normative): CC state transition tables.....		285
B.1	CC state transitions at PT side.....	285
B.1.1	CC state table at PT side.....	285
B.1.2	CC transition procedures at PT side.....	286
B.2	CC state transitions at FT side.....	288
B.2.1	CC state table at FT side.....	288
B.2.2	CC transition procedures at FT side.....	288
Annex C (informative): DLC states as viewed by the LCE.....		291
Annex D (normative): DECT standard character sets.....		292
D.1	General.....	292
D.2	DECT standard 8-bit characters.....	292
D.2.1	General.....	292
D.2.2	Control codes.....	293
D.2.3	Standard IA5 codes.....	294
D.2.4	extended codes and escape to alternative character sets.....	294
D.3	DECT standard 4-bit characters.....	294
Annex E (normative): Default coding of information elements.....		295
E.1	Default coding of <<IWU-ATTRIBUTES>> and <CALL-ATTRIBUTES>> information elements for basic speech.....	295

E.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES>> and <<CONNECTION-ATTRIBUTES>> information elements for wideband speech	295
E.2.1	Default setup attributes for basic service wideband speech	296
Annex F (normative): Broadcast attributes coding		297
F.1	Higher layer capabilities.....	297
F.2	Extended higher layer capabilities	298
F.3	Extended higher layer capabilities (part 2).....	298
Annex G (normative): Use of <<IWU-PACKET>> and <<IWU-TO-IWU>> information elements		300
G.1	General	300
G.2	Sending of <<IWU-PACKET>> elements.....	300
G.2.1	CC and MM use of <<IWU-PACKET>>	300
G.2.2	COMS and CLMS use of <<IWU-PACKET>>.....	300
G.2.3	Rejection of <<IWU-PACKET>> elements	300
G.3	Use of <<IWU-TO-IWU>> elements	301
G.3.1	Sending of <<IWU-TO-IWU>> elements.....	301
G.3.2	Rejection of <<IWU-TO-IWU>> elements	301
Annex H (normative): Transaction identifier flags (TIF) assignment in MM procedures.....		302
H.1	General	302
H.2	Nested procedures	302
H.3	Stand alone procedures.....	303
H.3.1	Location update procedure	303
H.3.2	Location registration procedure with temporary identity assignment	303
H.3.3	PT initiated cipher switching.....	304
H.3.4	Key allocation	304
H.4	External protocol information procedure.....	305
Annex I (normative): Distributed communications.....		306
I.1	Introduction	306
I.2	General requirements	306
I.2.1	DCDL-net.....	306
I.2.2	Subscription.....	306
I.2.3	Communication	307
I.3	Procedure description.....	308
I.3.1	HyP Identities	308
I.3.2	Membership Access Rights Allocation	308
I.3.3	Re-initialization of membership access rights	309
I.3.4	Members Data Transfer	309
I.3.5	Presence/Absence Indication.....	311
I.3.6	Bandwidth management	311
I.3.7	Direct Link Establishment.....	312
I.3.8	Indirect Link Establishment	313
I.3.9	MASTER management	314
I.3.9.1	MASTER assign	314
I.3.9.2	MASTER Change	314
I.3.9.3	DCDL-net System bearer management	314
I.3.10	Common Subscription Database management	315
I.3.10.1	IdN.....	315
I.3.10.2	RFPI, PARK and PLI.....	315
I.3.10.3	IPUI	316
I.3.10.4	TPUI and LAL.....	316