TECHNICAL REPORT

ISO/TR 14813-3

First edition 2000-12-15

Transport information and control systems — Reference model architecture(s) for the TICS sector —

Part 3:

Example elaboration

iTeh STANDARD PREVIEW
Systèmes de commande et d'information des transports — Architecture(s)

du modèle de référence du secteur TICS —

Partie 3: Élaboration d'exemple

ISO/TR 14813-3:2000

https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TR 14813-3:2000</u> https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Forew	vord	ix
Introd	ductionduction	x i
1	Scope	1
2	Normative References	2
3	Terms and Definitions	2
4	Symbols and Abbreviated Terms	4
4.1	Use Case diagram	4
4.2	Package Diagram	
4.3	Class diagram	
4.4	Association	6
4.5	Sequence (interaction) diagram	6
5	Elaboration Method	7
6	Elaboration of the Classes	7
6.1	Control Classes	9
6.1.1	Roadway Classes .: T. A. C.T. A. N.D. A. D.D. D.D. T.Y. I.T. Y.	9
6.1.2	Roadway Classes : Teh STANDARD PREVIEW Transport Classes	10
6.1.3	Vehicles Classes	12
6.1.4	Vehicles Classes (standards.itch.ai) Event Classes	12
6.1.5	Payment Classes	13
6.2	Interface Classes	14
6.2.1	Operating Interfaces://standards.iteh.a/catalog/standards/sist/49b390da-7d39-4ebd-be6e-	14
6.2.2	Travel Terminal <u>8636e661d659/iso-tr-14813-3-2000</u>	
6.2.3	Vehicle Interface	
6.2.4	Roadside Peripheral	
6.3	Information Classes	
6.3.1	Information Classes for Traffic Management and Traveller Information	
7	Elaboration of the Sequence Diagrams	
7.1	Traveller Information	
7.1.1	Pre-journey Information	
7.1.2	Route Guidance and Navigation	
7.1.3	Journey Schedule	
7.1.4	Journey Payment	
7.1.5	On-trip Traveller Information	
7.2	Traffic Management	
7.2.1	Traffic and Pollution Measurement and Control	
7.2.2	Performance Evaluation	
7.2.3 7.2.4	Performance Prediction	
7.2.4 7.2.5	Incident Management	
7.2.5 7.2.6	Demand Management	
7.2.7	Transport Planning Support	
7.2.7 7.2.8	Infrastructure Maintenance and Management	
7.2.9	Package Classes for Traffic Management	
7.2.9	Vehicle	
7.3.1	Vehicle Status	
7.3.1	Vehicle Operation	
7.3.2	Commercial Vehicle	
7.4.1	Order and Shipment	
		• ·

7.4.2	Commercial Vehicle Tour Planning	
7.4.3	Commercial Vehicle Administrative Processes	
7.4.4	Commercial Vehicle Road Operation	
7.5	Public Transport	
7.5.1	Route and Schedule Planning	
7.5.2 7.5.3	Fixed Route Public Transport	
7.5.3 7.6	Demand Responsive Public Transport Emergency	
7.6 7.6.1	Emergency Notification and Personal Security	
7.6.1 7.6.2	Emergency Resources Allocation	
7.6.3	Emergency Vehicle Management	
7.7 7.7	Electronic Payment	
7.7.1	Payment Means	
7.7.2	Fare Collection	
7.7.3	Vehicle Charges	84
7.7.4	Payment Transaction	85
7.8	Safety	
7.8.1	Safety Enhancement for Vulnerable Road Users	91
8	Elaboration of the Packages	93
8.1	Roadway	
8.2	Transport	
8.3	Vehicles	
8.4	Events	
8.5	Payment	
8.6	Interfaces	105
8.7	Class-Sequence Diagram Matrix	107
8.7.1	Matrix for Key Control and Information Classes	107
8.7.2	Matrix for Interface Classes(SLANGALGS.II.EQ.A.I.)	112
9	Package Interfaces	115
9.1	Package Interfaces	117
9.2	Transport Interfaces ps://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-	119
9.3	Vehicle Interfaces <u>8636e661d659/iso-tr-14813-3-2000</u>	120
9.4	Events Interfaces	121
9.5	Payment Interfaces	122
10	Dependencies between Packages	123
10.1	Roadway - Transport Collaboration	
10.2	Roadway - Vehicles Collaboration	
10.3	Roadway - Events Collaboration	
10.4	Roadway - Payment Collaboration	
10.5	Transport - Events Collaboration	
10.6	Transport - Payment Collaboration	127
10.7	Vehicles - Events Collaboration	127
Anney	x A (informative) Management and Information Centres Information Classes	128
A.1	Infrastructure Map	
A.2	Moving Components	
A.3	Effects on Operations	
A.4	Traffic Usage	
A.5	Traffic Management	
A.6	User Information	155
A.7	Transport Systems	157
8.A	Financial Data	159
A.9	TMIC Management	160
Biblio	ography	164
		104
	figures	-
⊢ıgure	e 1 — A use case diagram consisting of two use cases and one actor	4
Figure	e 2 — Package diagram showing nested packages and a dependency relationship	E
	, L I GUNGUU GIGUIGIII ƏHUWIHU HEƏLEU DAUNAUES AHU A UEDEHUEHUV FEIAHUHSHID	

Figure 3 — Class diagrams showing the use of a single name compartment and three compartments	5
Figure 4 — Common types of class association	6
Figure 5 — A sequence diagram consisting of three interactions	6
Figure 6 — Steps in the elaboration of the Core Reference Architecture	8
Figure 7 — Control class diagram of the Roadway package	10
Figure 8 — Control class diagram of the Transport package	12
Figure 9 — Control class diagram of the Events package	13
Figure 10 — Top level aggregation of Information classes derived from the 14827 naming tree	17
Figure 11 — Information classes in the aggregation of infrastructureMap	18
Figure 12 — Information classes in the aggregation of movingComponents	19
Figure 13 — Information classes in the aggregation of effectsOnOperations	20
Figure 14 — Information classes in the aggregation of trafficUsage	21
Figure 15 — Information classes in the aggregation of trafficManagement	22
Figure 16 — Information classes in the aggregation of userInformation	
Figure 17 — Information classes in the aggregation of transportSystems	24
ISO/TR 14813-3:2000 Figure 18 — Information classes in the aggregation of financial Data oda-7d39-4ebd-be6e	25
8636e661d659/iso-tr-14813-3-2000 Figure 19 — Information classes in the aggregation of tmicManagement	26
Figure 20 — Sequence diagram for Pre-journey Information	32
Figure 21 — Sequence diagram for Route Guidance and Navigation	33
Figure 22 — Sequence diagram for Journey Schedule	34
Figure 23 — Sequence diagram for Journey Payment	35
Figure 24 — Sequence diagram for On-trip Traveller Information	36
Figure 25 — Sequence diagram for Traffic and Pollution Measurement and Control	46
Figure 26 — Packages, control and information classes for Traffic and Pollution and Measurement and Control	47
Figure 27 — Sequence diagram for Performance Evaluation	48
Figure 28 — Packages, control and information classes for Performance Evaluation	49
Figure 29 — Sequence diagram for Performance Prediction	50
Figure 30 — Packages, control and information classes for Performance Prediction	50
Figure 31 —Sequence diagram for Traffic Control	51
Figure 32 — Packages, control and information classes for Traffic Control	52

Figure 33 — Sequence diagram for Incident management	53
Figure 34 — Packages, control and information classes for Incident Management	54
Figure 35 — Sequence diagram for Demand Management	55
Figure 36 — Packages, control and information classes for Demand Management	56
Figure 37 — Sequence diagram for Transportation Planning Support	57
Figure 38 — Packages, control and information classes for Transportation Planning Support	58
Figure 39 — Sequence diagram for Infrastructure Maintenance Management	59
Figure 40 — Packages, control and information classes for Infrastructure Maintenance and Management	59
Figure 41 — Roadway package class operations and information class associations for Traffic Management	60
Figure 42 — Events package class operations and information class associations for Traffic Management	61
Figure 43 — Transport package class operations and information class associations for Traffic Management	62
Figure 44 — Sequence diagram for Vehicle Status	64
Figure 45 — Sequence diagram for Vehicle Operation	64
Figure 46 — Sequence diagram for Order and Shipment	
Figure 47 — Sequence diagram for Commercial Vehicle Tour Planning	
ISO/TR 14813-3:2000 Figure 48 — Sequence diagram for Commercial Mehicle Administrative Processes d-beformance diagram for Commercial Mehicle Administrative Processes d-beform	71
8636e661d659/iso-tr-14813-3-2000 Figure 49 — Sequence diagram for Commercial Vehicle Road Operation	72
Figure 50 — Sequence diagram for Route and Schedule Planning	76
Figure 51 — Sequence diagram for Fixed Route Public Transport	77
Figure 52 — Sequence Diagram for Demand Responsive Public Transport	78
Figure 53 — Sequence diagram for Emergency Notification and Personal Security	81
Figure 54 — Sequence diagram for Emergency Resources Allocation	82
Figure 55 — Sequence diagram for Emergency Vehicle Management	83
Figure 56 — Sequence diagram for Payment Means	87
Figure 57 — Sequence diagram for Fare Collection	88
Figure 58 — Sequence diagram for Vehicle Charges	89
Figure 59 — Sequence diagram for Payment Transaction	90
Figure 60 — Sequence diagram for Safety Enhancement for Vulnerable Road Users	92
Figure 61 — Key classes of the Roadway package	93
Figure 62 — Key classes of the Transport package	96

Figure 63 — Key classes of the Vehicle package	100
Figure 64 — Key classes of the Events package	101
Figure 65 — Key classes of the Payment package	103
Figure 66 — Key classes of the interface packages	105
Figure 67 — Roadway Package Interfaces	116
Figure 68 — Transport Package Interfaces	118
Figure 69 — Vehicle Package Interfaces	120
Figure 70 — Events Package Interfaces	121
Figure 71 — Payment Package Interfaces	122
Figure 72 — Roadway - Transport Collaborations	124
Figure 73 — Roadway - Vehicles Collaborations	124
Figure 74 — Roadway - Events Collaborations	125
Figure 75 — Roadway - Payment Collaborations	126
Figure 76 — Transport - Events Collaborations	
Figure 77 — Transport - Payment Collaborations	
ISO/TR 14813-3:2000 Figure 78 — Vehicles - Events/Collaborationsatalog/standards/sist/49b390da-7d39-4ebd-be6e	127
8636e661d659/iso-tr-14813-3-2000 Figure A.1 — The top level of the naming tree for the information classes defined in the data dictionary	128
List of tables	
Table 1 —Control classes and operations of the Roadway package	9
Table 2 — Control classes and operations of the Transport package	11
Table 3 — Control classes and operations of the Vehicle package	12
Table 4 — Control classes and operations of the Events package	13
Table 5 — Control classes and operations of the Payment package	14
Table 6 — Operating Interface class and operations	14
Table 7 — Travel Terminal class and operations	15
Table 8 — Vehicle Interface class and operations	15
Table 9 — Roadside Peripheral class and operations	15
Table 10 — Matrix count of Roadway class Interface class collaborations	117
Table 11 — Matrix count of Transport class Interface class collaborations	119

Table 12 — Matrix count of Vehicles class Interface class collaborations	120
Table 13 — Matrix count of Events class Interface class collaborations	121
Table 14 — Matrix count of Payment class Interface class collaborations	122
Table 15 — Matrix count of Roadway class Transport class collaborations	123
Table 16 — Matrix count of Roadway class Events class collaborations	125
Table 17 — Matrix count of Roadway class Payment class collaborations	126

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TR 14813-3:2000 https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The main task of technical committees is to prepare International Standards, but in exceptional circumstances a technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when a technical committee has collected data of different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Technical Reports are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Attention is drawn to the possibility that some of the elements of this part of ISO TR 14813 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 14813-3, which is a Technical Report of type 2, was prepared by Technical Committee ISO/TC 204, *Transport information and control systems*.

This document is being issued in the Technical Report (type 2) series of publications (according to subclause G.3.2.2 of Part 1 of the ISO/IEC Directives, 1995) as a "prospective standard for provisional application" in the field of transport information and control systems because there is an urgent need for guidance on how standards in this field should be used to meet an identified need.

This document is not to be regarded as an "International Standard". It is proposed for provisional application so that information and experience of its use in practice may be gathered. Comments on the content of this document should be sent to the ISO Central Secretariat.

A review of this Technical Report (type 2) will be carried out not later than three years after its publication with the options of: extension for another three years; conversion into an International Standard; or withdrawal.

ISO TR 14813 consists of the following parts, under the general title Transport information and control systems — Reference model architecture(s) for the TICS sector:

- Part 1: TICS Fundamental Services: This document presents the definition of 32 TICS fundamental services
 that are the informational products or services or applications areas provided to a TICS user.
- Part 2: Core TICS Reference Architecture: This document describes an abstract object-oriented system architecture based on the TICS Fundamental Services.

© ISO 2000 – All rights reserved ix

- Part 3: Example Elaboration: This document refines the Core TICS Reference Architecture (Part 2) with some emphasis on traffic management.
- Part 4: Reference Model Tutorial: This document describes the basic terms, graphical representations and modelling views exploited in the object-oriented definition of the architecture development of Parts 2 and 3.
- Part 5: Requirements for Architecture Description in TICS Standards: Requirements for Architecture
 Description in TICS Standards: This document describes the terminology and form to be used when
 documenting or referencing aspects of architecture description in TICS standards.
- Part 6: Data Presentation in ASN.1: This document establishes the use of ASN.1 as the normal syntax notation to be used in standards for the TICS sector and a common message form for such ASN.1 based data elements.

Annex A of this part of ISO/TR 14813 is for information only.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TR 14813-3:2000 https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000

Introduction

TC204/WG1 is a working group whose prime objectives are to provide services to ISO TC204 and its working groups. A specific mission of WG1 is to:

"Provide ISO TC204, its working Groups, related bodies and those involved in the TICS sector, with a reference model of Conceptual Reference Architecture(s) that show the structure and inter-relationships of the sector ..."

It is expected that there may well be more than one single TICS Architecture approach to be considered and documented and that existing architecture approaches will have previously-produced documentation developed according to disparate standards and conventions.

It is also implicit in the work being undertaken by WG1, that working group members will require a clear, well-structured understanding of the work of the following participant groups:

- Other TC 204 Working Groups
- CEN TC 278 Working Groups
- Japanese initiatives

iTeh STANDARD PREVIEW

- European Road Transport and Traffic Telematics programs (standards.iteh.ai)
- US Intelligent Transportation Systems program

ISO/TR 14813-3:2000

- Australian initiatives https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000
- Canadian Initiatives

Full documentation of all possible architectural approaches is obviously not feasible given the high level of resources required to carry this out. Indeed full documentation and description of all possible approaches is undesirable as an item for Standardisation.

A defined and consistent approach is however required to facilitate the specification of architecture requirements to enable a clear view to be developed and presented of the work of each participant group This document is one of a set of WG1 documents intended to respond to stated WG1 objectives regarding the production of a TICS Reference Architecture.

In order to document an architecture, graphical and textual components of a model are required. WG1 has adopted a methodology based on the Unified Modelling Language (UML) for documenting the TICS Reference Architecture. A tutorial on the UML is provided in ISO/TR 14813 Part 4. UML is a visual modelling language for building object-oriented and component-based systems. A commercially available Computer Aided Software Engineering (CASE) tool has been used by WG1 to document the Architecture. While the tool is a commercial product, UML is open and non-proprietary.

© ISO 2000 – All rights reserved

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/TR 14813-3:2000 https://standards.iteh.ai/catalog/standards/sist/49b390da-7d39-4ebd-be6e-8636e661d659/iso-tr-14813-3-2000

Transport information and control systems — Reference model architecture(s) for the TICS sector — Part 3: Example elaboration

1 Scope

The architecture of an information and control system merges hardware and software considerations into a coordinated and integrated system view. The system architecture is a high level abstraction, or model, of the system. A system architecture should embrace both today's applications and the applications that are expected in the future. Architecture begins with the definition of the conceptual services (e.g. Part 1 - TICS Fundamental Services). There are several identifiable stages of system architecture development.

- a) Reference architecture
- b) Logical architecture
- c) Physical architecture

A reference architecture is the first of all architectures. It is a concise generic framework which guides the development of more concrete system architectures. It is large enough that distinct concepts are not merged out of necessity and small enough that it does not become unwieldy.

A most significant example of a reference architecture in information systems is the Reference Model of Open Systems Interconnection (often called the seven layer model) developed by ISO in the 1970's. This model has underpinned the development of all modern computer networks, allowing services such as global networking, of which the prime example is the Internet, to become a reality.

A reference architecture is generic and non-prescriptive and captures the concepts of the system. A logical architecture elaborates the conceptual behaviour, and in so doing it provides more detail about the modularity. A physical architecture is reached when the actual distribution of the system modules is defined, thus leading to important implications for communications.

There is no firm demarcation between a reference architecture and a logical architecture. Thus the essence of behaviour and modularity is present in a reference architecture. The TICS Reference Architecture developed by WG1 shows important inter-relationships that arise in the provision of the services of the sector. However the TICS Reference Architecture is more abstract than, for example, the logical architecture of the US National Architecture.

It is envisioned that the TICS Reference Architecture will be used by the TC204 Working Groups to develop their own logical and physical architectures in a cohesive manner.

Some TICS Fundamental Services are already well developed by the industry, while others are less mature. Therefore the TICS Reference Architecture does not have a uniform granularity across all services. This characteristic is a direct result of the fore mentioned requirement that architecture embrace the applications that are intended in the future. This suggests one of the ways in which the architecture will undergo change in the future.

Architectures may present only static characteristics or both static and dynamic characteristics. Dynamic characteristics may be seen as belonging solely to the design/implementation stages of system development. However by including dynamic characteristics at the reference architecture stage one can gain important insights into the static architecture. Thus two orthogonal views of architecture are presented:

© ISO 2000 – All rights reserved

- a) static relationship view (class diagram)
- b) dynamic interactive view (sequence diagram)

Part 2 develops a Core TICS Reference Architecture. The static scope is determined by deriving the system boundary and the use cases from an analysis of the TICS Fundamental Services (Part 1).

The Core Reference Architecture is a reference for the development of national architectures.

This Part elaborates the core by refinement of the two orthogonal views. The elaboration calls upon domain expertise which would be provided by other TC204 Working Groups in the development of ISO standards, or by national groups developing national architectures and standards.

The Core Reference Architecture is elaborated in Clauses 6 to 8. Clause 5 introduces the elaboration method employed. Clause 6 elaborates the classes. Clause 7 elaborates the sequence diagrams. Clause 8 describes the elaborated packages. Clauses 9 and 10 identify some of the main dependencies between the packages.

Readers should refer to Part 4 (Tutorial) for an introduction to the modelling views used in this Part and the overall methodology.

2 Normative references

The following normative documents contain provisions that, through reference in this text, constitute provisions of this part of ISO/TR 14813. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/TR 14813 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/TR 14813-3:2000

ISO/TR 14813-1:1999, *Transport information and control systems*) Reference4model6architecture(s) for the TICS sector – Part 1:TICS fundamental services. 8636e661d659/iso-tr-14813-3-2000

ISO/TR 14813-2:2000, Transport information and control systems – Reference model architecture(s) for the TICS sector – Part 2: Core TICS reference architecture.

ISO/TR 14813-4:2000, Transport information and control systems – Reference model architecture(s) for the TICS sector – Part 4: Reference model tutorial.

3 Terms and Definitions

For the purposes of this part of ISO/TR 14813, the following semantic definitions apply.

3.1

The **Unified Modeling Language** (UML) is the industry-standard language for specifying, visualising, constructing, and documenting the artefacts of software systems. It simplifies the complex process of software design, making a "blueprint" for construction.¹

3.2

A **use case** is a coherent unit of functionality provided by a system or class as manifested by sequences of messages exchanged among the system and one or more outside interactors (called actors) together with actions performed by the system.

¹ http://www.rational.com/uml/

3.3

An **actor** is a role of an object or objects outside of a system that interacts directly with it as part of a coherent work unit (a use case). An Actor element characterises the role played by an outside object; one physical object may play several roles and therefore be modelled by several actors.

3.4

Use case diagrams show elements from the use case model. The use case model represents functionality of a system or a class as manifested to external interactors with the system.

There are several standard relationships among use cases or between actors and use cases.

Communicates - The participation of an actor in a use case. This is the only relationship between actors and use cases.

Uses - A uses relationship from use case A to use case B indicates that an instance of the use case A will also include the behavior as specified by B.

To reinforce the externality of actors a system boundary separates the actor symbols from the use case symbols.

3.5

A **package** is a grouping of model elements. Packages themselves may be nested within other packages. A package may contain both subordinate packages and ordinary model elements. The entire system description can be thought of as a single high-level *system* package with everything else in it. All kinds of UML model elements and diagrams can be organised into packages.

Packages own model elements and model fragments and are the basis for configuration control. Each model element can be directly owned by a single package, so the package hierarchy is a strict tree.

Packages can reference other packages so the usage network is a graph. Relationships drawn between package symbols denote relationships between at least some of the elements in the packages. A dependency relationship implies one or more dependencies among the model elements in which a change in the targeted element may require a change in the source element.

8636e661d659/iso-tr-14813-3-2000

3.6

A **class** is the descriptor for a set of objects with similar structure, behavior, and relationships. UML provides notation for declaring classes and specifying their properties, as well as using classes in various ways. Classes are declared in class diagrams and used in most other diagrams. UML provides a graphical notation for declaring and using classes, as well as a textual notation for referencing classes within the descriptions of other model elements.

3.7

A **class diagram** is a graph of Classifier elements connected by their various static relationships. (Note that a "class" diagram may also contain interfaces, packages, relationships, and even instances, such as objects and links. Perhaps a better name would be "static structural diagram" but "class diagram" is shorter and well established.)

3.8

An **object** represents a particular instance of a class. It has identity and attribute values. The same notation also represents a role within a collaboration because roles have instance-like characteristics.

3.9

An **operation** is a service that an instance of the class may be requested to perform. It has a name and a list of arguments.

3.10

A binary **association** is an association among exactly two classes (including the possibility of a reflexive association from a class to itself).

© ISO 2000 – All rights reserved