



**SLOVENSKI STANDARD**  
**oSIST prEN 12007-4:2011**

**01-februar-2011**

---

**Infrastruktura za plin - Cevovodni sistemi za najvišji delovni tlak do vključno 16 bar - 4. del: Posebna funkcionalna priporočila za obnovo**

Gas infrastructure - Pipelines for maximum operating pressure up to and including 16 bar  
- Part 4: Specific functional recommendations for renovation

Gasinfrastruktur - Rohrleitungen mit einem maximal zulässigen Betriebsdruck bis einschließlich 16 bar - Teil 4: Besondere funktionale Empfehlungen für die Sanierung

Infrastructures gazières - Canalisations pour pression maximale de service inférieure ou égale à 16 bar - Partie 4: Recommandations fonctionnelles spécifiques pour la rénovation

**Ta slovenski standard je istoveten z: prEN 12007-4**

---

**ICS:**

91.140.40      Sistemi za oskrbo s plinom      Gas supply systems

**oSIST prEN 12007-4:2011**

**en**



EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**DRAFT**  
**prEN 12007-4**

November 2010

ICS 23.040.01

Will supersede EN 12007-4:2000

English Version

## Gas infrastructure - Pipelines for maximum operating pressure up to and including 16 bar - Part 4: Specific functional recommendations for renovation

Infrastructures gazières - Canalisations pour pression maximale de service inférieure ou égale à 16 bar - Partie 4: Recommandations fonctionnelles spécifiques pour la rénovation

Gasinfrastruktur - Rohrleitungen mit einem maximal zulässigen Betriebsdruck bis einschließlich 16 bar - Teil 4: Besondere funktionale Empfehlungen für die Sanierung

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 234.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

[e7cd-45a8-bb3c-27c32876eafb/sist-en-12007-4-2013](https://doi.org/10.25516/27c32876eafb/sist-en-12007-4-2013)

**Warning** : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: Avenue Marnix 17, B-1000 Brussels**

## Contents

Page

Foreword.....	4
<b>1 Scope .....</b>	<b>5</b>
<b>2 Normative references .....</b>	<b>5</b>
<b>3 Terms and definitions .....</b>	<b>5</b>
<b>4 Design .....</b>	<b>7</b>
4.1 General .....	7
4.2 Pressure uprating.....	7
4.3 Selection of renovation technique .....	7
4.4 Consultation with third parties.....	8
<b>5 Construction .....</b>	<b>8</b>
5.1 General .....	8
5.2 Disconnection/Reconnection of sections of the gas supply system .....	8
5.3 Excavation/No dig techniques .....	9
5.4 Laying .....	9
5.4.1 Laying of pipework .....	9
5.4.2 Cleaning of carrier pipe.....	9
5.4.3 Inspection of the pipework to be renovated .....	10
<b>6 Pressure testing .....</b>	<b>10</b>
<b>7 Service line transfer.....</b>	<b>10</b>
<b>8 Commissioning and decommissioning.....</b>	<b>10</b>
<b>9 Record system .....</b>	<b>10</b>
<b>Annex A (informative) Chart of renovation techniques.....</b>	<b>11</b>
<b>Annex B (informative) Advantages and disadvantages of renovation techniques .....</b>	<b>12</b>
<b>Annex C (informative) Renovation with continuous or discrete pipe.....</b>	<b>15</b>
C.1 Definition .....	15
C.2 Description .....	15
C.3 Conditions of application.....	15
C.4 Implementation .....	16
C.4.1 Preparation .....	16
C.4.2 Execution .....	16
<b>Annex D (informative) Lining with close-fit pipe.....</b>	<b>19</b>
D.1 Definition.....	19
D.2 Description .....	19
D.3 Conditions of application .....	19
D.4 Implementation .....	20
D.4.1 Materials .....	20
D.4.2 Preparation .....	20
D.4.3 Execution .....	20
<b>Annex E (informative) Lining with cured-in-place pipe .....</b>	<b>22</b>
E.1 Definition .....	22
E.2 Description .....	22
E.3 Conditions of application.....	22
E.4 Implementation .....	22
E.4.1 Preparation .....	22
E.4.2 Execution.....	23

<b>Annex F</b> (informative) <b>Renovation by bursting or splitting existing pipe</b> .....	<b>24</b>
<b>F.1</b> <b>Definition</b> .....	<b>24</b>
<b>F.2</b> <b>Description</b> .....	<b>24</b>
<b>F.3</b> <b>Conditions of application</b> .....	<b>24</b>
<b>F.4</b> <b>Implementation</b> .....	<b>24</b>
<b>F.4.1</b> <b>Preparation</b> .....	<b>24</b>
<b>F.4.2</b> <b>Execution</b> .....	<b>25</b>
<b>Annex G</b> (informative) <b>Renovation by the pulling or pushing of the existing pipe</b> .....	<b>26</b>
<b>G.1</b> <b>Definition</b> .....	<b>26</b>
<b>G.2</b> <b>Description</b> .....	<b>26</b>
<b>G.3</b> <b>Conditions of application</b> .....	<b>26</b>
<b>G.4</b> <b>Implementation</b> .....	<b>26</b>
<b>G.4.1</b> <b>Preparation</b> .....	<b>26</b>
<b>G.4.2</b> <b>Execution</b> .....	<b>26</b>
<b>Annex H</b> (informative) <b>Joint repairs</b> .....	<b>28</b>
<b>H.1</b> <b>Definition</b> .....	<b>28</b>
<b>H.2</b> <b>Description</b> .....	<b>28</b>
<b>H.3</b> <b>Conditions of application</b> .....	<b>28</b>
<b>H.3.1</b> <b>General</b> .....	<b>28</b>
<b>H.3.2</b> <b>Internal methods</b> .....	<b>28</b>
<b>H.3.3</b> <b>External methods – Commissioned pipework</b> .....	<b>29</b>
<b>H.4</b> <b>Implementation</b> .....	<b>29</b>
<b>H.4.1</b> <b>Internal repairs</b> .....	<b>29</b>
<b>H.4.2</b> <b>External repairs – Commissioned pipework</b> .....	<b>30</b>
<b>H.5</b> <b>Testing</b> .....	<b>30</b>
<b>H.6</b> <b>Commissioning</b> .....	<b>31</b>
<b>Annex I</b> (informative) <b>Resin lining</b> .....	<b>32</b>
<b>I.1</b> <b>Definition</b> .....	<b>32</b>
<b>I.2</b> <b>Description</b> .....	<b>32</b>
<b>I.3</b> <b>Conditions of application</b> .....	<b>32</b>
<b>I.4</b> <b>Implementation</b> .....	<b>32</b>
<b>I.4.1</b> <b>Preparation</b> .....	<b>32</b>
<b>I.4.2</b> <b>Execution</b> .....	<b>32</b>
<b>I.4.3</b> <b>Testing</b> .....	<b>33</b>
<b>I.4.4</b> <b>Commissioning</b> .....	<b>33</b>

prEN 12007-4:2010 (E)

## Foreword

This document (prEN 12007-4:2010) has been prepared by Technical Committee CEN/TC 234 “Gas infrastructure”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 12007-4:2000.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 12007-4:2013

<https://standards.iteh.ai/catalog/standards/sist/74972b04-c7cd-45a8-bb3c-27c32876eafb/sist-en-12007-4-2013>

## 1 Scope

This European Standard describes specific functional recommendations for the renovation of pipeworks existing in gas supply systems and includes some requirements for materials other than plastics covered by CEN/TC 155 "Plastics piping and ducting systems". This European Standard is intended to be applied in association with prEN 12007-1.

This European Standard does not apply to pipework in above ground installations.

This European Standard specifies common basic principles for gas supply systems. Users of this European Standard should be aware that more detailed national standards and/or codes of practice can exist in the CEN member countries.

This European Standard covers the various renovation technologies for gas piping in the range of sizes covering gas mains and gas service lines and is intended to be applied in association with prEN 12007 part 1.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

prEN 12007-1, *Gas infrastructure — Pipelines for maximum operating pressure up to and including 16 bar — Part 1: General functional recommendations*

prEN 12007-2, *Gas infrastructure — Pipelines for maximum operating pressure up to and including 16 bar — Part 2: Specific functional recommendations for polyethylene (MOP up to and including 10 bar)*

EN 12007-3, *Gas supply systems — Pipelines for maximum operating pressure up to and including 16 bar — Part 3: Specific functional recommendations for steel*

prEN 12327, *Gas infrastructure — Pressure testing, commissioning and decommissioning procedures — Functional requirements*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **gas supply system**

pipeline systems including pipework and their associated stations or plants for the transmission and distribution of gas

### 3.2

#### **pipeline operator**

private or public organization authorized to design, construct and/or operate and maintain the gas supply system

### 3.3

#### **competent person**

person who is trained, experienced and approved to perform activities relating to gas supply systems

NOTE Means of approval, if any, will be determined within each country.

**prEN 12007-4:2010 (E)**

- 3.4  
main**  
pipework in a gas supply system to which service lines are connected
- 3.5  
pipework**  
assembly of pipes and fittings
- 3.6  
station**  
plant or facility for the operation and/or processing of gas supply systems
- 3.7  
service line transfer**  
act of switching over the service pipe connection from the old pipe to the new one
- 3.8  
pressure uprating**  
activities pertaining to the increase of the operating pressure beyond the existing maximum operating pressure level of a gas supply system
- 3.9  
commissioning**  
activities required to pressurize pipework, stations, equipment and assemblies with the gas and to put them into operation
- 3.10  
decommissioning**  
activities required to take out of service any pipework, stations, equipment and assemblies filled with gas and to disconnect them from the system
- 3.11  
renovation**  
method by which the characteristics of the gas supply system are improved by re-using the existing structure or installing a new structure in its place
- 3.12  
carrier pipe**  
existing pipe in which a renovation system is installed
- NOTE The carrier pipe can be either a conduit pipe or a support pipe.
- 3.13  
support pipe**  
existing pipe which remains the gas carrying pipe and remains a structural integral part of the pressure system after lining
- 3.14  
sleeve**  
length of protective pipe through which a gas pipe passes
- 3.15  
conduit pipe**  
pipe through which a gas pipe is inserted without necessarily providing support
- 3.16  
annular space**  
space enclosed between the carrier pipe and the new pipe when the latter is inserted inside



### 3.17

#### close fit

after reshaping and relaxation, outer surface of the inserted pipe is in close contact with the internal surface of the old pipe

## 4 Design

### 4.1 General

Choice of renovation techniques to be used on pipeworks, up to and including 16 bar, shall be made by a competent person.

The selection of materials, dimensions and assembling techniques shall be the responsibility of the pipeline operator and comply with prEN 12007-1.

Further guidance on the design of polyethylene pipelines (PE) of gas supply systems is given in prEN 12007-2.

Further guidance on the design of steel pipelines of gas supply systems is given in EN 12007-3.

The uprating of renovated systems is the responsibility of the pipeline operator and should conform to the relevant procedure. The Maximum Operating Pressure (MOP) of a renovated system shall be limited by the weakest point of the system.

### 4.2 Pressure uprating

Renovation of a gas supply system can be a part of a strategy plan for uprating the maximum operating pressure. Some renovation techniques lead to a reduction in diameter of the pipe, so that an increase in pressure is required to maintain the flow capacity of the system.

Uprating of MOP is under the responsibility of the pipeline operator and he shall ensure that all pipeline components can withstand in strength and tightness the new pressure level.

### 4.3 Selection of renovation technique

The following factors should be considered when selecting a renovation technique. These include but are not limited to:

- the future structure of the distribution network;
- the pressure level at which the pipework will operate after renovation;
- the required capacity of the pipework;
- the number of gas service lines connected to the section of pipework;
- the presence and number of branches, bends, valves;
- the current condition of the pipework to be renovated;
- the position of the pipework;

EXAMPLE 1 The covering depth of the pipework.

EXAMPLE 2 Disruption to traffic and pedestrians.

**prEN 12007-4:2010 (E)**

EXAMPLE 3 The location of adjacent plant. EXAMPLE 4: Areas sensitive to break phenomena.

- the number, type and condition of pipe joints in the section of pipework;
- any supply obligations to consumers during and after renovation works.

NOTE 1 There are a range of renovation techniques which can be used. These are described generally in annex A. This annex does not represent an exhaustive list of available techniques.

NOTE 2 The advantages and disadvantages of the techniques described in annex A are outlined in annex B. Further details of the different techniques are given in annexes C to J.

**4.4 Consultation with third parties**

When planning works on gas supply systems, there should be communication with the owners of other plant and street authorities near the gas supply system. Any relevant information on the presence of any adjacent plant required to plan the intended works should be collected from these parties.

Further guidance is given in prEN 12007-1.

**5 Construction****5.1 General**

Pipework shall only be laid or renovated by competent persons working to the specification provided by the pipeline operator and/or pipework manufacturer. General guidance on the construction of gas supply systems up to and including 16 bar is given in prEN 12007-1. Specific guidance are given in prEN 12007-2 for polyethylene pipelines and in EN 12007-3 for steel pipelines.

A detailed procedure for the successive steps of the works should be made. Each technique has its specific considerations which are mentioned in the annexes C to J.

Where, as a requirement of the renovation technique, it is necessary to raise the temperature of polyethylene pipe, the pipe temperature shall not exceed the maximum allowable temperature stated by the pipe manufacturer.

The safety of personnel engaged on gas supply works, and of members of the public shall be ensured during the whole period of the works. Considerations shall be given to the needs of the elderly or disabled.

Before assembly and laying parts of gas supply systems the condition of all pipes and fittings shall be checked for conformity. Existing pipework should be checked for unwanted obstructions or blockages.

The construction of gas supply systems should be organized so that the impact on the environment during construction is reduced to the minimum practicable level. Further guidance on environmental considerations is given in prEN 12007-1.

Lubricants used to aid renovation by pipe insertion shall not have a detrimental effect on the existing or inserted pipe.

**5.2 Disconnection/Reconnection of sections of the gas supply system**

Where it is necessary to disconnect a section of the gas supply system to undertake renovation works, care should be taken to ensure that supplies in the other parts of the existing gas supply system are not adversely affected.

Care shall be taken to identify all service lines supplied from the section of main to be disconnected and consideration shall be given to the renovation of these service lines.

For transportation, storage, handling of materials and equipment and for limiting interference from external causes, prEN 12007-1 shall be considered.

### 5.3 Excavation/No dig techniques

The position and size of excavations shall be determined taking into account the covering depth of the pipework to be renovated, the diameter of the new pipe and other factors which can affect the insertion process.

EXAMPLE 1 The proximity of other buried plant.

EXAMPLE 2 The length of the new section of pipe.

EXAMPLE 3 The position of service lines to be transferred.

Consultation shall take place with other utilities before undertaking excavation work, so that adequate measures for the protection of other pipework, cables and underground constructions can be agreed.

The competent person on site shall ensure that the most appropriate information on the location of existing gas supply pipework and other utility plant are available on site. He should ensure that safe digging practices are followed at all times.

Adequate provision should be made for the effective temporary support of pipework, cables, and other apparatus during the progress of the work, and for their permanent support where the ground has been disturbed.

Further guidance on the precautions to be taken when excavating is given in prEN 12007-1.

Excavations created in the process of renovating gas supply systems shall be suitably backfilled and surface features such as roads and footways shall be reinstated according to standards agreed within the Member Countries.

## 5.4 Laying

### 5.4.1 Laying of pipework

Any new pipe installed shall be laid in accordance with the specific guidance if appropriate given in prEN 12007-2 for polyethylene pipelines and in EN 12007-3 for steel pipelines. Further general guidance is given in prEN 12007-1.

### 5.4.2 Cleaning of carrier pipe

When the carrier pipe contains quantities of dust or pitch or other contaminants which could affect the renovation process, consideration should be given to pipe cleaning. Pipe cleaning can be achieved by either mechanical, hydraulic, or pneumatic means.

NOTE In certain renovation techniques the condition of the internal bore of the carrier pipe is a major factor in determining whether the technique can be successfully applied.

EXAMPLE Close-fit lining.

During any pipe cleaning care should be taken:

- to minimize any damage to the environment;
- to the presence of pyrophoric dust;
- to dispose waste material in accordance with national or local legislation.

**prEN 12007-4:2010 (E)****5.4.3 Inspection of the pipework to be renovated**

In case of renovation techniques which use the pipe as carrier pipe, it should be inspected internally prior to introduction of the new pipe, in order to locate possible obstructions and deficiencies which can damage or have otherwise detrimental effects on the new pipe, or block the passage.

The inspection can be carried out with a camera.

**6 Pressure testing**

Pressure testing procedures to prove the integrity of renovated mains and service lines shall be selected from prEN 12327.

The pressure testing shall be carried out in accordance with minimum test pressure levels given in prEN 12007-1.

General guidance is given in prEN 12007-1. Further guidance for polyethylene systems is given in prEN 12007-2.

Where a tightness test cannot be carried out, for example joint repairs carried out under live conditions at operating pressure, the pipeline operator shall specify the test method.

**7 Service line transfer**

Service line transfer shall be carried out in accordance with the specifications given by the pipeline operator and the technical requirements of the renovation technique. A strength test, a tightness test or a combined test shall be carried out on the renovated service line and/or connection between service line and main before commissioning the service line. These tests shall be in accordance with prEN 12327.

If, for technical reasons, pressure testing of the service pipework is not completed prior to connection it should be tested at the same time as the new section of pipeline.

**8 Commissioning and decommissioning**

Commissioning and decommissioning shall be carried out in accordance with prEN 12327. General guidance is given in prEN 12007-1.

**9 Record system**

The requirements for the establishment and maintenance of a record system for gas supply systems are given in prEN 12007-1. The pipeline operator shall ensure that appropriate details of renovated pipework are included within this record system. The following data shall at least be included in the record system:

- type of pipes, diameters and lengths;
- the date of execution of the renovation;
- the technique used for the renovation;
- the presence and type of carrier pipe.