

DfYbcg`j]b`a i `h]d`Y_g]fUb`Y`fHAŁĚ; YbYf] bY`gfi _hi fY`c_j]fUnUdfYbcg`fUn`] b]`
g][bUcj `fj _`1 bc`g`WY]WLa]`Ug]b\ fcbY[UdfYbcgbY[UbU]bUf5 HAŁ]b`YYa Yb]`
g]b\ fcbYX][]H]bY\]YfU\]Y`fG8 <Ł`df]`]YfU\] b]` \]fcbg]` `&\$(, `_V]h]gž' (` * ,
_V]h]g]b`% - `&* (`_V]h]g]dc`df]dcfc]i `77 =HŽ; "+\$&

Transmission and Multiplexing (TM); Generic frame structures for the transport of various signals (including Asynchronous Transfer Mode (ATM) cells and Synchronous Digital Hierarchy (SDH) elements) at the ITU-T Recommendation G.702 hierarchical rates of 2 048 kbit/s, 34 368 kbit/s and 139 264 kbit/s

(standards.iteh.ai)

[SIST ETS 300 337 E1:2003](https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>

Ta slovenski standard je istoveten z: ETS 300 337 Edition 1

ICS:

33.040.20 Prenosni sistem Transmission systems

SIST ETS 300 337 E1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 337 E1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 337

February 1995

Source: ETSI TC-TM

Reference: DE/TM-03007

ICS: 33.080

Key words: Transmission, ATM, SDH

**Transmission and Multiplexing (TM);
Generic frame structures for the transport of various signals
(including Asynchronous Transfer Mode (ATM) cells
and Synchronous Digital Hierarchy (SDH) elements)
at the CCITT Recommendation G.702 hierarchical rates of
2 048 kbit/s, 34 368 kbit/s and 139 264 kbit/s**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 337 E1:2003](https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>

Contents

Foreword	5
1 Scope	7
2 Normative references	7
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	8
4 Frame structure at 2 048 kbit/s	8
4.1 Basic frame structure	8
4.2 Support of ATM cells in 2 048 kbit/s	8
5 Frame structure at 34 368 kbit/s	9
5.1 Basic frame structure	9
5.1.1 General	9
5.1.2 Path overhead	10
5.2 Support of ATM cells in 34 368 kbit/s	12
5.3 Support of 14 SDH TU-12's in 34 368 kbit/s	12
5.3.1 Coding of payload dependent bits for TU multiframe indication	13
6 Frame structure at 139 264 kbit/s	14
6.1 Basic frame structure	14
6.1.1 General	14
6.1.2 Path overhead	15
6.2 Support of ATM cells in 139 264 kbit/s	17
6.3 Support of SDH elements in 139 264 kbit/s	17
6.3.1 Coding of payload dependent bits for TU multiframe indication	18
6.3.2 Support of 20 x TUG-2	18
6.3.3 Support of 2 x TUG-3 and 5 x TUG-2	18
7 Conformance testing	19
Annex A (informative): Functions specific to the support of ATM cells	20
A.1 Cell rate adaptation	20
A.2 Header Error Control (HEC) generation	20
A.3 Cell delineation	20
A.4 Cell header verification and extraction	20
Annex B (informative): Bibliography	21
History	22

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 337 E1:2003](https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Transmission and Multiplexing (TM) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS specifies generic frame structures for the transport of various signals at the CCITT Recommendation G.702 [1] hierarchical rates of 2 048 kbit/s, 34 368 kbit/s and 139 264 kbit/s. The support of Asynchronous Transfer Mode (ATM) cells and Synchronous Digital Hierarchy (SDH) Tributary Units (TUs) in the Plesiochronous Digital Hierarchy (PDH) bit rates is also covered in this ETS.

Transposition dates	
Date of latest announcement of this ETS (doa):	31 May 1995
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 November 1995
Date of withdrawal of any conflicting National Standard (dow):	30 November 1995

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 337 E1:2003](https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 337 E1:2003](https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/eee1f395-40d9-4867-86d7-1730255f7bff/sist-ets-300-337-e1-2003>

1 Scope

This European Telecommunication Standard (ETS) specifies generic frame structures for the transport of various signals at the CCITT Recommendation G.702 [1] hierarchical rates of 2 048 kbit/s, 34 368 kbit/s and 139 264 kbit/s. The support of Asynchronous Transfer Mode (ATM) cells and Synchronous Digital Hierarchy (SDH) Tributary Units (TUs) in the Plesiochronous Digital Hierarchy (PDH) bit rates is covered in this ETS. Functions specific to the support of ATM cells performed in the transmitter and receiver are not part of this interface standard but are given for information in annex A.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] CCITT Recommendation G.702 (1988): "Digital hierarchy bit rates".
- [2] ETS 300 167: "Transmission and Multiplexing (TM); Functional characteristics of 2 048 kbit/s interfaces".
- [3] ETS 300 147 (1992): "Transmission and Multiplexing (TM); Synchronous digital hierarchy; Multiplexing structure".
- [4] CCITT Recommendation E.164 (1991): "Numbering plan for the ISDN era".
- [5] CCITT Recommendation T.50 (1992): "International Reference Alphabet (IRA), Information technology - 7-bit coded character set for information interchange".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this ETS, the following definitions apply:

idle cell: A cell which is inserted and extracted by the adaptation function between the ATM virtual path layer network and the PDH path layer network in order to adapt the cell flow rate to the available payload capacity of the PDH path used.

valid cell: A cell whose header is declared by the cell Header Error Control (HEC) process to be free of errors.

NOTE: The order of transmission of information in all diagrams in this ETS is first from left to right and then top to bottom. Within each byte the most significant bit is transmitted first. The most significant bit (bit 1) is illustrated at the left of all diagrams.

3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

ATM	Asynchronous Transfer Mode
BIP-8	Bit Interleaved Parity - 8
CRC	Cyclic Redundancy Check
ETSI	European Telecommunications Standards Institute
HEC	Header Error Control
IEC	Incoming Error Count
REI	Remote Error Indication
RDI	Remote Defect Indication
MSB	Most Significant Bit
OAM	Operations, Administration and Maintenance
PDH	Plesiochronous Digital Hierarchy
SDH	Synchronous Digital Hierarchy
TS	Time Slot
TTI	Trail Trace Identifier
TU	Tributary Unit
TU-x	Tributary Unit - x
TUG-n	Tributary Unit Group of level n

4 Frame structure at 2 048 kbit/s

4.1 Basic frame structure

The basic frame structure at 2 048 kbit/s as described in ETS 300 167 [2] shall be used. This comprises a generic path overhead and a generic payload capacity of 1 984 kbit/s.

4.2 Support of ATM cells in 2 048 kbit/s

Valid or idle cells are supported in bits 9 to 128 and bits 137 to 256 of the 2 048 kbit/s frame with the octet structure of the cells aligned with the octet structure of the frame (see figure 1). Bits 129 to 136 correspond to Time Slot 16 (TS 16) in an octet structured frame and are reserved for future use. Valid or idle cells occupy the whole of the payload and a cell can cross a 125 μ s frame boundary. The ATM cell payload is scrambled using a self-synchronizing scrambler with the generator polynomial $x^{43} + 1$. Cell payload field scrambling is required to provide security against false cell delineation and to prevent the cell payload replicating the 2 048 kbit/s frame alignment word.




Figure 1: Frame structure at 2 048 kbit/s

5 Frame structure at 34 368 kbit/s

5.1 Basic frame structure

5.1.1 General

The basic frame structure at 34 368 kbit/s comprises 7 octets of generic path overhead and 530 octets of payload capacity per 125 μ s as shown in figure 2.




Figure 2: Frame structure at 34 368 kbit/s