INTERNATIONAL STANDARD

ISO 12164-2

First edition 2001-12-01

Hollow taper interface with flange contact surface —

Part 2: Receivers — Dimensions

iTeh Sinterfaces à cône creux-face EVIEW Partie 2: Nez de broche — Dimensions (standards.iteh.al)

ISO 12164-2:2001 https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001



Reference number ISO 12164-2:2001(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 12164-2:2001</u> https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001

© ISO 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.ch Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 12164 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 12164-2 was prepared by Technical Committee ISO/TC 29, Small tools.

ISO 12164 consists of the following parts, under the general title Hollow taper interface with flange contact surface:

- Part 1: Shanks Dimensions h STANDARD PREVIEW
- Part 2: Receivers Dimensions

^s (standards.iteh.ai)

Annex A of this part of ISO 12164 is for information only.

<u>ISO 12164-2:2001</u> https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 12164-2:2001 https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001

Hollow taper interface with flange contact surface —

Part 2:

Receivers — Dimensions

1 Scope

This part of ISO 12164 specifies dimensions for receivers with taper and flange contact surfaces for hollow taper shanks in accordance with ISO 12164-1 to be applied on machine tools (e.g. turning machines, drilling machines, milling machines and grinding machines). A range of sizes is specified.

This part of ISO 12164 specifies two styles of receiver. Style A is for automatic tool exchange and style C is for manual clamping which is achieved via holes in both the receiver and the tool shank.

Torque is transmitted via the tail end of the shank through keys as well as friction.

iTeh STANDARD PREVIEW

2 Normative references

(standards.iteh.ai)

There are no normative references at present. ISO 12164-2:2001

https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-

ISO 1101: $^{1)}$, Geometrical Product Specifications (GPS) $\stackrel{2164-2-2001}{=}$ Geometrical tolerancing - Tolerances of form, orientation, location and run-out

ISO 2768-1:1989, General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications

ISO 3040:1990, Technical drawings — Dimensioning and tolerancing — Cones

ISO 12164-1, Hollow taper interface with flange contact surface — Part 1: Shanks — Dimensions

3 Dimensions

3.1 General

Dimensions of receivers for hollow taper shanks with flange contact surfaces for automatic tool exchange are specified in Figure 1 and Table 1, and additional dimensions of receivers for hollow taper shanks with flange contact surfaces for manual tool exchange are specified in Figure 2 and Table 2. Tolerancing of form, orientation, location and run-out is in accordance with ISO 1101. Dimensioning and tolerancing of cones is in accordance with ISO 3040. Details not specified shall be chosen expediently. Tolerances not specified shall be of tolerance class "m" in accordance with ISO 2768-1.

¹⁾ To be published. (Revision of ISO 1101:1983)

3.2 Receiver for hollow shank, style A

See Figure 1 and Table 1.

Dimensions in millimetres, surface roughness values in micrometers



Key

- 1 Cutting edge ^b
- 2 Tenon ^c
- ^a When tenons are inserted the taper hole may be conical over the total length l_1
- ^b Position of the cutting edge for right hand tools with single cutting edge
- ^c Tenon alternative integrated or inserted
- ^d Not convex

Figure 1

Dimensions in millimetres

Nominal size		32	40	50	63	80	100	125	160
b_1	\pm 0,05	6,8	7,8	10,3	12,3	15,8	19,78	24,78	29,78
d_1	min.	32	40	50	63	80	100	125	160
d_2		23,998	29,998	37,998	47,998	59,997	74,997	94,996	119,995
$d_3{}^{a}$		17	21	26	34	42	53	67	85
$d_4{}^{b}$	+0,1 0	23,28	29,06	36,85	46,53	58,1	72,6	92,05	116,1
d_5	+0,2 0	23,8	29,6	37,5	47,2	58,8	73,4	93	118
l1 ^b	+0,2 0	16,5	20,5	25,5	33	41	51	64	81
l_2		3,2	4	5	6,3	8	10	12,5	16
l_3	+0,2 0	11,4	14,4	17,9	22,4	28,4	35,4	44,4	57,4
l_4	+0,2 0	13,4	16,9	20,9	26,4	32,4	40,4	51,4	64,4
l_5		0,8	0,8	1	1	1,5	1,5	2	2
l_6	+0,1 0	1	1	1,5	1,5	2	2	2,5	2,5
l_7	\pm 0,1	2	2	2	2,5	3	3	4	4
$r_1{}^{c}$	0 _0,05	1,5	2	2,5	3	4	5	6	8
t		0,001 5	0,001 5	0,002	0,002	0,002 5	0,003	0,003 5	0,003 5

Table 1 — Dimensions

Depending on the clamping system.

See note a to Figure 1.

 r_1 tangent to b_1 and d_4 .

b

с

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO 12164-2:2001

https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001

3.3 Receiver for hollow taper shank, style C

See Figure 2 and Table 2.

For non-specified dimensions, see Figure 1.



 $^{a}~$ Inside edge min. 0,5 mm \times 45 $^{\circ}$ chamfer.

Figure 2

Table 2 — Additional dimensions of style C^a

Dimensions in millimetres

Nominal size		32	40	50	63	80	100			
l_8	\pm 0,1	5	6	7,5	9	12	15			
d_6		Hole diameter to be chosen by the manufacturer.								
^a All other dimensions see style A.										

4 Designation

A receiver for hollow taper shanks in accordance with this part of ISO 12164 shall be designated by:

- a) "Receiver for hollow taper shank"
- b) Reference to this part of ISO 12164, i.e. ISO 12164-2;
- c) "HSK";
- d) Type: A or C;
- e) Nominal size, in millimetres.

EXAMPLE 1 A receiver for hollow taper shanks (HSK) for automatic tool exchange, of type A and with nominal size 50 mm is designated as follows:

Receiver for hollow taper shank ISO 12164-2-HSK-A 50

EXAMPLE 2 A receiver for hollow taper shanks (HSK) for manual tool exchange, of type C and with nominal size 50 mm is designated as follows:

Receiver for hollow taper shank ISO 12164-2-HSK-C 50

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 12164-2:2001 https://standards.iteh.ai/catalog/standards/sist/f8aceedb-601a-4ade-b38d-06f06b21b318/iso-12164-2-2001