

SLOVENSKI STANDARD SIST EN ISO 3382-3:2012

01-april-2012

Akustika - Merjenje parametrov prostorske akustike - 3. del: Velike odprte pisarne (ISO 3382-3:2012)

Acoustics - Measurement of room acoustic parameters - Part 3: Open plan offices (ISO 3382-3:2012)

Akustik - Messung von Parametern der Raumakustik - Teil 3: Großraumbüros (ISO 3382 -3:2012) iTeh STANDARD PREVIEW

Acoustique - Mesurage des paramètres acoustiques des salles - Partie 3: Bureaux ouverts (ISO 3382-3:2012) SIST EN ISO 3382-3:2012

https://standards.iteh.ai/catalog/standards/sist/c5fdf8c1-ce6c-48bc-a6c2-

Ta slovenski standard je istoveten z: EN ISO 3382-3-2012 EN ISO 3382-3:2012

ICS:

17.140.01 Akustična merjenja in blaženje hrupa na splošno Akustika v stavbah. Zvočna 91.120.20 izolacija

Acoustic measurements and noise abatement in general Acoustics in building. Sound insulation

SIST EN ISO 3382-3:2012

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 3382-3

February 2012

ICS 91.120.20

English Version

Acoustics - Measurement of room acoustic parameters - Part 3: Open plan offices (ISO 3382-3:2012)

Acoustique - Mesurage des paramètres acoustiques des salles - Partie 3: Bureaux ouverts (ISO 3382-3:2012)

Akustik - Messung von Parametern der Raumakustik - Teil 3: Durchgehende Räume (ISO 3382-3:2012)

This European Standard was approved by CEN on 14 January 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions. Teh STANDARD PREVIEW

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

SIST EN ISO 3382-3:2012 https://standards.iteh.ai/catalog/standards/sist/c5fdf8c1-ce6c-48bc-a6c2-5d37f7dd7d57/sist-en-iso-3382-3-2012



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

This document (EN ISO 3382-3:2012) has been prepared by Technical Committee ISO/TC 43 "Acoustics" in collaboration with the Technical Committee CEN/TC 126 "Acoustic properties of building elements and of buildings" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2012, and conflicting national standards shall be withdrawn at the latest by August 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANEndersement potice VIEW

The text of ISO 3382-3:2012 has been approved by CEN as a EN ISO 3382-3:2012 without any modification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

INTERNATIONAL STANDARD

ISO 3382-3

First edition 2012-01-15

Acoustics — Measurement of room acoustic parameters —

Part 3: Open plan offices

Acoustique — Mesurage des paramètres acoustiques des salles — Partie 3: Bureaux ouverts **iTeh STANDARD PREVIEW**

(standards.iteh.ai)

SIST EN ISO 3382-3:2012 https://standards.iteh.ai/catalog/standards/sist/c5fdf8c1-ce6c-48bc-a6c2-5d37f7dd7d57/sist-en-iso-3382-3-2012



Reference number ISO 3382-3:2012(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 3382-3:2012</u> https://standards.iteh.ai/catalog/standards/sist/c5fdf8c1-ce6c-48bc-a6c2-5d37f7dd7d57/sist-en-iso-3382-3-2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

ISO 3382-3:2012(E)

Page

Contents

Forew	vord	iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Single number quantities	2
5 5.1 5.2	Measurement conditions Equipment Measurement procedure	
6 6.1 6.2 6.3 6.4	Determination of single number quantities Sound power spectrum of normal speech Spatial decay rate of A-weighted sound pressure level of speech. Distraction and privacy distances Background noise	6 6 9 9
7	Test report	9
Annex	x A (informative) Examples of target values for evaluation of measurement data	11
Anne» Biblio	x B (informative) Relation between speech transmission index and work performance graphy	12 14
	(Stanuar us.lten.al)	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3382-3 was prepared by Technical Committee ISO/TC 43, Acoustics, Subcommittee SC 2, Building acoustics.

ISO 3382 consists of the following parts, under the general title *Acoustics* — *Measurement of room acoustic parameters*:

- Part 1: Performance spaces
- Part 2: Reverberation time in ordinary rooms DARD PREVIEW
- Part 3: Open plan offices

(standards.iteh.ai)

Introduction

The phrase "open plan offices" in the context of this part of ISO 3382 covers offices and similar spaces where a large number of people can work, have a conversation, or concentrate independently in well-defined work stations. In open plan offices, the occupants are affected by activities surrounding them. Insufficient acoustic conditions lead to distraction and a lack of speech privacy. Distraction weakens the ability to concentrate and reduces productivity, especially in tasks requiring cognitive resources. Low speech privacy prevents confidential or partly confidential conversations. Speech can be intrusive for the listener, whereas for the speaker, it can be desirable to avoid involuntary spread of speech of a private nature.

The design of open plan spaces includes careful consideration of the layout of the workstations and mutual arrangement of teams or workgroups. Other factors affecting the acoustical performance of open plan spaces are sound absorption, height of screens and storage units, background noise, degree of workstation enclosure, distance between workstations, and room dimensions. The reverberation time of a room used to be regarded as the predominant indicator of its acoustical properties. However, there is evidence that other types of measurements such as rate of spatial decay of sound pressure levels, speech transmission index and background noise levels are needed for a more complete evaluation. If reverberation time is considered relevant, it should be measured in accordance with ISO 3382-2.

This part of ISO 3382 specifies a measurement method which results in single number quantities indicating the general acoustical performance of open plan offices. The principal aim is good speech privacy between workstations. The measurement method and resulting single number quantities correspond well with perceived acoustic conditions of the worker.

Furniture strongly affects acoustic conditions. Therefore, the measurements are performed only when the room is completely finished, including furniture. Measurement in an unfurnished room does not describe the perceived acoustical conditions. It is also important that the measurements are carried out when people are absent, but with the normal daytime background noise, whether it is caused by ventilation, traffic noise or an artificial masking sound system. If people are present, the background noise level varies strongly with time and the determination of reliable results becomes impossible.

The single number quantities are **designed to** represent the situation where a single person is talking and the rest are silent. Therefore, the measurements are made by using a single loudspeaker. If many people speak simultaneously, the masking is increased and the degree of distraction gets weaker (see Reference [10]). Therefore, the results describe the most distracting situation. However, this part of ISO 3382 can be used to determine the room acoustic quality of, for example, call centres where many speakers are active continuously. In such cases, the sound environment caused by many simultaneous speakers may cause a positive speech masking effect and the results of this part of ISO 3382 may underestimate the perceived speech privacy.