



**SLOVENSKI STANDARD**  
**kSIST-TS prCEN/TS 15883:2009**  
**01-januar-2009**

---

**Stanovanjski aparati na trdna goriva - Emisijska preskusna metoda**

Residential solid fuel burning appliances - Emission test methods

Häusliche Feuerstätten für feste Brennstoffe - Emissionsprüfverfahren

Appareils résidentiels à combustibles solides - Méthodes d'essai des émissions

**Ta slovenski standard je istoveten z: prCEN/TS 15883**

---

**ICS:**

97.100.30      Grelniki na trdo gorivo      Solid fuel heaters

**kSIST-TS prCEN/TS 15883:2009      en**



TECHNICAL SPECIFICATION  
SPÉCIFICATION TECHNIQUE  
TECHNISCHE SPEZIFIKATION

**FINAL DRAFT**  
**prCEN/TS 15883**

November 2008

---

ICS 97.100.30

English Version

## Residential solid fuel burning appliances - Emission test methods

Appareils résidentiels à combustibles solides - Méthodes  
d'essai des émissions

Häusliche Feuerstätten für feste Brennstoffe -  
Emissionsprüfverfahren

This draft Technical Specification is submitted to CEN members for Technical Committee Approval. It has been drawn up by the Technical Committee CEN/TC 295.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

**Warning** : This document is not a Technical Specification. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a Technical Specification.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

## Contents

Page

Foreword .....	3
Introduction .....	4
1 Scope.....	5
2 Normative references .....	5
3 Terms and definitions.....	5
3.1 Definitions.....	5
4 Emission test methods: measurements of total hydrocarbons (THC).....	6
4.1 General procedure .....	6
4.2 Equipment.....	7
4.3 Calculation of organic gaseous compounds (OGC) .....	7
4.4 Uncertainty of measurement .....	8
5 Emissions test methods: measurement of nitrogen oxides.....	8
5.1 General procedure .....	8
5.2 Measuring principles of analysers .....	9
5.2.1 Chemiluminescence method .....	9
5.2.2 Non-dispersive infrared (NDIR) method .....	10
5.2.3 Other methods.....	11
5.3 Calculation method.....	11
A.1 Austrian and German particle test methods .....	12
A.1.1 General.....	12
A.1.2 Dust measuring equipment.....	12
A.2 Norwegian particle test methods .....	13
A.2.1 The test methods for particle emissions .....	14
A.3 UK particle test methods.....	17
A.3.1 Background to legislation and basis of testing .....	17
A.3.2 Measurement of smoke emission from Fuels: summary of the BS 3841 Test Procedure .....	18
A.3.3 Measurement of Smoke Emission from a Smoke Reducing Appliance.....	19
A.3.4 Brief summary of BS 3841 smoke measurement apparatus .....	20
Bibliography .....	26

## Foreword

This document (prCEN/TS 15883:2008) has been prepared by Technical Committee CEN/TC 295 “Residential solid fuel burning appliances”, the secretariat of which is held by BSI.

This document is currently submitted to the Technical Committee Approval.

## Introduction

All the standards of CEN/TC 295 deal with the field of residential heating and cooking appliances burning solid fuels covering the standardization of appliance construction, safety and commissioning requirements and performance requirements (e.g. heat outputs, efficiency and emissions) together with supporting test methods.

This European Technical Specification (TS) deals with methods for the measurements of NO<sub>x</sub>, and OGC/total hydrocarbons emissions and particulate and dust produced by the above mentioned heating and cooking appliances.

For the nitrogen oxides this European Technical Specification describes the 'Chemiluminescence method' and the 'Non-dispersive infrared (NDIR) method'. Besides these two techniques, there are also the 'Non-dispersive ultraviolet (NDUV) method' and the 'Non-extractive (in situ) method' which are described in detail in ISO 10849:1996.

For the total hydrocarbon contents the method is described but the TS does not give any information regarding separate constituents due to the measurements being expressed as equivalents of a reference substance. In this method the measurement is continuous.

Finally, for the measurements of particulate and dust, this European Technical Specification reports, in the Annex, three official methods that coincide respectively with the combined Austrian and German method, the Norwegian method and the UK method currently in force in these countries.

## 1 Scope

This European Technical Specification is applicable to residential heating and cooking appliances burning solid fuels and details methods for the measurements of NO<sub>x</sub>, and OGC/total hydrocarbons emissions and particulate and dust produced by these appliances and is to be used in conjunction with the test methods given in the European Standards covering these appliances.

This European Technical Specification covers the NO<sub>x</sub>, and OGC/total hydrocarbons emission test methods, however it does not cover input data and detailed calculation procedures.

For the particulate and dust emissions test methods, the national documents of those countries that have a test method are reference methods which are summarised in Informative Annex A, whilst those countries that do not have a specific test method, could choose one of these methods listed in the annex.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12815:2001, *Residential cookers fired by solid fuel — Requirements and test methods*

EN 13229:2001, *Inset appliances including open fires fired by solid fuels — Requirements and test methods*

ISO 10849:1996, *Stationary source emissions — Determination of the mass concentration of nitrogen oxides — Performance characteristics of automated measuring systems*

## 3 Terms and definitions

### 3.1 Definitions

For the purposes of this Technical Specification, the following definitions apply.

#### 3.1.1

##### **absorption**

incorporation of a substance into the body of a liquid or solid

#### 3.1.2

##### **calibration**

set of operations that establish the relationship between values of quantities indicated by a measuring instrument or measuring system, or values represented by a material measure or a reference material, and the corresponding values realized by standards

#### 3.1.3

##### **dew point**

temperature at, or below which, the condensation from the gas phase will occur

#### 3.1.4

##### **dust**

particles of various shape, structure and density scattered in the gaseous phase of the flue gas

**prCEN/TS 15883:2008 (E)****3.1.5****gas sample**

portion of gaseous material on which observations can be made in order to provide data on the gaseous material from which it has been removed

NOTE A sample is taken as being representative of the gaseous material if the same observations are supplied on any other samples taken from this gaseous material to furnish the same data within preset intervals.

**3.1.6****line**

gas-tight system of tubing equipped with accessories such as valves, manometers, etc. enabling gas to be transported from one point to another

**3.1.7****measured value**

estimated value of the air quality characteristics derived from an output signal; this usually involves calculations related to the calibration process and conversion to required quantities

**3.1.8****nominal heat output**

declared heat output of an appliance achieved under defined test conditions when burning the specified test fuel in accordance with the European standard relevant to that appliance

**3.1.9****reference material**

material or substance one or more of whose property values is sufficiently homogeneous and well established to be used for the calibration of an apparatus, the assessment of measurement method, or for assigning values to materials

**3.1.10****resolution**

smallest difference between indications, for an identifiable component, of a recording or display device that can be meaningfully distinguished

**3.1.11****sample line**

line provided to remove a representative sample of a gas to be analysed and to transport it from the sample point to the analyzer

**4 Emission test methods: measurements of total hydrocarbons (THC)**

NOTE These methods are intended to determine the total hydrocarbon content in the flue gases from appliances burning solid fuels. The method uses an instrument equipped with a flame ionisation detector (FID). The measurement is continuous. The result obtained is expressed as equivalents of a reference substance, usually methane or propane. The measurement concerns only the total hydrocarbon content and does not give any information of separate constituents. The sampling point should be as described for the measurement section detailed in the test methods appropriate to the appliance as given in the European Standard covering the requirement and testing of these residential heating and cooking appliances burning solid fuels.

**4.1 General procedure**

The measurement is extractive and continuous, i.e. a sample of test gas flow is continuously extracted and is analyzed in a free-standing instrument. The sampling point shall be as described in the test methods detailed in the European Standard appropriate to the appliance being tested. If there is a damper or any other device which favours the lack of homogeneity in the flow, the measuring point shall be moved to a position where the flow is homogenous. The measuring system shall be heated to 195 °C.



## 4.2 Equipment

The measuring system consists of the following components.

- *Instrument with flame ionisation detector, FID.* Measuring range, usually between 0 -10 and 0 - 100 000 ppm. The instrument shall be equipped with a heated filter.
- *Gas probe with a cleaning filter for particulates.* The probe shall consist of a suitable material, such as corrosion resistant steel. The filter shall be heated so that condensation is avoided. This requires a temperature in the filter of 195 °C.
- *Sample line.* The sample line shall be heated to the same temperature as the filter. The inner line shall be of PTFE and be exchangeable. The sample line shall be as short as possible.

## 4.3 Calculation of organic gaseous compounds (OGC)

**4.3.1** This method describes how to calculate the content of organic gaseous compounds expressed in mg/Nm<sup>3</sup> (dry) (at normal condition<sup>1)</sup>) and based upon an oxygen content of 13 % in the exit flue gases. The calculation of total hydrocarbons (THC) content is based on a continuous measurement as described in 4.1.

### 4.3.2 Calculation assumptions

In order to undertake the calculations given in 4.3.3 the following data shall be available:

- total hydrocarbon content in methane or propane equivalents, mean value;
- O<sub>2,m</sub>, CO<sub>2,m</sub>, CO<sub>m</sub> content, mean values;
- carbon, hydrogen and moisture content of the test fuel (C, H and W );
- carbon content of the residue crossing the grate referred to the quantity of the test fuel fired (C<sub>r</sub>).

### 4.3.3 Calculations of organic gaseous compounds

If the OGC content is required in methane equivalents it is determined as follows:

$$C_{OGC} = \frac{(THC \times 12)}{22,36} \times \frac{(21 - 13)}{(21 - O_{2,m})} \times \frac{G_W}{G_D} \quad (1)$$

Alternatively, if the OGC content is required in propane equivalents it is determined as follows:

$$C_{OGC} = \frac{(THC \times 36)}{21,93} \times \frac{(21 - 13)}{(21 - O_{2,m})} \times \frac{G_W}{G_D} \quad (2)$$

where

C<sub>OGC</sub> is the calculated content of organic gaseous compound expressed in mg/Nm<sup>3</sup> dry flue gas at 13 % O<sub>2</sub>;

THC is the measured total hydrocarbon content in the wet flue gas either in ppm methane equivalents or propane equivalents;

O<sub>2,m</sub> is the measured content of oxygen in dry flue gas expressed in % as mean value;

G<sub>w</sub> is the actual specific wet flue gas volume expressed in Nm<sup>3</sup>/kg fuel;

<sup>1)</sup> Referred to 273 K and 1013 mbar.

**prCEN/TS 15883:2008 (E)**

$G_D$  is the actual specific dry flue gas volume expressed in  $\text{Nm}^3/\text{kg}$  fuel.

The actual specific flue gas volume in wet condition is to be calculated as:

$$G_w = \frac{(C - C_r)}{(0,536 \times (CO_{2,m} + CO_m))} + 1,24 \times \frac{(9 \times H + W)}{100} \quad (3)$$

where

- $G_w$  is the specific flue gas volume in wet conditions in  $\text{Nm}^3/\text{kg}$  fuel;
- $C$  is the carbon content of the test fuel in % of mass;
- $C_r$  is the carbon content of the residue referred to the quantity of the test fuel fired in % of mass;
- $CO_{2,m}$  is the measured mean content of carbon dioxide in the dry flue gas in %;
- $CO_m$  is the measured mean content of carbon monoxide in the dry flue gas in %;
- $H$  is the hydrogen content of the test fuel in % of mass;
- $W$  is the moisture content of the test fuel in % of mass.

The actual specific dry flue gas volume,  $G_D$ , is calculated as:

$$G_D = \frac{(C - C_r)}{0,536 \times (C_{2,m} + CO)} \quad (4)$$

where

- $G_D$  is the specific flue gas volume in wet conditions in  $\text{Nm}^3/\text{kg}$  fuel;
- $C$  is the carbon content of the test fuel in % of mass;
- $C_r$  is the carbon content of the residue referred to the quantity of the test fuel fired in % of mass;
- $CO_{2,m}$  is the measured mean content of carbon dioxide in the dry flue gas in %;
- $CO_m$  is the measured mean content of carbon monoxide in the dry flue gas in %;

#### 4.4 Uncertainty of measurement

The uncertainty of the measurement for total hydrocarbon is maximum  $\pm 10$  % of the measured value. The total uncertainty of the calculated OGC value, according to this instruction, is  $\pm 15$  % of the calculated value.

## 5 Emissions test methods: measurement of nitrogen oxides

**NOTE** The methods detailed in 5.2.1 to 5.2.3 are intended to determine the content of nitrogen oxides (NO) in flue gases from small combustion appliances. The methods are continuous. The result obtained is expressed as equivalents of nitrogen dioxide ( $\text{NO}_2$ ). The sampling point should be as described for the measurement section detailed in the test methods as appropriate to the appliance as given in the European Standard covering the requirement and testing of these residential heating and cooking appliances burning solid fuels.

### 5.1 General procedure

The measurement is extractive and continuous, i.e. the test gas flow is extracted from the measuring point by the suction pyrometer and is analysed by an arrangement of a complete measuring system as shown in Figure 1A or Figure 1B. This system is suitable for use with all the analysers described in 5.2. The sampling point and the suction pyrometer shall be as described in the test methods detailed in the European Standard appropriate to the appliance being tested.