



# SLOVENSKI STANDARD

## SIST ISO 16740:2005

01-december-2005

NfU `bUXYcj bYa `a Ygli `È8c`c Yj Ub`Y`ýYglj UYbfbY[ U\_fca Uj ``YVXY ]\ `XYW\ `È  
A YtcXUn`]cbg\_c`\_fca Urc[ fU`c` ]b`gdY\_fcc`hca Yff]`g\_c`XYH`\_W`c`ni dcfUvc`X]Zyb]  
\_UfVUn]XU

Workplace air -- Determination of hexavalent chromium in airborne particulate matter --  
Method by ion chromatography and spectrophotometric measurement using diphenyl  
carbazine

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-a1c1a1b5060c/sist-iso-16740-2005)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-a1c1a1b5060c/sist-iso-16740-2005>  
Air des lieux de travail -- Détermination du chrome hexavalent dans les particules en  
suspension dans l'air -- Méthode par chromatographie ionique et détection  
spectrophotométrique avec diphényl carbazine

**Ta slovenski standard je istoveten z: ISO 16740:2005**

### **ICS:**

13.040.30 Kakovost zraka na delovnem mestu Workplace atmospheres  
mestu

**SIST ISO 16740:2005**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>

# INTERNATIONAL STANDARD

**ISO**  
**16740**

First edition  
2005-02-01

---

---

## Workplace air — Determination of hexavalent chromium in airborne particulate matter — Method by ion chromatography and spectrophotometric measurement using diphenyl carbazide

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

*Air des lieux de travail — Détermination du chrome hexavalent dans les  
particules en suspension dans l'air — Méthode par chromatographie  
ionique et détection spectrophotométrique avec diphényl carbazide*

SIST ISO 16740:2005

[https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-  
ac1eaf85660e/sist-iso-16740-2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)



Reference number  
ISO 16740:2005(E)

© ISO 2005

**ISO 16740:2005(E)****PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 16740:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword.....	v
Introduction .....	vi
1 Scope.....	1
2 Normative references .....	1
3 Terms and definitions.....	2
3.1 General definitions.....	2
3.2 Particle size fraction definitions.....	3
3.3 Sampling definitions.....	3
3.4 Analytical definitions .....	4
3.5 Statistical terms .....	5
4 Principle .....	6
5 Reactions .....	7
6 Requirement .....	7
7 Reagents .....	7
8 Apparatus.....	10
8.1 Sampling equipment.....	10
8.2 Laboratory apparatus .....	12
9 Occupational exposure assessment.....	15
9.1 General.....	15
9.2 Personal sampling .....	15
9.3 Static sampling.....	16
9.4 Selection of measurement conditions and measurement pattern.....	16
10 Sampling method .....	17
10.1 Preliminary considerations.....	17
10.2 Preparation for sampling.....	18
10.3 Sampling position .....	19
10.4 Collection of samples .....	19
10.5 Transportation.....	20
11 Analysis.....	21
11.1 Analytical requirements .....	21
11.2 Preparation of solutions for determination of soluble hexavalent chromium compounds .....	22
11.3 Preparation of solutions for determination of insoluble hexavalent chromium compounds .....	23
11.4 Instrumental analysis .....	25
11.5 Estimation of detection and quantification limits.....	27
11.6 Quality control .....	27
11.7 Measurement uncertainty.....	28
12 Expression of results.....	28
13 Method performance.....	29
13.1 Sample collection and stability .....	29
13.2 Hotplate extraction.....	29
13.3 Ultrasonic extraction .....	29
13.4 Interferences.....	29
14 Special cases.....	30
14.1 Spray-painting .....	30

## ISO 16740:2005(E)

14.2	Action to be taken when particles have become dislodged from the filter during transportation .....	30
15	Test report .....	30
15.1	Test record .....	30
15.2	Laboratory report .....	31
Annex A	(informative) Temperature and pressure corrections .....	32
Annex B	(informative) Background on methods for determination of hexavalent chromium in air and guidance on their use .....	34
Bibliography	.....	38

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16740 was prepared by Technical Committee ISO/TC 146, *Air quality*, Subcommittee SC 2, *Workplace atmospheres*.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>

## Introduction

The health of workers in many industries is at risk through exposure by inhalation of hexavalent chromium compounds. Industrial hygienists and other public health professionals need to determine the effectiveness of measures taken to control workers' exposure, and this is generally achieved by making workplace air measurements. This International Standard has been published in order to make available a method for making valid exposure measurements for hexavalent chromium compounds used in industry. It will be of benefit to agencies concerned with health and safety at work; industrial hygienists and other public health professionals; analytical laboratories; industrial users of hexavalent chromium compounds and their workers.

It has been assumed in the drafting of this International Standard that the execution of its provisions, and the interpretation of the results obtained, is entrusted to appropriately qualified and experienced people.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>



# Workplace air — Determination of hexavalent chromium in airborne particulate matter — Method by ion chromatography and spectrophotometric measurement using diphenyl carbazide

## 1 Scope

This International Standard specifies a method for the determination of the time-weighted average mass concentration of hexavalent chromium in workplace air.

Separate sample preparation methods are specified for the extraction of soluble and insoluble hexavalent chromium. The method for insoluble hexavalent chromium can also be used to prepare samples for determination of total hexavalent chromium, if desired.

This International Standard is applicable to the personal sampling of the inhalable fraction of airborne particles, as defined in ISO 7708, and to static (area) sampling. The analytical method is applicable to the determination of masses of 0,01 µg to 10 µg of hexavalent chromium per sample, without dilution.

The concentration range of hexavalent chromium in air for which the measuring procedure is applicable is determined by the sampling method selected by the user (see 10.1). For a 1 m<sup>3</sup> air sample, without sample dilution, the working range is approximately 0,01 µg·m<sup>-3</sup> to 10 µg·m<sup>-3</sup>.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 648, *Laboratory glassware — One-mark pipettes*

ISO 1042, *Laboratory glassware — One-mark volumetric flasks*

ISO 3585, *Borosilicate glass 3.3 — Properties*

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

ISO 7708:1995, *Air quality — Particle size fraction definitions for health-related sampling*

ISO 8655-1, *Piston-operated volumetric apparatus — Part 1: Terminology, general requirements and user recommendations*

ISO 8655-2, *Piston-operated volumetric apparatus — Part 2: Piston pipettes*

ISO 8655-5, *Piston-operated volumetric apparatus — Part 5: Dispensers*

ISO 8655-6, *Piston-operated volumetric apparatus — Part 6: Gravimetric methods for the determination of measurement error*

EN 13205, *Workplace atmospheres — Assessment of performance of instruments for measurement of airborne particle concentrations*

## ISO 16740:2005(E)

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1 General definitions

##### 3.1.1

##### **chemical agent**

any chemical element or compound, on its own or admixed, as it occurs in the natural state or as produced, used or released, including release as waste by any work activity, whether or not produced intentionally and whether or not placed on the market

[EN 1540 <sup>[1]</sup>]

##### 3.1.2

##### **breathing zone**

(general definition) space around the worker's face from where he or she takes his or her breath

##### 3.1.3

##### **breathing zone**

(technical definition) hemisphere (generally accepted to be 0,3 m in radius) extending in front of the human face, centred on the midpoint of a line joining the ears; the base of the hemisphere is a plane through this line, the top of the head and the larynx

NOTE 1 This definition is not applicable when respiratory protective equipment is used.

NOTE 2 Adapted from EN 1540 <sup>[1]</sup>.

##### 3.1.4

##### **exposure**

(by inhalation) situation in which a chemical agent is present in air which is inhaled by a person

##### 3.1.5

##### **measuring procedure**

procedure for sampling and analysing one or more chemical agents in the air and including storage and transportation of the sample

##### 3.1.6

##### **operating time**

period during which a sampling pump can be operated at specified flow rate and back pressure without recharging or replacing the battery

[EN 1232 <sup>[2]</sup>]

##### 3.1.7

##### **time-weighted average concentration**

##### **TWA concentration**

concentration of a chemical agent in the atmosphere, averaged over the reference period

NOTE A more detailed discussion of TWA concentrations is available in Reference [3].

##### 3.1.8

##### **limit value**

reference figure for concentration of a chemical agent in air

NOTE An example is the Threshold Limit Value<sup>®</sup> (TLV) for a given substance in workplace air, as established by the American Conference of Government Industrial Hygienists (ACGIH) <sup>[3]</sup>.

### 3.1.9

#### **reference period**

specified period of time stated for the limit value of a specific chemical agent

NOTE Examples of limit values for different reference periods are short-term and long-term exposure limits, such as those established by the ACGIH [3].

### 3.1.10

#### **workplace**

defined area(s) in which the work activities are carried out

[EN 1540 [1]]

## 3.2 Particle size fraction definitions

### 3.2.1

#### **inhalable convention**

target specification for sampling instruments when the inhalable fraction is of interest

[ISO 7708]

### 3.2.2

#### **inhalable fraction**

mass fraction of total airborne particles which is inhaled through the nose and mouth

NOTE The inhalable fraction depends on the speed and direction of air movement, on breathing rate and other factors.

[ISO 7708]

### 3.2.3

#### **respirable convention**

target specification for sampling instruments when the respirable fraction is of interest

[ISO 7708]

### 3.2.4

#### **respirable fraction**

mass fraction of inhaled particles penetrating to the unciliated airways

[ISO 7708]

### 3.2.5

#### **total airborne particles**

all particles surrounded by air in a given volume of air

NOTE Because all measuring instruments are size-selective to some extent, it is often impossible to measure the concentration of total airborne particles.

[ISO 7708]

## 3.3 Sampling definitions

### 3.3.1

#### **personal sampler**

device attached to a person that samples air in the breathing zone

[EN 1540 [1]]

**ISO 16740:2005(E)****3.3.2****personal sampling**

process of sampling carried out using a personal sampler

[EN 1540 <sup>[1]</sup>]

**3.3.3****sampler**

device for collecting airborne particles

NOTE Instruments used to collect airborne particles are frequently referred to by a number of other terms, e.g. sampling heads, filter holders, filter cassettes, etc.

**3.3.4****static sampling****area sampling**

process of air sampling carried out in a particular location

**3.3.5****static sampler****area sampler**

device, not attached to a person, used in static sampling

**3.4 Analytical definitions****3.4.1****blank solution**

solution prepared by taking a reagent blank, laboratory blank or field blank through the same procedure used for sample dissolution

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

[SIST ISO 16740:2005](https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005)

**3.4.2****calibration blank solution**

calibration solution prepared without the addition of any working standard solution

<https://standards.iteh.ai/catalog/standards/sist/79a41619-d323-42c0-b45e-ac1eaf85660e/sist-iso-16740-2005>

NOTE The concentration of the analyte(s) of interest in the calibration blank solution is taken to be zero.

**3.4.3****calibration solution**

solution, prepared by dilution of the working standard solution, containing the analyte(s) of interest at a concentration that is suitable for use in calibration of the analytical instrument

**3.4.4****field blank**

filter that is taken through the same handling procedure as a sample, except that it is not used for sampling, but is loaded into a sampler, transported to the sampling site and then returned to the laboratory for analysis

**3.4.5****laboratory blank**

unused filter, taken from the same batch used for sampling, that does not leave the laboratory

**3.4.6****linear dynamic range**

range of concentrations over which the calibration curve for an analyte is linear

NOTE The linear dynamic range extends from the detection limit to the onset of calibration curvature.

**3.4.7****reagent blank**

all reagents used in sample dissolution, in the same quantities used for preparation of laboratory blank, field blank and sample solutions

**3.4.8****sample dissolution**

process of obtaining a solution containing all analytes of interest from a sample, which might or might not involve complete dissolution of the sample

**3.4.9****sample preparation**

all operations carried out on a sample, after transportation and storage, to prepare it for analysis, including transformation of the sample into a measurable state, if necessary

**3.4.10****sample solution**

solution prepared from a sample by the process of sample dissolution

NOTE A sample solution might need to be subjected to further operations, e.g. dilution, in order to produce a test solution that is ready for analysis.

**3.4.11****test solution**

blank solution or sample solution that has been subjected to all operations required to bring it into a state in which it is ready for analysis, e.g. dilution

NOTE The blank test solution is the blank solution and the sample test solution is the sample solution, if these solutions are not subjected to any further operations before analysis.

**3.4.12****working standard solution**

solution, prepared by dilution of the stock standard solution, that contains the analyte(s) of interest at a concentration(s) that is better suited to preparation of calibration solutions than the concentration(s) of the analyte(s) in the stock standard solution(s)

**3.5 Statistical terms****3.5.1****analytical recovery**

ratio of the mass of analyte measured in a sample when it is analysed to the known mass of analyte in that sample, expressed as a percentage

**3.5.2****bias**

consistent deviation of the results of a measurement process from the true value of the air quality characteristic itself

[ISO 6879 [4]]

**3.5.3****overall uncertainty**

(of a measuring procedure or of an instrument) quantity used to characterise as a whole the uncertainty of a result given by an apparatus or measuring procedure

NOTE Uncertainty is expressed, as a percentage, by a combination of bias and precision, usually according to the formula:

$$\frac{|\bar{x} - x_{\text{ref}}| + 2s}{x_{\text{ref}}} \times 100$$