



SLOVENSKI STANDARD

SIST ES 202 553 V1.2.1:2009

01-september-2009

Metode za preskušanje in specificiranje (MTS) - TPLan: Zapis za izražanje namenov preskušanja

Methods for Testing and Specification (MTS) - TPLan: A notation for expressing Test Purposes

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ES 202 553 Version 1.2.1

SIST ES 202 553 V1.2.1:2009
<https://standards.iteh.ai/catalog/standards/sist/61bdc326-69bf-462e-8027-be55516af486/sist-es-202-553-v1-2-1-2009>

ICS:

33.040.01

Telekomunikacijski sistemi
na splošno

Telecommunication systems
in general

SIST ES 202 553 V1.2.1:2009

en

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST ES 202 553 V1.2.1:2009

<https://standards.iteh.ai/catalog/standards/sist/61bde326-b9bf-462e-8027-be55516af486/sist-es-202-553-v1-2-1-2009>

ETSI ES 202 553 V1.2.1 (2009-06)

ETSI Standard

Methods for Testing and Specification (MTS); TPlan: A notation for expressing Test Purposes

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ES 202 553 V1.2.1:2009](https://standards.iteh.ai/catalog/standards/sist/61bde326-b9bf-462e-8027-be55516af486/sist-es-202-553-v1-2-1-2009)

<https://standards.iteh.ai/catalog/standards/sist/61bde326-b9bf-462e-8027-be55516af486/sist-es-202-553-v1-2-1-2009>



Reference

RES/MTS-00100[2]-TPLan

Keywords

methodology, testing, TTCN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ES 202 553 V1.2.1:2009

<https://standards.iteh.ai/catalog/standards/sist/61bde326-b9bf-462e-8027-be55516a454d/sist-es-202-553-v1-2-1-2009>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions and abbreviations.....	7
3.1 Definitions.....	7
3.2 Abbreviations	7
4 Introduction	8
4.1 TPLan: A formal notation for expressing test purposes	8
4.2 Extensibility of TPLan	8
4.3 The Test Suite Structure	8
4.4 Areas of application.....	8
4.5 Limitations of TPLan	9
5 TPLan keywords, comments and identifiers	9
5.1 TPLan keywords	9
5.2 Comments.....	10
5.3 TPLan identifiers.....	10
5.4 Uniqueness of identifiers.....	11
5.5 Including files.....	11
6 TSS Header	11
6.1 Standard TSS header entries.....	11
6.2 User-defined TSS Header entries.....	12
7 External references	12
8 User definitions	13
8.1 User-defined words	13
8.2 User-defined headers.....	13
8.3 User-defined test entities	13
8.4 User-defined events and parameters.....	13
8.5 User-defined values.....	14
8.6 User-defined units	14
8.7 User-defined conditions	15
8.8 Constraining keywords to specific contexts	15
9 Groups	16
10 TP Header.....	17
10.1 Standard TP Header entries	17
10.2 User-defined TP Header entries	18
11 TP body	18
11.1 TP body structure	18
11.2 TP pre-conditions	19
11.3 TP stimuli	19
11.4 TP responses.....	20
11.5 Precedence of TPLan statements.....	20
11.6 Temporal ordering of TPLan statements	20
11.7 Using user-defined test entities, conditions and words.....	21
11.8 Glue words and readability.....	21
Annex A (normative): The TPLan Grammar	22

A.1	Syntactic Rules	22
A.2	TPLan EBNF Productions	22
Annex B (informative): Use of the IPT Testing Framework		27
B.1	IPT naming conventions	27
B.1.1	IPT identifiers	27
B.1.2	The Requirements Identifier	27
B.1.3	The Configuration Identifier	27
B.1.4	The Test Purpose Identifier	27
B.1.5	The Test Case Identifier	27
B.1.6	The Test Description Identifier	28
B.2	IPT cross references	28
B.2.1	References to the Requirements Catalogue	28
B.2.2	References to test configurations	28
Annex C (informative): A guide to using TPLan in a communications testing environment		29
C.1	General considerations	29
C.1.1	Introduction	29
C.1.2	Structure of a TPLan specification	29
C.1.3	Choosing a suitable text editor	30
C.2	The TPLan header	31
C.2.1	TSS Header	31
C.2.2	Cross-references	31
C.2.2.1	Requirement sources	31
C.2.2.2	Configurations	31
C.2.3	User-defined extensions to TPLan	32
C.2.3.1	General layout of user definitions	32
C.2.3.2	Header fields	33
C.2.3.3	Entities	33
C.2.3.4	Events	34
C.2.3.5	Conditions	34
C.2.3.6	Values	35
C.2.3.7	Units	35
C.2.3.8	Keywords	35
C.2.3.9	Syntactical context	36
C.3	Test Purposes	36
C.3.1	Grouping TPs	36
C.3.1.1	TP header	37
C.3.1.2	TP Body	38
C.3.1.2.1	Preconditions	38
C.3.1.2.2	Stimulus and response	38
C.3.1.2.2.1	The when and then construct	38
C.3.1.2.2.2	Identifying the contents of message events	39
C.3.1.2.2.3	Interactions with the user	40
C.3.1.2.2.4	Establishing the order of a sequence of events	40
C.3.1.2.2.5	The "do nothing" response	41
Annex D (informative): Some communications testing examples		42
D.1	IPv6 Interoperability Test Purposes	42
D.2	QSIG Interoperability Test Purposes	46
D.3	ISDN Conformance Test Purposes	49
Annex E (informative): Bibliography		51
History		52

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Methods for Testing and Specification (MTS).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ES 202 553 V1.2.1:2009
<https://standards.iteh.ai/catalog/standards/sist/61bde326-b9bf-462e-8027-be55516af486/sist-es-202-553-v1-2-1-2009>

1 Scope

The present document specifies the syntax and use of a notation for the definition of Test Purposes, TPLan. This notation provides a structure and a common set of English keywords for the specification of Test Purposes. The basic notation is oriented towards testing of reactive, black-box communication systems and uses terminology derived from ISO/IEC 9646-1 [3]. However, facilities are also included to allow users to extend the notation with application-specific keywords of their own.

The use of TPLan as the means of specifying Test Purposes is optional but, if it is used, the requirements specified in the present document shall be met.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- | | |
|-----|--|
| [1] | ETSI ES 201 873-1: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 1: TTCN-3 Core Language". |
| [2] | ETSI EG 202 568 (V1.1.3): "Methods for Testing and Specification (MTS); Internet Protocol Testing (IPT); Testing: Methodology and Framework". |
| [3] | ISO/IEC 9646-1: "Information Technology - Open Systems Interconnection - Conformance Testing Methodology and Framework - Part 1: General concepts". |
| [4] | ISO/IEC 9646-2: "Information Technology - Open Systems Interconnection - Conformance Testing Methodology and Framework - Part 2: Abstract Test Suite specification". |

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

event: something observable (measurable) at a given place and time

NOTE: The cause of a stimulus or the result of a response.

notation: textual means of representing ideas

programming language: artificial language that can be used to control the behaviour of a machine

test case: specification of the actions required to achieve a specific test purpose, starting in a stable testing state, ending in a stable testing state and defined in either natural language for manual operation or in a machine-readable language (such as TTCN-3) for automatic execution

test description: systematic specification of the test steps (generally in tabulated text) that must be taken to reach a specific test verdict

test purpose: description of a well-defined objective of testing, focussing on a single interoperability requirement or a set of related interoperability requirements

test suite structure: logical grouping of test purposes or test cases which should be both relevant and convenient

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EBNF	Extended Backus-Naur Form
EUT	Equipment Under Test
ICS	Implementation Conformance Statement
IETF	International Engineering Task Force
IP	Internet Protocol
IPT	Internet Protocol Testing
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
QE	Qualified Equipment
QSIG	Q interface Signalling protocol
RFC	Request For Comments

NOTE: IETF terminology for a draft standard.

RQ	ReQuirement
TC	Test Case
TD	Test Description
TP	Test Purpose
TPAn	Test Purpose Notation
TSS	Test Suite Structure
TTCN-3	Testing and Test Control Notation edition 3

4 Introduction

4.1 TPLan: A formal notation for expressing test purposes

ISO/IEC 9646-1 [3] and ISO/IEC 9646-2 [4] recommend that test specifications include a concise and unambiguous description of each test which focuses on its purpose. These Test Purposes, or TPs, define **what** is to be tested rather than **how** the testing is performed. The TPs are based on the **requirements** identified in the relevant standard (or standards) from which the test specification is derived. The detailed coding of each Test Purpose is specified in a Test Case. Often Test Cases, or TCs, are written in a test specification language such as TTCN-3 [1]. The specification of Test Cases is outside the scope of the present document.

Generally, Test Purposes are written in prose (possibly displayed in a tabular format). There is considerable benefit to be gained by having all TPs written in a similar and consistent way. With this in mind, a simple, structured notation called TPLan has been developed for the expression of TPs. TPLan is defined with a minimal set of test-oriented keywords but with the capability that permits users to define extensions to the notation. is an example of how TPLan can be extended into a specific application area; in this case, telecommunications.

The benefits of using TPLan are:

- consistency in test purpose descriptions - less room for misinterpretation;
- clear identification of the TP pre-conditions, test body, and verdict criteria;
- automatic syntax checking and syntax highlighting in text editors;
- a basis for a TP transfer format and representation in tools.

4.2 Extensibility of TPLan

TPLan provides a framework for a consistent representation (format, layout, structure and logical ordering) and a consistent use of words and patterns of words for expressing TPs. This is achieved without unnecessarily restricting the expressive power of pure prose.

TPLan allows the use of keywords in combination with free-text strings (enclosed by single quotes). Thus, the TP writer has considerable freedom of expression in the use of unstructured text between the keywords.

The basic set of pre-defined TPLan keywords has been kept to a minimum. These keywords are mainly concerned with providing structure to the TPs. The intention is that this set of keywords is extended by the user for specific testing applications through the use of user-defined keywords (see clause 8) which can be checked by automatic tools for consistency and, to some extent, correctness.

4.3 The Test Suite Structure

Test Purposes should be grouped in a tree-like structure. This structure is known as the Test Suite Structure, or TSS. The combination of structure and Test Purposes is known as the TSS&TP [3].

The general composition of a TPLan TSS&TP is as follows:

```
TSS Header           -- title, author, version etc.
Cross References     -- references to base standards, configuration descriptions etc.
Definitions         -- user-defined words, events, test entities, conditions, headers etc.
TSS Groups          -- if any and possibly nested
Test Purposes       -- contained in the groups (if any)
```

4.4 Areas of application

TPLan is not specific to a particular type or area of testing. The fundamental set of predefined TPLan keywords is oriented towards conformance and interoperability testing (keywords such as **IUT**, **TESTER** and **TD**) but the extensibility of the language means that the user can adapt TPLan to a wide range of testing contexts.

4.5 Limitations of TPLan

The TPLan grammar provides limited syntax checking and an enhanced visual representation of the TP in, for example, a syntax sensitive text editor. However, in order to retain expressive power, TPLan is only loosely defined in that no strict relation between certain words (especially the user-defined words) is specified. Thus, it is possible to write nonsensical constructions if care is not taken. Of course, appropriate tools may be able to identify such constructions but there are no constructs for doing this explicitly in the notation.

5 TPLan keywords, comments and identifiers

5.1 TPLan keywords

Only those words listed in table 1 shall be considered to be valid TPLan keywords.

Table 1: TPLan keywords

TSS header keywords	
author	Author
date	Date
title	Title
TSS	tss
version	Version
Cross-references keywords	
xref	Xref
Definitions keywords	
condition	Condition
context	Context
def	Def
entity	Entity
event	Event
header	Header
value	Value
unit	Unit
word	Word
TP grouping keywords	
end	End
group	Group
objective	Objective
TP header keywords	
config	Config
id	Id
ref	Ref
role	Role
RQ	rq
summary	Summary
TC	tc
TD	td
TP	tp
TP body keywords	
ensure	Ensure
that	That
with	With
when	When
then	Then
Test entity keywords	
IUT	iut
TESTER	tester

TPLan glue words	
a	A
an	An
as	As
in	In
is	Is
no	No
of	Of
the	The
Logical words	
and	And
not	Not
or	Or
Stimulus and Response words	
receives	Receives
sends	Sends
Data-related words	
containing	Containing
indicating	Indicating
Direction-related words	
from	From
to	To
Time- and order-related words	
after	After
before	Before
unordered	Unordered
within	Within

5.2 Comments

Comments shall be introduced by the string "--" and terminated at the end of the same line.

5.3 TPLan identifiers

Letters, numbers and special characters may be used in a TPLan identifier, as follows:

- alphabetic:
 - a to z;
 - A to Z.
- Numeric:
 - 0 to 9.
- special characters:
 - |._-&%\$*@?!></\#.

Typical TPLan identifiers are TP identifier, event names, cross reference identifiers and requirements identifiers. For example:

```
MyTSS&TP
TP_UMTS_0789_01
RQ_001_789
REQ3952.Arev2
CONF/HOST/INVALID/#75
CF_MOB_02
PICS_c.2
```

A TPLan identifier shall not contain any white space (e.g. tabs or spaces).

NOTE: In certain contexts it can be desirable to overlay TPLan with an additional level of checking related to a particular methodology or naming convention. Generally, such overlays are outside the scope of the present document. However, the ETSI IPT Testing Framework [2] includes naming rules for TPs and other identifiers. These conventions are summarized in annex B.

5.4 Uniqueness of identifiers

All user-defined words, headers, entities, conditions and events shall be unique in the scope of one TSS&TP. Parameter names of events shall be unique in the scope of the list in which they are declared.

No user-defined name shall be the same as any pre-defined TPLan keyword.

5.5 Including files

TPLan supports a limited form of file inclusion. This shall be indicated by the pre-processing directive, **#include**, followed by the location of the included file enclosed in quotes. TPLan does not define the form of this location reference. Typical locations may be a file path, reference to an ETSI standard, an object identifier or a URL. For example:

```
#include 'root/MyTPLan/MyDefs.txt'
#include 'root/MyTPLan/MyTPs.txt'
```

The include statement shall only be used to include definitions (see clause 8) or complete test purposes comprising the test purpose header and body (see clauses 10 and 11). Thus, the included file shall follow the syntax for definitions and test purposes as defined in annex A.

6 TSS Header

6.1 Standard TSS header entries

A TPLan specification (i.e. a TSS&TP) shall begin with the following headers (though not all entries are mandatory, see annex A):

- TSS identifier (mandatory):
 - The keyword **TSS** followed by the formal identifier of the TSS&TP.
- Title (optional):
 - The keyword **title** followed by the name of the TSS&TP as quoted free text.
- Version (optional):
 - The keyword **version** followed by the version number as any number of numeric values separated by dots (".").
- Date (optional):
 - The keyword **date** followed by three numeric values separated by dots ("."), forward slash ("/") or dash ("-"). The following examples are all valid date entries:
 - 01-12-2007.
 - 1.12.07.
 - 31/5/2007.
 - 05-31-07.
- Author (optional):
 - The keyword **author** followed by the document author(s) as quoted free text.

Each TSS header keyword shall be followed by a colon (":").

A complete TSS&TP header:

```
TSS      : UMTS_TSS
title    : 'My TSS&TP as an example'
version  : 1.0      -- other examples may be 1.0.0 or 11.01
date     : 29.11.2004 -- could also be written as 29/11/2004 or 29-11-2004
author   : 'ETSI PTCC'
```

6.2 User-defined TSS Header entries

Additional user-defined TSS&TP headers may be included with the standard headers. A user-defined TSS header may comprise one or more defined header words, followed by a list of one or more identifiers separated by commas, or a quoted string separated by a colon (see clause 8.2). For example:

```
TSS      : UMTS_TSS
title    : 'My TSS&TP as an example'
version  : 1.0
date     : 29.11.2004
author   : 'ETSI PTCC'
status   : 'Public'      -- user-defined TSS header
```

A user-defined header may also use the predefined keyword **ref**. For example:

```
PICS ref : 'Release 7'
```

A header (either predefined or user-defined) shall not appear more than once in a TSS.

7 External references

References to external sources of information shall be made using the **xref** keyword followed by an identifier and a list of the external sources. Examples of the use of the **xref** keyword are as follows:

- References to base standards or other sources from which the TPs have been derived. For example:

```
xref BaseStandards {TS123456-1, TS789345}
```

In the case where a PICS [3] is used the reference might be:

```
xref PICS {TS123456-1, TS123456-2}
```

The TPLan syntax allows reference to be made in any appropriate form such as Object identifiers or URLs. For example:

```
xref MyWebDocs {www.tplan.info}
```

- References to explicit test configurations. For example:

```
xref TestConfig1 {3GPPSpecXYZ_AnnexA_page10_fig1}
```
- The list of configuration sources may include references to file names as well as or instead of document information, thus:

```
xref TestConfig2 {OurProjectConfigs.pdf}
```

NOTE: The identifiers associated with **xref** statements could be used by software tools to check for consistency within the specifications of test purposes. For example, a tool could check that TPs refer only to configurations that have been previously declared in **xref** statements.

