

---

---

**Diesel engines — High-pressure fuel  
injection pipe end-connections with 60°  
female cone**

*Moteurs diesels — Raccords finaux à cône femelle de 60° pour lignes  
d'injection de carburant haute pression*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 2974:2000](https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000)

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>



Reference number  
ISO 2974:2000(E)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 2974:2000

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 2974 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles*.

This fifth edition cancels and replaces the fourth edition (ISO 2974:1994), which has been technically revised.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

[ISO 2974:2000](https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000)

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 2974:2000

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>

# Diesel engines — High-pressure fuel injection pipe end-connections with 60° female cone

## 1 Scope

This International Standard specifies the dimensional requirements of high-pressure pipe end-connections for diesel (compression ignition) engine fuel injection equipment.

It is applicable to externally threaded end-connections of types 1 and 2 having a 60° female cone (see Figures 1 to 3), as well as to the pipe end assemblies of high-pressure fuel injection pipes with diameters of up to and including 12 mm (see Figure 4).

## 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 261:1998, *ISO general-purpose metric screw threads — General plan*.

ISO 3508:1976, *Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262*.

ISO 7876-4, *Fuel injection equipment — Vocabulary — Part 4: High-pressure pipes and end-connections*.

## 3 Requirements

### 3.1 Dimensions and tolerances

Figures 1 and 2 indicate the basic requirements for the end-connection at the fuel injector and fuel injection pump to allow interchangeability for high-pressure fuel injection pipe assemblies.

The 60° female cone and its relationship to the external thread of the end-connection shall meet the requirements of Figure 1. However, variations at the smaller end of the female cone as shown in Figure 3 are acceptable.

Dimensions and tolerances are given in Table 1. Unspecified details are left to the manufacturer's choice.

With reference to dimension  $T$  in Figures 1 and 2, the external thread may be of either type 1 or type 2. However, it shall be possible to screw the GO-gauge for the thread up to the plane specified by dimension  $T$  for both types.

Figure 4 identifies the pipe end assembly dimensions that are important to sealing — those normally on the leading edge of the sealing face of the connection end (see also 3.2).

### 3.2 Materials

The specification of material and heat treatment shall be made according to intended use.

To ensure that deformation takes place at the sealing face of the connection end, the connection end shall be softer than the female cone of the end-connection of the fuel injection pump or the fuel injector.

### 4 Designation


An end-connection conforming to this International Standard shall be designated by the following elements, in the order given:

- a) reference to this International Standard;
- b) the shape, in accordance with Figure 3;
- c) the pipe outside diameter, in millimetres;
- d) the thread designation, in accordance with ISO 261.

EXAMPLE An end-connection of shape A, of pipe outside diameter 10 mm, with an M22 × 1,5 thread is designated:


**ISO 2974 A 10 - M22 × 1,5**

Dimensions in millimetres, surface roughness values in micrometres



- a Chamfer to root of thread.
- b Female sealing face.
- c See Figure 3

Figure 1 — End-connection — Type 1



NOTE All dimensions and specifications other than<sup>a)</sup>, as for type 1.


<sup>a</sup> Undercut to ISO 3508.

**Figure 2 — End-connection — Type 2**


**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 2974:2000

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>



a) Shape A




b) Shape B

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 2974:2000

<https://standards.iteh.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af23e40e8f/iso-2974-2000>




c) Shape C

<sup>a</sup> Reference diameter plane.

Figure 3 — Shapes of detail X on female cones, types 1 and 2





- a The connection end bore entrance configuration shall be so chosen that, after final assembly, the pipe inside diameter is not reduced.
- b  $58^\circ \pm 1^\circ$  included angle (other shapes by agreement)
- c Design of the shoulder of connection end and the connector nut shall be agreed between customer and manufacturer.
- d Connection end sealing face
- e Chamfer to root of threads

**ITeh STANDARD PREVIEW**

**(standards.itech.ai)**  
**Figure 4 — Pipe end assembly**

ISO 2974:2000

<https://standards.itech.ai/catalog/standards/sist/c93cb7da-e9f9-46ed-97d6-31af03cd0af4/iso-2974-2000>  
**Table 1**

Dimensions in millimetres

Tube outside diameter	Thread <sup>a</sup> <i>A</i>	Reference diameter <i>S</i>	$F_1^b$ $\pm 0,1$	$F_3^b$ max.	$E$ $+0,3_0$	$P$ $\pm 0,5$	$G$ $+0,5_0$	$L$ max.	$T$ min.
4,5	M10 × 1,25 M12 × 1,5	5	1,12 to 2,24	—	0,8	7	0,5	7	10
6	M12 × 1,5 M14 × 1,5	6,5	1,5 to 3	6,1	0,8	9	0,8	8	11
8	M16 × 1,5 M18 × 1,5 M22 × 1,5	8,5	2 to 4	7,3	2,6	11,5	0,9	11	16,5
10	M20 × 1,5 M22 × 1,5 M24 × 1,5	10,5	2,5 to 5	9,3	2,6	13,5	0,9	12,5	18
12	M22 × 1,5 M26 × 1,5	12,5	3 to 5	10,3	2,6	15,5	1,8	15,5	21

<sup>a</sup> Tolerance classes of threads: 6g for externally threaded end-connection; 6H for connector nuts.

<sup>b</sup> Dimension  $F_1$  shall be adapted to the inside diameter of the pipe for the sake of optimum flow conditions. If required, for instance for edge filters, application of dimension  $F_3$  is allowed.