

First edition
1999-11-01

Corrected and reprinted
2000-02-15

**Identification cards — Integrated circuit(s)
cards with contacts —**

Part 10:

**Electronic signals and answer to reset for
synchronous cards**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Cartes d'identification — Cartes à circuit(s) intégré(s) à contacts —

*Partie 10: Signaux électroniques et réponse à la mise à zéro des cartes
synchrones*

[ISO/IEC 7816-10:1999](https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcda01fe0d7/iso-iec-7816-10-1999)

<https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcda01fe0d7/iso-iec-7816-10-1999>

Reference number
ISO/IEC 7816-10:1999(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 7816-10:1999](https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcda01fe0d7/iso-iec-7816-10-1999)

<https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcda01fe0d7/iso-iec-7816-10-1999>

© ISO/IEC 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Term and definition	1
4 Symbols and abbreviated terms.....	2
5 Electrical characteristics of the contacts	2
5.1 Contact assignments.....	2
5.2 Voltage and current values.....	2
5.3 Card type selection.....	2
6 Reset of the card.....	2
6.1 Synchronous card type 1	2
6.2 Synchronous card type 2	3
7 Answer-to-Reset	3
7.1 Clock frequency and bit rate.....	3
7.2 Structure of the Answer-to-Reset header.....	3
7.3 Timing of the header	3
7.3.1 Synchronous card type 1	3
7.3.2 Synchronous card type 2	4
7.4 Data content of the header	4
8 Deactivation of the contacts.....	4
Annex A (informative) Example of data structure introduced by H3 = '10'	6
Annex B (informative) Example of coding of H1 and H2	7

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO/IEC 7816 may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 7816-10 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Identification cards and related devices*.

ISO/IEC 7816 consists of the following parts, under the general title *Identification cards — Integrated circuit(s) cards with contacts*:

- Part 1: *Physical characteristics*
- Part 2: *Dimensions and location of the contacts*
- Part 3: *Electronic signals and transmission protocols*
- Part 4: *Interindustry commands for interchange*
- Part 5: *Numbering system and registration procedure for application identifiers*
- Part 6: *Interindustry data elements*
- Part 7: *Interindustry commands for Structured Card Query Language (SCQL)*
- Part 8: *Security related interindustry commands*
- Part 9: *Additional interindustry commands and security attributes*
- Part 10: *Electronic signals and answer to reset for synchronous cards*

Annexes A and B of this part of ISO/IEC 7816 are for information only.

Introduction

This part of ISO/IEC 7816 is one of a series of standards describing the parameters for integrated circuit(s) cards with contacts and the use of such cards for international interchange.

These cards are identification cards intended for information exchange negotiated between the outside and the integrated circuit in the card. As a result of an information exchange, the card delivers information (computation results, stored data) and/or modifies its content (data storage, event memorization).

During the preparation of this part of ISO/IEC 7816, information was gathered concerning relevant patents upon which application of this standard might depend. Relevant patents were identified in France and USA, the patent holder being Bull S.A. in each case. However, ISO cannot give authoritative or comprehensive information about evidence, validity or scope of patents or like rights.

The patent holder has stated that licenses will be granted in appropriate terms to enable application of this part of ISO/IEC 7816, provided that those who seek licenses agree to reciprocate.

Further information is available from:

BULL S.A.
Division de la Propriété Industrielle
25, avenue de la Grande Armée
75016 PARIS
FRANCE

ITeH STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcd401fe0d7/iso-iec-7816-10-1999>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 7816-10:1999

<https://standards.iteh.ai/catalog/standards/sist/153e603e-97b6-4207-8427-0fcd01fe0d7/iso-iec-7816-10-1999>

Identification cards — Integrated circuit(s) cards with contacts —

Part 10:

Electronic signals and answer to reset for synchronous cards

1 Scope

This part of ISO/IEC 7816 specifies the power, signal structures, and the structure for the answer to reset between an integrated circuit(s) card with synchronous transmission and an interface device such as a terminal.

The specifications in ISO/IEC 7816-3 apply where appropriate, unless otherwise stated here.

It also covers signal rates, operating conditions, and communication with the integrated circuit(s) card.

This part of ISO/IEC 7816 specifies two types of synchronous cards: type 1 and type 2.

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 7816. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/IEC 7816 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 1177:1985, *Information processing — Character structure for start/stop and synchronous character oriented transmission.*

ISO/IEC 7810:1995, *Identification cards — Physical characteristics.*

ISO/IEC 7816-2:1999, *Information technology — Identification cards — Integrated circuit(s) cards with contacts — Part 2: Dimensions and location of the contacts.*

ISO/IEC 7816-3:1997, *Information technology — Identification cards — Integrated circuit(s) cards with contacts — Part 3: Electronic signals and transmission protocols.*

ISO/IEC 7816-4:1995, *Information technology — Identification cards — Integrated circuit(s) cards with contacts — Part 4: Interindustry commands for interchange.*

ISO/IEC 7816-4:1995/Amd.1:1997, *Information technology — Identification cards — Integrated circuit(s) cards with contacts — Part 4: Interindustry commands for interchange — Amendment 1: Impact of secure messaging on the structures of APDU messages.*

3 Term and definition

For the purposes of this part of ISO/IEC 7816, the following term and definition applies.

3.1

interface device

a terminal, communication device or machine to which the integrated circuit(s) card is electrically connected during operation

[ISO/IEC 7816-3:1997, 3.1.1]

4 Symbols and abbreviated terms

For the purposes of this part of ISO/IEC 7816, the following notation applies:

state H: High state logic level,

state L: Low state logic level,

state Z: Mark (as defined in ISO 1177),

state A: Space (as defined in ISO 1177),

'XY': Hexadecimal notation, equal to XY to the base 16.

5 Electrical characteristics of the contacts

5.1 Contact assignments

In addition to those contacts assigned in ISO/IEC 7816-2 the contact C4 is assigned to function code (FCB) for type 2 synchronous cards. FCB is used in conjunction with RST in order to indicate the type of command to be executed in the card (e.g. reset, read, write).

5.2 Voltage and current values

All voltage and current values are those defined in ISO/IEC 7816-3 for class A operating conditions. The electrical characteristics of the FCB contact (synchronous card type 2) are the same of those of RST contact.

5.3 Card type selection

The interface device may start with type 1 or type 2 operating conditions. If the card does not provide an Answer-to-Reset, or provides an inconsistent answer (see subclause 7.4), then the interface device shall deactivate the contacts and, after a delay of at least 10 ms, may apply other operating conditions.

6 Reset of the card

6.1 Synchronous card type 1

The interface device sets all lines to state L. See figure 1. VCC is then powered, VPP is set to idle state, CLK and RST remain in state L, I/O is put in reception mode in the interface device. RST shall be maintained in state H for at least 50 μs (t_{12}), before returning to state L again. The maximum value for fall/rise time is 0,5 μs (t_f and t_r in figures 1 and 2).

The clock pulse is applied after an interval (t_{10}) from the rising edge of the reset signal. The duration for the state H of the clock pulse can be any value between 10 μs and 50 μs ; no more than one clock pulse during reset high is allowed. The time interval between the falling edges on CLK and RST is t_{11} .

The first data bit is obtained as an answer on I/O while CLK is in state L and is valid after an interval t_{13} from the falling edge on RST.

6.2 Synchronous card type 2

The interface device sets all the lines to state L. See figure 2. VCC is then powered, VPP is set to idle state, CLK, RST and FCB remain in state L, I/O is put in reception mode in the interface device. The clock pulse is applied after an interval (t_{20}) from the rising edge of the VCC. The duration of the clock pulse is t_{25} . FCB shall be maintained to L at least during the time t_{22} after the rising edge of clock pulse.

The first data bit is obtained as an answer on I/O while CLK is in state L and is valid after an interval t_{27} from the falling edge of CLK.

When FCB is set to state H, each clock pulse allows the reading on I/O of the next data bit.

7 Answer-to-Reset

In synchronous transmission, a series of bits is transmitted on the I/O line in half duplex mode in synchronization with the clock signal on CLK.

7.1 Clock frequency and bit rate

There is a linear relationship between the bit rate on the I/O line and the clock frequency delivered by the interface device on CLK e.g. a clock frequency of 7 kHz corresponds to 7 kbit/s.

The maximum value for fall/rise time is 0,5 μ s (t_f and t_r in figures 1 and 2).

For card type 1 - any frequency below 50 kHz may be used.

For card type 2 - any frequency below 280 kHz may be used.

7.2 Structure of the Answer-to-Reset header

The reset operation results in an answer from the card containing a header transmitted from the card to the interface. The header has a fixed length of 32 bits and begins with two mandatory fields of 8 bits, H1 and H2.

The chronological order of transmission of the information bits shall correspond to bit identification b1 to b32 with the least significant bit transmitted first. The numerical meaning corresponding to each information bit considered in isolation is that of the digit

- 0 for a unit corresponding to state A (space);
- 1 for a unit corresponding to state Z (mark).

7.3 Timing of the header

7.3.1 Synchronous card type 1

After the reset procedure, see 6.1, the output information is controlled by clock pulses. The first clock pulse is applied between 10 μ s and 100 μ s (t_{14}) after the falling edge on RST. The duration of state H of clock pulses can be varied between 10 μ s and 50 μ s (t_{15}) and the duration of state L between 10 μ s and 100 μ s (t_{16}).

The first data bit is obtained as defined in 6.1. The second and the following data bits are valid between t_{17} measured from the falling edge on CLK. The data bits can therefore be sampled at the rising edge of subsequent clock pulses.