



**SLOVENSKI STANDARD**  
**SIST EN 300 392-3-2 V1.4.1:2010**  
**01-oktober-2010**

---

**Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 3. del: Medsebojno delovanje na medsystemske vmesniku (ISI) - 2. poddel: Dodatna omrežna funkcija: posamezni klic (ANF-ISIIC)**

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 3: Interworking at the Inter-System Interface (ISI) - Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 392-3-2 V1.4.1:2010](https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010)  
<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010>

**Ta slovenski standard je istoveten z: EN 300 392-3-2 Version 1.4.1**

---

**ICS:**

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

<b>SIST EN 300 392-3-2 V1.4.1:2010</b>	<b>en</b>
--	-----------

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 300 392-3-2 V1.4.1:2010

<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010>

# ETSI EN 300 392-3-2 V1.4.1 (2010-08)

---

*European Standard (Telecommunications series)*

**Terrestrial Trunked Radio (TETRA);  
Voice plus Data (V+D);  
Part 3: Interworking at the Inter-System Interface (ISI);  
Sub-part 2: Additional Network Feature  
Individual Call (ANF-ISIIC)**

---

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 392-3-2 V1.4.1:2010](https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010>



## Reference

---

REN/TETRA-03193

## Keywords

---

air interface, TETRA, V+D**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 300 392-3-2 V1.4.1:2010<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b0574/sist-en-300-392-3-2-v1-4-1-2010>  
**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
1 Scope .....	10
2 References .....	11
2.1 Normative references .....	11
2.2 Informative references.....	12
3 Definitions and abbreviations.....	12
3.1 Definitions.....	12
3.2 Abbreviations .....	13
4 ANF-ISIIC stage 1 specification .....	14
4.1 Description .....	14
4.1.1 General description .....	14
4.1.2 Qualifications on applicability to telecommunication services.....	14
4.2 Procedures .....	15
4.2.1 Provision/withdrawal.....	15
4.2.2 Normal procedures.....	15
4.2.2.1 Activation/deactivation/registration/interrogation .....	15
4.2.2.2 Invocation and operation.....	15
4.2.2.2.1 Call routing .....	15
4.2.2.2.2 Control of call time-out timers.....	16
4.2.2.2.3 Transmission control.....	16
4.2.2.2.3a Setup modification.....	16
4.2.2.2.4 Call modification.....	16
4.2.2.2.5 Call restoration after migration.....	16
4.2.2.2.6 Call clearing.....	17
4.2.2.2.7 Interaction between ANF-ISIICs.....	17
4.2.2.2.8 Radio traffic channel resource queuing and allocation policies .....	18
4.2.3 Exceptional procedures.....	18
4.2.3.1 Activation/deactivation/registration/interrogation .....	18
4.2.3.2 Invocation and operation.....	18
4.3 Interactions with other TETRA supplementary services and ANFs.....	19
4.3.1 Calling Line Identification Presentation (SS-CLIP) .....	19
4.3.2 Connected Line identification Presentation (SS-COLP).....	19
4.3.3 Calling/connected Line Identification Restriction (SS-CLIR).....	19
4.3.4 Call Report (SS-CR) .....	19
4.3.5 Talking Party Identification (SS-TPI).....	19
4.3.6 Call Forwarding Unconditional (SS-CFU) .....	19
4.3.7 Call Forwarding on Busy (SS-CFB).....	21
4.3.8 Call Forwarding on No Reply (SS-CFNRY).....	22
4.3.9 Call Forwarding on Not Reachable (SS-CFNRC).....	22
4.3.10 List Search Call (SS-LSC).....	23
4.3.11 Call Authorized by Dispatcher (SS-CAD).....	23
4.3.12 Short Number Addressing (SS-SNA) .....	24
4.3.13 Area Selection (SS-AS) .....	24
4.3.14 Access Priority (SS-AP) .....	24
4.3.15 Priority Call (SS-PC) .....	25
4.3.16 Call Waiting (SS-CW).....	25
4.3.17 Call Hold (SS-HOLD).....	25
4.3.18 Call Completion to Busy Subscriber (SS-CCBS).....	25
4.3.19 Late Entry (SS-LE).....	25
4.3.20 Void.....	25
4.3.21 Pre-emptive Priority Call (SS-PPC).....	25
4.3.22 Include Call (SS-IC) .....	26
4.3.23 Advice of Charge (SS-AoC).....	26

4.3.24	Barring of Outgoing Calls (SS-BOC) .....	26
4.3.25	Barring of Incoming Calls (SS-BIC) .....	26
4.3.26	Discreet Listening (SS-DL) .....	27
4.3.27	Ambience Listening (SS-AL) .....	27
4.3.28	Dynamic Group Number Assignment (SS-DGNA) .....	27
4.3.29	Call Completion on No Reply (SS-CCNR) .....	27
4.3.30	Call Retention (SS-CRT) .....	27
4.3.31	Additional Network Feature - Inter System Interface Group Call (ANF-ISIGC) .....	28
4.3.32	Additional Network Feature - Inter System Interface Short Data Service (ANF-ISISDS) .....	28
4.3.33	Additional Network Feature - Inter System Interface Mobility Management (ANF-ISIMM) .....	28
4.3.34	Additional Network Feature - Inter System Interface Supplementary service (ANF-ISISS) .....	28
4.4	Interworking considerations .....	28
4.5	Static description of ANF-ISIIC using attributes .....	30
4.6	Overall SDL .....	32
5	ANF-ISIIC stage 2 specification .....	37
5.1	Functional model .....	37
5.1.1	Functional model description .....	37
5.1.2	Description of functional entities .....	38
5.1.2.1	SwMI A individual call control application functional entity, FE1 .....	38
5.1.2.2	ISI individual call originating functional entity, FE2 .....	39
5.1.2.3	ISI individual outgoing call route determining functional entity, FE3 .....	39
5.1.2.4	ISI individual call migration handling functional entity, FE4 .....	39
5.1.2.5	ISI information provision functional entity, FE5 .....	40
5.1.2.6	ISI individual call migrated called user routeing functional entity, FE6 .....	40
5.1.2.7	ISI individual call terminating functional entity, FE7 .....	40
5.1.2.8	Terminating SwMI call control functional entity, FE8 .....	41
5.1.3	Relationship of functional model to basic call functional model .....	41
5.2	Information flow .....	42
5.2.1	Examples of information flow sequences .....	42
5.2.1.1	Successful call set-up when the called user is registered in SwMI B and uses on/off hook signalling .....	43
5.2.1.2	Successful call set-up when the called user is registered in SwMI B and uses direct set-up signalling .....	45
5.2.1.3	ANF-ISIIC set-up to a called user having migrated from SwMI B, using forward switching .....	46
5.2.1.4	ANF-ISIIC set-up to a called user having migrated from SwMI B, using re-routeing .....	46
5.2.1.5	Loop avoidance in case of intra-TETRA call .....	49
5.2.1.6	Unsuccessful ANF-ISIIC call set-up .....	50
5.2.1.7	Transmission control .....	52
5.2.1.8	Call modify .....	53
5.2.1.9	Call restoration after migration .....	54
5.2.1.10	Call clearing .....	56
5.2.1.11	Radio traffic channel resource queuing and allocation .....	56
5.2.2	Definition of information flows .....	57
5.2.2.1	CALL RESTORE .....	57
5.2.2.2	CALL RESTORE PREPARE .....	58
5.2.2.3	CHARACTERISTIC CHANGE .....	59
5.2.2.4	COMPLETE .....	59
5.2.2.5	INFORM 1 .....	60
5.2.2.6	INFORM 2 .....	60
5.2.2.7	INFORM 3 .....	60
5.2.2.8	MIGRATION .....	61
5.2.2.9	MODIFY .....	61
5.2.2.10	RELEASE .....	62
5.2.2.11	SETUP .....	62
5.2.2.12	SETUP PROLONGATION .....	63
5.2.2.13	TROMBONE .....	64
5.2.2.14	TX-CEASED .....	64
5.2.2.14.1	TX-CEASED 1 .....	64
5.2.2.14.2	TX-CEASED 2 .....	64
5.2.2.15	TX-CONTINUE 1 .....	65
5.2.2.16	TX-CONTINUE 2 .....	65

5.2.2.17	TX-DEMAND .....	65
5.2.2.18	TX-GRANTED .....	66
5.2.2.19	TX-INTERRUPT .....	66
5.2.2.20	TX-WAIT.....	66
5.2.3	Relationship of information flows to basic call information flows.....	66
5.3	Functional entity actions .....	67
5.4	Allocation of functional entities to physical equipment/SwMIs.....	67
6	ANF-ISIIC stage 3 specification .....	69
6.1	ANF-ISIIC description .....	69
6.2	ANF-ISIIC operational requirements .....	69
6.2.1	Requirements on the originating SwMI .....	69
6.2.2	Requirements on the terminating SwMI .....	70
6.2.3	Requirements on a called SwMI when it is different from the terminating SwMI .....	70
6.2.4	Requirements on a routeing SwMI .....	71
6.2.5	Requirements on a SwMI with PSTN/ISDN/PISN incoming gateway .....	71
6.2.6	Requirements on a SwMI with PSTN/ISDN/PISN outgoing gateways.....	72
6.3	ANF-ISIIC coding requirements .....	73
6.3.1	TETRA PDUs.....	73
6.3.1.1	TETRA PDU giving complementary information in the PSS1 SETUP message sent by the originating or the incoming gateway SwMI.....	74
6.3.1.2	TETRA PDU giving complementary information in a PSS1 PROGRESS message .....	77
6.3.1.3	TETRA message sent by the called SwMI in a PSS1 FACILITY message when it is not the terminating SwMI because of migration or SS-CF invocation .....	77
6.3.1.4	TETRA message sent by the originating SwMI in a PSS1 FACILITY message to request forward switching .....	79
6.3.1.5	TETRA PDU giving complementary information in the PSS1 ALERTING message .....	80
6.3.1.6	TETRA PDU giving complementary information in the PSS1 CONNECT message.....	80
6.3.1.7	TETRA information sent by the terminating SwMI in PSS1 FACILITY messages before the PSS1 ALERTING or CONNECT message .....	82
6.3.1.8	TETRA information sent by the terminating SwMI in a PSS1 FACILITY message during call establishment after the PSS1 ALERTING or CONNECT message.....	83
6.3.1.9	TETRA information sent by the originating SwMI in a PSS1 FACILITY message before the call has been established.....	83
6.3.1.10	TETRA CONNECT ACKNOWLEDGE sent by the originating SwMI in a PSS1 FACILITY message .....	83
6.3.1.11	Other TETRA messages possibly sent by the originating SwMI in PSS1 FACILITY messages .....	83
6.3.1.12	TETRA messages possibly sent by either the originating or the terminating SwMI in a PSS1 FACILITY message .....	85
6.3.1.13	TETRA messages possibly sent by the terminating SwMI in PSS1 FACILITY messages .....	86
6.3.1.14	TETRA PDUs giving complementary information in PSS1 messages to restore the call after the calling or the connected user has migrated in a new SwMI .....	87
6.3.1.14.1	Case where no connection between the old SwMI and the new SwMI already exists or has been identified .....	88
6.3.1.14.2	Cases where no new connection is needed between the old SwMI and the new SwMI.....	89
6.3.1.15	TETRA PDUs giving complementary information in PSS1 DISCONNECT messages.....	92
6.3.1.16	TETRA PDU giving complementary information in a PSS1 RELEASE message .....	93
6.3.1.17	TETRA PDUs giving complementary information in a PSS1 RELEASE COMPLETE message .....	93
6.3.1.18	TETRA PDUs specific for interaction with supplementary service protocol sent to the originating SwMI in a PSS1 FACILITY message .....	93
6.3.1.19	TETRA PDUs sent towards the Called or Visited SwMI in a PSS1 FACILITY after the PSS1 call has been connected.....	94
6.3.1.20	TETRA PDUs sent towards the Called or Originating SwMI in a PSS1 FACILITY after the PSS1 call has connected.....	96
6.3.2	TETRA PDU information element coding .....	97
6.3.2.1	Specific ISI definition of some information elements already defined for air interface messages .....	97
6.3.2.1.1	Basic service information .....	97
6.3.2.1.2	Call status .....	97
6.3.2.1.3	Call time-out, set-up phase .....	97
6.3.2.1.4	Disconnect cause information element.....	98
6.3.2.1.5	PDU type .....	99
6.3.2.2	New information elements used at the ISI .....	100

6.3.2.2.1	Call diverted to a dispatcher .....	100
6.3.2.2.2	Call has been forward switched .....	100
6.3.2.2.3	Call identified as fleet call .....	100
6.3.2.2.4	Called/forwarded-to external subscriber number .....	100
6.3.2.2.5	Called/forwarded-to party extension .....	100
6.3.2.2.6	Called/forwarded-to party SSI .....	100
6.3.2.2.7	Called/forwarded-to party fleet number SSI .....	100
6.3.2.2.8	Called/forwarded-to user having migrated .....	101
6.3.2.2.9	Calling external subscriber number .....	101
6.3.2.2.10	Calling external subscriber number parameters .....	101
6.3.2.2.11	Calling party fleet number SSI .....	101
6.3.2.2.12	Calling party presentation indicator .....	101
6.3.2.2.13	Cause for PDU addressed to originating SwMI .....	102
6.3.2.2.14	Connected external subscriber number .....	102
6.3.2.2.15	Connected external subscriber number parameters .....	102
6.3.2.2.16	Connected party presentation indicator .....	102
6.3.2.2.17	Connected party extension .....	102
6.3.2.2.18	Connected party SSI .....	102
6.3.2.2.19	Connected party fleet number SSI .....	103
6.3.2.2.20	Controlling SwMI .....	103
6.3.2.2.21	Incoming call barring status .....	103
6.3.2.2.22	Forwarded-to external subscriber number .....	103
6.3.2.2.23	Forwarded-to user extension .....	103
6.3.2.2.24	Forwarded-to user SSI .....	103
6.3.2.2.25	Last Forwarding SwMI MNI .....	103
6.3.2.2.26	Modify accepted .....	103
6.3.2.2.27	Modify request .....	104
6.3.2.2.28	MSISDN present as external subscriber number .....	104
6.3.2.2.29	New SwMI MNI .....	104
6.3.2.2.30	Number of digits in called/forwarded-to external subscriber number .....	104
6.3.2.2.31	Number of digits in calling external subscriber number .....	104
6.3.2.2.32	Number of digits in connected external subscriber number .....	104
6.3.2.2.33	Number of digits in forwarded-to external subscriber number .....	105
6.3.2.2.34	Number of digits in visited/forwarded-to SwMI PISN number .....	105
6.3.2.2.35	Originating SwMI MNI .....	105
6.3.2.2.36	Other end SwMI MNI .....	105
6.3.2.2.37	Override SS-CAD invocation .....	105
6.3.2.2.38	PDU addressed to originating SwMI .....	105
6.3.2.2.39	Possible ISI trombone or loop connection detected .....	105
6.3.2.2.40	Restoring party extension .....	106
6.3.2.2.41	Restoring party SSI .....	106
6.3.2.2.41a	Radio traffic channel release permission .....	106
6.3.2.2.41b	Radio traffic channel release signalling supported .....	107
6.3.2.2.41c	Resource indicator .....	107
6.3.2.2.42	Routeing method choice .....	107
6.3.2.2.43	Routeing method response .....	108
6.3.2.2.44	Security level at calling user air interface .....	108
6.3.2.2.44a	Setup resource allocation .....	108
6.3.2.2.45	Speech service requested/chosen/used .....	108
6.3.2.2.46	Speech services supported .....	109
6.3.2.2.47	SS-CF invocation counter .....	109
6.3.2.2.48	SS-CF invoked .....	109
6.3.2.2.49	SS-CLIR invoked for other party .....	109
6.3.2.2.50	Terminating SwMI MNI .....	109
6.3.2.2.51	Visited/forwarded-to SwMI MNI .....	109
6.3.2.2.52	Visited/forwarded-to SwMI PISN number .....	109
6.3.3	PSS1 facility information element .....	110
6.4	ANF-ISIIC state definitions .....	111
6.5	ANF-ISIIC signalling procedures .....	111
6.5.1	Call establishment .....	111
6.5.1.1	Call request, information channel selection, PISN called number sending and call proceeding .....	111
6.5.1.2	Called user migration .....	111



6.5.1.2.1	Called user having migrated in SwMI C different from SwMI A .....	112
6.5.1.2.2	Called user having migrated in SwMI C coinciding with SwMI A .....	115
6.5.1.3	Call characteristics and set-up time negotiation by the terminating SwMI .....	115
6.5.1.4	Call confirmation indication and call connected by the terminating SwMI .....	116
6.5.1.5	Failure of call establishment .....	117
6.5.2	Call maintenance procedures .....	118
6.5.2.1	Transmission control procedures .....	118
6.5.2.2	Call modification and/or continuation .....	118
6.5.2.3	Call restoration .....	118
6.5.2.3.1	General call restoration procedure .....	118
6.5.2.3.2	Specific call restoration procedure in a SwMI already on the path of the call .....	120
6.5.3	DTMF procedures .....	123
6.5.4	ANF-ISIIC clearing .....	123
6.5.5	Call collisions .....	124
6.6	ANF-ISIIC impact of interworking with ISDN/PISN/PSTN .....	125
6.7	Protocol interactions between ANF-ISIIC and supplementary services and other ANFs .....	125
6.7.1	Interaction with SS-CLIR .....	125
6.7.2	Interactions with SS-CF .....	126
6.7.2.1	Interaction with SS-CF at call establishment .....	126
6.7.2.2	Specific interaction with SS-CFNry at call establishment .....	126
6.7.2.3	Interaction with SS-CF at call restoration .....	126
6.7.3	Interaction with SS-CAD .....	127
6.7.3.1	Invocation of a specific ANF-ISIIC .....	127
6.7.3.2	Interception of an already invoked ANF-ISIIC .....	127
6.7.3.3	Call authorization by a distant dispatcher .....	127
6.7.3.4	Completion of call establishment .....	127
6.7.3.4.1	Call not diverted to dispatcher .....	127
6.7.3.4.2	Call diverted to dispatcher .....	128
6.7.4	Interactions with SS-PC, SS-PPC and SS-CRT .....	128
6.7.5	Interaction with SS-CW .....	129
6.7.6	Interaction with SS-HOLD .....	129
6.7.7	Interaction with SS-CCBS and SS-CCNR .....	129
6.7.8	Interaction with SS-BIC .....	129
6.7.9	Interactions with SS-AS .....	129
6.7.10	Area Selection (SS-AS) and selected area number .....	130
6.7.11	Interactions with other supplementary services .....	130
6.8	ANF-ISIIC parameter values (timers) .....	130
<b>Annex A (informative):</b>	<b>Static description of the TETRA individual call bearer service, using attributes .....</b>	<b>131</b>
<b>Annex B (informative):</b>	<b>Definition of the ISI ROSE operation .....</b>	<b>132</b>
<b>Annex C (informative):</b>	<b>Interactions of SS-CFU with ANF-ISIIC .....</b>	<b>133</b>
C.1	Possible SS-CFU activation .....	133
C.2	Invocation and operation .....	133
C.2.1	Called user home SwMI being SwMI A .....	133
C.2.2	Called user home SwMI being SwMI B .....	133
C.2.2.1	Forwarded-to user with home SwMI being SwMI B, being registered in its home SwMI .....	134
C.2.2.2	Forwarded-to user with home SwMI being SwMI B, having migrated .....	135
C.2.2.3	Forwarded-to user with home SwMI different from SwMI B, being registered in its home SwMI .....	135
C.2.2.4	Forwarded-to user with home SwMI different from SwMI B, having migrated .....	135
<b>Annex D (informative):</b>	<b>Change Requests .....</b>	<b>138</b>
History	.....	139

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA).

The present document is part 3, sub-part 2 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

EN 300 392-1: "General network design";

EN 300 392-2: "Air Interface (AI)";

**EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";**

EN 300 392-3-1: "General design";

**EN 300 392-3-2: "Additional Network Feature Individual Call (ANF-ISIIC)";**

EN 300 392-3-3: "Additional Network Feature Group Call (ANF-ISIGC)";

EN 300 392-3-4: "Additional Network Feature Short Data Service (ANF-ISISDS)";

EN 300 392-3-5: "Additional Network Feature for Mobility Management (ANF-ISIMM)";

TS 100 392-3-6: "Speech format implementation for circuit mode transmission";

TS 100 392-3-7: "Speech Format Implementation for Packet Mode Transmission";

TS 100 392-3-8: "Generic Speech Format Implementation";

ETS 300 392-4: "Gateways basic operation";

EN 300 392-5: "Peripheral Equipment Interface (PEI)";

EN 300 392-7: "Security";

EN 300 392-9: "General requirements for supplementary services";

EN 300 392-10: "Supplementary services stage 1";

EN 300 392-11: "Supplementary services stage 2";

EN 300 392-12: "Supplementary services stage 3";

ETS 300 392-13: "SDL model of the Air Interface (AI)";

ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";

TS 100 392-16: "Network Performance Metrics";

TR 100 392-17: "TETRA V+D and DMO specifications";

TS 100 392-18: "Air interface optimized applications".

NOTE: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

#### National transposition dates

Date of adoption of this EN:	2 August 2010
Date of latest announcement of this EN (doa):	30 November 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2011
Date of withdrawal of any conflicting National Standard (dow):	31 May 2011

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 392-3-2 V1.4.1:2010](https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010>

# 1 Scope

The present document defines the Terrestrial Trunked Radio (TETRA) system supporting Voice plus Data (V+D). It specifies:

- general design aspects (e.g. reference points, numbering and addressing, or protocol architecture);
- the system bearer and mobility management services, and the corresponding air interface protocols;
- the interworking between TETRA networks;
- the interworking of TETRA networks with other networks, via gateways;
- the peripheral equipment interface on the mobile station;
- the Line Station (LS) interface with TETRA networks;
- the security protocols and mechanisms applicable to TETRA networks and to TETRA terminal equipment;
- the supplementary services applicable to the basic TETRA tele- or bearer services.

The TETRA V+D interworking - basic operation part defines the interworking between TETRA networks over the corresponding interface: the Inter-System Interface (ISI). It comprises the following subparts:

- ISI general design;
- Additional Network Feature - ISI Individual Call (ANF-ISIIC);
- Additional Network Feature - ISI Group Call (ANF-ISIGC);
- Additional Network Feature - ISI Short Data service (ANF-ISISDS);
- Additional Network Feature - ISI Mobility Management (ANF-ISIMM);
- 8 kbit/s encoding of user information at the ISI.

The present document is the ANF-ISIIC sub-part.

ANF-ISIIC enables calls to be set-up by a user registered in one TETRA network to another user registered in another TETRA network, operating at the ISI of both SwMIs. It also supports call restoration when a user has migrated to another TETRA network during an established call. Additionally, ANF-ISIIC allows TETRA signalling information to be passed from a TETRA SwMI to another TETRA SwMI supporting the TETRA individual call procedures as defined in clauses 11 and 14 of EN 300 392-2 [1].

Like all other Additional Network Feature (ANF) specifications, those of ANF-ISIIC are produced in three stages, according to the method described in ITU-T Recommendation I.130 [i.5]. The present document contains the stage 1 and 2 descriptions of ANF-ISIIC, and its partial stage 3 description. The stage 1 description specifies the ANF as seen by its users, which are essentially the individual call control entities in both TETRA networks. The stage 2 description identifies the functional entities involved in the ANF and the information flows between them. And the partial stage 3 description of ANF-ISIIC specifies its protocol.

**NOTE:** According to ITU-T Recommendation I.130 [i.5], the stage 3 description of a bearer or tele-service addresses the network implementation aspects. Consequently, it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step.

The latter have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

The present document applies to TETRA networks which support inter-TETRA individual calls. More specifically, it applies to their Circuit Mode Control Entities (CMCE), as defined in clause 14.2 of EN 300 392-2 [1], and to their ANF-ISIIC entities defined in the stage 2 description.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-3-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 1: General design".
- [3] ETSI EN 300 392-3-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".
- [4] ETSI EN 300 392-3-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [5] Void.
- [6] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] ETSI EN 300 172: "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Circuit-mode basic services [ISO/IEC 11572 (2000) modified]".
- [8] ETSI EN 300 392-12-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 4: Call Forwarding (CF)".
- [9] ISO/IEC 11572: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit mode bearer services - Inter-exchange signalling procedures and protocol".
- [10] ISO/IEC 11574: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit mode 64 kbit/s bearer services - Service description, functional capabilities and information flows".
- [11] ISO/IEC 11582: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Generic functional protocol for the support of supplementary services - Inter-exchange signalling procedures and protocol".
- [12] ITU-T Recommendation I.460: "Multiplexing, rate adaption and support of existing interfaces".
- [13] ETSI EN 300 392-12-8: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 8: Area Selection (AS)".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.2] ETSI TS 100 921: "Digital cellular telecommunications system (Phase 2+) (GSM); Service accessibility (3GPP TS 02.11)".
- [i.3] ETSI EN 300 392-10-19: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 19: Barring of Incoming Calls (BIC)".
- [i.4] ETSI EN 300 395-2: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 2: TETRA codec".
- [i.5] ITU-T Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.6] ITU-T Recommendation I.140: "Attribute technique for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.7] ITU-T Recommendation I.210: "Principles of telecommunication services supported by an ISDN and the means to describe them".
- [i.8] ITU-T Recommendation Z.100: "Specification and Description Language (SDL)".
- [i.9] ITU-T Recommendation V.110: "Support by an ISDN of data terminal equipments with V-Series type interfaces".
- [i.10] ETSI TR 102 300-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Designers' guide; Part 5: Guidance on numbering and addressing".

<https://standards.iteh.ai/catalog/standards/sist/587408b7-fb35-4d66-9116-bd237d2b053a/sist-en-300-392-3-2-v1-4-1-2010>

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 392-3-1 [2] and the following apply:

**called SwMI or SwMI B:** Switching and Management Infrastructure to which ANF-ISIIC routes the first call attempt

**fleet call:** call to a closed user group using a Fleet Specific Short Number

NOTE: Refer to TR 102 300-5 [i.10] clause 5.4.3.

**forward switching:** network routing algorithm which performs the routing from SwMI A to SwMI C by joining together the first connection, from SwMI A to SwMI B, and a second connection from SwMI B to SwMI C

**home SwMI:** SwMI which is the home of the MS (or LS) ITSI, i.e. to which the Mobile Network Identity (MNI) which is part of the ITSI belongs

**loop connection:** ISI connection which has both its ends in the same SwMI

**originating SwMI or SwMI A:** Switching and Management Infrastructure in which the calling user has registered

**re-routing:** network routing algorithm which performs the routing from SwMI A to SwMI C by replacing the connection from SwMI A to SwMI B by another connection from SwMI A to SwMI C

**SwMI C:** Switching and Management Infrastructure in which the called user has registered after having migrated from SwMI B, in the case where its home SwMI is SwMI B

**terminating SwMI:** Switching and Management Infrastructure in which the connected user is registered

NOTE: Unless an interaction with one or more supplementary services which modify the routing of the call (e.g. call forwarding) has occurred, the connected user will be the called user; and the terminating SwMI will be the SwMI where the called user is registered, i.e. SwMI B or SwMI C.

**trombone connection:** special case of loop connection where all inter-TETRA connections making up the loop connection are used twice

NOTE: If no interaction occurs with supplementary services which modify the routing of the call (e.g. call forwarding), the only loop connection which can be established by an invoked ANF-ISIIC is a trombone connection (i.e. when SwMI C coincides with SwMI A).

## 3.2 Abbreviations

For the purpose of the present document, the following abbreviations apply:

AL	Ambience Listening
ANF	Additional Network Feature
AoC	Advice of Charge
AP	Access Priority
APDU	Application Packet Data Unit
AS	Area Selection
BIC	Barring of Incoming Calls
BOC	Barring of Outgoing Calls
CAD	Call Authorized by Dispatcher
CC	Call Control (PISN functional entity)
CCAp	Call Control Application (SwMI functional entity)
CCBS	Call Completion to Busy Subscriber
CCNR	Call Completion on No Reply
CF	Call Forwarding
CFB	Call Forwarding on Busy
CFNRc	Call Forwarding on Not Reachable
CFNRy	Call Forwarding on No Reply
CFU	Call Forwarding Unconditional
CLIP	Calling Line Identification Presentation
CLIR	Calling/connected Line Identification Restriction
CMCE	Circuit Mode Control Entities
COLP	COnnected Line identification Presentation
CR	Call Report
CRT	Call ReTention
CRV	Call Retention Value
CW	Call Waiting
DGNA	Dynamic Group Number Assignment
DL	Discreet Listening
DTMF	Dual Tone Multi Frequency
FE	Functional Entity
GTSI	TETRA Subscriber Group Identity
HOLD	Call Hold
IC	Include Call
IPE	In-band Parameter Exchange
ISDN	Integrated Services Digital Network
ISI	Inter System Interface
ISIGC	Inter System Interface Group Call
ISIIC	Inter System Interface Individual Call
ISIMM	Inter System Interface Mobility Management
ISISDS	Inter System Interface Short Data Service
ISSS	Inter System Interface Supplementary Service
ITSI	Individual TETRA Subscriber Identity
LE	Late Entry
LS	Line Station
LSC	List Search Call