

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);**

**Part 3: Interworking at the Inter-System Interface (ISI);
Sub-part 2: Additional Network Feature
Individual Call (ANF-ISIIC)**

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ec49a3e-00d3-426d-a43f-60655e902ae6/etsi-en-300-392-3-2-v1.4.1-2010-08>



Reference

REN/TETRA-03193

Keywords

air interface, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD
(Standards.iteh.org)
Full standard:
<http://standards.iteh.org/catalog/standards/sist/300-392-3-2-v1.4.0-032013e-0032/>

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered
for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	10
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions and abbreviations.....	12
3.1 Definitions.....	12
3.2 Abbreviations	13
4 ANF-ISIIC stage 1 specification	14
4.1 Description	14
4.1.1 General description	14
4.1.2 Qualifications on applicability to telecommunication services.....	14
4.2 Procedures	15
4.2.1 Provision/withdrawal	15
4.2.2 Normal procedures.....	15
4.2.2.1 Activation/deactivation/registration/interrogation	15
4.2.2.2 Invocation and operation.....	15
4.2.2.2.1 Call routeing	15
4.2.2.2.2 Control of call time-out timers	16
4.2.2.2.3 Transmission control	16
4.2.2.2.4 Setup modification.....	16
4.2.2.2.5 Call modification	16
4.2.2.2.6 Call restoration after migration.....	16
4.2.2.2.7 Call clearing	17
4.2.2.2.8 Interaction between ANF-ISIICs.....	17
4.2.2.2.9 Radio traffic channel resource queuing and allocation policies	18
4.2.3 Exceptional procedures	18
4.2.3.1 Activation/deactivation/registration/interrogation	18
4.2.3.2 Invocation and operation	18
4.3 Interactions with other TETRA supplementary services and ANFs.....	19
4.3.1 Calling Line Identification Presentation (SS-CLIP)	19
4.3.2 Connected Line identification Presentation (SS-COLP).....	19
4.3.3 Calling/connected Line Identification Restriction (SS-CLIR).....	19
4.3.4 Call Report (SS-CR)	19
4.3.5 Talking Party Identification (SS-TPI).....	19
4.3.6 Call Forwarding Unconditional (SS-CFU)	19
4.3.7 Call Forwarding on Busy (SS-CFB).....	21
4.3.8 Call Forwarding on No Reply (SS-CFNRY)	22
4.3.9 Call Forwarding on Not Reachable (SS-CFNRC)	22
4.3.10 List Search Call (SS-LSC)	23
4.3.11 Call Authorized by Dispatcher (SS-CAD).....	23
4.3.12 Short Number Addressing (SS-SNA)	24
4.3.13 Area Selection (SS-AS)	24
4.3.14 Access Priority (SS-AP)	24
4.3.15 Priority Call (SS-PC)	25
4.3.16 Call Waiting (SS-CW).....	25
4.3.17 Call Hold (SS-HOLD)	25
4.3.18 Call Completion to Busy Subscriber (SS-CCBS)	25
4.3.19 Late Entry (SS-LE)	25
4.3.20 Void	25
4.3.21 Pre-emptive Priority Call (SS-PPC).....	25
4.3.22 Include Call (SS-IC)	26
4.3.23 Advice of Charge (SS-AoC)	26

4.3.24	Barring of Outgoing Calls (SS-BOC)	26
4.3.25	Barring of Incoming Calls (SS-BIC)	26
4.3.26	Discreet Listening (SS-DL)	27
4.3.27	Ambience Listening (SS-AL)	27
4.3.28	Dynamic Group Number Assignment (SS-DGNA).....	27
4.3.29	Call Completion on No Reply (SS-CCNR)	27
4.3.30	Call Retention (SS-CRT)	27
4.3.31	Additional Network Feature - Inter System Interface Group Call (ANF-ISIGC).....	28
4.3.32	Additional Network Feature - Inter System Interface Short Data Service (ANF-ISISDS).....	28
4.3.33	Additional Network Feature - Inter System Interface Mobility Management (ANF-ISIMM)	28
4.3.34	Additional Network Feature - Inter System Interface Supplementary service (ANF-ISISS)	28
4.4	Interworking considerations	28
4.5	Static description of ANF-ISIIC using attributes	30
4.6	Overall SDL	32
5	ANF-ISIIC stage 2 specification	37
5.1	Functional model.....	37
5.1.1	Functional model description.....	37
5.1.2	Description of functional entities.....	38
5.1.2.1	SwMI A individual call control application functional entity, FE1	38
5.1.2.2	ISI individual call originating functional entity, FE2.....	39
5.1.2.3	ISI individual outgoing call route determining functional entity, FE3.....	39
5.1.2.4	ISI individual call migration handling functional entity, FE4.....	39
5.1.2.5	ISI information provision functional entity, FE5	40
5.1.2.6	ISI individual call migrated called user routeing functional entity, FE6.....	40
5.1.2.7	ISI individual call terminating functional entity, FE7.....	40
5.1.2.8	Terminating SwMI call control functional entity, FE8	41
5.1.3	Relationship of functional model to basic call functional model.....	41
5.2	Information flow	42
5.2.1	Examples of information flow sequences.....	42
5.2.1.1	Successful call set-up when the called user is registered in SwMI B and uses on/off hook signalling.....	43
5.2.1.2	Successful call set-up when the called user is registered in SwMI B and uses direct set-up signalling.....	45
5.2.1.3	ANF-ISIIC set-up to a called user having migrated from SwMI B, using forward switching	46
5.2.1.4	ANF-ISIIC set-up to a called user having migrated from SwMI B, using re-routeing	46
5.2.1.5	Loop avoidance in case of intra-TETRA call.....	49
5.2.1.6	Unsuccessful ANF-ISIIC call set-up	50
5.2.1.7	Transmission control	52
5.2.1.8	Call modify	53
5.2.1.9	Call restoration after migration	54
5.2.1.10	Call clearing	56
5.2.1.11	Radio traffic channel resource queuing and allocation.....	56
5.2.2	Definition of information flows	57
5.2.2.1	CALL RESTORE	57
5.2.2.2	CALL RESTORE PREPARE	58
5.2.2.3	CHARACTERISTIC CHANGE	59
5.2.2.4	COMPLETE	59
5.2.2.5	INFORM 1	60
5.2.2.6	INFORM 2	60
5.2.2.7	INFORM 3	60
5.2.2.8	MIGRATION	61
5.2.2.9	MODIFY	61
5.2.2.10	RELEASE	62
5.2.2.11	SETUP	62
5.2.2.12	SETUP PROLONGATION	63
5.2.2.13	TROMBONE	64
5.2.2.14	TX-CEASED	64
5.2.2.14.1	TX-CEASED 1.....	64
5.2.2.14.2	TX-CEASED 2.....	64
5.2.2.15	TX-CONTINUE 1.....	65
5.2.2.16	TX-CONTINUE 2.....	65

5.2.2.17	TX-DEMAND	65
5.2.2.18	TX-GRANTED	66
5.2.2.19	TX-INTERRUPT	66
5.2.2.20	TX-WAIT	66
5.2.3	Relationship of information flows to basic call information flows	66
5.3	Functional entity actions	67
5.4	Allocation of functional entities to physical equipment/SwMIs	67
6	ANF-ISIIC stage 3 specification	69
6.1	ANF-ISIIC description	69
6.2	ANF-ISIIC operational requirements	69
6.2.1	Requirements on the originating SwMI	69
6.2.2	Requirements on the terminating SwMI	70
6.2.3	Requirements on a called SwMI when it is different from the terminating SwMI	70
6.2.4	Requirements on a routeing SwMI	71
6.2.5	Requirements on a SwMI with PSTN/ISDN/PISN incoming gateway	71
6.2.6	Requirements on a SwMI with PSTN/ISDN/PISN outgoing gateways	72
6.3	ANF-ISIIC coding requirements	73
6.3.1	TETRA PDUs	73
6.3.1.1	TETRA PDU giving complementary information in the PSS1 SETUP message sent by the originating or the incoming gateway SwMI	74
6.3.1.2	TETRA PDU giving complementary information in a PSS1 PROGRESS message	77
6.3.1.3	TETRA message sent by the called SwMI in a PSS1 FACILITY message when it is not the terminating SwMI because of migration or SS-CF invocation	77
6.3.1.4	TETRA message sent by the originating SwMI in a PSS1 FACILITY message to request forward switching	79
6.3.1.5	TETRA PDU giving complementary information in the PSS1 ALERTING message	80
6.3.1.6	TETRA PDU giving complementary information in the PSS1 CONNECT message	80
6.3.1.7	TETRA information sent by the terminating SwMI in PSS1 FACILITY messages before the PSS1 ALERTING or CONNECT message	82
6.3.1.8	TETRA information sent by the terminating SwMI in a PSS1 FACILITY message during call establishment after the PSS1 ALERTING or CONNECT message	83
6.3.1.9	TETRA information sent by the originating SwMI in a PSS1 FACILITY message before the call has been established	83
6.3.1.10	TETRA CONNECT ACKNOWLEDGE sent by the originating SwMI in a PSS1 FACILITY message	83
6.3.1.11	Other TETRA messages possibly sent by the originating SwMI in PSS1 FACILITY messages	83
6.3.1.12	TETRA messages possibly sent by either the originating or the terminating SwMI in a PSS1 FACILITY message	85
6.3.1.13	TETRA messages possibly sent by the terminating SwMI in PSS1 FACILITY messages	86
6.3.1.14	TETRA PDUs giving complementary information in PSS1 messages to restore the call after the calling or the connected user has migrated in a new SwMI	87
6.3.1.14.1	Case where no connection between the old SwMI and the new SwMI already exists or has been identified	88
6.3.1.14.2	Cases where no new connection is needed between the old SwMI and the new SwMI	89
6.3.1.15	TETRA PDUs giving complementary information in PSS1 DISCONNECT messages	92
6.3.1.16	TETRA PDU giving complementary information in a PSS1 RELEASE message	93
6.3.1.17	TETRA PDUs giving complementary information in a PSS1 RELEASE COMPLETE message	93
6.3.1.18	TETRA PDUs specific for interaction with supplementary service protocol sent to the originating SwMI in a PSS1 FACILITY message	93
6.3.1.19	TETRA PDUs sent towards the Called or Visited SwMI in a PSS1 FACILITY after the PSS1 call has been connected	94
6.3.1.20	TETRA PDUs sent towards the Called or Originating SwMI in a PSS1 FACILITY after the PSS1 call has connected	96
6.3.2	TETRA PDU information element coding	97
6.3.2.1	Specific ISI definition of some information elements already defined for air interface messages	97
6.3.2.1.1	Basic service information	97
6.3.2.1.2	Call status	97
6.3.2.1.3	Call time-out, set-up phase	97
6.3.2.1.4	Disconnect cause information element	98
6.3.2.1.5	PDU type	99
6.3.2.2	New information elements used at the ISI	100

6.3.2.2.1	Call diverted to a dispatcher	100
6.3.2.2.2	Call has been forward switched.....	100
6.3.2.2.3	Call identified as fleet call.....	100
6.3.2.2.4	Called/forwarded-to external subscriber number.....	100
6.3.2.2.5	Called/forwarded-to party extension	100
6.3.2.2.6	Called/forwarded-to party SSI.....	100
6.3.2.2.7	Called/forwarded-to party fleet number SSI.....	100
6.3.2.2.8	Called/forwarded-to user having migrated	101
6.3.2.2.9	Calling external subscriber number	101
6.3.2.2.10	Calling external subscriber number parameters.....	101
6.3.2.2.11	Calling party fleet number SSI	101
6.3.2.2.12	Calling party presentation indicator.....	101
6.3.2.2.13	Cause for PDU addressed to originating SwMI.....	102
6.3.2.2.14	Connected external subscriber number.....	102
6.3.2.2.15	Connected external subscriber number parameters	102
6.3.2.2.16	Connected party presentation indicator	102
6.3.2.2.17	Connected party extension.....	102
6.3.2.2.18	Connected party SSI	102
6.3.2.2.19	Connected party fleet number SSI.....	103
6.3.2.2.20	Controlling SwMI.....	103
6.3.2.2.21	Incoming call barring status	103
6.3.2.2.22	Forwarded-to external subscriber number	103
6.3.2.2.23	Forwarded-to user extension	103
6.3.2.2.24	Forwarded-to user SSI.....	103
6.3.2.2.25	Last Forwarding SwMI MNI.....	103
6.3.2.2.26	Modify accepted	103
6.3.2.2.27	Modify request	104
6.3.2.2.28	MSISDN present as external subscriber number	104
6.3.2.2.29	New SwMI MNI.....	104
6.3.2.2.30	Number of digits in called/forwarded-to external subscriber number	104
6.3.2.2.31	Number of digits in calling external subscriber number	104
6.3.2.2.32	Number of digits in connected external subscriber number	104
6.3.2.2.33	Number of digits in forwarded-to external subscriber number	105
6.3.2.2.34	Number of digits in visited/forwarded-to SwMI PISN number	105
6.3.2.2.35	Originating SwMI MNI.....	105
6.3.2.2.36	Other end SwMI MNI	105
6.3.2.2.37	Override SS-CAD invocation.....	105
6.3.2.2.38	PDU addressed to originating SwMI	105
6.3.2.2.39	Possible ISI trombone or loop connection detected.....	105
6.3.2.2.40	Restoring party extension	106
6.3.2.2.41	Restoring party SSI.....	106
6.3.2.2.41a	Radio traffic channel release permission	106
6.3.2.2.41b	Radio traffic channel release signalling supported	107
6.3.2.2.41c	Resource indicator	107
6.3.2.2.42	Routeing method choice	107
6.3.2.2.43	Routeing method response	108
6.3.2.2.44	Security level at calling user air interface	108
6.3.2.2.44a	Setup resource allocation	108
6.3.2.2.45	Speech service requested/chosen/used	108
6.3.2.2.46	Speech services supported	109
6.3.2.2.47	SS-CF invocation counter	109
6.3.2.2.48	SS-CF invoked	109
6.3.2.2.49	SS-CLIR invoked for other party	109
6.3.2.2.50	Terminating SwMI MNI.....	109
6.3.2.2.51	Visited/forwarded-to SwMI MNI	109
6.3.2.2.52	Visited/forwarded-to SwMI PISN number	109
6.3.3	PSS1 facility information element	110
6.4	ANF-ISIIC state definitions	111
6.5	ANF-ISIIC signalling procedures.....	111
6.5.1	Call establishment.....	111
6.5.1.1	Call request, information channel selection, PISN called number sending and call proceeding.....	111
6.5.1.2	Called user migration	111

6.5.1.2.1	Called user having migrated in SwMI C different from SwMI A	112
6.5.1.2.2	Called user having migrated in SwMI C coinciding with SwMI A.....	115
6.5.1.3	Call characteristics and set-up time negotiation by the terminating SwMI.....	115
6.5.1.4	Call confirmation indication and call connected by the terminating SwMI	116
6.5.1.5	Failure of call establishment	117
6.5.2	Call maintenance procedures	118
6.5.2.1	Transmission control procedures	118
6.5.2.2	Call modification and/or continuation.....	118
6.5.2.3	Call restoration.....	118
6.5.2.3.1	General call restoration procedure.....	118
6.5.2.3.2	Specific call restoration procedure in a SwMI already on the path of the call	120
6.5.3	DTMF procedures.....	123
6.5.4	ANF-ISIIC clearing	123
6.5.5	Call collisions	124
6.6	ANF-ISIIC impact of interworking with ISDN/PISN/PSTN	125
6.7	Protocol interactions between ANF-ISIIC and supplementary services and other ANFs	125
6.7.1	Interaction with SS-CLIR	125
6.7.2	Interactions with SS-CF.....	126
6.7.2.1	Interaction with SS-CF at call establishment	126
6.7.2.2	Specific interaction with SS-CFNRY at call establishment	126
6.7.2.3	Interaction with SS-CF at call restoration	126
6.7.3	Interaction with SS-CAD	127
6.7.3.1	Invocation of a specific ANF-ISIIC	127
6.7.3.2	Interception of an already invoked ANF-ISIIC.....	127
6.7.3.3	Call authorization by a distant dispatcher	127
6.7.3.4	Completion of call establishment.....	127
6.7.3.4.1	Call not diverted to dispatcher.....	127
6.7.3.4.2	Call diverted to dispatcher.....	128
6.7.4	Interactions with SS-PC, SS-PPC and SS-CRT	128
6.7.5	Interaction with SS-CW	129
6.7.6	Interaction with SS-HOLD	129
6.7.7	Interaction with SS-CCBS and SS-CCNR	129
6.7.8	Interaction with SS-BIC.....	129
6.7.9	Interactions with SS-AoC	129
6.7.10	Area Selection (SS-AS) and selected area number	130
6.7.11	Interactions with other supplementary services	130
6.8	ANF-ISIIC parameter values (timers)	130
Annex A (informative):	Static description of the TETRA individual call bearer service, using attributes.....	131
Annex B (informative):	Definition of the ISI ROSE operation	132
Annex C (informative):	Interactions of SS-CFU with ANF-ISIIC.....	133
C.1	Possible SS-CFU activation	133
C.2	Invocation and operation	133
C.2.1	Called user home SwMI being SwMI A	133
C.2.2	Called user home SwMI being SwMI B.....	133
C.2.2.1	Forwarded-to user with home SwMI being SwMI B, being registered in its home SwMI	134
C.2.2.2	Forwarded-to user with home SwMI being SwMI B, having migrated	135
C.2.2.3	Forwarded-to user with home SwMI different from SwMI B, being registered in its home SwMI	135
C.2.2.4	Forwarded-to user with home SwMI different from SwMI B, having migrated	135
Annex D (informative):	Change Requests.....	138
History	139	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 3, sub-part 2 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

EN 300 392-1: "General network design";

EN 300 392-2: "Air Interface (AI)";

EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";

EN 300 392-3-1: "General design";

EN 300 392-3-2: "Additional Network Feature Individual Call (ANF-ISIIC)";

EN 300 392-3-3: "Additional Network Feature Group Call (ANF-ISIGC)";

EN 300 392-3-4: "Additional Network Feature Short Data Service (ANF-ISIDS)";

EN 300 392-3-5: "Additional Network Feature for Mobility Management (ANF-ISIMM)";

TS 100 392-3-6: "Speech format implementation for circuit mode transmission";

TS 100 392-3-7: "Speech Format Implementation for Packet Mode Transmission";

TS 100 392-3-8: "Generic Speech Format Implementation";

ETS 300 392-4: "Gateways basic operation";

EN 300 392-5: "Peripheral Equipment Interface (PEI)";

EN 300 392-7: "Security";

EN 300 392-9: "General requirements for supplementary services";

EN 300 392-10: "Supplementary services stage 1";

EN 300 392-11: "Supplementary services stage 2";

EN 300 392-12: "Supplementary services stage 3";

ETS 300 392-13: "SDL model of the Air Interface (AI)";

ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";

TS 100 392-16: "Network Performance Metrics";

TR 100 392-17: "TETRA V+D and DMO specifications";

TS 100 392-18: "Air interface optimized applications".

NOTE: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ec49a3e-00d3-426d-a43f-60655e902ae6/etsi-en-300-392-3-2-v1.4.1-2010-08>

1 Scope

The present document defines the Terrestrial Trunked Radio (TETRA) system supporting Voice plus Data (V+D). It specifies:

- general design aspects (e.g. reference points, numbering and addressing, or protocol architecture);
- the system bearer and mobility management services, and the corresponding air interface protocols;
- the interworking between TETRA networks;
- the interworking of TETRA networks with other networks, via gateways;
- the peripheral equipment interface on the mobile station;
- the Line Station (LS) interface with TETRA networks;
- the security protocols and mechanisms applicable to TETRA networks and to TETRA terminal equipment;
- the supplementary services applicable to the basic TETRA tele- or bearer services.

The TETRA V+D interworking - basic operation part defines the interworking between TETRA networks over the corresponding interface: the Inter-System Interface (ISI). It comprises the following subparts:

- ISI general design;
- Additional Network Feature - ISI Individual Call (ANF-ISIIC);
- Additional Network Feature - ISI Group Call (ANF-ISIGC);
- Additional Network Feature - ISI Short Data service (ANF-ISISDS);
- Additional Network Feature - ISI Mobility Management (ANF-ISIMM);
- 8 kbit/s encoding of user information at the ISI.

The present document is the ANF-ISIIC sub-part.

ANF-ISIIC enables calls to be set-up by a user registered in one TETRA network to another user registered in another TETRA network, operating at the ISI of both SwMIs. It also supports call restoration when a user has migrated to another TETRA network during an established call. Additionally, ANF-ISIIC allows TETRA signalling information to be passed from a TETRA SwMI to another TETRA SwMI supporting the TETRA individual call procedures as defined in clauses 11 and 14 of EN 300 392-2 [1].

Like all other Additional Network Feature (ANF) specifications, those of ANF-ISIIC are produced in three stages, according to the method described in ITU-T Recommendation I.130 [i.5]. The present document contains the stage 1 and 2 descriptions of ANF-ISIIC, and its partial stage 3 description. The stage 1 description specifies the ANF as seen by its users, which are essentially the individual call control entities in both TETRA networks. The stage 2 description identifies the functional entities involved in the ANF and the information flows between them. And the partial stage 3 description of ANF-ISIIC specifies its protocol.

NOTE: According to ITU-T Recommendation I.130 [i.5], the stage 3 description of a bearer or tele-service addresses the network implementation aspects. Consequently, it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step.

The latter have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

The present document applies to TETRA networks which support inter-TETRA individual calls. More specifically, it applies to their Circuit Mode Control Entities (CMCE), as defined in clause 14.2 of EN 300 392-2 [1], and to their ANF-ISIIC entities defined in the stage 2 description.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-3-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 1: General design".
- [3] ETSI EN 300 392-3-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".
- [4] ETSI EN 300 392-3-5; "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [5] Void.
- [6] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] ETSI EN 300 172: "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Circuit-mode basic services [ISO/IEC 11572 (2000) modified]".
- [8] ETSI EN 300 392-12-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 4: Call Forwarding (CF)".
- [9] ISO/IEC 11572: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit mode bearer services - Inter-exchange signalling procedures and protocol".
- [10] ISO/IEC 11574: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit mode 64 kbit/s bearer services - Service description, functional capabilities and information flows".
- [11] ISO/IEC 11582: "Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Generic functional protocol for the support of supplementary services - Inter-exchange signalling procedures and protocol".

- [12] ITU-T Recommendation I.460: "Multiplexing, rate adaption and support of existing interfaces".
- [13] ETSI EN 300 392-12-8: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 8: Area Selection (AS)".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI EN 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.2] ETSI TS 100 921: "Digital cellular telecommunications system (Phase 2+) (GSM); Service accessibility (3GPP TS 02.11)".
- [i.3] ETSI EN 300 392-10-19: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 19: Barring of Incoming Calls (BIC)".
- [i.4] ETSI EN 300 395-2: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 2: TETRA codec".
- [i.5] ITU-T Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.6] ITU-T Recommendation I.140: "Attribute technique for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.7] ITU-T Recommendation I.210: "Principles of telecommunication services supported by an ISDN and the means to describe them".
- [i.8] ITU-T Recommendation Z.100: "Specification and Description Language (SDL)".
- [i.9] ITU-T Recommendation V.110: "Support by an ISDN of data terminal equipments with V-Series type interfaces".
- [i.10] ETSI TR 102 300-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Designers' guide; Part 5: Guidance on numbering and addressing".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 392-3-1 [2] and the following apply:

called SwMI or SwMI B: Switching and Management Infrastructure to which ANF-ISIIC routes the first call attempt

fleet call: call to a closed user group using a Fleet Specific Short Number

NOTE: Refer to TR 102 300-5 [i.10] clause 5.4.3.

forward switching: network routeing algorithm which performs the routeing from SwMI A to SwMI C by joining together the first connection, from SwMI A to SwMI B, and a second connection from SwMI B to SwMI C

home SwMI: SwMI which is the home of the MS (or LS) ITSI, i.e. to which the Mobile Network Identity (MNI) which is part of the ITSI belongs

loop connection: ISI connection which has both its ends in the same SwMI

originating SwMI or SwMI A: Switching and Management Infrastructure in which the calling user has registered

re-routeing: network routeing algorithm which performs the routeing from SwMI A to SwMI C by replacing the connection from SwMI A to SwMI B by another connection from SwMI A to SwMI C

SwMI C: Switching and Management Infrastructure in which the called user has registered after having migrated from SwMI B, in the case where its home SwMI is SwMI B

terminating SwMI: Switching and Management Infrastructure in which the connected user is registered

NOTE: Unless an interaction with one or more supplementary services which modify the routeing of the call (e.g. call forwarding) has occurred, the connected user will be the called user; and the terminating SwMI will be the SwMI where the called user is registered, i.e. SwMI B or SwMI C.

trombone connection: special case of loop connection where all inter-TETRA connections making up the loop connection are used twice

NOTE: If no interaction occurs with supplementary services which modify the routeing of the call (e.g. call forwarding), the only loop connection which can be established by an invoked ANF-ISIIC is a trombone connection (i.e. when SwMI C coincides with SwMI A).

3.2 Abbreviations

For the purpose of the present document, the following abbreviations apply:

AL	Ambience Listening
ANF	Additional Network Feature
AoC	Advice of Charge
AP	Access Priority
APDUs	Application Packet Data Unit
AS	Area Selection
BIC	Barring of Incoming Calls
BOC	Barring of Outgoing Calls
CAD	Call Authorized by Dispatcher
CC	Call Control (PISN functional entity)
CCAp	Call Control Application (SwMI functional entity)
CCBS	Call Completion to Busy Subscriber
CCNR	Call Completion on No Reply
CF	Call Forwarding
CFB	Call Forwarding on Busy
CFNRc	Call Forwarding on Not Reachable
CFNRY	Call Forwarding on No Reply
CFU	Call Forwarding Unconditional
CLIP	Calling Line Identification Presentation
CLIR	Calling/connected Line Identification Restriction
CMCE	Circuit Mode Control Entities
COLP	COnnected Line identification Presentation
CR	Call Report
CRT	Call ReTention
CRV	Call Retention Value
CW	Call Waiting
DGNA	Dynamic Group Number Assignment
DL	Discreet Listening
DTMF	Dual Tone Multi Frequency
FE	Functional Entity
GTSI	TETRA Subscriber Group Identity
HOLD	Call Hold
IC	Include Call
IPE	In-band Parameter Exchange
ISDN	Integrated Services Digital Network
ISI	Inter System Interface
ISIGC	Inter System Interface Group Call
ISIIC	Inter System Interface Individual Call
ISIMM	Inter System Interface Mobility Management