

SLOVENSKI STANDARD SIST EN 15947-5:2010

01-december-2010

Nadomešča:

SIST EN 14035-4:2003/AC:2005

SIST EN 14035-5:2006

Pirotehnični izdelki - Ognjemetni izdelki, kategorije 1, 2 in 3 - 5. del: Zahteve za izdelavo in delovanje

Pyrotechnic articles - Fireworks, Categories 1, 2, and 3 - Part 5: Requirements for construction and performance

iTeh STANDARD PREVIEW

Pyrotechnische Gegenstände - Feuerwerkskörper, Kategorien 1, 2 und 3 - Teil 5: Anforderungen an Bauart und Funktion

SIST EN 15947-5:2010

Articles pyrotechniques Artifices de divertissement, Catégories 1, 2, et 3 - Partie 5: Exigences de construction et de performances

Ta slovenski standard je istoveten z: EN 15947-5:2010

ICS:

71.100.30 Eksplozivi. Pirotehnika Explosives. Pyrotechnics

SIST EN 15947-5:2010 en,fr,de

SIST EN 15947-5:2010

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 15947-5:2010</u> https://standards.iteh.ai/catalog/standards/sist/73a57dec-d92e-4bd3-b0f8-ff414e1dd470/sist-en-15947-5-2010 EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 15947-5

September 2010

ICS 71.100.30

Supersedes EN 14035-7:2004, EN 14035-31:2005, EN 14035-35:2004, EN 14035-28:2004, EN 14035-36:2004, EN 14035-36:2004, EN 14035-36:2004, EN 14035-24:2004, EN 14035-9:2004, EN 14035-23:2003, EN 14035-15:2003, EN 14035-12:2003, EN 14035-27:2003, EN 14035-29:2004, EN 14035-33:2005, EN 14035-38:2006, EN 14035-33:2004, EN 14035-10:2004, EN 14035-3:2004, EN 14035-13:2004, EN 14035-13:2005, EN 14035-13:2004, EN 14035-13:2005, EN 14035-13:2004, EN 14035-13:2005, EN 14035-13:2004, EN 14035-13:2005, EN 1

English Version

Pyrotechnic articles - Fireworks, Categories 1, 2, and 3 - Part 5: Requirements for construction and performance

Articles pyrotechniques - Artifices de divertissement, Catégories 1, 2, et 3 - Partie 5: Exigences de construction rds.iteh.ai)

Pyrotechnische Gegenstände - Feuerwerkskörper, Catégories 1, 2, et 3 - Partie 5: Exigences de construction rds.iteh.ai)

Kategorien 1, 2 und 3 - Teil 5: Anforderungen an et de performances

SIST EN 15947-5:2010

This European Standard was approved by CEN on 21 August 2010. ft414e1dd470/sist-en-15947-5-2010

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Cont	tents	Page
Forew	ord	4
1	Scope	6
2	Normative references	
3	Terms and definitions	
		_
4 4.1	Construction materials (type test and batch test)	8
4.1.1	General requirements	
4.1.2	Specific requirements	8
4.2	Length of handle (type test and batch test)	
4.3 4.4	Permitted elements in batteries and combinations (type test and batch test) Dimensions for mini rockets (type test and batch test)	
	,	
5	Pyrotechnic composition (type test)	
6	Means of ignition	12
6.1 6.2	Permitted means of ignition (type test and batch test)	12 1 <i>4</i>
6.3	Protection of initial fuse (type test and batch test)	14
6.4	Fuse requirements (type test and batch test)	14
6.4.1	General requirements (Standards.Iteh.al)	14
6.4.2	Specific requirements	
7	Performance SIST EN 15947-5:2010	15
7.1 7.1.1	Properties to be checked before functioning tests/sist/73a57dec-d92e-4bd3-h0f8-Loose pyrotechnic composition after mechanical conditioning (type test)	
7.1.1 7.1.2	Integrity (type test and batch test)	
7.1.3	Stabilisation of flight (type test and batch test)	
7.1.4	Other requirements (type test)	
7.2 7.2.1	Properties to be checked during functioning tests (type test and batch test)	
7.2.1 7.2.2	Principal effects	
7.2.3	Angle of ascent or flight	
7.2.4	Motion	
7.2.5 7.2.6	Stability during functioning	
7.2.6 7.2.7	Height of explosionSound pressure level	
7.2.8	Explosions and other failures	
7.2.9	Burning or incandescent matter	18
7.2.10		
7.2.11 7.2.12	Projected debrisBurning rate of pyrotechnic composition	
7.2.12	Pull-string or -strip	
7.3	Properties to be checked after functioning tests (type test and batch test)	20
7.3.1	Droop	
7.3.2 7.3.3	Plastics body Rocket motor	
7.3.3 7.3.4	Integrity after functioning	
8	Primary pack or selection pack (type test and batch test)	
	, , , , , , , , , , , , , , , , , , , ,	
9 9.1	Type testingGeneral	
J. I		4 I

9.2	Number of items to be tested	22
9.3	Number of primary packs to be examined	22
9.4	Test report	
10	Batch testing	23
10.1	General	23
10.2	Sampling plans	
10.3	Unit of product	
10.4	Nonconformities	
10.5	Test report	24
10.6	Acceptance or rejection of a batch	
10.6.1	Nonconforming units	
10.6.2	Critical nonconforming units	
10.6.3		
10.6.4	•	
	Fireworks supplied in primary packs or selection packs	
Annex	A (informative)	26
	ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2007/23/EC on the placing on the market of pyrotechnic articles	
Diblica		
	graphy	ZÖ

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 15947-5:2010</u> https://standards.iteh.ai/catalog/standards/sist/73a57dec-d92e-4bd3-b0f8-ff414e1dd470/sist-en-15947-5-2010

Foreword

This document (EN 15947-5:2010) has been prepared by Technical Committee CEN/TC 212 "Pyrotechnic articles", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2011, and conflicting national standards shall be withdrawn at the latest by March 2011.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14035-7:2004, EN 14035-31:2005, EN 14035-35:2004, EN 14035-28:2004, EN 14035-6:2004. EN 14035-24:2004. EN 14035-23:2003. EN 14035-36:2004. EN 14035-9:2004. EN 14035-15:2003, EN 14035-12:2003, EN 14035-34:2003, EN 14035-29:2004, EN 14035-27:2003, EN 14035-38:2006, EN 14035-33:2005, EN 14035-20:2005, EN 14035-8:2004, EN 14035-10:2004, EN 14035-18:2004, EN 14035-3:2004, EN 14035-22:2004, EN 14035-13:2004, EN 14035-5:2006, EN 14035-4:2003, EN 14035-25:2005, EN 14035-17:2004, EN 14035-19:2003, EN 14035-21:2005.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

This European Standard is one of the series of standards as listed below:

— EN 15947-1, Pyrotechnic articles and Fireworks Categories 1/72 and 3-d9 Part 1: Terminology ff414e1dd470/sist-en-15947-5-2010

- EN 15947-2, Pyrotechnic articles Fireworks, Categories 1, 2 and 3 Part 2: Categories and types of firework
- EN 15947-3, Pyrotechnic articles Fireworks, Categories 1, 2 and 3 Part 3: Minimum labelling requirements
- EN 15947-4, Pyrotechnic articles Fireworks, Categories 1, 2 and 3 Part 4: Test methods
- EN 15947-5, Pyrotechnic articles Fireworks, Categories 1, 2 and 3 Part 5: Requirements for construction and performance

CEN/TC 212 is currently also developing European Standards for:

- Pyrotechnic articles Fireworks Category 4;
- Pyrotechnic articles Theatrical pyrotechnic articles;
- Pyrotechnic articles Pyrotechnic articles for vehicles;
- Pyrotechnic articles Other pyrotechnic articles.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia,

Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 15947-5:2010</u> https://standards.iteh.ai/catalog/standards/sist/73a57dec-d92e-4bd3-b0f8-ff414e1dd470/sist-en-15947-5-2010

1	Sco	pe
-		_

This	European	Standard	specifies	requirements	for the	construction,	performance	and	primary	packaging	, of
firev	vorks of cat	egory 1, 2	and 3 of	the following ty	ypes:						

_	aerial wheels;	
—	bangers;	
_	batteries and combinatio	ns;
_	Bengal flames;	
_	Bengal matches;	
_	Bengal sticks;	
_	Christmas crackers;	
—	crackling granules;	
	double bangers;	
_	flash bangers;	iTeh STANDARD PREVIEW
_	flash pellets;	(standards.iteh.ai)
—	fountains;	
_	ground movers;	SIST EN 15947-5:2010 https://standards.iteh.ai/catalog/standards/sist/73a57dec-d92e-4bd3-b0f8
_	ground spinners;	ff414e1dd470/sist-en-15947-5-2010
_	hand-held sparklers;	
	jumping crackers;	
	jumping ground spinners	;
_	mines;	
_	mini rockets;	
_	non-hand-held sparklers;	,
_	novelty matches;	
_	party poppers;	
_	rockets;	
_	Roman candles;	
_	serpents;	
	shot tubes;	

	snaps;
	spinners;
_	table bombs;
	throwdowns;
	wheels.
age	s European Standard does not apply for articles containing military explosives or commercial blasting ints except for black powder or flash composition. This European Standard does not apply for articles taining pyrotechnic composition that includes any of the following substances:
—	arsenic or arsenic compounds;
	hexachlorobenzene;
	mixtures containing a mass fraction of chlorates greater than 80 %;
	mixtures of chlorates with metals;
	mixtures of chlorates with red phosphorus (except when used in Christmas crackers, party poppers or snaps);
_	mixtures of chlorates with potassium hexacyanoferrate(II);
	(standards.iteh.ai) mixtures of chlorates with sulfur (these mixtures are allowed for friction heads only);
	mixtures of chlorates with sulfides; SIST EN 15947-5:2010 https://standards.iteh.ai/catalog/standards/sist/73a57dec-d92e-4bd3-b0f8-
_	lead or lead compounds; ff414e1dd470/sist-en-15947-5-2010
_	mercury compounds;
_	white phosphorus;
_	picrates or picric acid;
	potassium chlorate with a mass fraction of bromates greater than 0,15 %;
	sulfur with an acidity, expressed in mass fraction of sulphuric acid, greater than 0,002 %;
	zirconium with a particle size of less than 40 μm.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15947-1:2010, Pyrotechnic articles — Fireworks, Categories 1, 2 and 3 — Part 1: Terminology

EN 15947-2, Pyrotechnic articles — Fireworks, Categories 1, 2 and 3 — Part 2: Categories and types of firework

EN 15947-3, Pyrotechnic articles — Fireworks, Categories 1, 2 and 3 — Part 3: Minimum labelling requirements

EN 15947-4:2010, Pyrotechnic articles — Fireworks, Categories 1, 2 and 3 — Part 4: Test Methods

ISO 2859-1, Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 15947-1:2010 apply.

4 Construction

4.1 Construction materials (type test and batch test)

4.1.1 General requirements

- The body of the firework case shall be made of paper, cardboard or plastics. The base (end closures) or means of fixing shall be made of non-metallic material. Where technically necessary, wood, staples, nails, aluminium coated foil or binding wires may be used. Conformity to this requirement shall be verified by visual examination.
 TANDARD PREVIEW
- For articles fitted with a friction head; the primary pack shall be fitted with a striking surface for safety matches. Conformity to this requirement shall be verified by visual examination.
- The striking surface shall be resistant enough to allow-ignition of all the articles included within the primary pack when tested in accordance with 6.16 of EN/15947-4:20102 The striking surface on the pack shall be covered or the pack shall be sealed, verified by visual examination.

4.1.2 Specific requirements

- For bangers and flash bangers: cardboard wrapped in cord is permitted as construction material.
- For batteries of mines, Roman candles or shot tubes: the tubes shall have a maximum angle of 30° to the vertical, when tested in accordance with 6.18 of EN 15947-4:2010. For combinations this requirement applies to the tubes of mines, Roman candles and shot tubes.
- For Bengal matches and Bengal sticks: the stick shall be made of wood.
- For Christmas crackers and snaps: the overlapping strips shall be made of cardboard, paper or string.
- For jumping crackers: the firework case shall be made of paper only.
- For mini rockets: the tube containing the propellant charge shall be made of cardboard or, when no report charge is present, plastics.
- For novelty matches: the stick shall be made of cardboard or wood.
- For party poppers: the shape shall not be confused with a gun.
- For rockets: the tube containing the propellant charge shall be made of cardboard, plastics or sheathed aluminium.

- For Roman candles and shot tubes: the case, if any, of the pyrotechnic unit, shall be made of paper, cardboard or plastics.
- For Roman candles: the inside diameter of the tube shall not exceed 30 mm. Conformity to this requirement shall be verified by the method described in 6.1.5 of EN 15947-4:2010.
- For shot tubes: the inside diameter of the tube shall not exceed 30 mm (category 2) or 50 mm (category 3). Conformity to these requirements shall be verified by the method described in 6.1.5 of EN 15947-4:2010.
- For spinners: the aerofoils, if any, shall be made of cardboard or plastics.
- For throwdowns: the body shall be made of tissue paper or foil.

Conformity to above requirements shall be verified by visual examination, unless stated otherwise.

4.2 Length of handle (type test and batch test)

- For Bengal matches: the uncoated end of a Bengal match (handle) shall have a length of at least 40 % of the total length of the Bengal match with a minimum of 20 mm.
- For Bengal sticks: the uncoated end of a Bengal stick (handle) shall have a minimum length of 75 mm.
- For hand-held fountains: the end of the firework case of a hand-held fountain which is not filled with pyrotechnic composition and which acts as a handle, or the handle, if the handle is a separate component, shall have a minimum length of 40 mm.
- (standards.iteh.ai)
 For hand-held sparklers: a category 1 hand-held sparkler shall have a minimum handle length of 75 mm; a category 2 hand-held sparkler shall have a minimum handle length of 75 mm when the total length does not exceed 450 mm and 150 mm when the total length is more than 450 mm.
- For novelty matches: the uncoated end of a novelty match (handle) shall have a minimum length of 20 mm.

Conformity to above requirements shall be verified by the test method described in 6.1.1.2.1 or 6.1.1.2.2 of EN 15947-4:2010.

- For Christmas crackers and snaps: the total length of the pull-strip or -string shall be at least 50 mm.
- For party poppers: the length of the pull-string shall be at least 75 mm.

Conformity to above requirements shall be verified by the method described in 6.1.4 of EN 15947-4:2010.

4.3 Permitted elements in batteries and combinations (type test and batch test)

The following elements can be used in batteries: bangers and flash bangers, Bengal flames, crackling granules, fountains, ground spinners, mines, rockets (assembled in a launcher), Roman candles, spinners, shot tubes and wheels; the same limits (mass, composition, etc.) as given in Table 1 apply to these elements.

The following elements can be used in combinations: bangers and flash bangers, Bengal flames, fountains, mines, Roman candles, shot tubes, spinners and wheels; the same limits (mass, composition, etc.) as given in Table 1 apply to these elements.

Conformity to above requirements shall be verified by visual examination.

4.4 Dimensions for mini rockets (type test and batch test)

When tested in accordance with 6.1.5 and 6.1.3 of EN 15947-4:2010, mini rockets shall have the following dimensions:

- outer diameter of tube: maximum 10 mm;
- length of tube: maximum 60 mm;
- total length: minimum 250 mm, maximum 350 mm.

5 Pyrotechnic composition (type test)

When tested in accordance with 6.2.2 of EN 15947-4:2010, the net explosive contents shall comply with Table 1. For report and/or bursting charges with a composition other than black powder, nitrate/metal-based compositions or perchlorate/metal-based compositions the same upper limits as for perchlorate/metal-based compositions apply.

Table 1 — Pyrotechnic composition

Firework types	Cat.	Net explosive content
aerial wheels	3	Not more than 160 g, shall not contain more than eight pyrotechnic units. A pyrotechnic unit shall have a net explosive content of not more than 20 g. A report charge, if any, shall have a net explosive content of not more than 10,0 g of black powder or 4,0 g of nitrate/metal-based report composition or 2,0 g of perchlorate/metal-based report composition.
bangers	2	Not more than 6,0 g black powder.
	3	Not more than 10,0 g black powder S.iteh.ai
batteries and combinations	2	A battery or combination, except a combination containing fountains, shall have a net explosive content of not more than 500 g; the net explosive content of a combination containing fountains shall have a net explosive content of not more than 600 g, of which not more than 500 g shall be contained in elements other than fountains; the net explosive content of a battery containing fountains shall have a net explosive content of not more than 600 g.
		Bangers used in batteries or combinations shall have a total net explosive content of not more than 100 g.
		Flash bangers used in batteries or combinations shall have a total net explosive content of not more than 25 g.
	3	A battery or combination, except a combination containing fountains, shall have a net explosive content of not more than 1 000 g; a combination containing fountains shall have a net explosive content of not more than 3 000 g, of which not more than 1 000 g shall be contained in elements other than fountains; a battery containing fountains shall have a net explosive content of not more than 3 000 g.
		Bangers used in batteries or combinations shall have a total net explosive content of not more than 1 000 g.
		Flash bangers used in batteries or combinations shall have a total net explosive content of not more than 250 g.
Bengal flames	1	Not more than 20 g.
	2	Not more than 250 g.
	3	Not more than 1 000 g.
Bengal matches	1	Not more than 3,0 g.
Bengal sticks	1	Not more than 7,5 g.
	2	Not more than 50 g.
Christmas crackers 1 Not more than 16,0 mg report composition based on potassium chlorate and in phosphorous, or not more than 1,6 mg silver fulminate as report composition.		Not more than 16,0 mg report composition based on potassium chlorate and red phosphorous, or not more than 1,6 mg silver fulminate as report composition.