



SLOVENSKI STANDARD
SIST EN 300 392-12-4 V1.2.1:2010
01-oktober-2010

Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 12. del: Dopolnilne storitve stopnje 3 - 4. poddel: Predaja klica (CF)

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 12: Supplementary services stage 3 - Sub-part 4: Call Forwarding (CF)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 392-12-4 Version 1.2.1**

SIST EN 300 392-12-4 V1.2.1:2010
<https://standards.iteh.ai/catalog/standards/sist/b6ca0e59-e87d-413d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-12-4 V1.2.1:2010 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-12-4 V1.2.1:2010

<https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010>

ETSI EN 300 392-12-4 V1.2.1 (2010-07)

European Standard (Telecommunications series)

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 4: Call Forwarding (CF)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-12-4 V1.2.1:2010](https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010>



Reference

REN/TETRA-03199

Keywords

radio, TETRA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-12-4 V1.2.1:2010

[https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637c0/sist-en-300-392-12-4-v1-2-1-2010](https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637c0/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637c0/sist-en-300-392-12-4-v1-2-1-2010)
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	14
3.3 Abbreviations	14
4 Signalling protocol for the support of SS-CF.....	15
4.1 SS-CF description	15
4.2 SS-CF services offered over the TNSS-SAP.....	15
4.2.1 ACTIVATE request.....	16
4.2.2 ACTIVATE ACK indication	17
4.2.3 DEACTIVATE request.....	17
4.2.4 DEACTIVATE ACK indication.....	17
4.2.5 DISABLE request.....	18
4.2.6 DISABLE ACK indication	18
4.2.7 ENABLE request	18
4.2.8 ENABLE ACK indication	19
4.2.9 INFORM2 indication.....	19
4.2.10 INFORM5 indication.....	19
4.2.11 INFORM8 indication.....	20
4.2.12 INFORM9 indication.....	20
4.2.13 INTERROGATE request.....	20
4.2.14 INTERROGATE ACK indication	21
4.2.15 INTERROGATE2 request.....	21
4.2.16 INTERROGATE2 ACK indication	21
4.3 Parameter description	22
5 Signalling procedures for the support of SS-CF.....	24
5.1 SS-CF operational requirements.....	24
5.1.1 Requirements on the originating SwMI	24
5.1.2 Requirements on the served user SwMI	25
5.1.3 Requirements on the forwarded-to SwMI.....	25
5.1.4 Requirements on the re-routeing SwMI.....	25
5.1.5 Requirements on a forward switching SwMI	25
5.1.6 Requirements on the served or authorized user visited SwMI.....	25
5.2 SS-CF Coding requirements.....	26
5.2.1 SS-CF PDUs	26
5.2.1.1 ACTIVATE PDU.....	26
5.2.1.2 ACTIVATE ACK PDU	26
5.2.1.3 DEACTIVATE PDU	27
5.2.1.4 DEACTIVATE ACK PDU	28
5.2.1.5 DISABLE PDU	28
5.2.1.6 DISABLE ACK PDU	29
5.2.1.7 ENABLE PDU	30
5.2.1.8 ENABLE ACK	30
5.2.1.9 INFORM2 PDU	31
5.2.1.10 INFORM4 PDU	31
5.2.1.11 INFORM5 PDU	33
5.2.1.12 INFORM8 PDU	34

5.2.1.13	INFORM9 PDU	35
5.2.1.14	INTERROGATE PDU	35
5.2.1.15	INTERROGATE ACK PDU	36
5.2.1.16	INTERROGATE2 PDU	36
5.2.1.17	INTERROGATE2 ACK PDU	37
5.2.1.18	REPORT PDU	37
5.2.2	TETRA PDU information element coding	38
5.2.2.1	Accept/reject	38
5.2.2.2	Activating/deactivating user type	38
5.2.2.3	Activation by served user	38
5.2.2.4	Addressing information elements	38
5.2.2.4.1	General on addresses	38
5.2.2.4.2	Address type of the authorized user	39
5.2.2.4.3	Address type of the forwarded-to user	39
5.2.2.4.4	Address type of the last forwarding user	39
5.2.2.4.5	Address type of the originally called user	39
5.2.2.4.6	Address type of the served user	39
5.2.2.5	Basic service information	40
5.2.2.6	CF-PDU type	41
5.2.2.7	Enabled authorized user definition	42
5.2.2.8	External subscriber number	42
5.2.2.9	External subscriber number digit	42
5.2.2.10	Forwarded-to definition	42
5.2.2.11	Forwarding type	43
5.2.2.12	Invoked call forwarding type	43
5.2.2.13	Last forwarding type	43
5.2.2.14	Number of external subscriber number digits	43
5.2.2.15	Original forwarding type	43
5.2.2.16	Reject cause	44
5.2.2.17	Served user definition	44
5.2.2.18	SS-CF invocation counter	45
5.2.2.19	SS type	45
5.2.3	Additional coding requirements over the ISDN	45
5.3	SS-CF State Definitions	47
5.3.1	General on state definitions	47
5.3.2	States at the calling user MS	47
5.3.3	States at the originating SwMI	47
5.3.4	States at the Served User MS	47
5.3.5	States at the served user SwMI	47
5.3.6	States at the forwarded-to user MS	47
5.3.7	States at the forwarded-to SwMI	47
5.3.8	States at the re-routeing SwMI	48
5.3.9	States at the authorized user MS	48
5.3.10	States at the Activating SwMI	48
5.3.11	States at the deactivating user MS	48
5.3.12	States at the deactivating SwMI	48
5.3.13	States at the interrogating user MS	48
5.3.14	States at the interrogating SwMI	48
5.4	SS-CF signalling procedures	48
5.4.1	Actions at MSs	48
5.4.1.1	Activation requesting user MS	48
5.4.1.1.1	Normal operation	48
5.4.1.1.2	Exceptional procedures	49
5.4.1.2	Deactivation requesting user MS	49
5.4.1.2.1	Normal operation for served or authorized user MS	49
5.4.1.2.2	Exceptional procedures for served or authorized user MS	49
5.4.1.2.3	Normal operation for forwarded-to user MS	49
5.4.1.2.4	Exceptional procedures for forwarded-to user MS	49
5.4.1.3	Interrogation requesting user MS	50
5.4.1.3.1	Normal operation of interrogation	50
5.4.1.3.2	Exceptional procedures for forwarding services	50
5.4.1.4	Interrogation requesting forwarded-to user MS	50

5.4.1.4.1	Normal operation of interrogation.....	50
5.4.1.4.2	Exceptional procedures for forwarding services.....	50
5.4.1.5	Unsolicited indication to the served user	50
5.4.1.6	Invocation and operation at MS	50
5.4.1.6.1	General on SS-CF invocation indications.....	50
5.4.1.6.2	Notification to the calling user	50
5.4.1.6.3	Additional indication to the calling user.....	51
5.4.1.6.4	Notification to the forwarded-to user	51
5.4.1.6.5	Additional indication to the forwarded-to user.....	51
5.4.1.6.6	Identification of the forwarded-to user to the calling user.....	51
5.4.1.7	Reminder notification to the served user.....	51
5.4.1.7.1	Normal operation.....	51
5.4.1.7.2	Exceptional procedures.....	51
5.4.2	Actions at the originating SwMI.....	51
5.4.2.1	General requirements	51
5.4.2.2	Normal Procedure	51
5.4.2.3	Exceptional Procedures	52
5.4.3	Actions at the served user home SwMI	52
5.4.3.1	Normal Procedure	52
5.4.3.1.1	Activation	52
5.4.3.1.2	Deactivation.....	52
5.4.3.1.3	Interrogation	52
5.4.3.1.4	Invocation and operation	52
5.4.3.1.5	Reminder notification to the served user	54
5.4.3.2	Exceptional Procedures.....	54
5.4.3.2.1	Activation	54
5.4.3.2.2	Deactivation.....	54
5.4.3.2.3	Interrogation	54
5.4.3.2.4	Invocation.....	54
5.4.4	Actions at the Forwarding SwMI.....	55
5.4.4.1	Functionalities in the case of call forwarding by re-routing.....	55
5.4.4.2	Functionalities in the case of call forwarding by forward switching.....	55
5.4.4.3	Normal procedure.....	55
5.4.4.4	Exceptional procedures.....	55
5.4.5	Procedures at the forwarded-to SwMI	55
5.4.5.1	Normal procedure on invocation.....	55
5.4.5.2	Exceptional Procedures.....	55
5.4.6	Procedures at the served or authorized user visited SwMI	56
5.4.6.1	Normal Procedure	56
5.4.6.2	Exceptional Procedures	56
5.4.7	Protocol for SS-CF invocation counter	56
5.5	Interworking.....	56
5.6	Protocol Interactions between SS-CF and other SSs and ANFs.....	56
5.6.1	Interactions with Ambience Listening (SS-AL)	56
5.6.2	Interactions with Call Authorized by Dispatcher (SS-CAD).....	57
5.6.3	Other protocol interactions of SS-CFU.....	57
5.6.3.1	Interaction with Completion of Call to Busy Subscriber (SS-CCBS).....	57
5.6.3.1.1	Originating SwMI procedures for invoking CCBS at a CFU forwarded-to user.....	57
5.6.3.1.2	Originating SwMI procedures if CFU is activated by SS-CCBS user A.....	57
5.6.3.1.3	Terminating SwMI procedures if CFU is activated by user B after CCBS has been invoked.....	57
5.6.3.2	Interaction with Completion of Calls on No Reply (SS-CCNR).....	57
5.6.3.2.1	Originating SwMI procedures for invoking CCNR at a CFU diverted-to user	58
5.6.3.2.2	Originating SwMI procedures if CFU is activated by SS-CCNR user A	58
5.6.3.2.3	Terminating PINX procedures if CFU is activated by user B after CCNR has been invoked.....	58
5.6.3.3	Interaction with Call Forwarding Busy (SS-CFB)	58
5.6.3.4	Interaction with Call Forwarding No Reply (SS-CFNR)	58
5.6.4	Protocol interactions of SS-CFB.....	58
5.6.4.1	Interaction with Completion of Calls to Busy Subscriber (SS-CCBS)	58
5.6.4.1.1	Originating SwMI procedures for invoking CCBS at a CFB diverted-to user	58
5.6.4.1.2	Originating SwMI procedures if CFB is activated by SS-CCBS user A	58
5.6.4.1.3	Terminating SwMI procedures if CFB is activated by user B after CCBS has been invoked.....	59
5.6.4.2	Interaction with Completion of Calls on No Reply (SS-CCNR).....	59

5.6.4.2.1	Originating SwMI procedures for invoking CCNR at a CFB diverted-to user.....	59
5.6.4.2.2	Originating SwMI procedures if CFB is activated by SS-CCNR user A	59
5.6.4.2.3	Terminating SwMI procedures if CFB is activated by user B after CCNR has been invoked	59
5.6.4.3	Interaction with Call Forwarding Unconditional (SS-CFU)	59
5.6.4.4	Interaction with Call Forwarding No Reply (SS-CFNry)	59
5.6.4.5	Interaction with Call Waiting (SS-CW)	59
5.6.5	Protocol interactions of SS-CFNry	59
5.6.5.1	Interaction with Completion of Calls to Busy Subscriber (SS-CCBS)	59
5.6.5.2	Interaction with Completion of Calls on No Reply (SS-CCNR).....	59
5.6.5.2.1	Originating SwMI procedures for invoking CCNR at a CFNR diverted-to user.....	59
5.6.5.2.2	Originating SwMI procedures if CFNR is activated by SS-CCNR user A.....	59
5.6.5.2.3	Terminating SwMI procedures if CFNR is activated by user B after CCNR has been invoked	60
5.6.5.3	Interaction with Call Forwarding Unconditional (SS-CFU)	60
5.6.5.4	Interaction with Call Forwarding Busy (SS-CFB)	60
5.6.6	Other protocol interactions of SS-CFNrc	60
5.6.6.1	Protocol interactions of SS-CFNrc in the case of early CFNRc	60
5.6.6.2	Protocol interactions of SS-CFNrc in the case of late CFNRc	60
5.6.7	Protocol interactions of SS-CF with ANF-Inter-System-Interface Individual Call (ANF-ISIIC)	60
5.6.7.1	General on interactions	60
5.6.7.2	Interactions of SS-CFU with ANF-ISIIC.....	60
5.6.7.3	Interactions of SS-CFNrc with ANF-ISIIC	61
5.6.7.4	Interactions of SS-CFB and SS-CFNry with ANF-ISIIC	61
5.6.8	Protocol Interactions of SS-CF with ANF Group Call	61
5.6.8.1	Protocol interactions of SS-CFU with ANF-ISIGC	61
5.6.8.2	Protocol interactions of SS-CFB with ANF-ISIGC	61
5.6.9	Protocol Interactions of SS-CF with ANF-SDS	62
5.6.10	Protocol interactions of SS-CF with ANF Mobility Management	62
5.6.10.1	Protocol interactions of SS-CFU, early SS-CFB and early SS-CFNrc with ANF-MM.....	65
5.6.10.2	Protocol interactions of late SS-CFB, SS-CFNry and SS-CFNrc with ANF-MM	65
5.6.10.2.1	Protocol interactions affecting the calling user	65
5.6.10.2.2	Protocol interactions affecting the called/served user	65
5.6.10.2.3	Protocol interactions affecting the forwarded-to user	66
5.6.10.3	Interaction with SS-CF at call restoration	66
5.7	SS-CF parameter values (timers).....	67
5.8	Support of SDS.....	67

Annex A (informative): Interactions of SS-CFB and SS-CFNry with ANF-ISIIC.....68

A.1	Interactions of SS-CFB and SS-CFNry with ANF-ISIIC	68
A.2	Interactions	68
A.2.1	Interactions of late SS-CFB and SS-CFNry with ANF-ISIIC.....	68
A.2.2	Protocol interactions in cases 1, 10 and 11.....	71
A.2.2.1	General on cases 1, 10 and 11.....	71
A.2.2.2	Case 1	71
A.2.2.3	Case 10	72
A.2.2.4	Case 11	73
A.2.3	Protocol interactions affecting the called/served user	75
A.2.3.1	General.....	75
A.2.3.2	Case 2	75
A.2.3.3	Case 4	77
A.2.3.4	Case 5	78
A.2.3.5	Case 7	80
A.2.4	Protocol interactions affecting the forwarded-to user.....	82
A.2.4.1	General.....	82
A.2.4.2	Case 3	82
A.2.4.3	Case 6	83
A.2.4.4	Case 8	85
A.2.4.5	Case 9	87
A.2.4.6	Case 12	89

Annex B (normative): Interworking with other networks90

B.1	Procedures for interworking with public ISDNs	90
B.1.1	Actions at an incoming gateway SwMI	90
B.1.2	Actions at an outgoing gateway SwMI	90
B.1.3	Procedures where a call from the public ISDN is forwarded within or beyond TETRA	90
B.1.3.1	Normal operation	90
B.1.3.2	Exceptional procedures	91
B.1.3.3	Presentation of a forwarded call from a public ISDN to the TETRA network	91
B.1.3.3.1	Normal operation	91
B.1.3.3.2	Exceptional procedures	91
B.1.4	Procedures where a call from the TETRA network is forwarded within or beyond the public ISDN	92
B.1.5	Presentation of a forwarded call from a TETRA network to the public ISDN	92
B.1.5.1	Normal operation	92
B.1.5.2	Exceptional procedures	92
B.1.6	Procedures where a call from the public ISDN is forwarded within or beyond the TETRA network and partial re-routing takes place in the public ISDN	93
B.1.6.1	Normal operation	93
B.1.6.2	Exceptional procedures	95
B.1.7	Procedures where a call from the public ISDN to the TETRA network is forwarded by the public ISDN	95
B.2	SS-CF Impact of interworking with non-ISDNs	96
B.2.1	Impact of interworking on incoming calls	96
B.2.2	Impact of interworking on outgoing calls	96
Annex C (normative):	SS-CF profile for mobility management	97
C.1	Profile exchange	97
C.2	Profile definitions	97
C.2.1	General on SS-CF profiles	97
C.2.2	PDU definitions	97
C.2.2.1	SS-PROFILE REJECT PDU	97
C.2.2.2	SS-PROFILE UPDATE PDU	98
C.2.2.3	SS-PROFILE UPDATE RESPONSE PDU	98
C.2.3	Information element definitions	99
C.2.3.1	Basic migration profile info	99
C.2.3.2	Individual basic migration profile (original and temporary)	100
C.2.3.3	Profile type	100
C.2.3.4	Profile status	101
C.2.3.5	SS-information	101
C.2.3.6	SS-information response	101
C.2.3.7	SS-migration profile (original)	102
C.2.3.8	SS-migration profile response (temporary)	102
C.2.3.9	SS-profile response status	102
C.2.3.10	SS-profile update indicator	103
C.2.3.11	SS-response status	103
C.2.3.12	SS-status	103
C.2.3.13	SS-type	103
C.2.3.14	SS-CF profiles	104
C.2.3.14.1	SS-CF migration original profile	104
C.2.3.14.2	SS-CF served user migration information PDU	104
C.2.3.14.3	Number of Call forwarding types information element content	105
Annex D (informative):	Specification and Description Language (SDL) representation of procedures	106
Annex E (informative):	Bibliography	107
Annex F (informative):	Change Requests	108
History		109

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA).

The present document is part 12, sub-part 4 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

- EN 300 392-1: "General network design";
- EN 300 392-2: "Air Interface (AI)";
- EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";
- ETS 300 392-4: "Gateways basic operation";
- EN 300 392-5: "Peripheral Equipment Interface (PEI)";
- EN 300 392-7: "Security";
- EN 300 392-9: "General requirements for supplementary services";
- EN 300 392-10: "Supplementary services stage 1";
- EN 300 392-11: "Supplementary services stage 2";
- EN 300 392-12: "Supplementary services stage 3";**
 - EN 300 392-12-1: "Call Identification (CI)";
 - ETS 300 392-12-2: "Call Report (CR)";
 - EN 300 392-12-3: "Talking Party Identification (TPI)";
 - EN 300 392-12-4: "Call Forwarding (CF)";**
 - ETS 300 392-12-5: "List Search Call (LSC)";
 - EN 300 392-12-6: "Call Authorized by Dispatcher (CAD)";
 - ETS 300 392-12-7: "Short Number Addressing (SNA)";
 - EN 300 392-12-8: "Area Selection (AS)";
 - ETS 300 392-12-9: "Access Priority (AP)";
 - EN 300 392-12-10: "Priority Call (PC)";
 - ETS 300 392-12-11: "Call Waiting (CW)";
 - EN 300 392-12-12: "Call Hold (HOLD)";

ETS 300 392-12-13: "Call Completion to Busy Subscriber (CCBS)";

EN 300 392-12-14: "Late Entry (LE)";

EN 300 392-12-16: "Pre-emptive Priority Call (PPC)";

EN 300 392-12-17: "Include Call (IC)";

EN 300 392-12-18: "Barring of Outgoing Calls (BOC)";

EN 300 392-12-19: "Barring of Incoming Calls (BIC)";

ETS 300 392-12-20: "Discreet Listening (DL)";

EN 300 392-12-21: "Ambience Listening (AL)";

EN 300 392-12-22: "Dynamic Group Number Assignment (DGNA)";

ETS 300 392-12-23: "Call Completion on No Reply (CCNR)";

ETS 300 392-12-24: "Call Retention (CRT)";

ETS 300 392-13: "SDL model of the Air Interface (AI)";

ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

TS 100 392-15: "TETRA frequency bands, duplex spacing and channel numbering";

TS 100 392-16: "Network Performance Metrics";

TR 100 392-17: "TETRA V+D and DMO specifications";

TS 100 392-18: "Air interface optimized applications";

SIST EN 300 392-12-4 V1.2.1:2010
National transposition dates
<https://standards.iteh.ai/catalog/standards/sist/en-300-392-12-4-v1-2-1-2010/87d-415d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010>

Date of adoption of this EN:	15 July 2010
Date of latest announcement of this EN (doa):	31 October 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2011
Date of withdrawal of any conflicting National Standard (dow):	30 April 2011

Introduction

The supplementary service stage 3 description is preceded by the stage 1 [2] and the stage 2 [3] description of the service, according to the method described in ITU-T Recommendation I.130 [i.4]. The stage 1 description specifies the service from the user's point of view. The stage 2 description identifies the functional capabilities of each SS and the information flows needed to support the supplementary service as specified in its stage 1 description. The present stage 3 description specifies the protocols at the air interface and at the various Inter-System Interfaces (ISI) to support each Supplementary Service.

NOTE: According to ITU-T Recommendation I.130 [i.4], the stage 3 description of any telecommunication service addresses the network implementation aspects. Consequently it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step. The latter have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

1 Scope

The present document specifies the stage 3 description of the Supplementary Services CFU Call Forwarding Unconditional, CFB Call Forwarding on Busy, CFNRy Call Forwarding on No Reply and CFNRc Call Forwarding on Not Reachable for the Terrestrial Trunked Radio (TETRA).

SS-CFU, SS-CFB, SS-CFNRy and SS-CFNRc are supplementary services which allow a served user to have a TETRA network send all or specific incoming calls addressed to the served user's TETRA number to another number.

Man-Machine Interface and charging principles are outside the scope of the present document.

The present document is applicable to Voice plus Data individual call or group call; some parts of the present document are applicable to SDS (Short Data Service); more specifically to the following entities:

- the MS of either the calling user or the called user during an individual call or a group call;
- the originating Switching and Management Infrastructure (SwMI) in an individual call or a group call;
- the group controlling SwMI for a group call;
- the terminating SwMI in an individual call;
- the interworking SwMI for an individual call.

The present document is based on the latest version of ECMA-174 [i.1]. Contrary to ECMA-174 [i.1], the present document does not define Call Deflection supplementary service and the present document distinguishes between the case of No Reply and the case of Not Reachable. Moreover, the present document defines the protocol in cases of group calls and of mobility not covered by ECMA-174 [i.1].

The present document also specifies additional signalling protocol requirements for the support of interactions at the ISI reference point, other supplementary services and ANFs. The present document is applicable to SwMIs that can interconnect to form a TETRA network.

<https://standards.iteh.ai/catalog/standards/sist/b6ea0e59-e87d-415d-9c49-493ed49637cc/sist-en-300-392-12-4-v1-2-1-2010>

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-10-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 4: Call Forwarding (CF)".
- [3] ETSI EN 300 392-11-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 4: Call Forwarding (CF)".
- [4] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".

- [5] ETSI EN 300 392-3-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 1: General design".
- [6] ETSI EN 300 392-3-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)".
- [7] ETSI EN 300 392-3-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".
- [8] ETSI EN 300 392-3-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 4: Additional Network Feature Short Data Service (ANF-ISISDS)".
- [9] ETSI EN 300 392-10-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 1: Call Identification (CI)".
- [10] ETSI ETS 300 392-12-13: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 13: Call Completion to Busy Subscriber (CCBS)".
- [11] ETSI ETS 300 392-12-23: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 23: Call Completion on No Reply (CCNR)".
- [12] ETSI EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [13] ETSI EN 300 195-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Supplementary service interactions; Part 1: Protocol specification".
- [14] ETSI EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [15] ETSI EN 300 392-3-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [16] ETSI EN 300 207-1 (V1.2.5): "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [17] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [18] ITU-T Recommendation X.219: "Remote Operations: Model, notation and service definition".
- [19] ITU-T Recommendation X.229: "Remote Operations: Protocol specification".
- [20] ITU-T Recommendation X.217: "Information technology - Open Systems Interconnection - Service definition for the Association Control Service Element".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ECMA-174: "Private Integrated Services Network (PISN) - Inter-Exchange Signalling Protocol - Call Diversion Supplementary Services (QSIG-CF)".
- [i.2] ITU-T Recommendation I.210: "Principles of telecommunication services supported by an ISDN and the means to describe them".

- [i.3] ITU-T Recommendation Z.100: "ITU-T Specification and Description Language (SDL)".
- [i.4] ITU-T Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.5] ITU-T Recommendation Q.9: "Vocabulary of switching and signalling terms".
- [i.6] ECMA-173: "Private Integrated Services Network (PISN) - Specification, Functional Model and Information Flows - Call Diversion Supplementary Services (CFSD)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Additional Network Feature (ANF): capability, over and above that of a basic service, provided by a SwMI, but not directly to a SwMI user

busy: user is engaged in another telecommunication service

NOTE: TETRA destination is considered to be busy if either a "network determined user busy" NDUB or a "user determined user busy" UDUB condition exists by analogy to ISDN.

call, basic call: instance of the use of a basic service

call forwarding type: reason for call forwarding

NOTE: In order to distinguish SS-CFU, SS-CFB, SS-CFNRY and SS-CFNRC, the (invoked call) forwarding type is used; the word "type" instead of "procedure" is used to avoid possible confusions with other use of the word "procedures" e.g. signalling procedure, etc.

forwarded-to number: number to which a call is forwarded

forwarded-to SwMI: SwMI serving the forwarded-to user

forwarded-to user: user to which a call is forwarded

forwarding: redirection of a call, on behalf of a called user and prior to answer, to a number different from the number of that called user

forwarding number: forwarding number is the number of the served user

forwarding SwMI: forwarding SwMI is the SwMI which executes call forwarding

NOTE: In case of re-routeing, the forwarding SwMI is either the originating SwMI or the incoming gateway SwMI. In case of forward switching, the forwarding SwMI is the terminating SwMI.

forwarding type: cause for the forwarding: CFU, CFB, CFNRY or CFNRC

NOTE: Forwarding cause is called forwarding type in the present document.

forwarding user: called user for which the call forwarding is invoked

NOTE: Forwarding user may be the called user first and then any of the successive forwarded-to users (see also last forwarding user).

forward switching: network routeing algorithm which performs the redirection by joining together the first connection from user A's node to user B's node and a second, new connection from user B's node to user C's node

NOTE: In TETRA the connections between users may not exist before the user C has answered to the call.

forward switching SwMI: SwMI which performs the forwarding of the call by joining together the first connection from user A's node to user B's node and a second, new connection from user B's node to user C's node

NOTE: In TETRA the connections between users may not exist before the user C has answered to the call.

forwarding type: reason for forwarding

NOTE: The forwarding type and the call forwarding type may be used interchangeably.

last forwarding user: served user from the point of view of the forwarded-to user for a particular stage of call forwarding

NOTE: In the case of a call subject to a single stage of call forwarding, user B is the last forwarding user from the point of view of user C. In the case of a call subject to multiple stages of call forwarding, user B1 is the last forwarding user from the point of view of user B2, user B2 is the last forwarding user from the point of view of user B3, etc. The served user for the final stage of call forwarding is the last forwarding user from the point of view of user C.

Mobile Station (MS): physical grouping that contains all of the mobile equipment that is used to obtain TETRA services

original called number: number of the first called user B in the call (in case of multiple call forwarding user B1)

original called user: first served user of a call which is subject to one or more stages of call forwarding, i.e. user B or B1

partial re-routeing: network routeing algorithm which performs the call forwarding by replacing a particular part of the connection from user A's node to user B's node by another connection from user A's node to user C's node

re-routeing: network routeing algorithm which performs the call forwarding by replacing the connection from user A's node to user B's node by another connection from user A's node to user C's node

served user: user for which the call forwarding supplementary service concerned has been subscribed

NOTE: When a call is made to a served user and call forwarding is invoked, this user may then also be referred to as the forwarding user or if it is the first call forwarding the (original) called user.

served user SwMI: SwMI where the served user is currently registered; it may be served user home SwMI or a visited SwMI

signalling connection: connection used to exchange information between peer supplementary service protocol control entities independently of a basic call

SS-CF invocation counter: counter for the number of call forwarding involved in a call or signalling connection during the call establishment phase

supplementary service: any service provided by a network in addition to its basic service or services (defined in ITU-T Recommendation Q.9 [i.5])

NOTE: A supplementary service modifies or supplements a basic telecommunication service. Consequently, it cannot be offered to a customer as a stand alone service. "It must be offered together with or in association with a basic telecommunication service" (excerpt from ITU-T Recommendation I.210 [i.2]).

Switching and Management Infrastructure (SwMI): all of the TETRA equipment for a Voice plus Data (V+D) network except for subscriber terminals

NOTE: The SwMI enables subscriber terminals to communicate with each other via the SwMI.

SwMI number: SwMI number is a number belonging to a SwMI numbering plan (ITSI or GTSI)

user A: calling user of a call which is subject to call forwarding

user B: served user (or forwarding user) of a call which is subject to call forwarding