

SLOVENSKI STANDARD

SIST EN 12640:2000

01-december-2000

Securing of cargo on road vehicles - Lashing points on commercial vehicles for goods transportation - Minimum requirements and testing

Securing of cargo on road vehicles - Lashing points on commercial vehicles for goods transportation - Minimum requirements and testing

Ladungssicherung auf Straßenfahrzeugen - Zurrpunkte an Nutzfahrzeugen zur Güterbeförderung - Mindestanforderungen und Prüfung

Arrimage des charges a bord des véhicules routiers - Points d'arrimage a bord des véhicules utilitaires pour le transport des marchandises - Prescriptions minimales et essais

<https://standards.iteh.ai/catalog/standards/sist/805564d6-2eff-485f-a506-953588c60019/sist-en-12640-2000>

Ta slovenski standard je istoveten z: EN 12640:2000

ICS:

43.080.01	Tovorna vozila na splošno	Commercial vehicles in general
55.180.99	Drugi standardi v zvezi z distribucijo blaga s prevozom	Other standards related to freight distribution of goods

SIST EN 12640:2000

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 12640:2000

<https://standards.iteh.ai/catalog/standards/sist/805564d6-2eff-485f-a506-953588c60019/sist-en-12640-2000>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 12640

July 2000

ICS 43.080.10; 55.180.99

English version

Securing of cargo on road vehicles - Lashing points on
commercial vehicles for goods transportation - Minimum
requirements and testing

Arrimage des charges à bord des véhicules routiers -
Points d'arrimage à bord des véhicules utilitaires pour le
transport des marchandises - Prescriptions minimales et
essais

Ladungssicherung auf Straßenfahrzeugen - Zurrpunkte an
Nutzfahrzeugen zur Güterbeförderung -
Mindestanforderungen und Prüfung

This European Standard was approved by CEN on 30 June 2000.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Content

	Page
Foreword	3
1 Scope	4
2 Terms and definitions	4
2.1 Lashing point	4
2.2 Lashing equipment	4
2.3 Angle of inclination β	4
2.4 Angle of rotation α	4
3 Identification	4
4 Requirements	5
4.1 Design requirements	5
4.2 Number and layout of the lashing points	5
4.3 Strength of the lashing points	7
4.4 Verification	7
5 Testing	7
6 Marking	7
Annex A (informative) Example of calculation	8

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 12640:2000

<https://standards.iteh.ai/catalog/standards/sist/805564d6-2eff-485f-a506-953588c60019/sist-en-12640-2000>

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 119 "Swap bodies for combined goods transport", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2001 and conflicting national standards shall be withdrawn at the latest by January 2001.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Annex A is informative.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 12640:2000

<https://standards.iteh.ai/catalog/standards/sist/805564d6-2eff-485f-a506-953588c60019/sist-en-12640-2000>

1 Scope

This Standard specifies the minimum requirements and test methods for lashing points fitted to commercial vehicles and trailers with flatbed body construction of maximum total mass above 3,5 t and intended for general use.

The standard does not apply to

- Vehicles designed and constructed exclusively for the transportation of bulk materials;
- Vehicles designed and constructed exclusively for the transportation of specific cargo with particular securing requirements.

2 Terms and definitions

For the purpose of this standard the following terms and definitions apply :

2.1 Lashing point

Securing device on a vehicle to which a lashing may be directly attached. A lashing point can be e.g. an oval link, a hook, a ring, a lashing shoulder.

2.2 Lashing equipment

Device designed to be attached to the lashing points in order to secure the cargo on the vehicle. The lashing equipment consists of tensioning elements (e.g. belt, chain, cable), tensioning device (e.g. wrench, ratchet, spanner, tension jack) and connections, if required (e.g. hook, eyelet).

2.3 Angle of inclination β

The angle between a vertical line through the lashing point and the direction of application of the lashing force (see figure 1).

2.4 Angle of rotation α

The smallest angle between a plane through the lashing point parallel to the vehicle's longitudinal centre plane and a vertical plane through the direction of application of the lashing force (see figure 1).

3 Identification

To comply with this Standard the lashing points shall be identified by reference to the number of this Standard and the permissible tensile load according to 4.3.

EXAMPLE Identification of a lashing point for a permissible tensile load of e.g. 20 kN:

Lashing point EN 12640 -20.

4 Requirements

4.1 Design requirements

4.1.1 Lashing points shall be designed so that they transmit the forces they receive into the structural elements of the vehicle. They shall be fixed in the loading platform and in the vertical front end wall. In their position of rest they shall not project above the horizontal level of the loading platform nor beyond the vertical surface of the front end wall into the loading space.

NOTE The recesses in the loading platform required to accommodate the lashing points should be as small as possible.

4.1.2 Lashing points shall be designed to accommodate lashing forces applied from any direction within the conical area determined as follows (see figure 1):

- angle of inclination β from 0° to 60°
- angle of rotation (α) from 0° to 180° for lashing points with a transverse distance from the side wall and the lashing points ≤ 50 mm;
- angle of rotation (α) from 0° to 360° for lashing points within a transverse distance from the side wall and the lashing points ≥ 50 mm but ≤ 250 mm.

4.1.3 If the lashing point has a round inside profile then the useable inside diameter shall be ≥ 40 mm. If it is oval then the clearance in the most unfavourable angle position shall have a width of ≥ 25 mm and a length of ≥ 40 mm.

The material cross section of the ring or of an oval link shall fit into a circle with a diameter of ≤ 18 mm (see figure 2).

Rings which can move around their complete perimeter when lashed shall not be permitted.

4.1.4 The lashing points shall be designed so as not to compromise the splash protection and the customs security of the cargo area.

4.2 Number and layout of the lashing points

4.2.1 Lashing points on the floor

4.2.1.1 The number of lashing points shall be determined by the highest result of the following:

- length of the loading platform (see 4.2.1.2)
- maximum distance between lashing points (see 4.2.1.3)
- permissible tensile load (see 4.2.1.4).

4.2.1.2 For vehicles with an effective cargo loading length not exceeding 2200 mm there shall be at least 4 lashing points - at least 2 on each side.

For vehicles with an effective cargo loading length greater than 2200 mm there shall be at least 6 lashing points - at least 3 on each side.

4.2.1.3 The lashing points are to be arranged in such a way that

- with the exception of the area above the rear axle the distance between two adjacent lashing points on one side shall be not more than 1200 mm. In the area above the rear axle the distance between two adjacent lashing points shall be as close to 1200 mm as practicable but in any case shall not be more than 1500 mm;
- the distance from front or rear end wall shall not be greater than 500 mm;
- the distance from the side walls of the loading area should be as small as possible and in any case shall not be greater than 250 mm.

4.2.1.4

a) For vehicles with a maximum authorised total mass greater than 12 tonnes the number of lashing points X shall be calculated by use of the formula (1).

$$X = \frac{1,5 \times P}{20} \quad (1)$$

In this case P is the inertial force in kN resulting from the maximum payload.

b) for vehicles with a maximum total mass exceeding 7,5 tonnes, but not greater than 12 tonnes the number of lashing points X shall be calculated by using the formula (2).

$$X = \frac{1,5 \times P}{10} \quad (2)$$

c) for vehicles with a maximum total mass exceeding 3,5 tonnes, but not greater than 7,5 tonnes the number of lashing points X shall be calculated by using the formula (3).

$$X = \frac{1,5 \times P}{8} \quad (3)$$

4.2.2 Lashing points in the front wall

The front wall of a vehicle shall be equipped with at least 2 lashing points mounted symmetrically on either side of the vehicle centre line. The lashing points shall be located such that

- a) the vertical distance of the two lashing points measured from the surface of the loading platform is 1000 mm \pm 200 mm (see figure 1),
- b) the distance measured in transverse direction from the side of the front wall should be as small as possible and in any case not greater than 250 mm.

4.3 Strength of the lashing points

4.3.1 Each lashing point on the loading platform shall be designed for a permissible tensile load as specified in table 1.

Table 1

maximum allowed mass (m) of the vehicle in t	permissible tensile load for lashing point in kN *
$3,5 < m \leq 7,5$	8
$7,5 < m \leq 12$	10
$m > 12$	20
* 1 kN = 100 daN	

4.3.2 Each lashing point on the front wall shall be designed for a permissible load of 10 kN.

4.4 Verification

The reference test method for compliance with this standard shall be as specified in clause 5. Upon completion of the test there shall be no permanent deformation which could impair the function of the lashing point.

The strength of the lashing points may also be determined by calculation, provided that the equivalence of the calculation to the reference test method can be demonstrated.

5 Testing

5.1 One lashing point on the loading platform and one lashing point on the front end wall shall be used for testing. The test force F to be applied shall be 1,25 times the permissible tensile force. In the test, the lashing point shall be connected to a suitable lashing hook in accordance with the manufacturers instructions.

5.2 The direction of application of the test force shall lie within the ranges of angles defined in 4.1.2. One test shall be performed in each of the three most unfavourable directions of application.

5.3 The test force shall be applied for at least 3 min.

5.4 To apply the test forces a test frame shall be used which shall be fixed appropriately to the load area (see figure 3) or the bulkhead (analogous). This frame shall be fitted with its longitudinal edge 500 ± 30 mm from the lashing point being tested, parallel to the longitudinal axis of the vehicle. The width of the frame corresponds to the distance between the lashing points arranged in pairs less 1000 mm. The width of the frame sections is ≥ 50 mm.

6 Marking

Vehicles with lashing points in compliance with this standard, shall be fitted with a marking plate in accordance with figure 4 in a clearly visible place. For the convenience of the users the tensile load should be indicated in daN. The plate shall have a blue background, white lettering and white border.