

---

---

**Information technology — Generic coding  
of moving pictures and associated audio  
information —**

**Part 6:  
Extensions for DSM-CC**

iTeh STANDARD PREVIEW

**AMENDMENT 1**

(standards.iteh.ai)

**Additions to support data broadcasting**

ISO/IEC 13818-6:1998/Amd 1:2000

[https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-](https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e479c750e/iso-iec-13818-6-amd-1-2000)

[0d1e479c750e/iso-iec-13818-6-amd-1-2000](https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e479c750e/iso-iec-13818-6-amd-1-2000)

**Technologies de l'information — Codage générique des images animées et  
des informations sonores associées —**

*Partie 6: Extensions pour DSM-CC*

*AMENDEMENT 1*

*Additions à la diffusion de soutien de données*

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 13818-6:1998/Amd 1:2000](https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e4b480e65/iso-iec-13818-6-1998-amd-1-2000)

<https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e4b480e65/iso-iec-13818-6-1998-amd-1-2000>

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this Amendment may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to International Standard ISO/IEC 13818-6:1998 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e4b480e65/iso-iec-13818-6-1998-amd-1-2000>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 13818-6:1998/Amd 1:2000

<https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e4b480e65/iso-iec-13818-6-1998-amd-1-2000>

# Information technology — Generic coding of moving pictures and associated audio information — Part 6: Extensions for DSM-CC

## AMENDMENT 1: Additions to support data broadcasting

1) Replace the semantic definition of DownloadInfoIndication **moduleSize** in subclause 7.3.2 with the following:

"  
The **moduleSize** field is the length, in bytes, of the described module. A value of zero indicates that the module size is not specified.  
"

2) Replace the last paragraph in subclause 9.2.1 with the following:

"  
MPEG-2 Systems, ISO/IEC 13818-1:2000, defines generic table section syntax that DSM-CC uses to provide re-assembly of Transport Stream packets into DSM-CC messages. This specification defines additional semantics on ISO/IEC 13818-1:2000 sections to support additional DSM-CC requirements. Called DSMCC\_section and DSMCC\_Addressable\_section, the syntax is compatible with the generic section syntax so that compliant MPEG-2 Systems decoders may be used.  
"

3) In subclause 9.2.2, replace every occurrence of "private\_section" with "generic\_section"

4) In subclause 9.2.2, replace every occurrence of "private\_indicator" with "complement\_indicator".

5) Replace Table 9-3 with the following:

**Table 9-3 DSM-CC table\_id assignments**

| table_id    | DSMCC Section Type   |
|-------------|--|
| 0x00 - 0x37 | ITU-T Rec. H.222.0   ISO/IEC 13818-1 defined                           |
| 0x38 - 0x39 | ISO/IEC 13818-6 reserved   |
| 0x3A        | DSM-CC Sections containing multi-protocol encapsulated data            |
| 0x3B        | DSM-CC Sections containing U-N Messages, except Download Data Messages |
| 0x3C        | DSM-CC Sections containing Download Data Messages                      |
| 0x3D        | DSM-CC Sections containing Stream Descriptors                          |
| 0x3E        | DSM-CC Sections containing private data                                |
| 0x3F        | DSM-CC Addressable Sections  |
| 0x40 - 0xFE | User private   |
| 0xFF        | forbidden  |

6) In subclause 9.2.2.1 replace the corresponding paragraphs with the following:

"  
**version\_number** -- This field is a 5-bit field. If the value of the table\_id field equals 0x3A or 0x3B, this field shall be set to zero. If the value of the table\_id field equals 0x3C and a DownloadDataBlock Message is conveyed, this field shall have the value of the least significant 5 bits of the moduleVersion field of the conveyed DownloadDataBlock Message. If the value of the table\_id field equals 0x3C and a DownloadDataRequest Message is conveyed, this

field shall be set to zero. If the value of table\_id equals 0x3D, then this field shall be set as defined in ISO/IEC 13818-1:2000. If the value of the table\_id field equals 0x3E, then the value and use of this field are defined by the user.

**current\_next\_indicator** -- This is a 1 bit flag. If the value of the table\_id field equals 0x3A, 0x3B or 0x3C, this bit shall be set to '1'. Otherwise, this field shall be set as defined in ISO/IEC 13818-1:2000.

**section\_number** -- This field is a 8-bit field. If the value of the table\_id field equals 0x3A or 0x3B, this field shall be set to zero. If the value of the table\_id field equals 0x3C, this field shall have a value of the least significant 8 bits of the blockNumber field of the conveyed DownloadDataBlock or DownloadDataRequest Message. If the value of the table\_id field is not in the range of 0x3A to 0x3C, then this field shall be set as defined in ISO/IEC 13818-1:2000.

**last\_section\_number** -- This field is a 8-bit field. This field specifies the number of the last section (that is, the section with the highest section number) of the table of which this section is a part. (Note: This means that this field shall be set to the maximum value that is encoded in the section\_number field for the same table\_id, table\_id\_extension and version\_number field).

"

7) Delete the footnote under Table 9-2.

8) Add the following to subclause 9.2.2.1 after last\_section\_number:

"

**LLCSNAP()** -- This structure shall contain the datagram according to the ISO/IEC 8802-2 Logical Link Control (LLC) and ISO/IEC 8802-1a SubNetwork Attachment Point (SNAP) specifications. For more information, see subclause 9.2.5, Encapsulation within MPEG-2 Transport Streams.

"



9) Add the following subclauses after subclause 9.2.2:

"

**9.2.3 DSM-CC Addressable Sections** [ISO/IEC 13818-6:1998/Amd 1:2000](https://standards.itech.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-)

<https://standards.itech.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7->

The DSMCC\_addressable\_section() format is used to send a DSM-CC encapsulated datagram to a specific device or group of devices. This format embeds the deviceld of the target device into the section header to allow address filtering at the section level. It also supports scrambling mechanisms.

The following table defines the format and semantics of the DSMCC\_addressable\_section:

**Table 9-4 Addressable Sections**

| Syntax                            | No. of bits | Mnemonic      |
|-----------------------------------|-------------|---------------|
| DSMCC_addressable_section() {     |             |               |
| <b>table_id</b>                   | <b>8</b>    | <b>uimsbf</b> |
| '0'                               | 1           |               |
| <b>error_detection_type</b>       | <b>1</b>    | <b>bslbf</b>  |
| <b>reserved</b>                   | <b>2</b>    | <b>bslbf</b>  |
| <b>addressable_section_length</b> | <b>12</b>   | <b>uimsbf</b> |
| <b>deviceld[7..0]</b>             | <b>8</b>    | <b>uimsbf</b> |
| <b>deviceld[15..8]</b>            | <b>8</b>    | <b>uimsbf</b> |
| <b>reserved</b>                   | <b>2</b>    | <b>bslbf</b>  |
| <b>payload_scrambling_control</b> | <b>2</b>    | <b>bslbf</b>  |
| <b>address_scrambling_control</b> | <b>2</b>    | <b>bslbf</b>  |
| <b>LLCSNAP_flag</b>               | <b>1</b>    | <b>bslbf</b>  |
| '1'                               | 1           |               |
| <b>section_number</b>             | <b>8</b>    | <b>uimsbf</b> |
| <b>last_section_number</b>        | <b>8</b>    | <b>uimsbf</b> |
| <b>deviceld[23..16]</b>           | <b>8</b>    | <b>uimsbf</b> |
| <b>deviceld[31..24]</b>           | <b>8</b>    | <b>uimsbf</b> |
| <b>deviceld[39..32]</b>           | <b>8</b>    | <b>uimsbf</b> |

```

deviceld[47..40]                8      uimsbf
if (LLCSNAP_flag == '1') {
    LLCSNAP()
}
else{
    for (j=0;j<N1;j++) {
        datagram_data_byte        8      bslbf
    }
}
if (section_number ==
last_section_number) {
    for (j=0;j<N2;j++) {
        stuffing_byte            8      bslbf
    }
}

if (error_detection_type == 1) {
    checksum                    32     uimsbf
}
else {
    CRC_32                      32     rpchof
}
}

```

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

**9.2.3.1 Semantic definitions of fields in DSMCC\_addressable\_section**

For field semantics not defined below, refer to subclause 9.2.2.1.

**table\_id** -- this is an 8-bit field which shall be set to 0x3F.

**error\_detection\_type** -- This is a 1 bit flag. When set to '1', it indicates the presence of the checksum field. When set to '0', it indicates the presence of the CRC\_32 field.

**deviceld** -- This 48-bit field contains the deviceld of the intended device. The deviceld is fragmented into 6 fields of 8-bits. The deviceld fields contain either a clear or a scrambled deviceld as indicated by the address\_scrambling\_control field.

**payload\_scrambling\_control** -- This 2-bit field defines the scrambling mode of the payload of the section. This includes the payload that starts after the deviceld[47..40] byte and excludes the checksum field. The value of this field is defined in the following table. The scrambling method applied is user private.

**Table 9-5 Coding of the payload\_scrambling\_control field**

| Value | payload scrambling control |
|-------|----------------------------|
| 00    | unscrambled                |
| 01    | user defined               |
| 10    | user defined               |
| 11    | user defined               |

**address\_scrambling\_control** -- This 2-bit field defines the scrambling mode of deviceld in this section. The scrambling method applied is user private.

**Table 9-6 Coding of the address\_scrambling\_control field**

| Value | address scrambling control |
|-------|----------------------------|
| 00    | unscrambled                |
| 01    | user defined               |
| 10    | user defined               |
| 11    | user defined               |

**LLCSNAP\_flag** -- This is a 1-bit flag. If this flag is set to '1', the payload carries an LLC/SNAP encapsulated datagram following the deviceld[47..40] field. The LLC/SNAP structure shall indicate the type of the datagram conveyed. If this flag is set to '0', the section shall contain an IP datagram without LLC/SNAP encapsulation. See subclause 9.2.5 for use of LLC/SNAP.

**datagram\_data\_byte** -- This 8 bit field shall contain a byte of the datagram payload.

**stuffing\_byte** -- This is an optional 8-bit field whose value is not specified. Note: If the payload of the section is scrambled, these bytes shall be scrambled. The number of stuffing\_bytes used should meet the data alignment requirements defined by the user.

**CRC\_32** -- This field shall be set as defined in ISO/IEC 13818-1:2000 Annex B. This field is only present when error\_detection\_type is set to '0'.

**checksum** -- A 32 bit checksum calculated over the entire DSMCC\_addressable\_section. The checksum shall be calculated by treating the DSMCC\_addressable\_section as a sequence of 32-bit integers and performing one's complement addition (an Exclusive-Or or XOR operation) over all the integers, most significant byte first, then taking the one's complement of the result. For the purpose of computing the checksum, the value of the checksum field shall be considered 0. If the message length is not a multiple of four bytes, the message shall be considered to be appended with zeroed bytes for the purpose of checksum calculation only. If the computed result is 0, then the result shall be set to 0xFFFFFFFF (the alternative value for a one's complement representation of 0). In cases where a checksum is not desired, the value of this field shall be set to 0 to indicate the checksum has not been calculated. This feature is useful for networks where error detection is provided at a protocol layer lower than the MPEG-2 Transport Stream. This field is only present when error\_detection\_type is set to '1'.

"  
10) Replace existing Table 9-4 with the following:

Table 9-7 DSM-CC Stream Types

| stream_type | Description   |
|-------------|---|
| 0x00-0x09   | ITU-T Rec. H.222.0   ISO/IEC 13818-1 defined                                      |
| 0x0A        | Multi-protocol Encapsulation  |
| 0x0B        | DSM-CC U-N Messages   |
| 0x0C        | DSM-CC Stream Descriptors   |
| 0x0D        | DSM-CC Sections (any type, including private data) or DSM-CC Addressable Sections |
| 0x0E - 0x7F | ITU-T Rec. H.222.0   ISO/IEC 13818-1 reserved                                     |
| 0x80 - 0xFF | User private  |

"  
11) Increment numbers of tables by 3 starting with existing Table 9-5 and subclauses by 1 starting with existing subclause 9.2.3:



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 13818-6:1998/Amd 1:2000

<https://standards.iteh.ai/catalog/standards/sist/0cd11566-fd97-4881-9bd7-0d1e4b480e65/iso-iec-13818-6-1998-amd-1-2000>