



SLOVENSKI STANDARD
SIST ISO 6336-1:2002/TC 1:2002
01-julij-2002

Priloga k slovenski standardu SIST ISO 6336-1:2002/TC 1:2002, ki je istovetna s slovenskim standardom SIST ISO 6336-1:1996/Cor 1:1998.

Calculation of load capacity of spur and helical gears — Part 1: Basic principles, introduction and general influence factors - TECHNICAL CORRIGENDUM 1

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ISO 6336-1:1996/Cor 1:1998**
<https://standards.iteh.ai/catalog/standards/sis/160cbb28-2774-47b8-bb16-019562d904bf/sist-iso-6336-1-2002-tc-1-2002>

ICS:

21.200 Gonila Gears

SIST ISO 6336-1:2002/TC 1:2002 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 6336-1:2002/TC 1:2002

<https://standards.iteh.ai/catalog/standards/sist/160ebb28-2774-47b8-bb16-019562d904bf/sist-iso-6336-1-2002-tc-1-2002>

INTERNATIONAL STANDARD ISO 6336-1:1996
TECHNICAL CORRIGENDUM 1

Published 1998-10-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

**Calculation of load capacity of spur and helical gears —
Part 1:
Basic principles, introduction and general influence factors**

TECHNICAL CORRIGENDUM 1

*Calcul de la capacité de charge des engrenages cylindriques à dentures droite et hélicoïdale —
Partie 1: Principes de base, introduction et facteurs généraux d'influence*

RECTIFICATIF TECHNIQUE 1

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

Technical Corrigendum 1 to International Standard ISO 6336-1:1996 was prepared by Technical Committee ISO/TC 60, Gears, Subcommittee SC 2, Gear capacity calculation.

Page 48, subclause 7.6.1

In list item a), amend the first sentence to read as follows:

"..., positioned symmetrically between bearings ($s/l \leq 0,1$, see figure 16)."

Page 49, footnote 9)

Amend the first sentence to read as follows:

"..., i.e. gap width small compared to the facewidth [$(B - 2b_B) \leq 0,5b_B$]."

ICS 21.200

Ref. No. ISO 6336-1:1996/Cor.1:1998(E)

Descriptors: gears, cylindrical gears, spur gears, helical gears, load capacity, rules of calculation, generalities.

© ISO 1998

Printed in Switzerland

Page 57, Figure 16 c)

Amend the limit on s/l to read as follows:

"with $s/l \leq 0,3$ "

Page 77, Table 6

Replace the existing table with the following:

Table 7 — Transverse load factors $K_{H\alpha}$ and $K_{F\alpha}$ determined by method C

Specific Loading ($F_t K_A$) / b			> 100 N/mm					≤ 100 N/mm	
			6	7	8	9	10		11-12
Case or surface hardened nitrided or nitro-carburized	Spur gearing	$K_{H\alpha}$	1,0		1,1	1,2	$1/Z_\epsilon^2 \geq 1,2$		
		$K_{F\alpha}$					$1/Y_\epsilon \geq 1,2$		
	Helical gearing	$K_{H\alpha}$	1,0	1,1 **)	1,2	1,4	$\epsilon_\alpha / \cos^2 \beta_b \geq 1,4 *$		
		$K_{F\alpha}$							
Not hardened nor nitrided nor carburized	Spur gearing	$K_{H\alpha}$	1,0		1,1	1,2	$1/Z_\epsilon^2 \geq 1,2$		
		$K_{F\alpha}$					$1/Y_\epsilon \geq 1,2$		
	Helical gearing	$K_{H\alpha}$	1,0		1,1	1,2	1,4	$e_\alpha / \cos^2 \beta_b \geq 1,4 *$	
		$K_{F\alpha}$							
*) See note 10 in 8.3.4									
**) For modified profiles which accounts for distortion caused with load $K_{H\alpha} = K_{F\alpha} = 1,0$									

<https://standards.iteh.ai/catalog/standards/sist/160ebb28-2774-47b8-bb16-019562d904bf/sist-iso-6336-1-2002-tc-1-2002>