

**SLOVENSKI STANDARD
SIST ISO 6336-2:2002/TC 1:2002
01-julij-2002**

=nfU i b 'bcg]`bcgh]fUj bcncV]`]b 'dcýYj bcncV]` ncVb]_cj '!&"XY. =nfU i b
cVfUc]j UþYj nXfý`jj cgh]`ncVb]` Vc_cj `fUa] Yb^L!HM b] b]`dcdfUj Y_-%

Calculation of load capacity of spur and helical gears — Part 2: Calculation of surface durability (pitting) - TECHNICAL CORRIGENDUM 1

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

Ta slovenski standard je istoveten z: [SIST ISO 6336-2:2002/TC 1:2002](https://standards.iteh.ai/catalog/standards/sist/613315cb-a725-4c09-ab65-cb37236eaacd/sist-iso-6336-2-2002-tc-1-2002)
[ISO 6336-2:1996/Cor 1:1998](https://standards.iteh.ai/catalog/standards/sist/613315cb-a725-4c09-ab65-cb37236eaacd/sist-iso-6336-2-2002-tc-1-2002)

ICS:

21.200 Gonila Gears

SIST ISO 6336-2:2002/TC 1:2002 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST ISO 6336-2:2002/TC 1:2002](#)

<https://standards.iteh.ai/catalog/standards/sist/613315c6-a723-4c09-ab65-cb37236eaacd/sist-iso-6336-2-2002-tc-1-2002>



**INTERNATIONAL STANDARD ISO 6336-2:1996
TECHNICAL CORRIGENDUM 1**

Published 1998-10-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Calculation of load capacity of spur and helical gears — Part 2: Calculation of surface durability (pitting)

TECHNICAL CORRIGENDUM 1

*Calcul de la capacité de charge des engrenages cylindriques à dentures droite et hélicoïdale —
Partie 2: Calcul de la résistance à la pression superficielle (piquage)*

*RECTIFICATIF TECHNIQUE 1 iTeh STANDARD PREVIEW
(standards.iteh.ai)*

Technical Corrigendum 1 to International Standard ISO 6336-2:1996 was prepared by Technical Committee ISO/TC 60, Gears, Subcommittee SC 2, *Gear capacity calculation*.
 SIST ISO 6336-2:2002/TC 1:2002
<https://standards.iteh.ai/catalog/standards/sist-iso-6336-2-2002-1-2002>
 cb37236eaacd/sist-iso-6336-2-2002-1-2002

Page 23, subclause 11.2.1.1

Replace the last sentence with the following:

"The values for ν_{40} apply for the viscosity index, VI = 95 and viscosities up to 500 cSt at 40 °C; for higher viscosity use the value obtained at 500 cSt at 40 °C or 300 cSt at 50 °C to determine the value of K_L ."