



SLOVENSKI STANDARD
oSIST prEN 300 674-3-1 V3.0.0:2010
01-september-2010

Inteligentni transportni sistemi (ITS) - Cestna transportna in prometna telematika (RTTT) - Enouporabniška (osebna) komunikacija kratkega dosega (DSRC) - Tehnične karakteristike in preskusne metode za HDR oddajniško opremo, ki deluje v pasu 5,8 GHz, namenjenem industrijski, znanstveni in medicinski uporabi

Intelligent Transport Systems (ITS) - Road Transport and Traffic Telematics (RTTT) - Dedicated Short Range Communications (DSRC) - Part 3-1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band

(standards.iteh.ai)

[oSIST prEN 300 674-3-1 V3.0.0:2010](https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010)

<https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010>

Ta slovenski standard je istoveten z: EN 300 674-3-1 Version 3.0.0

ICS:

35.240.60	Uporabniške rešitve IT v transportu in trgovini	IT applications in transport and trade
-----------	---	--

oSIST prEN 300 674-3-1 V3.0.0:2010 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 300 674-3-1 V3.0.0:2010](https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010)

<https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010>

Draft ETSI EN 300 674-3-1 V3.0.0 (2010-06)

European Standard (Telecommunications series)

**Intelligent Transport Systems (ITS);
Road Transport and Traffic Telematics (RTTT);
Dedicated Short Range Communications (DSRC);
Part 3-1: Technical characteristics and test methods for High
Data Rate (HDR) data transmission equipment operating in
the 5,8 GHz Industrial, Scientific and Medical (ISM) band**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 300 674-3-1 V3.0.0:2010](https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010)

<https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010>



Reference

REN/ITS-0020014

Keywords

DSRC, ITS, protocol, testing**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN 300 674-3-1 V3.0.0:2010

<https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-f9a6682ac3ad/osist-prEN-300-674-3-1-v3-0-0-2010>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chairecor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Introduction	11
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references.....	14
3 Definitions, symbols and abbreviations	14
3.1 Definitions.....	14
3.1.1 Layer 1 definitions.....	14
3.1.2 Layer 2 definitions.....	18
3.1.3 Layer 7 definitions.....	18
3.1.4 Security definitions.....	18
3.2 Definitions from other standards.....	19
3.2.1 Layer 2 related definitions.....	19
3.2.2 Layer 7 related definitions.....	19
3.3 Symbols.....	19
3.4 Abbreviations	20
4 General	21
4.1 Presentation of equipment for testing purposes.....	21
4.1.1 Choice of model for testing.....	21
4.1.2 Choice of operating frequencies	21
4.1.3 Testing of equipment with or without a permanent external RF port	21
4.1.4 Equipment with a permanent internal RF port.....	21
4.1.5 Equipment with a temporary RF port.....	22
4.1.6 Antennas	22
4.2 Mechanical and electrical design.....	22
4.2.1 General.....	22
4.2.2 Controls	22
4.2.3 Marking	22
4.2.3.1 Equipment identification.....	22
4.2.4 Receiver data squelch	22
4.3 Declarations by the applicant	22
4.4 Auxiliary test equipment	23
4.5 Interpretation of the measurement results	23
5 Test conditions, power sources and ambient temperatures	23
5.1 Normal and extreme test conditions	23
5.2 External test power source.....	23
5.3 Normal test conditions.....	24
5.3.1 Normal temperature and humidity.....	24
5.3.2 Normal test power source	24
5.3.2.1 Mains voltage.....	24
5.3.2.2 Regulated lead-acid battery power sources	24
5.3.2.3 Other power sources.....	24
5.4 Extreme test conditions	24
5.4.1 Extreme temperatures	24
5.4.1.1 Procedure for tests at extreme temperatures.....	24
5.4.1.1.1 Procedure for equipment designed for continuous transmit operation.....	24
5.4.1.1.2 Procedure for equipment designed for intermittent transmit operation	25
5.4.1.2 Extreme temperature ranges.....	25
5.4.2 Extreme test source voltages.....	25
5.4.2.1 Mains voltage.....	25
5.4.2.2 Lead-acid battery, regulated power sources	25

5.4.2.3	Power sources using other types of batteries.....	26
5.4.2.4	Other power sources.....	26
6	General conditions.....	26
6.1	Test signals and test modulation.....	26
6.1.1	Normal test signals (wanted and unwanted signals)	26
6.1.1.1	Signals for bit stream measurements.....	27
6.1.1.2	Signal for messages.....	27
6.2	Modes of operation of the transmitter	27
6.3	Encoder for receiver measurements	28
6.4	Facilities for access	28
6.4.1	Analogue access.....	28
6.4.2	Access points for data stream measurement	28
6.4.3	Coupling arrangements	29
6.4.3.1	Arrangements for measurements with continuous bit streams	29
6.4.3.2	Arrangement for measurements with messages	29
6.4.4	Message received indicator.....	29
6.5	Test sites and general arrangements for radiated measurements	29
6.6	Artificial antenna.....	29
6.7	Test fixture	29
6.7.1	Calibration	30
6.7.2	Mode of use	30
6.8	Specific RSU test conditions	30
6.8.1	Antenna polarization.....	30
6.8.2	Signal modulation.....	31
6.8.3	Data coding.....	31
6.8.4	Bit rate	31
6.8.5	Angular E.I.R.P. mask.....	31
6.8.6	Wake-up trigger for OBU.....	31
6.9	Specific OBU test conditions	32
6.9.1	Antenna polarization.....	32
6.9.2	Modulation on carrier	32
6.9.3	Data coding.....	32
6.9.4	Use of sidebands.....	32
6.9.5	Responding bit rate and sub-carrier frequencies.....	32
6.9.6	Antenna characteristics.....	32
7	Layer 1: Methods of measurement and limits for road side unit transmitter parameters.....	33
7.1	Generalities.....	33
7.2	Equivalent isotropically radiated power (e.i.r.p.)	33
7.2.1	Definition.....	33
7.2.2	Method of measurement	33
7.2.3	Limits.....	34
7.3	Frequency error	34
7.3.1	Definition.....	34
7.3.2	Method of measurement	34
7.3.3	Limits.....	34
7.4	Transmitter spectrum mask	34
7.4.1	Definition.....	34
7.4.2	Method of measurement	35
7.4.3	Limits.....	35
7.5	Modulation depth	36
7.5.1	Definition.....	36
7.5.2	Method of measurement	36
7.5.3	Limits.....	36
7.6	Eye pattern.....	37
7.6.1	Definition.....	37
7.6.2	Method of measurement	37
7.6.3	Limits.....	38
7.7	Spurious emissions	38
7.7.1	Definition.....	38
7.7.2	Measuring receiver	38

7.7.3	Method of measurement conducted spurious emission.....	38
7.7.4	Method of measurement cabinet spurious radiation	39
7.7.5	Method of measurement radiated spurious emission	40
7.7.6	Limits.....	40
8	Layer 1: Methods of measurement and limits for road side unit receiver parameters	40
8.1	Maximum useable sensitivity	41
8.1.1	Definition.....	41
8.1.2	Method of measurements under normal and extreme test conditions	41
8.1.2.1	Test arrangement for equipment with integral antenna	41
8.1.2.2	Test arrangement for equipment with antenna connector	43
8.1.2.3	Test procedure for continuous bit streams	43
8.1.2.4	Test procedure for messages	44
8.1.3	Limits.....	44
8.2	Error behaviour at high wanted input signals	44
8.2.1	Definition.....	44
8.2.2	Method of measurement	44
8.2.3	Limits.....	45
8.3	Degradation measurements	45
8.3.1	Definition.....	45
8.3.2	General conditions	45
8.3.3	Co-channel rejection	46
8.3.3.1	Definition	46
8.3.3.2	Method of measurement.....	46
8.3.3.3	Limits	47
8.3.4	Adjacent channel selectivity	47
8.3.4.1	Definition	47
8.3.4.2	Method of measurement.....	47
8.3.4.3	Limits	48
8.3.5	Spurious response rejection and blocking/desensitization.....	48
8.3.5.1	Definition	48
8.3.5.2	Method of measurement.....	48
8.3.5.3	Limits	49
8.3.6	Intermodulation response rejection.....	49
8.3.6.1	Definition	49
8.3.6.2	Method of measurement.....	49
8.3.6.3	Limits	50
8.4	Spurious emissions	50
8.4.1	Definition.....	50
8.4.2	Method of measurement - conducted spurious emissions.....	50
8.4.3	Method of measurement - cabinet radiation	51
8.4.4	Method of measurement - radiated spurious components.....	51
8.4.5	Limits.....	52
9	Layer 1: Method of measurements and limits for on-board units	52
9.1	OBU sensitivity	52
9.1.1	Definition.....	52
9.1.2	Method of measurement	52
9.1.3	Limits.....	53
9.2	On board unit access.....	53
9.2.1	Definition.....	53
9.2.2	Method of measurement	53
9.2.3	Limits.....	55
9.3	Transponder conversion gain	55
9.3.1	Definition.....	55
9.3.2	Method of measurement	55
9.3.3	Limits.....	57
9.4	OBU maximum radiated subcarrier.....	57
9.4.1	Definition.....	57
9.4.2	Method of measurement	57
9.4.3	Limits.....	57
9.5	OBU frequency error.....	58

9.5.1	Definition.....	58
9.5.2	Method of measurement	58
9.5.3	Limits.....	59
9.6	OBU spurious radiation.....	59
9.6.1	Definition.....	59
9.6.2	Method of measurement	59
9.6.3	Limits.....	60
10	Layer 2 parameters and procedures.....	60
10.1	General conditions.....	60
10.2	Frame Structure	60
10.2.1	Definition.....	60
10.2.2	Limits.....	61
10.2.2.1	Validity of frames	61
10.2.2.2	Bit order	61
10.2.2.3	Transparency.....	61
10.2.2.4	Frame length	61
10.3	Opening and closing flags	61
10.3.1	Definition.....	61
10.3.2	Limits.....	62
10.4	LPDU	62
10.4.1	Definition.....	62
10.4.2	Limits.....	62
10.5	Frame check sequence.....	63
10.5.1	Definition.....	63
10.5.2	Limits.....	63
10.6	Frame transmission procedure.....	63
10.7	Frame reception procedure.....	63
10.8	Specific Road Side Unit parameters and procedures.....	63
10.8.1	Link ID allocation.....	63
10.8.2	Frame transmission.....	64
10.8.3	Frame reception	64
10.9	Specific On Board Units (OBUs) parameters and functions.....	64
10.9.1	Link ID allocation.....	64
10.9.2	Frame transmission.....	64
10.9.3	Frame reception	64
11	Layer 7 parameters and procedures.....	65
11.1	General conditions.....	65
11.2	General protocol rules	65
11.2.1	Protocol data unit formats.....	65
11.2.2	Concatenation	65
11.2.3	Sessions	65
11.3	Protocol messages and parameters: ASN.1 definitions	66
11.4	Encoding rules.....	70
11.4.1	Encoding of the primitive types.....	71
11.4.1.1	BIT STRING type.....	71
11.4.1.2	INTEGER type.....	71
11.4.2	Encoding of the structured types.....	71
11.4.2.1	SEQUENCE type.....	71
11.4.2.2	SEQUENCE OF type.....	71
11.4.2.3	CHOICE type.....	71
11.4.2.4	SET type.....	71
11.4.2.5	SET OF type.....	71
11.5	RSU specific parameters and procedures	72
11.5.1	Application protocol data unit formats	72
11.5.2	Open-Rq directive.....	72
11.5.2.1	Definition	72
11.5.2.2	Method of measurement.....	72
11.5.2.3	Limits	73
11.5.3	Close-Rq directive	73
11.5.3.1	Definition	73

11.5.3.2	Method of measurement.....	73
11.5.3.3	Limits	73
11.5.4	Select-TBA-Id-Rq directive.....	73
11.5.4.1	Definition	73
11.5.4.2	Method of measurement.....	73
11.5.4.3	Limits	73
11.5.5	Read-Display-Type-Rq directive	74
11.5.5.1	Definition	74
11.5.5.2	Method of measurement.....	74
11.5.5.3	Limits	74
11.5.6	Read-Master-Core-Rq directive.....	74
11.5.6.1	Definition	74
11.5.6.2	Method of measurement.....	74
11.5.6.3	Limits	74
11.5.7	Get-Master-Record-Rq directive	74
11.5.7.1	Definition	74
11.5.7.2	Method of measurement.....	74
11.5.6.3	Limits	75
11.5.8	Read-Appl-Core-Rq directive.....	75
11.5.8.1	Definition	75
11.5.8.2	Method of measurement.....	75
11.5.8.3	Limits	75
11.5.9	Write-Appl-Core-Rq directive	75
11.5.9.1	Definition	75
11.5.9.2	Method of measurement.....	75
11.5.9.3	Limits	75
11.5.10	Write-Appl-Core-Conf-Rq directive	76
11.5.10.1	Definition	76
11.5.10.2	Method of measurement.....	76
11.5.10.3	Limits	76
11.5.11	Write-Data-To-External-Rq directive	76
11.5.11.1	Definition	76
11.5.11.2	Method of measurement.....	77
11.5.11.3	Limits	77
11.5.12	Read-Data-From-External-Rq directive.....	77
11.5.12.1	Definition	77
11.5.12.2	Method of measurement.....	77
11.5.12.3	Limits	77
11.5.13	Read-Appl-Record-Rq directive	77
11.5.13.1	Definition	77
11.5.13.2	Method of measurement.....	78
11.5.13.3	Limits	78
11.5.14	Write-Appl-Record-Curr-Rq directive.....	78
11.5.14.1	Definition	78
11.5.14.2	Method of measurement.....	78
11.5.14.3	Limits	78
11.5.15	Write-Appl-Record-Curr-Conf-Rq directive	78
11.5.12.1	Definition	78
11.5.15.2	Method of measurement.....	78
11.5.15.3	Limits	79
11.5.16	Write-Appl-Record-Next-Rq directive	79
11.5.16.1	Definition	79
11.5.16.2	Method of measurement.....	79
11.5.16.3	Limits	79
11.5.17	Write-Appl-Record-Next-Conf-Rq directive	79
11.5.17.1	Definition	79
11.5.17.2	Method of measurement.....	79
11.5.17.3	Limits	80
11.5.18	Set-UIF-Rq directive.....	80
11.5.18.1	Definition	80
11.5.18.2	Method of measurement.....	80
11.5.18.3	Limits	80

11.5.19	Action-Rq directive.....	80
11.5.19.1	Definition	80
11.5.19.2	Method of measurement.....	81
11.5.19.3	Limits	81
11.5.17	Set-Password-Rq directive.....	81
11.5.17.1	Definition	81
11.5.17.2	Method of measurement.....	81
11.5.17.3	Limits	81
11.5.18	Use-Last-Password-Rq directive	82
11.5.18.1	Definition	82
11.5.18.2	Method of measurement.....	82
11.5.18.3	Limits	82
11.5.19	Get-TBA-Random-Rq directive.....	82
11.5.19.1	Definition	82
11.5.19.2	Method of measurement.....	82
11.5.19.3	Limits	82
11.5.20	Set-Credential-Rq directive	83
11.5.20.1	Definition	83
11.5.20.2	Method of measurement.....	83
11.5.20.3	Limits	83
11.5.21	Get-Credential-Rq directive.....	83
11.5.21.1	Definition	83
11.5.21.2	Method of measurement.....	83
11.5.21.3	Limits	83
11.6	OBU specific parameters and procedures	83
11.6.1	Application protocol data unit formats	84
11.6.2	Receiving Protocol Data Units.....	84
11.6.3	Response to Open-Rq	85
11.6.3.1	Definition	85
11.6.3.2	Method of measurement.....	85
11.6.3.3	Limits	85
11.6.4	Response to Close-Rq	85
11.6.4.1	Definition.....	85
11.6.4.2	Method of measurement.....	85
11.6.4.3	Limits	85
11.6.5	Response to Select-TBA-Id-Rq	86
11.6.5.1	Definition	86
11.6.5.2	Method of measurement.....	86
11.6.5.3	Limits	86
11.6.6	Response to Read-Display-Type-Rq.....	86
11.6.6.1	Definition	86
11.6.6.2	Method of measurement.....	86
11.6.6.3	Limits	86
11.6.7	Response to Read-Master-Core-Rq	87
11.6.7.1	Definition	87
11.6.7.2	Method of measurement.....	87
11.6.7.3	Limits	87
11.6.8	Response to Get-Master-record-Rq	87
11.6.8.1	Definition	87
11.6.8.2	Method of measurement.....	87
11.6.8.3	Limits	87
11.6.9	Response to Read-Appl-Core-Rq	88
11.6.9.1	Definition	88
11.6.9.2	Method of measurement.....	88
11.6.9.3	Limits	88
11.6.10	Response to Write-Appl-Core-Rq.....	88
11.6.10.1	Definition	88
11.6.10.2	Method of measurement.....	89
11.6.10.3	Limits	89
11.6.11	Response to Write-Appl-Core-Conf-Rq	89
11.6.11.1	Definition	89
11.6.11.2	Method of measurement.....	89

11.6.11.3	Limits	89
11.6.12	Response to Write-Data-To-External-Rq.....	89
11.6.12.1	Definition	89
11.6.12.2	Method of measurement.....	89
11.6.12.3	Limits	90
11.6.13	Response to Read-Data-From-External-Rq	90
11.6.13.1	Definition	90
11.6.13.2	Method of measurement.....	90
11.6.13.3	Limits	90
11.6.14	Response to Read-Appl-Record-Rq.....	90
11.6.14.1	Definition	90
11.6.14.2	Method of measurement.....	90
11.6.14.3	Limits	91
11.6.15	Response to Write-Appl-Record-Curr-Rq	91
11.6.15.1	Definition	91
11.6.15.2	Method of measurement.....	91
11.6.15.3	Limits	91
11.6.16	Response to Write-Appl-Record-Curr-Conf-Rq.....	91
11.6.16.1	Definition	91
11.6.16.2	Method of measurement.....	91
11.6.16.3	Limits	92
11.6.17	Response to Write-Appl-Record-Next-Rq.....	92
11.6.17.1	Definition	92
11.6.17.2	Method of measurement.....	92
11.6.17.3	Limits	92
11.6.18	Response to Write-Appl-Record-Next-Conf-Rq.....	92
11.6.18.1	Definition	92
11.6.18.2	Method of measurement.....	92
11.6.18.3	Limits	92
11.6.19	Response to Set-UIF-Rq	93
11.6.19.1	Definition	93
11.6.19.2	Method of measurement.....	93
11.6.19.3	Limits	93
11.6.20	Response to Action-Rq.....	93
11.6.20.1	Definition	93
11.6.20.2	Method of measurement.....	93
11.6.20.3	Limits	93
11.6.21	Response to Set-Password-Rq	94
11.6.21.1	Definition	94
11.6.21.2	Method of measurement.....	94
11.6.21.3	Limits	94
11.6.22	Response to Use-Last-Password-Rq	94
11.6.22.1	Definition	94
11.6.22.2	Method of measurement.....	94
11.6.22.3	Limits	95
11.6.23	Response to Get-TBA-Random-Rq	95
11.6.23.1	Definition	95
11.6.23.2	Method of measurement.....	95
11.6.23.3	Limits	95
11.6.24	Response to Set-Credential-Rq.....	95
11.6.24.1	Definition	95
11.6.24.2	Method of measurement.....	95
11.6.24.3	Limits	96
11.6.25	Response to Get-Credential-Rq	96
11.6.25.1	Definition	96
11.6.25.2	Method of measurement.....	96
11.6.25.3	Limits	96
12	Measurement uncertainty	96
Annex A (normative):	Radiated measurement.....	98
A.1	Test sites and general arrangements for measurements involving the use of radiated fields.....	98

A.1.1	Anechoic chamber	98
A.1.2	Anechoic chamber with a conductive ground plane	99
A.1.3	Open Area Test Site (OATS)	100
A.1.4	Test antenna	101
A.1.5	Substitution antenna	102
A.1.6	Measuring antenna	102
A.2	Guidance on the use of radiation test sites	102
A.2.1	Verification of the test site	102
A.2.2	Preparation of the EUT	102
A.2.3	Power supplies to the EUT	102
A.2.4	Range length	103
A.2.5	Site preparation	103
A.3	Coupling of signals	104
A.3.1	General	104
A.3.2	Data Signals	104
Annex B (normative): General description of measurement methods		106
B.1	Conducted measurements	106
B.2	Radiated measurements	106
Annex C (normative): Receiver methods of measurements using messages		107
C.1	General	107
C.2	Test signals	107
C.3	Method of measurement for receiver sensitivity	107
C.4	Method of measurements for receiver degradation	108
Annex D (normative): Profile for the European Electronic Fee Collection service		109
D.1	General	109
D.2	Common limits	109
D.2.1	Data to be used for EETS transactions	109
D.2.2	Directives to be used for EETS applications	110
D.2.3	OBU memory structure	110
D.2.4	Security algorithms and requirements	111
D.2.4.1	Generalities	111
D.2.4.2	Authenticator computed on PaymentMeans attribute	111
D.2.4.3	Access credentials computation	112
D.2.4.4	Authentication key computation	113
D.2.4.5	Access key computation	114
D.2.4.6	Transaction counter	114
D.3	OBU specific limits	114
D.3.1	DSRC communication limits	114
D.3.2	Security requirements	114
D.4	RSU specific limits	115
History	116

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Intelligent Transport System (ITS), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document is part 3 of a multi-part deliverable covering the Road Transport and Traffic Telematics (RTTT), as identified below:

Part 1: General characteristics and test methods for Road Side Units (RSU) and On-Board Units (OBU);

Part 2: Harmonized EN under article 3.2 of the R&TTE Directive;

Part 3-1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Introduction

The present document was drafted on the assumption that type test measurements, performed in an accredited test laboratory, will be accepted by the various national regulatory authorities in order to grant type approval, provided the national regulatory requirements are met. This is in compliance with CEPT/ERC Recommendation 70-03 [2].

The present document specifies the requirements for a dedicated 5,8 GHz short range microwave link intended for High Data Rate communication system for Road Transport and Traffic Telematics (RTTT) applications.

The present document supports the necessary transmitter and receiver High Data Rate (HDR) of up to 1 Mbit/s.

The RSU transmitter operates on a non-exclusive basis on frequencies depending on the declared application according to CEPT/ECC/DEC(02)01 [1].

A channel spacing of 10 MHz is used, see table 1.

Table 1: RTTT transmitter frequencies for 10 MHz channel spacing systems

	Initial road to Vehicle systems	Multi lane road junctions (options)
Channel 1	5 800 MHz	
Channel 2		5 810 MHz

In order to permit the greatest freedom of design of equipment, whilst protecting other radio services from interference, a balance is required between the permitted range of frequencies on which the equipment may be used, and its frequency stability and modulation characteristics. The present document specifies the operational frequencies and system bandwidths. However, the present document does not fully describe the permitted range of optional frequencies as these are covered by national regulations. The optional range of frequencies offered should be specified on each type approval certificate issued.

Clauses 1 to 3 give a general description of the types of equipment covered by the present document and the definitions and abbreviations used. Clause 4 gives general requirement in order that type tests may be carried out and any markings on the equipment to be provided by the manufacturer.

Clauses 5 and 6 specify the test conditions.

Clauses 7 and 8 specify the limits of the Physical Layer parameters which are required to be tested for the RSU transmitters and receivers. These limits have been chosen to minimize harmful interference to and from other equipment and services. These clauses also specify how the equipment is to be tested and the conditions which are applied.

Clause 9.1 specifies the limits of the Physical Layer parameters which are required to be tested for transponders. These limits are chosen to restrict the access to and radiation from transponders. Details on the test methods for the transponders are also specified.

Clause 12 specifies the maximum measurement uncertainty values.

Clause 10 specifies the parameters and protocol procedures for Layer 2 (Data Link Layer).

Clause 11 specifies the parameters and protocol procedures for Layer 7 (Application Layer).

Annex A provides specifications concerning test sites for radiated measurements.

Annex B provides descriptions of measurement methods for radiated measurements.

Annex C provides descriptions of alternative measurement methods for receivers.

Annex D provides the choices for parameters and protocol procedures to be tested for a system to be compliant to the European Electronic Tolling Service (EETS).

1 Scope

The present document specifies radio parameters, data link services and protocol data units, and application services and protocol data units which are necessary for the efficient use of the radio spectrum and for the purpose of DSRC based applications. This includes methods of measurements for verifying the limits stated in the present document.

The present document applies to 5,8 GHz Short Range Devices (SRDs) for use in Road Transport Traffic and Telematics (RTTT):

- with a Radio Frequency (RF) output connection and specified antenna or with an integral antenna;
- for data transmission only;
- operating on radio frequencies in the 5 725 MHz to 5 875 MHz Industrial, Scientific and Medical (ISM) band.

The applicability of the present document covers both the Road Side Units (RSUs) and the On Board Units (OBUs) with transceivers and transponders.

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable.

The present document complies with CEPT/ECC/DEC(02)01 [1] and CEPT/ERC Recommendation 70-03 [2]. It is a specific standard covering various RTTT applications. The RTTT data rate specified in the present document is:

- RTTT systems using down and up link data rate of up to 1 Mbit/s.

For non-harmonized parameters, national regulatory conditions may apply regarding the type of modulation, channel/frequency separation, maximum transmitter output power/effective radiated power, equipment marking as a condition of the issue of an individual or general license, or, as a condition of use under license exemption.

Additional standards or specifications may be required for equipment such as that intended for connection to the Public Switched Telephone Network (PSTN) or other systems.

<https://standards.iteh.ai/catalog/standards/sist/fe089202-70ae-4bea-bd3a-faa6682ac3ad/osist-pren-300-674-3-1-v3-0-0-2010>

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] CEPT ECC/DEC(02)01: "ECC Decision of 15 March 2002 on the frequency bands to be designated for the coordinated introduction of Road Transport and Traffic Telematic Systems".
- [2] CEPT ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [3] CISPR 16-1: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1: Radio disturbance and immunity measuring apparatus".
- [4] ETSI TR 100 028 (all parts): " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".