



**INTERNATIONAL STANDARD ISO 11997-1:1998
TECHNICAL CORRIGENDUM 1**

Published 1998-10-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Paints and varnishes — Determination of resistance to cyclic corrosion conditions —

**Part 1:
Wet (salt fog)/dry/humidity**

TECHNICAL CORRIGENDUM 1

Peintures et vernis — Détermination de la résistance aux conditions de corrosion cyclique —

Partie 1: Brouillard salin/sécheresse/humidité

RECTIFICATIF TECHNIQUE 1

STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/5df4c3fd-b104-41e4-905a-9a5d32026788/iso-11997-1-1998-cor-1-1998>

Technical Corrigendum 1 to International Standard ISO 11997-1:1998 was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

Page 3

Subclause 6.4

After “Drying-air supply”, add “of (50 ± 20) % relative humidity”.

Page 9

Clause C.2

In steps 2 and 5, add in the “Notes” column “Air purge (see 6.4)”.

Page 11

Clause E.2

In steps 2, 4 and 7, add in the “Notes” column “Air purge (see 6.4)”.

In steps 1, 4 and 5, change the temperature in the “Temp. (°C)” column from “ 25 ± 2 ” to “ 30 ± 2 ”.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 11997-1:1998/Cor 1:1998
<https://standards.iteh.ai/catalog/standards/sist/5df4c3fd-b104-41e4-905a-8a3d5d26289e/iso-11997-1-1998-cor-1-1998>