



SLOVENSKI STANDARD
SIST EN 301 575 V1.1.1:2012
01-julij-2012

Okoljski inženiring (EE) - Merilna metoda za porabo energije opreme pri porabniku (CPE)

Environmental Engineering (EE) - Measurement method for energy consumption of Customer Premises Equipment (CPE)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 301 575 Version 1.1.1**
<https://standards.iteh.ai/catalog/standards/sist/58c0bd19-a650-41e0-8114-5101039ad99f/sist-en-301-575-v1-1-1-2012>

ICS:

19.040	Preskušanje v zvezi z okoljem	Environmental testing
--------	-------------------------------	-----------------------

SIST EN 301 575 V1.1.1:2012	en
------------------------------------	-----------

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 575 V1.1.1:2012](https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012>

ETSI EN 301 575 V1.1.1 (2012-05)



Environmental Engineering (EE); Measurement method for energy consumption of Customer Premises Equipment (CPE)

[SIST EN 301 575 V1.1.1:2012](https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012>

Reference

DEN/EE-00021

Keywords

CPE, power measurement

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 575 V1.1.1:2012

<https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad27858-ef-301-575-v1-1-1-2012>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Operating modes	7
5 General requirements for measurement conditions.....	7
5.1 Measurement conditions.....	8
5.2 Measurement instruments requirements.....	8
6 Measurement configurations	8
6.1 Off mode	8
6.2 Standby mode.....	9
6.3 Idle state	9
6.4 On mode	10
Annex A (informative): Bibliography.....	13
History	14

[SIST EN 301 575 V1.1.1:2012](https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012)
<https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE).

National transposition dates	
Date of adoption of this EN:	28 March 2012
Date of latest announcement of this EN (doa):	30 June 2012
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2012
Date of withdrawal of any conflicting National Standard (dow):	31 December 2012

SIST EN 301 575 V1.1.1:2012

<https://standards.iteh.ai/catalog/standards/sist/58c6bd19-a850-4fe0-8f14-5101039ad99f/sist-en-301-575-v1-1-1-2012>

Introduction

The present document defines the energy consumption measurement methods for Broadband CPE telecommunication equipment.

1 Scope

The present document defines the methodology and the tests conditions to measure the power consumption of end-user broadband equipment (CPE) within the scope of EU regulation 1275/2008 [1] in:

- Disconnected mode
- Off mode (as defined in Commission Regulation 1275/2008)
- Standby (as defined in Commission Regulation 1275/2008)
- Idle states
- Low Power states
- On mode

Moreover, these different modes of operation are defined.

The methods of measurement are applicable to customer premises equipment which can be directly connected to the mains.

Equipment drawing electricity via the network connection (indirectly connected to the mains) or via local Personal Computer (i.e. via USB) is out of scope.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode electric power consumption of electrical and electronic household and office equipment.

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] "Code Of Conduct on Energy Consumption of Broadband Communication Equipment" European Commission Directorate-General, Joint Research Centre; Final v4: 10 February 2011.
- [i.2] IEEE 802.16: "IEEE Standard for Local and metropolitan area networks Part 16: Air Interface for Broadband Wireless Access Systems".

- [i.3] Directive 2004/108/EC of the European Parliament and of the Council of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC.
- [i.4] CENELEC EN 50160: "Voltage characteristics of electricity supplied by public electricity networks".
- [i.5] Cablelabs: "Data-Over-Cable Service Interface Specifications - DOCSIS® 2.0 Interface".
- [i.6] Cablelabs: "Data-Over-Cable Service Interface Specifications- DOCSIS® 3.0 Interface".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply:

broadband telecommunication network equipment: equipment comprising broadband technology that is part of a telecommunication network

broadband terminal equipment: equipment comprising broadband technology that is connected to a telecommunication network at a point beyond the Network Termination Point

Customer-Premises Equipment (CPE): any terminal and associated equipment located at a subscriber's premises and connected with a carrier's telecommunication channel(s) at the Network Termination Points (NTPs)

directly connected to the mains: equipment that could draw electricity from mains power outlet itself via its internal or external power supply

indirectly connected to the mains power source: not directly connected to the mains power source e.g. the equipment could draw electricity via the network connection from a linked equipment that draws power from mains

NOTE: Examples include Power over Ethernet (PoE) and Power over USB.

Network Termination Point (NTP): point established in a building or complex to separate customer equipment from communications providers equipment

power consumption: power used by a device to achieve an intended application performance

reactivation function: function facilitating the activation of other modes, including active mode, by remote switch including remote control, internal sensor, timer to a condition providing additional functions, including the main function

telecommunication network: network operated under a license granted by a national telecommunications authority, which provides telecommunications between Network Termination Points (NTPs) (i.e. excluding terminal equipment and/or CPE's beyond the NTPs)

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ADSL	Asymmetric Digital Subscriber Line
ADSL2plus	Second generation ADSL with extended bandwidth
AP	Access Point
CoC	Code of Conduct
CPE	Customer Premises Equipment
DECT	Digital Enhanced Cordless Technology
DSLAM	Digital Subscriber Line Access Multiplexer
FE	Fast Ethernet
FXO	Foreign eXchange Office

FXS	Foreign eXchange Station
GE	Gigabit Ethernet
HG	Home Gateway
LAN	Local Area Network
Ms/s	Mega symbols per second
NDR	Non Drop Rate
PSD	Power Spectral Density
QAM	Quadrature Amplitude Modulation
USB	Universal Serial Bus
VAC	Volts Alternating Current
VDSL	Very high speed Digital Subscriber Line
VDSL2	Second generation VDSL
WAN	Wide Area Network
WLAN	Wireless Local Area Network

4 Operating modes

This clause reports a detailed explanation of the different operating mode applicable to CPE.

- Disconnected mode: the CPE is disconnected from all external power sources.
- Off mode (from Regulation 1275/2008) [1]: means a condition in which the equipment is connected to the mains power source and is not providing any function; the following shall also be considered as off mode:
 - a) conditions providing only an indication of off mode condition;
 - b) conditions providing only functionalities intended to ensure electromagnetic compatibility pursuant to Directive 2004/108/EC [1.3].
- Standby mode (from Regulation 1275/2008 [1]): means a condition where the equipment is connected to the mains power source, depends on energy input from the mains power source to work as intended and provides only the following functions, which may persist for an indefinite time:
 - a) reactivation function, or reactivation function and only an indication of enabled reactivation function; and/or
 - b) information or status display.
- Idle-state: in this state the device is not processing or transmitting a significant amount of traffic, but is ready to detect activity. All the components are in their individual Idle states.
- Other Low Power states: these are energy saving modes where settings should be adjustable by the user /operator and designed in a way that it is likely to be adjusted if necessary to an alternative or custom setting, more suitable to their typical use (e.g. ADSL2plus L2 mode). Other innovative solutions shall be considered.
- On mode: equipment is connected to the mains power source and at least one of the main function(s) providing the intended service has been activated.

5 General requirements for measurement conditions

This clause describes the methods to measure the power consumption of broadband CPE equipment and also gives the conditions under which these measurements shall be performed.