
**Industrial valves — Measurement, test
and qualification procedures for fugitive
emissions —**

**Part 2:
Production acceptance test of valves**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Robinetterie industrielle — Mesurage, essais et modes opératoires de
qualification pour émissions fugitives —*

*Partie 2: Essais de réception en production des appareils de
robinetterie*

[https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-
b16afd5e90cb/iso-15848-2-2006](https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15848-2:2006

<https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15848-2 was prepared by Technical Committee ISO/TC 153, *Valves*, Subcommittee SC 1, *Design, manufacture, marking and testing*.

ISO 15848 consists of the following parts, under the general title *Industrial valves — Measurement, test and qualification procedures for fugitive emissions*:

— *Part 1: Classification system and qualification procedures for type testing of valves*

— *Part 2: Production acceptance test of valves*

Introduction

The aim of this part of ISO 15848 is to establish standard practice for the evaluation of production valves whose design has been successfully type-tested according to ISO 15848-1.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15848-2:2006](https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006>

Industrial valves — Measurement, test and qualification procedures for fugitive emissions —

Part 2: Production acceptance test of valves

1 Scope

This part of ISO 15848 specifies test procedures for the evaluation of external leakage of valve stems or shafts and body joints of isolating valves and control valves intended for application with volatile air pollutants and hazardous fluids. End connection joints, vacuum application, effects of corrosion and radiation are excluded from this part of ISO 15848. The production acceptance test is intended for standard production valves where fugitive emissions standards are specified.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15848-1:2006, *Industrial valves — Measurement, test and qualification procedures for fugitive emissions — Part 1: Classification system and qualification procedures for type testing of valves*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15848-1 and the following apply.

3.1

production acceptance test

test carried out on production valves to verify conformance with the requirements of this part of ISO 15848

4 Preparation of test valves

4.1 Valve selection

The sampling percentage shall be according to a specific agreement between the manufacturer and the purchaser, with a minimum of one valve of the lot, and shall be selected at random from each production lot of valves per valve type, pressure class and nominal size.

4.2 Preconditioning

This part of ISO 15848 is applicable to valves the design of which has been successfully type-tested according to ISO 15848-1. The selected valves shall have been successfully tested according to the relevant production test standards and the purchaser's specifications, prior to the acceptance test specified in this part of ISO 15848.

The manufacturer shall ensure that the packing is dry before production.

4.3 Stem (or shaft) seal adjustment

Compression of stem (or shaft) seal(s) shall be initially adjusted according to the manufacturer's instructions.

5 Test conditions

5.1 Test fluid

The test fluid shall be helium gas with a minimum purity of 97 % by volume.

5.2 Leakage measurement

Leakages shall be measured by the sniffing method in accordance with ISO 15848-1:2006, Annex B, and shall be expressed in parts per million in volume (1 ppmv = 1 ml/m³ = 1 cm³/m³).

5.3 Test pressure

The test pressure shall be 6 bar (1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm²), unless otherwise agreed by the manufacturer and the purchaser.

5.4 Test temperature

The test temperature shall be the room temperature as defined in ISO 15848-1.

6 Test procedure and evaluation of test results

6.1 Measurement of stem (or shaft) seal leakages

The procedure for measuring the leakage of stem or shaft seals is as follows.

- a) Half open the test valve and pressurize to the level specified in 5.3. Measure stem seal leakage using the sniffing method in accordance with ISO 15848-1:2006, Annex B.
- b) Then fully open and close the pressurized test valve five times.
- c) Half open the test valve after the mechanical cycles, and measure stem seal leakages as in a).
- d) If the meter reading exceeds the parts per million in volume (1 ppmv = 1 ml/m³ = 1 cm³/m³) value of the required performance class according to Table 1, the test shall be considered as having been failed and the lot of valves (see 4.1) shall be rejected.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15848-2:2006

<https://standards.iteh.ai/en/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006>

Table 1 — Tightness classes for stem seals

Class	Value ^a	Remarks
A	≤ 50	Typically achieved with bellow seals or equivalent stem (shaft) sealing system for quarter turn valves
B	≤ 100	Typically achieved with PTFE based packings or elastomeric seals
C	≤ 1 000	Typically achieved with flexible graphite based packings
^a Expressed in ppmv measured with the sniffing method in accordance with ISO 15848-1:2006, Annex B.		

6.2 Measurement of leakage of body seal(s)

The procedure for measuring the leakage of body seals is as follows.

- a) Half open the test valve and pressurize to the level specified in 5.3. After the test pressure has been stabilized, detect leakage of the body seal(s) in accordance with ISO 15848-1:2006, Annex B.
- b) If the meter reading exceeds the parts per million in volume (1 ppmv = 1 ml/m³ = 1 cm³/m³) value according to Table 2, the test shall be considered as having been failed and the lot of valves (see 4.1) shall be rejected.

Table 2 — Emissions from body seals

Measured concentration ppmv
ISO 15848-2:2006 ≤ 50
NOTE Expressed in ppmv measured with the sniffing method in accordance with ISO 15848-1:2006, Annex B.

7 Marking

Only those valves which have been tested, classified and qualified in accordance with ISO 15848-1, and which comply with the requirements of this part of ISO 15848, shall be marked.

8 Certification of compliance

If requested by the purchaser, the manufacturer shall provide a certificate of compliance that this production acceptance test has been completed successfully.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15848-2:2006

<https://standards.iteh.ai/catalog/standards/sist/9dce61e7-df27-458d-95c7-b16afd5e90cb/iso-15848-2-2006>

ICS 23.060.01

Price based on 3 pages