



SLOVENSKI STANDARD
SIST EN 302 544-1 V1.1.2:2010
01-marec-2010

Širokopasovni sistemi za prenos podatkov, ki delujejo v frekvenčnem pasu od 2500 MHz do 2690 MHz - 1. del: TDD-bazne postaje - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

Broadband Data Transmission Systems operating in the 2 500 MHz to 2 690 MHz frequency band - Part 1: TDD Base Stations - Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 544-1 V1.1.2:2010](https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>

Ta slovenski standard je istoveten z: EN 302 544-1 Version 1.1.2

ICS:

| | | |
|-----------|----------------------------------|--------------------------------|
| 33.060.01 | Radijske komunikacije na splošno | Radiocommunications in general |
|-----------|----------------------------------|--------------------------------|

SIST EN 302 544-1 V1.1.2:2010 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 544-1 V1.1.2:2010

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>

ETSI EN 302 544-1 V1.1.2 (2010-01)

Harmonized European Standard (Telecommunications series)

**Broadband Data Transmission Systems operating in the
2 500 MHz to 2 690 MHz frequency band;
Part 1: TDD Base Stations;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 544-1 V1.1.2:2010](https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>



Reference

REN/BRAN-0060005-1

Keywords

broadband, cellular, digital, IMT-2000, mobile,
multipoint, radio, regulation, TDD

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 544-1 V1.1.2:2010

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|----|
| Intellectual Property Rights | 5 |
| Foreword..... | 5 |
| Introduction | 6 |
| 1 Scope | 7 |
| 2 References | 7 |
| 2.1 Normative references | 7 |
| 2.2 Informative references | 8 |
| 3 Definitions, symbols and abbreviations | 8 |
| 3.1 Definitions | 8 |
| 3.2 Symbols | 9 |
| 3.3 Abbreviations | 10 |
| 4 Essential requirements specification | 10 |
| 4.1 Environmental profile..... | 10 |
| 4.2 Conformance requirements | 10 |
| 4.2.1 Introduction..... | 10 |
| 4.2.2 Spectrum emission mask | 11 |
| 4.2.2.1 Definition | 11 |
| 4.2.2.2 Limits | 11 |
| 4.2.2.2.1 Spectrum emission mask for 5 MHz bandwidth | 11 |
| 4.2.2.2.2 Spectrum emission mask for 10 MHz bandwidth..... | 12 |
| 4.2.2.3 Conformance | 13 |
| 4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR) | 14 |
| 4.2.3.1 Definition | 14 |
| 4.2.3.2 Limits | 14 |
| 4.2.3.2.1 ACLR requirements for 5 MHz Bandwidth | 14 |
| 4.2.3.2.2 ACLR requirements for 10 MHz bandwidth | 14 |
| 4.2.3.3 Conformance..... | 15 |
| 4.2.4 Transmitter spurious emissions..... | 15 |
| 4.2.4.1 Definition | 15 |
| 4.2.4.2 Limits | 15 |
| 4.2.4.3 Conformance..... | 16 |
| 4.2.5 Maximum output power accuracy | 16 |
| 4.2.5.1 Definition | 16 |
| 4.2.5.2 Limits | 16 |
| 4.2.5.3 Conformance..... | 16 |
| 4.2.6 Transmit Intermodulation | 16 |
| 4.2.6.1 Definition | 16 |
| 4.2.6.2 Limits | 16 |
| 4.2.6.3 Conformance..... | 16 |
| 4.2.7 Receiver spurious emissions | 17 |
| 4.2.7.1 Definition | 17 |
| 4.2.7.2 Limits | 17 |
| 4.2.7.3 Conformance..... | 17 |
| 4.2.8 Receiver Adjacent Channel Selectivity (ACS) | 17 |
| 4.2.8.1 Definition | 17 |
| 4.2.8.2 Limits | 17 |
| 4.2.8.3 Conformance..... | 18 |
| 4.2.9 Receiver blocking characteristics | 18 |
| 4.2.9.1 Definition | 18 |
| 4.2.9.2 Limits | 18 |
| 4.2.9.3 Conformance..... | 19 |
| 4.2.10 Receiver intermodulation characteristics | 19 |
| 4.2.10.1 Definition and applicability..... | 19 |

| | | |
|-------------------------------|--|-----------|
| 4.2.10.2 | Limits | 19 |
| 4.2.10.3 | Conformance | 20 |
| 5 | Testing for compliance with technical requirements..... | 20 |
| 5.1 | Environmental conditions for testing | 20 |
| 5.2 | Product information..... | 20 |
| 5.3 | Interpretation of the measurement results | 21 |
| 5.4 | Essential radio test suites..... | 21 |
| 5.4.1 | Spectrum emission mask | 21 |
| 5.4.1.1 | Method of test for BS spectral emission mask | 22 |
| 5.4.1.1.1 | Initial conditions | 22 |
| 5.4.1.1.2 | Procedure..... | 22 |
| 5.4.2 | Transmitter Adjacent Channel Leakage power Ratio (ACLR) | 23 |
| 5.4.2.1 | Method of test for BS ACLR | 23 |
| 5.4.2.1.1 | Initial conditions | 23 |
| 5.4.2.1.2 | Procedure..... | 23 |
| 5.4.3 | Transmitter spurious emissions..... | 24 |
| 5.4.3.1 | Method of test | 25 |
| 5.4.3.1.1 | Initial conditions | 25 |
| 5.4.3.1.2 | Procedure..... | 25 |
| 5.4.4 | Maximum output power accuracy | 26 |
| 5.4.4.1 | Method of test | 26 |
| 5.4.4.1.1 | Initial conditions | 26 |
| 5.4.4.1.2 | Procedure..... | 26 |
| 5.4.5 | Transmitter Intermodulation | 27 |
| 5.4.5.1 | Method of test | 27 |
| 5.4.5.1.1 | Initial conditions | 27 |
| 5.4.5.1.2 | Procedure..... | 27 |
| 5.4.5.1.3 | Test requirements | 27 |
| 5.4.6 | Receiver spurious emissions | 27 |
| 5.4.6.1 | Method of test | 27 |
| 5.4.6.1.1 | Initial conditions | 28 |
| 5.4.6.1.2 | Procedure..... | 28 |
| 5.4.7 | Receiver adjacent channel selectivity | 28 |
| 5.4.7.1 | Method of test | 28 |
| 5.4.7.1.1 | Procedure..... | 29 |
| 5.4.8 | Receiver blocking characteristics | 30 |
| 5.4.8.1 | Method of test | 30 |
| 5.4.8.1.1 | Initial conditions | 30 |
| 5.4.8.1.2 | Procedure..... | 30 |
| 5.4.9 | Receiver intermodulation characteristics | 32 |
| 5.4.9.1 | Method of test | 32 |
| 5.4.9.1.1 | Initial conditions | 32 |
| 5.4.9.1.2 | Procedure..... | 32 |
| Annex A (normative): | HS Requirements and conformance Test specifications Table (HS-RTT)..... | 34 |
| Annex B (informative): | The EN title in the official languages | 36 |
| Annex C (informative): | Bibliography..... | 37 |
| History | | 38 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.5] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.1] are given in annex A.

The present document is part 1 of a multi-part deliverable covering the Base Stations (BS) and User Equipment (UE) for Broadband Data Transmission Systems in 2 500 MHz to 2 690 MHz frequency band, as identified below:

- Part 1: "TDD Base Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";**
- Part 2: "TDD User Equipment Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "FDD Base Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 4: "FDD User Equipment Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates

| | |
|--|-------------------|
| Date of adoption of this EN: | 24 December 2009 |
| Date of latest announcement of this EN (doa): | 31 March 2010 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 30 September 2010 |
| Date of withdrawal of any conflicting National Standard (dow): | 30 September 2011 |

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.2].

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 544-1 V1.1.2:2010](https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>

1 Scope

The present document is applicable to TDD Base Station radio equipment for mobile/nomadic Broadband Data Transmitting Systems operating in the 2 500 MHz to 2 690 MHz frequency band.

TDD radio equipment types operate in the 2 500 MHz to 2 690 MHz frequency band according to national frequency plans designed on the same basic assumption that the assigned blocks are in multiples of 5 MHz (same centre frequency). The present document covers the requirements for 5 MHz and 10 MHz channelized systems.

The document is equally applicable to systems utilizing integral or non integral antennas.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) article 3.2, which states that: "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive may apply to equipment within the scope of the present document. The present document does not address those IMT-2000 systems which are considered in EN 301 908 [i.3].

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 300 019 (all parts): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [2] ETSI TR 100 028 (parts 1 and 2) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] CEPT/ERC/REC 74-01E (2005): "Unwanted Emissions in the Spurious Domain".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.3] ETSI EN 301 908 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks".
- [i.4] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.5] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

ACLR Class 1: BS classification that identifies a level of ACLR performance generally appropriate for intra-system operation in contiguous channel assignments

ACLR Class 2: BS classification that identifies a level of ACLR performance appropriate for the boundary between FDD Uplink and TDD and for the boundaries between blocks with unsynchronized TDD usage

ACS Class 1: this class identifies a level of ACS performance appropriate for base stations operating at P_{nom} ≤ 25 dBm

ACS Class 2: this class identifies a level of intra-system ACS performance for base stations operating at P_{nom} > 25 dBm

ACS Class 3: this class identifies a level of inter-system ACS performance for base stations operating at P_{nom} > 25 dBm for the boundary between FDD Downlink and TDD and for the boundaries between blocks with unsynchronized TDD usage

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

environmental profile: declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant

Eval_BW 1: pass band of a rectangular filter with a bandwidth of 4,75 MHz for 5 MHz equipment and 9,5 MHz for 10 MHz equipment

Eval_BW 2: measurement for Eval_BW 2 on the operating channel is performed using a rectangular filter with a 4,75 MHz or 9,5 MHz bandwidth and the measurement on the victim channel is performed using an RRC filter with a 3,84 MHz or 7,68 MHz bandwidth (respectively) both with roll-off factor of 0,22 centred on the 1st or 2nd adjacent victim channel

Eval_BW 3: measurement for Eval_BW 3 on the operating channel is performed using a rectangular filter with a 9,5 MHz bandwidth and the measurement on the victim channel is performed using a RRC filter with a 3,84 MHz bandwidth (with roll-off factor of 0,22) centred on the corresponding adjacent victim channel

integral antenna: antenna which is declared to be part of the radio equipment by the supplier

NOTE: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of this multi-part EN may be done separately.

maximum output power: mean power level per carrier of the base station or mobile station measured at the antenna connector in a specified reference condition

mean power: when applied to a modulated signal, this is the power (transmitted or received) in a bandwidth

NOTE: The term "mean" here is used to exclude the amplitude fluctuation related to those theoretical variations present in signal for example due to amplitude modulation, pulse shaping, pre-equalization etc. Time averaging should be applied to estimate mean power with the affect of the theoretical variations. The duty cycle corresponding to burst activity within a frame should be also incorporated for "mean" power estimation.

nominal maximum output power: maximum nominal mean power level per carrier measured over total allocated channel bandwidth of the base station available at the antenna connector declared by the manufacturer; for equipment implementing dynamic change of modulation format, it is intended as the maximum nominal mean power associated to the modulation format delivering the highest power

operating nominal RF channel width: nominal amount of spectrum used by a single device operating on an identified centre frequency

TDD down-link frame: time interval in which the BS is transmitting and the UE is receiving

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.2 Symbols

SIST EN 302 544-1 V1.1.2:2010

For the purposes of the present document, the following symbols apply:

| | |
|-----------|--|
| A_{BS} | Base Station Interface A |
| A_{MS} | Mobile Station Interface A |
| A_{UUT} | Unit Under Test Interface A |
| dB | decibel |
| dBc | decibel relative to P _{nom} carrier power measured in Eval_BW 1 |
| dBm | decibel relative to 1 milliwatt |
| f | Frequency (of the assigned channel frequency of the wanted signal) |
| f_b | FDD/TDD border frequency |

NOTE: A more precise definition is provided below table 15.

| | |
|-----------------|---|
| f_c | centre frequency of the assigned channel |
| GHz | GigaHertz |
| M_{BS} | Base Station Interface M |
| M_{MS} | Mobile Station Interface M |
| MHz | MegaHertz |
| N _{th} | receiver thermal noise of the equipment (in dBm) |
| P | output Power (in dBm) |
| P_{nom} | nominal maximum output Power (in dBm) |
| P_{max} | maximum output Power of the base station (in dBm) |
| P_{SENS5} | Receiver sensitivity level at BER 10 ⁻⁶ for a 5 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology |
| P_{SENS10} | Receiver sensitivity level at BER 10 ⁻⁶ for a 10 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology |

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|---|
| ACLR | Adjacent Channel Leakage power Ratio |
| ACS | Adjacent Channel Selectivity |
| AWGN | Additive White Gaussian Noise |
| BER | Bit Error Ratio |
| BS | Base Station |
| FDD | Frequency Division Duplexing |
| PER | Packet Error Ratio |
| R&TTE | Radio equipment and Telecommunications Terminal Equipment |
| RF | Radio Frequency |
| TDD | Time Division Duplexing |
| Tx | Transmit, Transmitter |
| UE | User Equipment |
| UUT | Unit Under Test |

4 Essential requirements specification

With reference to article 3.2 of Directive 1999/5/EC [i.1] the phenomena in this clause have been identified as relevant to the essential requirements.

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

[SIST EN 302 544-1 V1.1.2:2010](https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/1554bb77-a7f4-48e5-b3b9-4c5ecdd0d0b2/sist-en-302-544-1-v1-1-2-2010>

4.2 Conformance requirements

4.2.1 Introduction

To meet the essential requirement under article 3.2 of the R&TTE Directive [i.1] six essential parameters have been identified. Table 1 provides a cross reference between these six essential parameters and the corresponding nine technical requirements for equipment within the scope of the present document. To fulfil an essential parameter the compliance with all the corresponding technical requirements in table 1 must be verified.

Table 1: Cross references

| Essential parameter | Corresponding technical requirements |
|---|--|
| Spectrum emissions mask | 4.2.2 Transmitter Spectrum emissions mask |
| | 4.2.3 Transmitter adjacent channel leakage power ratio |
| Conducted spurious emissions from the transmitter antenna connector | 4.2.4 Transmitter spurious emissions |
| Output power | 4.2.5 Maximum output power tolerance |
| Intermodulation attenuation of the transmitter | 4.2.6 Transmit Intermodulation |
| Conducted spurious emissions from the receiver antenna connector | 4.2.7 Receiver spurious emissions |
| Impact of interference on receiver performance | 4.2.8 Receiver adjacent channel selectivity |
| | 4.2.9 Receiver blocking characteristics |
| | 4.2.10 Receiver intermodulation characteristics |

4.2.2 Spectrum emission mask

4.2.2.1 Definition

Spectrum emission mask defines an out of band emission requirement for the transmitter. These out of band emissions are unwanted emissions outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

4.2.2.2 Limits

A base station transmitting on a single RF carrier configured in accordance with the manufacturer's specification shall meet the requirement.

The spectrum emissions measured according to clause 5.4.1 shall not exceed the maximum level specified in tables 2 to 9 for the appropriate BS nominal maximum output power (P_{nom}) and channel widths of 5 MHz and 10 MHz.

4.2.2.2.1 Spectrum emission mask for 5 MHz bandwidth

The spectrum emission mask of the BS applies over the frequency range 0,015 MHz to 10 MHz from the channel edge on both sides of each carrier supported by the BS:

- f_{offset} is the separation between the channel edge and the centre frequency of the measuring filter.

The out-of-channel emission is specified as power level measured over the specified measurement bandwidth. P is the total mean power of the BS carrier set to operate at P_{nom} measured in Eval_BW 1 centred in the 5 MHz channel.

Table 2: Test Requirements for spectrum emission mask values for 5 MHz channels, $P_{nom} \geq 43$ dBm

| Frequency offset from channel edge of the measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|---|--|--|
| $0,015 \text{ MHz} \leq f_{offset} < 0,215 \text{ MHz}$ | -12,5 dBm | 30 kHz |
| $0,215 \text{ MHz} \leq f_{offset} < 1,015 \text{ MHz}$ | $-12,5 \text{ dBm} - 15 \left(\frac{f_{offset}}{\text{MHz}} - 0,215 \right) \text{ dB}$ | 30 kHz |
| $1,015 \text{ MHz} \leq f_{offset} < 1,5 \text{ MHz}$ | -24,5 dBm | 30 kHz |
| $1,5 \text{ MHz} \leq f_{offset} < 5,5 \text{ MHz}$ | -11,5 dBm | 1 MHz, by aggregation of 30 kHz measurements |
| $5,5 \text{ MHz} \leq f_{offset} < 10 \text{ MHz}$ | -11,5 dBm | 1 MHz, by aggregation of 30 kHz measurements |

Table 3: Test requirements for spectrum emission mask values for 5 MHz channels, $39 \text{ dBm} \leq P_{nom} < 43 \text{ dBm}$

| Frequency offset from channel edge of the measurement filter centre frequency, f_{offset} | Maximum level | Measurement bandwidth |
|---|--|--|
| $0,015 \text{ MHz} \leq f_{offset} < 0,215 \text{ MHz}$ | -12,5 dBm | 30 kHz |
| $0,215 \text{ MHz} \leq f_{offset} < 1,015 \text{ MHz}$ | $-12,5 \text{ dBm} - 15 \left(\frac{f_{offset}}{\text{MHz}} - 0,215 \right) \text{ dB}$ | 30 kHz |
| $1,015 \text{ MHz} \leq f_{offset} < 1,5 \text{ MHz}$ | -24,5 dBm | 30 kHz |
| $1,5 \text{ MHz} \leq f_{offset} < 5,5 \text{ MHz}$ | -11,5 dBm | 1 MHz, by aggregation of 30 kHz measurements |
| $5,5 \text{ MHz} \leq f_{offset} < 10 \text{ MHz}$ | P - 54,5 dB | 1 MHz, by aggregation of 30 kHz measurements |