### INTERNATIONAL STANDARD

ISO 10193

First edition 2000-10-15

# General use light gauge metal containers — Nominal filling volumes of round cylindrical and tapered containers of up to 40 000 ml

Récipients métalliques légers à usage général — Volumes nominaux de remplissage des récipients ronds cylindriques et tronconiques de volume inférieur ou égal à 40 000 ml

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10193:2000 https://standards.iteh.ai/catalog/standards/sist/737cc646-2ff0-4b0f-b8df-6323082801e2/iso-10193-2000



#### **PDF** disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10193:2000 https://standards.iteh.ai/catalog/standards/sist/737cc646-2ff0-4b0f-b8df-6323082801e2/iso-10193-2000

#### © ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 10193 was prepared by Technical Committee ISO/TC 52, *Light gauge metal containers*, Subcommittee SC 5, *General use containers*.

This first edition of ISO 10193 cancels and replaces both ISO/TR 10193:1989 and ISO 11944:1993 which have been technically revised.

In comparison with the ISO/TR 10193 and with ISO 11944, this International Standard gives a reduced number of filling volumes and as this standardization concerns containers up to 40 000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, 93:2000 ml, nominal diameters have been added for containers having a filling volume > 10 000 ml, nominal diameters have been added for containers have been added f

Annex A of this International Standard is for information only and gives the recommended nominal diameters for each nominal filling volume of the containers concerned.

© ISO 2000 – All rights reserved

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10193;2000 https://standards.iteh.ai/catalog/standards/sist/737cc646-2ff0-4b0f-b8df-6323082801e2/iso-10193-2000

# General use light gauge metal containers — Nominal filling volumes of round cylindrical and tapered containers of up to 40 000 ml

#### 1 Scope

This International Standard specifies a range of nominal filling volumes in common use for round cylindrical and tapered general use containers of up to 40 000 ml volumetric capacity, metal thickness not exceeding 0,49 mm nominal.

#### 2 Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 90-2, Light gauge metal containers — Definitions and determination of dimensions and capacities — Part 2: General use containers. https://standards.iteh.ai/catalog/standards/sist/737cc646-2ff0-4b0f-b8df-6323082801e2/iso-10193-2000

© ISO 2000 – All rights reserved

#### 3 Nominal filling volumes

Nominal filling volumes for round cylindrical and tapered general use metal containers of up to 40 000 ml shall be as listed in Table 1.

Table 1 — Nominal filling volumes for round cylindrical and tapered general use metal containers

Nominal filling volume			
ml			
75			
100			
125			
150			
200			
250			
375			
500			
iTeh STANDARD PREVIEW			
(standarods.iteh.ai)			
2 000 <u>ISO 10193:2000</u> https://standards.iteh.ai/catalog2s590ards/sist/737cc646-2ff0-4b0f-b8/632308283 0000000000000000000000000000000			
4 000			
5 000			
10 000			
12 500			
15 000			
17 500			
20 000			
22 500			
25 000			
30 000			
40 000			

### Annex A (informative)

### Recommended nominal diameters of round cylindrical and tapered general use metal containers of up to 40 000 ml

The recommended nominal diameters of round cylindrical and tapered general use metal containers of up to 40 000 ml should be as listed in Table A.1. Those diameters, which are underlined, are strongly recommended. The diameters quoted are as defined in ISO 90-2 and the tolerances of  $\pm$  1 mm for diameters up to 153 mm and  $\pm$  2 mm for diameters larger than 153 mm are those permitted in calculating the nominal diameters. They are intended to cover different manufacturing methods rather than manufacturing process variability.

Table A.1 — Recommended nominal diameters for round cylindrical and tapered general use metal containers

Nominal filling volume	Nominal diameter cylindrical D	Nominal diameter tapered
ml	mm	mm
75	<u>52 - 56 - 73</u>	_
100	<u>52 - 56 - 60 - 65 - 73</u>	_
125	52 - 56 - 60 165 473 STANDARD	PREVIEW _
150	52 - 56 - 60 - 65 - 73 - 99 standards.ite	eh ai) —
200	<u>52 - 56 - 60 - 65 - 73 - 83 - 99</u>	<del>-</del>
250	<u>52 - 56 - 60 - 65 - 73 - 83 - 99</u> ISO 10193:2000	_
375	52 - 56 - 65 p.73 ta79 a 83 it 86 i/ 90 to 99 ta 108 ds/sist/	737cc646-2ff0-4b0f-b8df- —
500	<u>56 - 73 - 79 - 83 - 86 - 90 - 992 308</u> 801e2/iso-1019	3-2000 —
750	<u>56</u> - <u>73</u> - <u>79</u> - <u>83</u> - <u>86</u> - <u>90</u> - <u>99</u> - <u>108</u> - <u>127</u>	_
1 000	<u>73</u> - <u>79</u> - <u>83</u> - <u>86</u> - <u>90</u> - <u>99</u> - <u>108</u> - <u>127</u> - <u>140</u>	_
1 500	<u>73</u> - <u>86</u> - <u>99</u> - <u>108</u> - <u>127</u> - <u>140</u> - <u>153</u>	_
2 000	<u>99</u> - <u>127</u> - <u>140</u> - <u>153</u> - 160 - <u>165</u> - <u>171</u> - 175	<u>160</u> - 165 - <u>180</u>
2 500	<u>127</u> - <u>140</u> - <u>153</u> - 160 - <u>165</u> - <u>171</u>	<u>160</u> - 165 - <u>168</u> - <u>180</u> - <u>190</u> -198
3 000	<u>153</u> - 160 - <u>165</u> - <u>171</u> - 175 - <u>180</u> - 190	<u>160</u> - 165 - <u>168</u> - <u>180</u> - <u>190</u> - 198
4 000	<u>153</u> - 160 - <u>165</u> - <u>171</u> - 175 - <u>180</u> - 190	<u>160</u> - <u>168</u> - <u>180</u> - 185 - <u>190</u> - 198
5 000	<u>153</u> - 160 - <u>165</u> - <u>171</u> - 175 - <u>180</u> - 190 - <u>230</u>	<u>160</u> - <u>168</u> - <u>180</u> - 185 - <u>190</u> - 198 - <u>220</u> - <u>230</u> - <u>242</u>
10 000	<u>220</u> - <u>230</u> - <u>286</u> - <u>292</u>	<u>220</u> - <u>230</u> - <u>242</u> - 274 - <u>286</u> - 292 - <u>305</u>
12 500	<u>220</u> - <u>230</u> - <u>286</u> - <u>292</u>	<u>230</u> - <u>242</u> - 274 - <u>286</u> - 292 - <u>305</u>
15 000	<u>230</u> - <u>280</u> - <u>286</u> - <u>292</u>	<u>242</u> - 274 - 280 - <u>286</u> - 292 - <u>305</u>
17 500	<u>280</u> - <u>286</u> - <u>292</u>	274 - 280 - <u>286</u> - 292 - <u>305</u>
20 000	<u>280</u> - <u>286</u> - <u>292</u> - <u>305</u>	280 - <u>286</u> - 292 - <u>305</u> - 328
22 500	<u>280</u> - <u>286</u> - <u>292</u> - <u>305</u>	280 - <u>286</u> - 292 - <u>305</u> - 328
25 000	<u>280</u> - <u>286</u> - <u>292</u> - <u>305</u>	<u>286</u> - 292 - <u>305</u> - 328
30 000	<u>286</u> - <u>292</u> - <u>305</u>	<u>286</u> - 292 - <u>305</u> - 328
40 000	<u>305</u>	292 - <u>305</u> - 328 - 380

#### Tolerance:

© ISO 2000 – All rights reserved

<sup>± 1</sup> mm, for diameters up to 153 mm;

 $<sup>\</sup>pm\,2$  mm, for diameters larger than 153 mm.

ISO 10193:2000(E)

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10193:2000 https://standards.iteh.ai/catalog/standards/sist/737cc646-2ff0-4b0f-b8df-6323082801e2/iso-10193-2000

Price based on 3 pages