

SLOVENSKI STANDARD SIST ISO/TS 14253-3:2003

01-julij-2003

GdYWJZJ_UWJYY [Yca Ylf]/g_]\`jY]]b`]nXY_U!`DfY]g_UjY`n`a YfYbYYa`]nXY_U]b a Yf]`bU`cdfYa U!''"XY`.`BUjcX]`U'nU`XcgY[UbYY`g_`UXbcgh]`]n/Uj`c`a Yf]`b] bY[chcjcgh]

Geometrical Product Specifications (GPS) -- Inspection by measurement of workpieces and measuring equipment -- Part 3: Guidelines for achieving agreements on measurement uncertainty statements DARD PREVIEW

(standards.iteh.ai)

SIST ISO/TS 14253-3:2003

Ta slovenski standard je istoveten z: ISO/TS 14253-3:2002

<u>ICS:</u>

17.040.01 Linearne in kotne meritve na Linear and angular splošno measurements in general

SIST ISO/TS 14253-3:2003

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO/TS 14253-3:2003</u> https://standards.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708df08b8d02dfc/sist-iso-ts-14253-3-2003

TECHNICAL SPECIFICATION

ISO/TS 14253-3

First edition 2002-10-15

Geometrical Product Specifications (GPS) — Inspection by measurement of workpieces and measuring equipment —

Part 3:

Guidelines for achieving agreements on iTeh measurement uncertainty statements

Spécification géométrique des produits (GPS) — Vérification par la mesure des pièces et des équipements de mesure —

Partie 3: Lignes directrices pour l'obtention d'accords sur la déclaration des https://standards.incertitudes de mésure df08b8d02dfc/sist-iso-ts-14253-3-2003



Reference number ISO/TS 14253-3:2002(E)

ISO/TS 14253-3:2002(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO/TS 14253-3:2003</u> https://standards.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708df08b8d02dfc/sist-iso-ts-14253-3-2003

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.ch Web www.iso.ch

Printed in Switzerland

ISO/TS 14253-3:2002(E)

Contents

Page

Forewo	ord	iv
Introdu	ction	. v
1	Scope	. 1
2	Normative references	. 1
3	Terms and definitions	. 2
4	Reaching an agreement on a stated expanded uncertainty	. 4
5	Sequential procedure for evaluating and reaching agreement on an uncertainty statement	. 7
Annex	A (informative) Relation to the GPS matrix model	12
Bibliog	raphy	13

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO/TS 14253-3:2003</u> https://standards.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708df08b8d02dfc/sist-iso-ts-14253-3-2003

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote h STANDARD PREVIEW
- an ISO Technical Specification (ISO/T\$) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

SIST ISO/TS 14253-3:2003

An ISO/PAS or ISO/TS is reviewed after three years with a view to deciding whether it should be confirmed for a further three years, revised to become an international Standard, or withdrawn. In the case of a confirmed ISO/PAS or ISO/TS, it is reviewed again after six years at which time it has to be either transposed into an International Standard or withdrawn.

Attention is drawn to the possibility that some of the elements of this part of ISO/TS 14253 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 14253-3 was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification.*

ISO 14253 consists of the following parts, under the general title *Geometrical Product Specifications (GPS)* — *Inspection by measurement of workpieces and measuring equipment*:

- Part 1: Decision rules for proving conformance or non-conformance with specifications
- Part 2: Guide to the estimation of uncertainty in GPS measurement, in calibration of measuring equipment and in product verification
- Part 3: Guidelines for achieving agreements on measurement uncertainty statements

Annex A of this part of ISO 14253 is for information only.

Introduction

This part of ISO 14253 is a geometrical product specification (GPS) Technical Specification and is to be regarded as a global GPS Technical Specification (see ISO/TR 14638). It influences links 4, 5 and 6 of all chains of standards in the general GPS matrix.

For more detailed information of the relation of this Technical Specification to other standards and the GPS matrix model, see annex A.

ISO 14253-1 provides decision rules for proving conformance or non-conformance with specifications of workpieces and measuring equipment when taking into account the uncertainty of measurement. ISO/TS 14253-2 provides instructions for preparing uncertainty budgets for determining measurement uncertainty as defined in the *Guide to the Expression of Uncertainty in Measurement (GUM)*. However, the possibility still exists that disagreement between customer and supplier can occur on the estimated measurement uncertainty.

It is becoming increasingly common for suppliers to have in place a quality system providing satisfactory assurance to the customer that the latter is receiving a product which conforms to specifications. This avoids the need for costly duplicate inspections.

For this reason, the most common case of disagreement over a measurement uncertainty statement or an uncertainty budget involves the customer questioning the supplier's uncertainty budget. The customer also may question the measured value of a characteristic of a workpiece or of measuring equipment, thus indirectly questioning the total uncertainty budget (see ISO 14253-1). iteh.ai)

In a rarer case of disagreement, the supplier may question the customer's uncertainty budget when the customer rejects a workpiece or measuring equipment (see 6.2 of ISO 14253-1:1998). https://standards.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708-

In addition to those mentioned, there are other cases of disagreement, as well as other motivations that may lead to discussion of stated uncertainties.

SIST ISO/TS 14253-3:2003

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO/TS 14253-3:2003</u> https://standards.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708df08b8d02dfc/sist-iso-ts-14253-3-2003

Geometrical Product Specifications (GPS) — Inspection by measurement of workpieces and measuring equipment —

Part 3: Guidelines for achieving agreements on measurement uncertainty statements

1 Scope

This part of ISO 14253 provides guidelines and defines procedures for assisting the customer and supplier to reach amicable agreements on disputed measurement uncertainty statements regulated in accordance with ISO 14253-1, and so avoid costly and time-consuming disputes.

2 Normative references eh STANDARD PREVIEW

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 14253. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 14253 are encouraged to investigate the possibility of applying the most recent editions of the normative document referred to applies.³ Members of ISO and IEC maintain registers of currently valid International Standards.¹²/₁₅₅₁₋₁₅₀₋₁₅, 2003

ISO 14253-1:1998, Geometrical Product Specifications (GPS) — Inspection by measurement of workpieces and measuring equipment — Part 1: Decision rules for proving conformance or non-conformance with specification

ISO/TS 14253-2:1999, Geometrical Product Specifications (GPS) — Inspection by measurement of workpieces and measuring equipment — Part 2: Guide to the estimation of uncertainty in GPS measurement, in calibration of measuring equipment and in product verification

ISO 14978:—¹⁾, Geometrical Product Specifications (GPS) — General concepts and requirements for GPS measuring equipment

ISO/TS 17450-1:—¹⁾, Geometrical Product Specifications (GPS) — General concepts — Part 1: Model for geometric specification and verification

ISO/TS 17450-2:—¹⁾, Geometrical Product Specifications (GPS) — General concepts — Part 2: Basic tenets, specifications, operators and uncertainties

Guide to the Expression of Uncertainty in Measurement (GUM). BIPM, IEC, IFCC, ISO, IUPAC, IUPAP, OIML, 1st edition, 1993, corrected and reprinted in 1995

International Vocabulary of Basic and General Terms in Metrology (VIM). BIPM, IEC, IFCC, ISO, IUPAC, IUPAP, OIML, 2nd edition, 1993

¹⁾ To be published.

ISO/TS 14253-3:2002(E)

3 Terms and definitions

For the purposes of this part of ISO 14253, the terms and definitions given in ISO 14253-1, ISO/TS 14253-2, ISO 14978, ISO/TS 17450-1, ISO/TS 17450-2, VIM and GUM, and the following apply.

3.1

operator

ordered set of operations

3.2

specification operator

ordered set of specification operations

NOTE 1 The specification operator is the result of the full interpretation of the combination of the GPS specification or specifications indicated in the technical product documentation in accordance with ISO GPS standards.

NOTE 2 A specification operator can be incomplete, in which case it could introduce specification uncertainty.

NOTE 3 A specification operator is intended to define, for example, a specific possible "diameter" in a cylinder (e.g. two-point diameter, minimum circumscribed circle diameter, maximum inscribed circle diameter, Least Squares circle diameter), and not the generic concept "diameter".

NOTE 4 The difference between the specification operator and the functional operator causes correlation uncertainty.

3.3

verification operator

ordered set of verification operationsh STANDARD PREVIEW

NOTE 1 The verification operator is the metrological emulation of a specification operator. The verification operator is the basis for the measurement procedure.

NOTE 2 A verification operator might not be a <u>Sperfect simulation of the</u> given specification operator. In that case, the differences between the specification operator and the verification operator will result in uncertainty contributors, which are part of the measurement uncertainty. df08b8d02dfc/sist-iso-ts-14253-3-2003

3.4

actual specification operator

specification operator derived from the actual specification given in the actual technical product documentation

NOTE 1 The standard or standards according to which the actual specification operator is to be interpreted are identified explicitly or implicitly.

NOTE 2 An actual specification operator can be a complete specification operator or an incomplete specification operator.

NOTE 3 An actual specification operator can be either a special specification operator or a default specification operator.

3.5

actual verification operator

ordered set of actual verification operations

NOTE The actual verification operator can be chosen so that it is different from the required perfect verification operator. The divergence between the perfect verification operator and the chosen actual verification operator is the measurement uncertainty (sum of the method uncertainty and implementation uncertainty).

3.6

perfect verification operator

verification operator based on a full set of perfect verification operations performed in the prescribed order

NOTE 1 The only measurement uncertainty contributions from a perfect verification operator are from metrological characteristic deviations in the implementation of the operator.

NOTE 2 The purpose of calibration is generally to evaluate the magnitude of these measurement uncertainty contributors, originating from the measuring equipment.

3.7

specification uncertainty

uncertainty inherent in an actual specification operator when applied to a real workpiece/feature

NOTE 1 Specification uncertainty is of the same nature as measurement uncertainty and can — if relevant — be part of an uncertainty budget.

NOTE 2 The specification uncertainty quantifies the ambiguity in the specification operator.

NOTE 3 For the purposes of this part of ISO 14253, specification uncertainty is considered part of the compliance uncertainty.

NOTE 4 Specification uncertainty is a property related to the actual specification operator.

NOTE 5 The magnitude of the specification uncertainty is also dependent on the expected or actual variation of the geometrical characteristics (deviations of form and angularity) of workpieces.

3.8

simplified verification operator

verification operator including one or more simplified verification operations or deviations from the prescribed order of operations, or both

NOTE 1 The simplified verification operations, deviation in the order of operations, or both, cause measurement uncertainty contributions in addition to those measurement uncertainty contributions from the metrological characteristic deviations in the implementation of the operator.

NOTE 2 The magnitude of these uncertainty contributions is also dependent on the geometrical characteristics (deviations of form and angularity) of the actual workpieces TANDARD PREVIEW

3.9

measuring task

(standards.iteh.ai)

quantification of a measurand according to its definition

SIST ISO/TS 14253-3:2003 [ISO/TS 14253-2:1999, definition:3:13]ds.iteh.ai/catalog/standards/sist/78a7b144-c410-43f8-8708df08b8d02dfc/sist-iso-ts-14253-3-2003

3.10

basic measurement task

measurement task(s) which, alone or together with others of its kind, forms the basis for the evaluation of more complicated characteristics of a workpiece or measuring equipment

[ISO/TS 14253-2:1999, definition 3.4]

3.11

overall measurement task

complicated measuring task, evaluated on the basis of several, possibly different, basic measurements

[ISO/TS 14253-2:1999, definition 3.5]

3.12

measurement

set of operations having the object of determining a value of a quantity

[VIM:1993, definition 2.1]

NOTE For the purposes of this Technical Specification, the term "measuring process" is used as a synonym for measurement.

3.13

basic measuring process

basic measurement

measuring process which, alone or together with others of its kind, forms the basis of the evaluation/measurement of more complex GPS characteristics