

---

---

**Information technology —  
Telecommunications and information  
exchange between systems — Private  
Integrated Services Network (PISN) —  
Specification, Functional Model and  
Information Flows — Message Waiting  
Indication Supplementary Service  
(standards.iteh.ai)**

*Technologies de l'information — Télécommunications et échange  
d'information entre systèmes — Réseau privé à intégration de services  
(PISN) — Spécifications, modèle fonctionnel et flux d'informations —  
Service supplémentaire d'indication d'attente de message*



This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 15505:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

<b>Contents</b>		<b>Page</b>
Foreword		v
Introduction		vi
<b>1</b>	Scope	<b>1</b>
<b>2</b>	Conformance	<b>1</b>
<b>3</b>	Normative references	<b>1</b>
<b>4</b>	Terms and definitions	<b>1</b>
<b>4.1</b>	External definitions	<b>1</b>
<b>4.2</b>	Other definitions	<b>2</b>
<b>5</b>	List of acronyms	<b>2</b>
<b>6</b>	SS-MWI stage 1 specification	<b>2</b>
<b>6.1</b>	Description	<b>2</b>
<b>6.1.1</b>	General description	<b>2</b>
<b>6.1.2</b>	Qualifications on applicability to telecommunication services	<b>2</b>
<b>6.2</b>	Procedures	<b>2</b>
<b>6.2.1</b>	Provision / withdrawal	<b>2</b>
<b>6.2.2</b>	Normal procedures	<b>2</b>
<b>6.2.3</b>	Exceptional procedures	<b>3</b>
<b>6.3</b>	Interactions with other Supplementary Services / Additional Network Features	<b>3</b>
<b>6.3.1</b>	Advice of Charge (AOC)	<b>3</b>
<b>6.3.2</b>	Call Deflection (CD)	<b>3</b>
<b>6.3.3</b>	Call Forwarding Unconditional (CFU)	<b>3</b>
<b>6.3.4</b>	Call Forwarding Busy (CFB)	<b>3</b>
<b>6.3.5</b>	Call Forwarding No Reply (CFNR)	<b>3</b>
<b>6.3.6</b>	Call Interception (CINT)	<b>3</b>
<b>6.3.7</b>	Call Intrusion (CI)	<b>4</b>
<b>6.3.8</b>	Call Offer (CO)	<b>4</b>
<b>6.3.9</b>	Call Transfer (CT)	<b>4</b>
<b>6.3.10</b>	Calling/Connected Line Identification Restriction (CLIR)	<b>4</b>
<b>6.3.11</b>	Calling/Connected Name Identification Restriction (CNIR)	<b>4</b>
<b>6.3.12</b>	Calling Line Identification Presentation (CLIP)	<b>4</b>
<b>6.3.13</b>	Calling Name Identification Presentation (CNIP)	<b>4</b>
<b>6.3.14</b>	Connected Line Identification Presentation (COLP)	<b>4</b>
<b>6.3.15</b>	Connected Name Identification Presentation (CONP)	<b>4</b>
<b>6.3.16</b>	Completion of Calls to Busy Subscribers (CCBS)	<b>4</b>
<b>6.3.17</b>	Completion of Calls on No Reply (CCNR)	<b>4</b>
<b>6.3.18</b>	Do Not Disturb (DND)	<b>4</b>
<b>6.3.19</b>	Do Not Disturb Override (DNDO)	<b>4</b>
<b>6.3.20</b>	Path Replacement (PR)	<b>4</b>
<b>6.3.21</b>	Recall (RE)	<b>4</b>
<b>6.3.22</b>	Route Restriction Class (RRC)	<b>4</b>
<b>6.3.23</b>	Cordless Terminal Location Registration (CTLR)	<b>4</b>

## ISO/IEC 15505:200(E)

6.3.24	Cordless Terminal Mobility Incoming Call (CTMI)	4
6.3.25	Cordless Terminal Mobility Outgoing Call (CTMO)	4
6.3.26	Authentication of a CTM user (CTAT)	4
6.3.27	Authentication of the PISN (CTAN)	5
6.4	Interworking considerations	5
6.5	Overall SDL	5
7	SS-MWI stage 2 specification	8
7.1	Functional model	8
7.1.1	Functional model description	8
7.1.2	Description of Functional Entities	8
7.1.3	Relationship of functional model to Basic Call functional model	8
7.2	Information flows	8
7.2.1	Definition of information flows	8
7.2.2	Relationship of information flows to Basic Call information flows	10
7.2.3	Information flow sequences	10
7.3	Functional Entity actions	12
7.3.1	Functional Entity actions of FE1	12
7.3.2	Functional Entity actions of FE2	12
7.4	Functional Entity behaviour	13
7.4.1	Behaviour of FE1	13
7.4.2	Behaviour of FE2	14
7.5	Allocation of Functional Entities to physical equipment	15
7.6	Interworking considerations	15

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 15505 was prepared by ECMA (as ECMA-241) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 15505:1997), which has been technically revised.

[ISO/IEC 15505:2000](https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000)

<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

## **Introduction**

This International Standard is one of a series of standards defining services and signalling protocols applicable to Private Integrated Services Networks (PISNs). The series uses ISDN concepts as developed by ITU-T and conforms to the framework of International Standards for Open Systems Interconnection as defined by ISO/IEC.

This International Standard specifies the Message Waiting Indication supplementary service.

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

# **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[ISO/IEC 15505:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

# Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network (PISN) — Specification, Functional Model and Information Flows — Message Waiting Indication Supplementary Service

## 1 Scope

This International Standard specifies supplementary service Message Waiting Indication (SS-MWI), which is related, but not limited, to various basic services supported by Private Integrated Services Networks (PISNs). Basic services are specified in ISO/IEC 11574.

This supplementary service MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled.

Service specifications are produced in three stages, according to the method described in CCITT Rec. I.130. This International Standard contains the stage 1 and stage 2 specifications of SS-MWI. The stage 1 specification (clause 6) specifies the supplementary service as seen by users of PISNs. The stage 2 specification (clause 7) specifies the functional entities involved in the supplementary service and the information flows between them.

## 2 Conformance

In order to conform to this International Standard, a stage 3 standard shall specify signalling protocols and equipment behaviour that are capable of being used in a PISN which supports the supplementary service specified in this International Standard. This means that, to claim conformance, a stage 3 standard is required to be adequate for the support of those aspects of clause 6 (stage 1) and clause 7 (stage 2) which are relevant to the interface or equipment to which the stage 3 standard applies.

## 3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 11574:2000, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows.*

ISO/IEC 11579-1:1994, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Part 1: Reference configuration for PISN exchanges (PINX).*

CCITT Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN.*

ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs.*

ITU-T Rec. I.210:1993, *Principles of telecommunication services supported by an ISDN and the means to describe them.*

ITU-T Rec. Z.100:1993, *Specification and description language.*

## 4 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

### 4.1 External definitions

This International Standard uses the following terms defined in other documents:

- Basic Service (ITU-T Rec. I.210)
- Private Integrated Services Network Exchange (PINX) (ISO/IEC 11579-1)
- Private Integrated Services Network (PISN) (ISO/IEC 11579-1)

## ISO/IEC 15505:200(E)

— Service	(ITU-T Rec. I.112)
— Signalling	(ITU-T Rec. I.112)
— Supplementary Service	(ITU-T Rec. I.210)
— User	(ISO/IEC 11574)

### 4.2 Other definitions

#### 4.2.1

##### Served User

user to whom the Message Waiting Indication is sent on initiative of the Message Centre

#### 4.2.2

##### Message Centre

entity which activates or deactivates the Message Waiting Indication as a result of the storage or retrieval of messages

#### 4.2.3

##### Message Waiting Indication

indication to the Served User when messages are waiting for the Served User

NOTE The indication may be a lamp, special tone, display etc. This is outside the scope of this International Standard.

## 5 List of acronyms

ANF	Additional Network Feature
FE	Functional Entity
ISDN	Integrated Services Digital Network
MWI	Message Waiting Indication
PINX	Private Integrated Services Network Exchange
PISN	Private Integrated Services Network
SDL	Specification and Description Language
SS	Supplementary Service

## 6 SS-MWI stage 1 specification

### 6.1 Description

#### 6.1.1 General description

The supplementary service MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled.

NOTE 1 The Message Waiting Indication is sent on activation by the Message Centre.

NOTE 2 The Message Waiting Indication is cancelled on deactivation by the Message Centre.

A Served User can receive separate MWIs for each of the services for which there is a message waiting.

NOTE A service for which there is a message waiting would normally use the related basic service to retrieve that message.

#### 6.1.2 Qualifications on applicability to telecommunication services

This supplementary service does not apply directly to any basic telecommunication service. However, a MWI relates to a basic service for which there are messages waiting.

### 6.2 Procedures

#### 6.2.1 Provision / withdrawal

SS-MWI may be provided or withdrawn after pre-arrangement with the service provider or may be generally available to all users.

#### 6.2.2 Normal procedures

##### 6.2.2.1 Activation, deactivation and interrogation

The PISN shall provide activation / deactivation by the Message Centre. In addition, the PISN may provide interrogation by the Served User.



To activate SS-MWI, the Message Centre shall supply the PISN number and the service for which there is a message waiting and may, as an implementation option, add any combination of the following pieces of information: the identity of the Message Centre; the number of messages waiting for the Served User for that service; the address of the user that left a message; the time when a message was left; the priority of the highest priority message waiting for that service. After activation, SS-MWI may be activated again whenever the number of waiting messages changes.

To deactivate SS-MWI, the Message Centre shall supply the PISN number and the service for which there is no longer a message waiting.

As a result of activation, a MWI shall be sent to the Served User. The MWI may include information on messages waiting, if provided by the Message Centre. As a result of deactivation, the MWI at the Served User, for the service concerned, shall be cancelled.

When the Message Centre activates or deactivates SS-MWI at the Served User, it shall be provided with an indication of acceptance.

When the Served User interrogates SS-MWI for a particular service, the Message Centre shall provide the Served User with an indication of whether SS-MWI is activated for that service and may add, as an implementation option, any of the following information:

- the identity of the Message Centre;
- the number of messages waiting;
- the address of the user that left a message;
- the time when a message was left;
- the priority of the highest priority message waiting.

When the Served User interrogates SS-MWI for all services, the Message Centre shall provide the Served User with a list of services for which SS-MWI is active and, as an implementation option, for each service, any of the additional information listed above.

#### 6.2.2.2 Invocation and operation

Not applicable.

[ISO/IEC 15505:2000](https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000)

#### 6.2.3 Exceptional procedures

<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

##### 6.2.3.1 Activation, deactivation and interrogation

If the Served User cannot accept activation or deactivation, then the Message Centre shall be informed and may also be given the reason. If the PISN cannot accept interrogation, then the Served User shall be informed and may also be given a reason.

##### 6.2.3.2 Invocation and operation

None.

### 6.3 Interactions with other Supplementary Services / Additional Network Features

Interactions with other supplementary services and ANFs for which PISN standards were available at the time of publication of this International Standard are specified below.

#### 6.3.1 Advice of Charge (AOC)

No interaction.

#### 6.3.2 Call Deflection (CD)

No interaction.

#### 6.3.3 Call Forwarding Unconditional (CFU)

No interaction.

#### 6.3.4 Call Forwarding Busy (CFB)

No interaction.

#### 6.3.5 Call Forwarding No Reply (CFNR)

No interaction.

#### 6.3.6 Call Interception (CINT)

No interaction.

## ISO/IEC 15505:200(E)

### 6.3.7 Call Intrusion (CI)

No interaction.

### 6.3.8 Call Offer (CO)

No interaction.

### 6.3.9 Call Transfer (CT)

No interaction.

### 6.3.10 Calling/Connected Line Identification Restriction (CLIR)

No interaction.

### 6.3.11 Calling/Connected Name Identification Restriction (CNIR)

No interaction.

### 6.3.12 Calling Line Identification Presentation (CLIP)

No interaction.

### 6.3.13 Calling Name Identification Presentation (CNIP)

No interaction.

### 6.3.14 Connected Line Identification Presentation (COLP)

No interaction.

### 6.3.15 Connected Name Identification Presentation (CONP)

No interaction.

### 6.3.16 Completion of Calls to Busy Subscribers (CCBS)

No interaction.

### 6.3.17 Completion of Calls on No Reply (CCNR)

No interaction.

### 6.3.18 Do Not Disturb (DND)

No interaction.

### 6.3.19 Do Not Disturb Override (DNDO)

No interaction.

### 6.3.20 Path Replacement (PR)

No interaction.

### 6.3.21 Recall (RE)

No interaction.

### 6.3.22 Route Restriction Class (RRC)

No interaction.

### 6.3.23 Cordless Terminal Location Registration (CTLR)

No interaction.

NOTE A MWI may be directed to the new location.

### 6.3.24 Cordless Terminal Mobility Incoming Call (CTMI)

No interaction.

### 6.3.25 Cordless Terminal Mobility Outgoing Call (CTMO)

No interaction.

### 6.3.26 Authentication of a CTM user (CTAT)

No interaction.

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

[ISO/IEC 15505:2000](https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000)

<https://standards.iteh.ai/catalog/standards/sist/1f926206-1d67-48f5-a5d5-6b0360619114/iso-iec-15505-2000>

### 6.3.27 Authentication of the PISN (CTAN)

No interaction.

### 6.4 Interworking considerations

A PISN may be able to accept MWIs from a Message Centre in another network. In this case, the PISN may also be able to interrogate that Message Centre.

A PISN may be able to send MWIs to a Served User in another network. In this case, the PISN may also be able to accept interrogation requests from that Served User.

### 6.5 Overall SDL

Figure 1 contains the dynamic description of SS-MWI using the Specification and Description Language (SDL) defined in ITU-T Rec. Z.100 (1993). The SDL process represents the behaviour of the network in providing SS-MWI.

Input signals from the left and output signals to the left represent primitives from and to the Message Centre.

Input signals from the right and output signals to the right represent primitives from and to the Served User.




Figure 1 (part 1) — SS-MWI Overall SDL