



SLOVENSKI STANDARD
SIST EN 300 175-3 V2.4.1:2012
01-junij-2012

Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 3. del: Plast krmiljenja dostopa do prenosnega medija (MAC)

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part 3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 175-3 Version 2.4.1**

SIST EN 300 175-3 V2.4.1:2012
<https://standards.iteh.ai/catalog/standards/sist/97af0002-3821-4922-b6bb-e677e7e2ba1d/sist-en-300-175-3-v2-4-1-2012>

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
-----------	--	---

SIST EN 300 175-3 V2.4.1:2012 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-3 V2.4.1:2012

<https://standards.iteh.ai/catalog/standards/sist/97af0002-382f-4922-bebb-e677e7e2ba1d/sist-en-300-175-3-v2-4-1-2012>

ETSI EN 300 175-3 V2.4.1 (2012-04)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

[SIST EN 300 175-3 V2.4.1:2012](https://standards.iteh.ai/catalog/standards/sist/97af0002-382f-4922-bebb-e677e7e2ba1d/sist-en-300-175-3-v2-4-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/97af0002-382f-4922-bebb-e677e7e2ba1d/sist-en-300-175-3-v2-4-1-2012>

Reference

REN/DECT-000259

Keywords

DECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-3 V2.4.1:2012

<https://standards.iteh.ai/catalog/standards/sist/97af0002-382f-4922-bebb-e677e7e2ba7c/ETSI-EN-300-175-3-v2-4-1-2012>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	15
3.1 Definitions.....	15
3.2 Symbols and abbreviations.....	16
4 Description of the MAC layer	18
4.1 MAC layer reference model	18
4.1.1 General.....	19
4.1.2 Cluster Control Function (CCF)	19
4.1.3 Cell Site Functions (CSF).....	19
4.1.4 Relationship to physical layer elements.....	19
4.2 Frame and multiframe structures.....	20
4.2.1 General.....	20
4.2.2 Frame structure	20
4.2.3 Multiframe structure	22
4.3 State definitions.....	22
4.3.1 PP states	22
4.3.2 RFP states	23
5 Overview of MAC layer services.....	24
5.1 General	24
5.1.1 Broadcast Message Control (BMC)	24
5.1.2 Connectionless Message Control (CMC)	24
5.1.3 Multi-Bearer Control	24
5.2 Service descriptions.....	24
5.2.1 Common functions.....	24
5.2.2 BMC service	25
5.2.3 CMC service	25
5.2.4 MBC services.....	25
5.3 Logical channels.....	26
5.3.1 MBC connection endpoints (MC-SAP logical channels)	26
5.3.1.1 The higher layer C-plane channels, C	26
5.3.1.2 The higher layer U-Plane channels, I	26
5.3.1.3 The higher layer U-Plane control channel, G _F	27
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	27
5.3.2 CMC endpoints (MB-SAP logical channels).....	28
5.3.2.1 The connectionless C-Plane channels, CL	28
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	28
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	28
5.3.3 BMC endpoint (MA-SAP logical channel).....	28
5.3.3.1 The slow broadcast channel, B _S	28
5.3.4 Internal MAC control channels.....	29
5.3.4.1 The system information channel, Q	29
5.3.4.2 Identities channel, N.....	29
5.3.4.3 The MAC control channel, M	29
5.3.4.4 MAC paging channel, P	29
5.4 SAP definitions	29
5.4.1 MA SAP	30
5.4.2 MB SAP	30
5.4.3 MC SAP.....	30

5.4.4	ME SAP	31
5.4.5	Order of transmission.....	31
5.5	Bearers.....	31
5.5.1	Bearer types	31
5.5.2	Bearer operation.....	32
5.6	Connection oriented services.....	32
5.6.1	Connection types	32
5.6.1.1	Basic connections.....	32
5.6.1.2	Advanced connections	33
5.6.1.2.1	Rules for ECN selection in advanced connections	33
5.6.1.3	Connection identifiers	33
5.6.1.4	Complementary connections	34
5.6.2	Symmetric and asymmetric connections.....	34
5.6.2.1	Symmetric connections	34
5.6.2.2	Asymmetric connections	40
5.7	Broadcast and connectionless services	51
5.7.1	The broadcast services	51
5.7.1.1	The continuous broadcast service	51
5.7.1.2	The non-continuous broadcast service	52
5.7.2	The connectionless services	52
5.7.2.1	Connectionless downlink services	52
5.7.2.2	Connectionless uplink services	52
6	Multiplexing	53
6.1	CCF multiplexing functions	53
6.2	CSF multiplexing functions.....	53
6.2.1	Bit Mappings (MAP)	59
6.2.1.1	D-field mapping (D-MAP)	59
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	60
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	61
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	61
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	62
6.2.1.2	A-field Mapping (A-MAP)	63
6.2.1.3	B-field Mapping (B-MAP)	64
6.2.1.3.1	Unprotected format	64
6.2.1.3.2	Encoded protected format	66
6.2.1.3.3	Multisubfield protected format	66
6.2.1.3.4	Singlesubfield protected format switches	69
6.2.1.3.5	Constant-size subfield protected format	70
6.2.2	Time multiplexers	73
6.2.2.1	Tail MultipleXer (T-MUX)	73
6.2.2.1.1	T-MUX algorithm for RFP transmissions	73
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	74
6.2.2.2	B-field control multiplexer (E/U-MUX)	75
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes	77
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield	77
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation	91
6.2.2.4	Priority scheme in E or E+U mode	92
6.2.3	Encryption.....	93
6.2.4	Scrambling	93
6.2.5	Error control.....	95
6.2.5.1	R-CRC overview	95
6.2.5.2	R-CRC generation and checking	96
6.2.5.3	X-CRC overview.....	96
6.2.5.4	X-CRC generation and checking.....	96
6.2.5.5	B-CRC generation and checking	99
6.2.6	Broadcast controller	99
7	Medium access layer messages	99
7.1	Header field	100
7.1.1	Overview/formatting.....	100
7.1.2	Tail identification, TA, bits a_0 to a_2	100

7.1.3	The "Q1/BCK" bit, bit a_3	100
7.1.4	B-field identification, BA, bits a_4 to a_6	101
7.1.5	The "Q2" bit, bit a_7	102
7.2	Messages in the tail field	102
7.2.1	Overview	102
7.2.2	Identities information (N_T)	102
7.2.3	System information and multiframe marker (Q_T)	103
7.2.3.1	General	103
7.2.3.2	Static system information	104
7.2.3.2.1	General, $Q_H = 0, 1$ (hex)	104
7.2.3.2.2	Q_H and Normal-Reverse (NR)	104
7.2.3.2.3	Slot Number (SN)	104
7.2.3.2.4	Start Position (SP)	105
7.2.3.2.5	ESCAPE bit (ESC)	105
7.2.3.2.6	Number of transceivers	105
7.2.3.2.7	Extended RF carrier information available (M_c)	106
7.2.3.2.8	RF carriers available (RF-cars)	106
7.2.3.2.9	Spare bits (SPR)	106
7.2.3.2.10	Carrier number	106
7.2.3.2.11	Extended static system information available (Ext-System-Info) and spare bit	107
7.2.3.2.11.1	Extended static system information available (Ext-System-Info)	107
7.2.3.2.11.2	Spare bit (SPR)	107
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN)	107
7.2.3.3	Extended RF carrier information part 1	107
7.2.3.3.1	General, $Q_H = 2$ (hex)	107
7.2.3.3.2	Further RF carrier extensions	108
7.2.3.3.3	Number of RF carriers	108
7.2.3.4	Fixed part capabilities	108
7.2.3.4.1	General, $Q_H = 3$ (hex)	108
7.2.3.4.2	Standard capabilities	109
7.2.3.5	Extended fixed part capabilities	110
7.2.3.5.1	General, $Q_H = 4$ (hex)	110
7.2.3.5.2	Extended Physical and MAC layer capabilities	110
7.2.3.5.3	Extended higher layer capabilities	111
7.2.3.6	Secondary access rights identities	111
7.2.3.6.1	General, $Q_H = 5$ (hex)	111
7.2.3.6.2	SARI message	111
7.2.3.7	Multiframe number	112
7.2.3.7.1	General, $Q_H = 6$ (hex)	112
7.2.3.7.2	Multiframe number	112
7.2.3.8	Escape	112
7.2.3.8.1	General, $Q_H = 7$ (hex)	112
7.2.3.8.2	Escape information	112
7.2.3.9	Extended RF carrier information part 2	112
7.2.3.9.1	General, $Q_H = 9$ (hex)	112
7.2.3.10	Transmit information	113
7.2.3.10.1	General, $Q_H = B$ (hex)	113
7.2.3.11	Extended fixed part capabilities (part 2)	114
7.2.3.11.1	General, $Q_H = C$ (hex)	114
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2)	114
7.2.3.11.3	Extended higher layer capabilities (part 2)	115
7.2.3.12	Extended static system information	115
7.2.3.12.1	General, $Q_H = D$ (hex)	115
7.2.3.12.2	Spare bits (Spare)	115
7.2.3.12.3	RFP slot scheme info	115
7.2.4	Paging Tail (P_T)	116
7.2.4.1	General format	116
7.2.4.1.1	P_T format for full and long page messages	116
7.2.4.1.2	P_T format for short page messages	116
7.2.4.1.3	P_T format for zero length page messages	116
7.2.4.1.4	P_T format for MAC_Resume_and_Control_page message	116
7.2.4.2	P_T header format	117

7.2.4.2.1	General format.....	117
7.2.4.2.2	Bit a_8 is the extend flag.....	117
7.2.4.2.3	B_S SDU length indication.....	117
7.2.4.3	MAC layer information for PT.....	118
7.2.4.3.1	Information type.....	118
7.2.4.3.2	Fill bits / Blind long slot ($j=640 / j=672$) information.....	118
7.2.4.3.3	Blind full slot information.....	119
7.2.4.3.4	Bearer description.....	119
7.2.4.3.5	Escape.....	120
7.2.4.3.6	Dummy or connectionless downlink bearer marker.....	120
7.2.4.3.7	Bearer handover/replacement and no-emission mode information.....	120
7.2.4.3.8	RFP status and modulation types.....	121
7.2.4.3.9	Active carriers.....	122
7.2.4.3.10	RFP power level.....	122
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	123
7.2.4.3.12	Extended modulation types.....	123
7.2.5	MAC control (M_T).....	124
7.2.5.1	General format and contents.....	124
7.2.5.2	Basic connection control.....	124
7.2.5.2.1	General.....	124
7.2.5.2.2	Format for most messages.....	125
7.2.5.2.3	WAIT.....	125
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}.....	125
7.2.5.3	Advanced connection control.....	126
7.2.5.3.1	General.....	126
7.2.5.3.2	ACCESS_REQUEST.....	126
7.2.5.3.3	BEARER_HANDOVER_REQUEST.....	126
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST.....	126
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST.....	127
7.2.5.3.6	BEARER_CONFIRM.....	127
7.2.5.3.7	WAIT.....	127
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}.....	127
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}.....	130
7.2.5.3.10	Channel_list.....	130
7.2.5.3.11	Unconfirmed_dummy.....	131
7.2.5.3.12	Unconfirmed_handover.....	131
7.2.5.3.13	RELEASE.....	131
7.2.5.4	MAC layer test messages.....	132
7.2.5.4.1	Basic format.....	132
7.2.5.4.2	FORCE_TRANSMIT.....	133
7.2.5.4.3	LOOPBACK_DATA.....	133
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	134
7.2.5.4.5	ESCAPE.....	135
7.2.5.4.6	NETWORK_TEST.....	135
7.2.5.4.7	CLEAR_TEST_MODES.....	135
7.2.5.4.8	CHANGE_MODULATION_SCHEME.....	135
7.2.5.5	Quality control.....	136
7.2.5.5.1	Prolonged preamble diversity.....	137
7.2.5.6	Broadcast and connectionless services.....	138
7.2.5.7	Encryption control.....	138
7.2.5.8	B-field setup, first PT transmission.....	139
7.2.5.9	Escape.....	139
7.2.5.10	TARI message.....	140
7.2.5.11	REP connection control.....	140
7.2.5.11.1	General.....	140
7.2.5.11.2	Format for most messages.....	140
7.2.5.11.3	REP CHANNEL MAP REQUEST.....	140
7.2.5.11.4	REP CHANNEL MAP CONFIRM.....	141
7.3	Messages in the B-field.....	141
7.3.1	Overview.....	141
7.3.2	Advanced connection control.....	142
7.3.2.1	General format.....	142

7.3.2.2	BEARER_REQUEST	143
7.3.2.3	BEARER_CONFIRM	143
7.3.2.4	WAIT	144
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}	144
7.3.2.6	BANDWIDTH_B_{Req;Cfm}	145
7.3.2.7	CHANNEL_LIST	145
7.3.2.8	UNCONFIRMED_DUMMY	145
7.3.2.9	UNCONFIRMED_HANDOVER	146
7.3.2.10	RELEASE	146
7.3.3	Null or I _{PF} segmentation info	147
7.3.3.1	Spare or I _{PF} segmentation info	148
7.3.3.2	Extended NCF bits	149
7.3.4	Quality control	149
7.3.4.1	General format	149
7.3.4.2	Bearer and connection control	149
7.3.4.3	RESET	151
7.3.4.4	Bearer quality in an asymmetric connection	151
7.3.5	Extended system information	152
7.3.5.1	General format	152
7.3.5.2	TARI messages	152
7.3.5.3	"no-emission" mode sync information	152
7.3.6	G _F channel data packet	153
7.3.7	Escape	153
8	Medium access layer primitives	153
8.1	Connection oriented service primitives	154
8.1.1	Connection setup: MAC_CON {req;ind;cfm}	154
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}	155
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}	156
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}	157
8.1.5	Restart DLC: MAC_RES_DLC {ind}	157
8.1.6	Connection release: MAC_DIS {req;ind}	157
8.1.7	MAC bandwidth: MAC_BW {ind;res}	158
8.1.8	Encryption	158
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}	158
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}	158
8.1.9	C-plane switching procedure	159
8.1.9.1	C-plane switching procedure: MAC_C _S C _F {req, cfm, ind, res}	159
8.1.9.2	C-plane switching procedure: MAC_C _S C _F _END {ind}	159
8.2	Connectionless and broadcast service primitives	160
8.2.1	Paging: MAC_PAGE {req;ind}	160
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}	160
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}	161
8.2.4	"no-emission" mode	161
8.3	Management primitives	161
8.3.1	Connection control	161
8.3.1.1	Connection setup: MAC_ME_CON {ind}	161
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}	161
8.3.1.3	Bearer release: MAC_ME_REL {req}	161
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind}	162
8.3.2	System information and identities	162
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}	162
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}	162
8.3.2.3	System information output: MAC_ME_INFO {ind;res}	162
8.3.2.4	Extended system info: MAC_ME_EXT_{req;ind;res;cfm}	162
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}	162
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}	163
8.3.5	Error reports: MAC_ME_ERROR {ind;res}	163
8.4	Flow control	163
8.4.1	MA SAP flow control	163
8.4.2	MB SAP flow control	163
8.4.3	MC SAP flow control	163

9	Broadcast and connectionless procedures	166
9.1	Downlink broadcast and connectionless procedures	166
9.1.1	Downlink broadcast procedure	166
9.1.1.1	Broadcast information	166
9.1.1.2	Channel selection for downlink broadcast services	166
9.1.1.3	Downlink broadcast procedure description	168
9.1.2	Downlink connectionless procedure	168
9.1.2.1	Channel selection at the RFP	168
9.1.2.2	Downlink connectionless procedure description	168
9.1.3	Paging broadcast procedure	168
9.1.3.1	RFP paging broadcasts	169
9.1.3.2	PP paging procedures	171
9.1.3.2.1	PP paging detection	171
9.1.3.2.2	PP paging processing	171
9.2	Uplink connectionless procedures	171
9.2.1	General	171
9.2.2	Bearer selection for the connectionless uplink	172
9.2.3	Procedure for the connectionless uplink	172
9.2.3.1	Predicates	172
9.2.3.2	PT D-field construction	172
9.2.3.3	PT transmission sequence	173
9.2.3.4	FT procedure	173
9.3	Non-continuous broadcast procedure	174
9.3.1	Request for specific Q channel information	174
9.3.1.1	A-field procedure	174
9.3.1.2	B-field procedure	174
9.3.2	Request for a new dummy bearer	175
9.4	"No-emission" mode procedures	175
9.4.1	Initiation of the "no-emission" mode	175
9.4.1.1	Successful activation (countdown to zero)	175
9.4.1.2	Multiframe countdown stopped by FT	176
9.4.1.3	Multiframe countdown stopped by PT	176
9.4.1.4	PT does not receive multiframe countdown "zero"	177
9.4.2	Behaviour during power-down mode	177
9.4.3	Waking up, FT initiated	177
9.4.4	Waking up, PT initiated	181
10	Connection oriented service procedures	182
10.1	Overview	182
10.2	C/O connection setup	183
10.2.1	General	183
10.2.2	Initiation of a basic and a normal connection setup	183
10.2.3	Initiation of a fast connection setup	183
10.2.4	Connection setup procedure description	184
10.2.4.1	Creation of MBCs	184
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	186
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation	187
10.2.4.3.1	Symmetric connection	189
10.2.4.3.2	Asymmetric uplink connection	189
10.2.4.3.3	Asymmetric downlink connection	189
10.2.4.3.4	Connection established	189
10.3	C/O connection modification	190
10.3.1	Advanced connection: bandwidth modification	190
10.3.1.1	Suspend and resume	192
10.3.1.2	MAC resume paging	192
10.3.2	Advanced connection: service type or slot type modification	192
10.3.2.1	Procedure for service type modification	192
10.3.2.2	Procedures for slot type modification	193
10.3.2.2.1	Procedure for slot type modification full to double	193
10.3.2.2.2	Procedure for slot type modification double to full	194
10.3.2.2.3	Procedures for slot type modification to/from long	194
10.3.2.2.4	Procedure for slot type modification in multibearer connections	195

10.3.2.3	Procedure for ECN number modification in an advanced connection	195
10.3.3	Connection type modification	195
10.3.3.1	Procedure for connection type modification basic to advanced	196
10.3.3.1.1	General procedure	196
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	196
10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long	197
10.3.3.2	Procedure for connection type modification advanced to basic	197
10.3.4	Modulation type modification	197
10.3.4.1	Adaptive code rate	199
10.4	C/O connection release	199
10.4.1	General	199
10.4.2	Procedure description	200
10.5	C/O bearer setup	200
10.5.1	Single bearer setup procedures	200
10.5.1.1	Basic bearer setup procedure	200
10.5.1.2	A-field advanced single bearer setup procedure	202
10.5.1.2.1	PT initiated	203
10.5.1.2.2	FT initiated	205
10.5.1.3	B-field single bearer setup procedure	206
10.5.1.3.1	PT initiated	207
10.5.1.3.2	FT initiated	209
10.5.1.4	Double simplex setup procedure	209
10.5.1.4.1	Terminology and Predicates	209
10.5.1.4.2	General description	210
10.5.1.4.3	Channel selection procedure for circuit mode connections	210
10.5.1.4.4	Channel selection procedure for packet mode connections	211
10.5.1.4.5	Indirect setup procedure	212
10.5.1.4.6	Direct setup procedure	212
10.5.1.4.7	Handling of encrypted connections	215
10.5.1.5	Complementary connection bearer setup	217
10.5.1.6	Double duplex bearer setup procedure Mapping procedure	217
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	218
10.5.1.7.1	Default rules for TA code "111"	219
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	219
10.5.2	Channel list procedures	220
10.5.2.1	General	220
10.5.2.2	Description of the channel list messages	220
10.5.2.3	Usage of the channel list messages	221
10.6	C/O bearer handover	222
10.6.1	General	222
10.6.2	Duplex bearer handover procedure	223
10.6.3	Double simplex bearer handover	224
10.6.4	Bearer replacement	224
10.6.4.1	General bearer replacement	224
10.6.4.2	Frequency replacement	225
10.7	C/O bearer release	226
10.7.1	General	226
10.7.2	Bearer release procedure description	226
10.7.2.1	Unacknowledged release procedure	226
10.7.2.1.1	Crossed bearer release procedure	227
10.7.2.2	Acknowledged release procedure	227
10.7.2.3	Fast release procedure	227
10.7.2.4	REP relayed bearer release	228
10.8	C/O data transfer	228
10.8.1	Higher layer associated signalling (C)	228
10.8.1.1	C _S channel data	228
10.8.1.1.1	Transmission principle	229
10.8.1.1.2	Numbering principle	229
10.8.1.2	C _F channel data	229
10.8.1.2.1	Transmission principle	229

10.8.1.2.2	Numbering principle.....	230
10.8.1.3	Q1 and Q2 bit settings for I_N and I_P error_detection services	230
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I_N	230
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I_P error_detect	230
10.8.1.3.3	Q2 bit settings.....	231
10.8.1.3.4	Q1 bit settings.....	232
10.8.2	MOD-2 protected I channel operation (I_P).....	233
10.8.2.1	General	233
10.8.2.1.1	Use of selective reception.....	233
10.8.2.2	Limiting the lifetime of packets	234
10.8.2.3	A-field shall always be correct.....	234
10.8.2.4	Use of the acknowledge bits.....	234
10.8.2.4.1	Q2 and BCK bit setting for I_P error_correction services	234
10.8.2.4.2	BCK bit setting.....	235
10.8.2.5	Data jump procedures	235
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement	235
10.8.2.5.2	Unilateral jump.....	235
10.8.2.5.3	MAC I_P bearer reset.....	237
10.8.2.6	Bearer handover and bearer replacement procedures.....	237
10.8.2.6.1	General	237
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	237
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel	238
10.8.2.7	Exchange of data from/to higher layers	239
10.8.2.7.1	Operation if I_{PF} channel is supported.....	239
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_P).....	239
10.8.3.1	I_N minimum_delay service (I_{NA})	239
10.8.3.2	I_N normal_delay service (I_{NB})	240
10.8.3.3	I_P error_detection service	240
10.8.3.3.1	Operation if I_{PF} channel is supported.....	240
10.8.3.4	I_P encoded_protected service (I_{PX})	241
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux.....	241
10.8.4.1	Purpose of the I_{PF} channel	241
10.8.4.2	Activation of the E+U type mux mode.....	241
10.8.4.3	I_{PF} procedures	241
10.8.4.3.1	I_{PF} basic procedures.....	242
10.8.4.3.2	I_{PF} advanced procedures	242
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	243
10.8.4.4	I_{PF} Mod-2 protected operation.....	243
10.8.4.5	I_{PF} error_detect operation	244
10.8.4.6	I_{PF} operation with I_N service	244
10.8.4.7	Backcompatibility rule	244
10.9	C/O procedures for FT connections with CRFP.....	244
10.9.1	Dual C/O bearer setup.....	244
10.9.2	C/O connection release of connection with CRFP.....	244
10.9.3	C/O connection suspend and resume	245
11	Medium access layer management procedures	245
11.1	Broadcasting.....	245
11.1.1	RFP transmission	245
11.1.2	PP reception.....	245
11.2	Extended system information	245
11.2.1	PP requests.....	245
11.2.2	RFP response	246
11.3	PP states and state transitions	246
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	246
11.3.2	Entry into the Idle_Locked state	246
11.3.3	Actions in the Idle_Locked state.....	246
11.3.3.1	Page detection in Idle_Locked state.....	247
11.3.3.2	Setup detection in Idle_Locked state.....	247
11.3.4	Idle_Locked and Active_Locked state transitions	248
11.4	Physical channel selection.....	248

11.4.1	The channel selection lists	248
11.4.2	Physical channel and RFP selection at the PP	250
11.4.3	Physical channel selection at the RFP.....	252
11.4.4	Hand over criteria due to in-connection base identification	253
11.4.5	Handover criteria due to interference.....	253
11.5	In-connection quality control	254
11.5.1	RFPI handshake	254
11.5.2	Frequency control	254
11.5.2.1	RFP measurement of frequency error	254
11.5.2.2	PT frequency correction	254
11.6	Maximum allowed system load at RFPs	254
11.7	PMID and FMID definitions	255
11.7.1	FMID definition.....	255
11.7.2	PMID definition.....	255
11.8	RFP idle receiver scan sequence	255
11.9	PT receiver scan sequence.....	256
11.10	Management of connections associated with Broadband data links.....	256
11.11	Management procedures for "no-emission" mode.....	256
11.11.1	Behaviour during "no-emission" mode.....	257
12	Medium access layer test message procedure	257
12.1	Introduction	257
12.2	General	257
12.2.1	Portable part testing	259
12.2.2	Fixed part testing	259
12.2.3	Applicability of test messages	259
12.3	FORCE_TRANSMIT.....	259
12.3.1	Portable part.....	259
12.3.2	Fixed part.....	260
12.4	LOOPBACK_DATA	260
12.4.1	Portable part.....	261
12.4.2	Fixed Part.....	261
12.4.2.1	IUTs implementing the DECT scrambler.....	261
12.4.2.2	IUTs implementing a proprietary scrambler.....	261
12.5	DEFEAT_ANTENNA_DIVERSITY	261
12.6	NETWORK_TEST	261
12.7	ESCAPE.....	261
12.8	CLEAR_TEST_MODES	261
12.9	CHANGE_MODULATION_SCHEME	261
Annex A (normative):	MAC layer timers and constants.....	262
A.1	Timers and Time Windows	262
A.2	Constants	262
Annex B (informative):	Construction of the CRC polynomial and error detecting performance	264
Annex C (informative):	MAC relationship to other layers.....	265
Annex D (informative):	Synchronization	266
Annex E (normative):	Scrambling patterns	267
Annex F (informative):	Seamless handover operation	268
F.1	I channel data flow for I _N _minimum_delay service	268
Annex G (normative):	Requirements for PPs with direct PP to PP communication mode.....	269
G.1	Description of operation in direct PP to PP communication mode	269
G.2	Requirements.....	270
G.2.1	Setting the PP in direct communications mode	270

G.2.2	Specific Alternative 1 requirements	270
G.2.2.1	When the PP has not initiated a call.....	270
G.2.2.2	When the PP initiates a call	270
G.2.3	Specific Alternative 2 Requirements.....	271
Annex H (normative): Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode.....272		
H.1	Introduction	272
H.2	Description of operation in W-FT2FT communication mode.....	273
Annex I (normative): Channel coding and Modulation274		
I.1	Channel coding.....	275
I.1.1	The parallel Turbo Code Principle	275
I.1.2	The FOCTC implementation.....	275
I.1.2.1	The FOCTC concept.....	275
I.1.2.2	The FOCTC structure and the component code.....	276
I.1.2.3	The FOCTC Inner interleaving algorithm	278
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats	279
I.2	Adaptive coding and Modulation Embodiment.....	281
I.2.1	Adaptive code rates	281
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80)	282
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32).....	283
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80).....	283
I.2.2	Puncturing patterns.....	284
I.2.3	Channel Capacity for the B-field map configurations	285
I.2.3.1	Double Slot Structure.....	285
I.2.3.2	Full Slot Structure.....	286
I.2.3.3	Half Slot Structure	287
I.3	Change Modulation Scheme	287
I.4	B-Field Binary Interleaving.....	287
I.4.1	General description.....	287
I.4.2	Mathematical Description	289
I.4.2.1	L(k) Expression	289
I.4.2.2	Interleaving Spreading $\Delta L(s)$ Expression	290
I.4.3	B-field binary interleaving parameters	291
I.4.3.1	Physical packet Format P80 (double slot structure).....	291
I.4.3.2	Physical packet Format P32 (full slot structure).....	292
I.4.3.3	Physical packet Format P00j with j=80 (Half-Slot structure).....	292
Annex J (informative): Channel decoding.....293		
Annex K (informative): Additional information on MAC messages.....294		
K.1	Historic use of some MAC service codes.....	294
Annex L (informative): Bibliography.....295		
Annex M (informative): Change history296		
History	297

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 3 of a multi-part deliverable ([1] to [8]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

National transposition dates	
Date of adoption of this EN:	17 April 2012
Date of latest announcement of this EN (doa):	31 July 2012
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2013
Date of withdrawal of any conflicting National Standard (dow):	31 January 2013