



SLOVENSKI STANDARD
SIST EN 300 175-5 V2.4.1:2012
01-junij-2012

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 5.
del: Omrežna plast (NWK)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
5: Network (NWK) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 175-5 Version 2.4.1**
<https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac5b-084046dc9723/sist-en-300-175-5-v2-4-1-2012>

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
35.100.30	Omrežni sloj	Network layer

SIST EN 300 175-5 V2.4.1:2012 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-5 V2.4.1:2012

<https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac3b-084046dc9723/sist-en-300-175-5-v2-4-1-2012>

ETSI EN 300 175-5 V2.4.1 (2012-04)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer

[SIST EN 300 175-5 V2.4.1:2012
https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac3b-084046dc9723/sist-en-300-175-5-v2-4-1-2012](https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac3b-084046dc9723/sist-en-300-175-5-v2-4-1-2012)

Reference

REN/DECT-000261

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-5 V2.4.1:2012<https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac3b-084046dc9772/etsi-en-300-175-v2-4-1-2012>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
1 Scope	17
2 References	17
2.1 Normative references	18
2.2 Informative references.....	21
3 Definitions, symbols and abbreviations	22
3.1 Definitions.....	22
3.2 Symbols and abbreviations.....	23
4 Overview of the NWK layer	26
5 Overview of procedures	28
5.1 General	28
5.2 Overview of Call Control (CC).....	28
5.2.1 General.....	28
5.2.2 Call establishment.....	28
5.2.2.1 Call setup	28
5.2.2.2 Service negotiation.....	29
5.2.3 Call connect	29
5.2.4 Call information.....	29
5.2.5 Service change.....	30
5.2.6 Call release.....	30
5.3 Overview of Supplementary Services (SS)	30
5.3.1 General.....	30
5.3.2 Keypad protocol.....	31
5.3.3 Feature key management protocol.....	31
5.3.4 Functional protocol.....	31
5.4 Overview of Connection Oriented Message Service (COMS).....	31
5.4.1 General.....	31
5.4.2 COMS establishment	32
5.4.3 Service negotiation	32
5.4.4 COMS connect.....	32
5.4.5 COMS data transfer	32
5.4.6 COMS suspend and resume	32
5.4.7 COMS release	33
5.5 Overview of ConnectionLess Message Service (CLMS).....	33
5.5.1 Fixed length message service.....	33
5.5.2 Variable length message service.....	33
5.6 Overview of Mobility Management (MM)	33
5.6.1 General.....	33
5.6.2 Identity procedures	34
5.6.3 Authentication procedures	34
5.6.4 Location procedures.....	35
5.6.5 Access rights procedures	35
5.6.6 Key allocation procedure	35
5.6.7 Parameter retrieval procedure	36
5.6.8 Cipherring related procedure.....	36
5.6.9 External protocol information procedure.....	36
5.7 Overview of Link Control Entity (LCE)	36
5.7.1 General.....	36
5.7.2 Data Link Endpoint Identifier (DLEI)	36
5.7.3 Data link establishment.....	37
5.7.4 Data link re-establishment	37
5.7.5 Data link release	37

5.7.6	Data link suspend and resume.....	38
5.7.7	Queuing of messages	38
5.7.8	Request paging.....	38
6	Message functional definitions.....	38
6.1	Overview of message structures	38
6.1.1	Messages.....	38
6.1.2	Information elements	39
6.2	Message summaries.....	40
6.2.1	Summary of CC messages	40
6.2.2	Summary of CISS messages	40
6.2.3	Summary of COMS messages	41
6.2.4	Summary of CLMS messages.....	41
6.2.5	Summary of MM messages	42
6.2.6	Summary of LCE messages	42
6.3	S-FORMAT message functional contents.....	43
6.3.1	S-FORMAT message overview.....	43
6.3.2	CC-messages.....	43
6.3.2.1	{CC-SETUP}.....	43
6.3.2.2	{CC-INFO}.....	45
6.3.2.3	{CC-SETUP-ACK}	46
6.3.2.4	{CC-CALL-PROC}	47
6.3.2.5	{CC-ALERTING}	48
6.3.2.6	{CC-CONNECT}	49
6.3.2.7	{CC-CONNECT-ACK}.....	50
6.3.2.8	{CC-RELEASE}.....	50
6.3.2.9	{CC-RELEASE-COM}.....	52
6.3.2.10	{CC-SERVICE-CHANGE}.....	53
6.3.2.11	{CC-SERVICE-ACCEPT}.....	54
6.3.2.12	{CC-SERVICE-REJECT}.....	54
6.3.2.13	{CC-NOTIFY}.....	55
6.3.2.14	{IWU-INFO}	55
6.3.3	SS-messages (call related and call independent).....	56
6.3.3.1	{FACILITY}.....	56
6.3.3.2	{HOLD}.....	57
6.3.3.3	{HOLD-ACK}	57
6.3.3.4	{HOLD-REJECT}	58
6.3.3.5	{RETRIEVE}	58
6.3.3.6	{RETRIEVE-ACK}	59
6.3.3.7	{RETRIEVE-REJECT}	59
6.3.3.8	{CISS-REGISTER}	60
6.3.3.9	{CISS-RELEASE-COM}	61
6.3.4	COMS-messages.....	61
6.3.4.1	{COMS-SETUP}	61
6.3.4.2	{COMS-INFO}	62
6.3.4.3	{COMS-ACK}.....	63
6.3.4.4	{COMS-CONNECT}	63
6.3.4.5	{COMS-RELEASE}.....	64
6.3.4.6	{COMS-RELEASE-COM}	64
6.3.4.7	{COMS-NOTIFY}.....	65
6.3.5	CLMS-message.....	65
6.3.5.1	{CLMS-VARIABLE}	65
6.3.6	MM-messages.....	66
6.3.6.1	{ACCESS-RIGHTS-ACCEPT}	66
6.3.6.2	{ACCESS-RIGHTS-REJECT}.....	66
6.3.6.3	{ACCESS-RIGHTS-REQUEST}	67
6.3.6.4	{ACCESS-RIGHTS-TERMINATE-ACCEPT}	67
6.3.6.5	{ACCESS-RIGHTS-TERMINATE-REJECT}	68
6.3.6.6	{ACCESS-RIGHTS-TERMINATE-REQUEST}.....	68
6.3.6.7	{AUTHENTICATION-REJECT}	69
6.3.6.8	{AUTHENTICATION-REPLY}.....	70
6.3.6.9	{AUTHENTICATION-REQUEST}	71

6.3.6.10	{CIPHER-REJECT}	71
6.3.6.11	{CIPHER-REQUEST}	72
6.3.6.12	{CIPHER-SUGGEST}	72
6.3.6.13	{DETACH}	72
6.3.6.14	{IDENTITY-REPLY}	73
6.3.6.15	{IDENTITY-REQUEST}	74
6.3.6.16	{KEY-ALLOCATE}	74
6.3.6.17	{LOCATE-ACCEPT}	75
6.3.6.18	{LOCATE-REJECT}	75
6.3.6.19	{LOCATE-REQUEST}	76
6.3.6.20	{MM-INFO-ACCEPT}	77
6.3.6.21	{MM-INFO-REJECT}	77
6.3.6.22	{MM-INFO-REQUEST}	78
6.3.6.23	{MM-INFO-SUGGEST}	79
6.3.6.24	{TEMPORARY-IDENTITY-ASSIGN}	79
6.3.6.25	{TEMPORARY-IDENTITY-ASSIGN-ACK}	80
6.3.6.26	{TEMPORARY-IDENTITY-ASSIGN-REJ}	80
6.3.6.27	{MM-IWU}	81
6.3.6.28	{MM-NOTIFY}	81
6.3.7	LCE-messages	82
6.3.7.1	{LCE-PAGE-RESPONSE}	82
6.3.7.2	{LCE-PAGE-REJECT}	82
6.4	B-FORMAT message functional contents	83
6.4.1	B-FORMAT message overview	83
6.4.2	{LCE-REQUEST-PAGE}	83
6.4.3	{CLMS-FIXED}	84
7	S-FORMAT message structures	84
7.1	Overview	84
7.2	Protocol Discrimination (PD) element	85
7.3	Transaction Identifier (TI) element	85
7.4	Message type element	86
7.4.1	Messages for CC	87
7.4.2	Messages for SS	87
7.4.3	Messages for COMS	87
7.4.4	Messages for CLMS	88
7.4.5	Messages for MM	88
7.4.6	Messages for LCE	88
7.5	Other information elements	89
7.5.1	Coding rules	89
7.5.2	Extensions of codesets	91
7.5.3	Locking shift procedure	91
7.5.4	Non-locking shift procedure	92
7.5.5	Display and keypad elements	92
7.5.6	Repeated elements	92
7.6	Fixed length information elements	93
7.6.1	Summary	93
7.6.2	Sending complete, delimiter request and use TPUI	93
7.6.3	Repeat indicator	94
7.6.4	Basic service	94
7.6.5	Single display	95
7.6.6	Single keypad	95
7.6.7	Release reason	96
7.6.8	Signal	97
7.6.9	Timer restart	98
7.6.10	Test hook control	98
7.7	Variable length information elements	98
7.7.1	Summary	98
7.7.2	Allocation type	100
7.7.3	Alphanumeric	100
7.7.4	Auth type	102
7.7.5	Call attributes	103

STANDARD PREVIEW

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/aaa6b975-1d70-447fac3b-084046dc9723/sist-en-300-175-5-v2-4-1-2012>

7.7.6	Call identity	106
7.7.7	Called party number.....	106
7.7.8	Called party subaddress	107
7.7.9	Calling party number	108
7.7.10	Cipher info	109
7.7.11	Connection attributes	110
7.7.12	Connection identity.....	113
7.7.13	Duration	114
7.7.14	End-to-end compatibility	115
7.7.15	Facility	118
7.7.16	Feature activate.....	118
7.7.17	Feature indicate.....	120
7.7.18	Fixed identity	122
7.7.19	Identity type	123
7.7.20	Info type.....	124
7.7.21	InterWorking Unit (IWU) attributes	125
7.7.22	IWU packet.....	130
7.7.23	IWU to IWU	131
7.7.24	Key.....	133
7.7.25	Location area	133
7.7.26	Multi-display.....	134
7.7.27	Multi-keypad.....	135
7.7.28	NetWorK (NWK) assigned identity.....	135
7.7.29	Network parameter	136
7.7.30	Portable identity	138
7.7.31	Progress indicator	142
7.7.32	RAND	143
7.7.33	Rate parameters	143
7.7.34	Reject reason.....	144
7.7.35	RES	145
7.7.36	RS	146
7.7.37	Segmented info	146
7.7.38	Service change info	147
7.7.39	Service class.....	148
7.7.40	Setup capability	149
7.7.41	Terminal capability	150
7.7.42	Transit delay	156
7.7.43	Window size	156
7.7.44	ZAP field	157
7.7.45	Escape to proprietary	157
7.7.46	Model identifier	158
7.7.47	MMS Generic Header.....	159
7.7.48	MMS Object Header.....	159
7.7.49	MMS Extended header	159
7.7.50	Time-Date	160
7.7.51	Ext h/o indicator	162
7.7.52	Called party Name	162
7.7.53	Calling party Name	163
7.7.54	Codec List.....	164
7.7.55	Events notification	165
7.7.56	Call information.....	169
8	B-FORMAT message structures	172
8.1	General	172
8.2	LCE request paging messages	172
8.2.1	Short format message.....	173
8.2.2	Full format message.....	174
8.2.3	Long format message.....	175
8.2.4	Message elements	176
8.2.4.1	LCE paging header.....	176
8.2.4.2	Info fields (Full format)	177
8.2.4.3	Default setup behaviour	178

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 300 175-5 V2.4.1:2012
<http://standards.itech.ai/catalog/standards/sist/aaa6b975-1d70-447f-ac3b-084046dc9723/sist-en-300-175-5-v2-4-1-2012>

8.2.4.4	Address elements in collective or group ringing.....	180
8.3	CLMS-FIXED messages	180
8.3.1	General message structure	180
8.3.2	Message elements	181
8.3.3	Standard message structures	183
8.3.3.1	General	183
8.3.3.2	Messages using 4-bit characters	183
8.3.3.3	Messages using 8-bit characters	183
9	Call Control (CC) procedures.....	183
9.1	General	183
9.2	Call Control (CC) states	186
9.2.1	States at PT	186
9.2.1.1	State T-00: "NULL"	186
9.2.1.2	State T-19: "RELEASE PENDING"	186
9.2.1.3	State T-10: "ACTIVE"	186
9.2.1.4	State T-01: "CALL INITIATED"	186
9.2.1.5	State T-02: "OVERLAP SENDING"	186
9.2.1.6	State T-03: "CALL PROCEEDING"	186
9.2.1.7	State T-04: "CALL DELIVERED"	186
9.2.1.8	State T-06: "CALL PRESENT"	186
9.2.1.9	State T-07: "CALL RECEIVED"	186
9.2.1.10	State T-08: "CONNECT PENDING"	186
9.2.2	States at FT	187
9.2.2.1	State F-00: "NULL"	187
9.2.2.2	State F-19: "RELEASE PENDING"	187
9.2.2.3	State F-10: "ACTIVE"	187
9.2.2.4	State F-01: "CALL INITIATED"	187
9.2.2.5	State F-02: "OVERLAP SENDING"	187
9.2.2.6	State F-03: "CALL PROCEEDING"	187
9.2.2.7	State F-04: "CALL DELIVERED"	187
9.2.2.8	State F-06: "CALL PRESENT"	187
9.2.2.9	State F-07: "CALL RECEIVED"	187
9.2.3	Optional states (PT and FT)	188
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING"	188
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING"	188
9.3	Call establishment procedures.....	188
9.3.1	PT initiated call establishment (outgoing call).....	188
9.3.1.1	Call request	188
9.3.1.2	Call accept or reject.....	189
9.3.1.3	Selection of lower layer resources	189
9.3.1.4	Connection of U-plane	190
9.3.1.5	Overlap sending	190
9.3.1.6	Call proceeding	191
9.3.1.7	Call confirmation	191
9.3.1.8	Call connection	192
9.3.1.9	Expiry of timer <CC.04>	192
9.3.2	FT initiated call establishment (incoming call).....	192
9.3.2.1	Call request	192
9.3.2.2	Call accept or reject.....	193
9.3.2.3	Selection of lower layer resources	193
9.3.2.4	Connection of U-plane	194
9.3.2.5	Overlap receiving	194
9.3.2.6	Call proceeding	194
9.3.2.7	Call confirmation	194
9.3.2.8	Call connection	194
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>.....	195
9.3.2.10	Expiry of timer <CC.04>	195
9.4	Call information procedures	195
9.5	Call release procedures.....	195
9.5.1	Normal call release	195
9.5.2	Abnormal call release	196

9.5.3	Release collisions.....	197
9.6	Service change procedures	197
9.6.1	General.....	197
9.6.2	Change of Bandwidth parameters (including changes in connection type)	198
9.6.3	Service rerouting.....	198
9.6.4	NWK layer service suspension and resumption.....	198
9.6.5	Modulation scheme change.....	199
9.7	NWK layer Packet mode procedures.....	199
9.7.1	General.....	199
9.7.2	PT initiated access	200
9.7.3	FT initiated access	200
9.7.4	NWK layer suspend and resume.....	200
9.7.4.1	General	200
9.7.4.2	C-plane NWK layer suspend and resume.....	201
9.7.4.3	U-plane NWK layer suspend and resume	201
9.8	Emergency call procedure.....	201
9.9	Segmentation of information in CC procedures	202
10	Supplementary Services procedures.....	203
10.1	General	203
10.2	Keypad protocol	204
10.3	Feature key management protocol.....	204
10.4	Functional protocol.....	205
10.4.1	Separate messages approach	205
10.4.1.1	Hold procedures	205
10.4.1.2	Retrieve procedures.....	205
10.4.1.3	Auxiliary states for hold and retrieve.....	206
10.4.2	Common information element approach.....	206
10.4.2.1	Call Related Supplementary Services (CRSS) procedures.....	206
10.4.2.2	Call Independent Supplementary Services (CISS) procedures	206
10.4.2.2.1	Transport of CISS.....	206
10.4.2.3	Connectionless Supplementary Service (CLSS) procedure	207
10.5	Co-existence of multiple protocols.....	207
10.6	Application protocols	208
10.6.1	DECT standard functional supplementary services	208
10.6.2	DECT specific supplementary services	209
10.6.2.1	Queue management.....	209
10.6.2.2	Indication of subscriber number.....	209
10.6.2.3	Control of echo control functions.....	210
10.6.2.4	Cost information	210
11	Connection Oriented Message Service (COMS).....	211
11.1	General	211
11.2	COMS states.....	211
11.2.1	States at PT	211
11.2.1.1	State TS-0: "NULL"	211
11.2.1.2	State TS-1: "CONNECT PENDING"	211
11.2.1.3	State TS-2: "RELEASE PENDING"	211
11.2.1.4	State TS-3: "ACTIVE"	211
11.2.2	States at FT	211
11.2.2.1	State FS-0: "NULL"	211
11.2.2.2	State FS-1: "CONNECT PENDING"	211
11.2.2.3	State FS-2: "RELEASE PENDING"	211
11.2.2.4	State FS-3: "ACTIVE"	212
11.3	COMS establishment procedures	212
11.3.1	PT initiated COMS establishment	212
11.3.1.1	COMS request.....	212
11.3.1.2	COMS connection.....	212
11.3.2	FT initiated COMS establishment	213
11.3.2.1	COMS request.....	213
11.3.2.2	COMS connection.....	213
11.4	COMS data transfer procedures	213

11.4.1	Procedure at the sending side.....	213
11.4.2	Procedure at the receiving side	214
11.5	COMS NWK layer suspend and resume procedures.....	215
11.6	COMS release procedures	215
11.6.1	Normal COMS release.....	215
11.6.2	Release collisions.....	215
12	ConnectionLess Message Service (CLMS).....	216
12.1	General	216
12.2	CLMS states	216
12.3	CLMS message transmission procedures	216
12.3.1	Fixed length messages	216
12.3.1.1	Procedure in the Fixed radio Termination (FT)	216
12.3.1.2	Procedure in the Portable radio Termination (PT)	217
12.3.2	Variable length messages.....	217
12.3.2.1	Procedure at the sending side	217
12.3.2.2	Procedure at the receiving side.....	217
12.3.2.3	Restrictions for portable side initiated messages.....	218
13	Mobility Management (MM) procedures.....	218
13.1	General	218
13.2	Identity procedures	219
13.2.1	Procedure for identification of PT	219
13.2.2	Procedure for temporary identity assignment	220
13.3	Authentication procedures.....	221
13.3.1	Authentication of a PT.....	221
13.3.2	Authentication of the user.....	223
13.3.3	Authentication of a FT.....	223
13.4	Location procedures	224
13.4.1	Location registration	225
13.4.2	Detach.....	226
13.4.3	Location update	227
13.5	Access rights procedure.....	227
13.5.1	Obtaining the access rights	227
13.5.2	Termination of access rights	228
13.5.3	Modification of access rights	230
13.6	Key allocation procedure.....	231
13.7	Parameter retrieval procedure.....	232
13.8	Ciphering related procedure	234
13.9	External protocol information procedure	236
13.9.1	Procedure for external protocol information initiated by the FT	236
13.9.2	Procedure for external protocol information initiated by the PT	236
13.9.3	Segmentation of information in MM procedures.....	237
14	Link Control Entity (LCE) procedures.....	238
14.1	General	238
14.2	Connection oriented link control procedures.....	239
14.2.1	Link establishment.....	239
14.2.2	Direct PT initiated link establishment.....	239
14.2.3	Indirect (paged) FT initiated link establishment	240
14.2.4	Direct FT initiated link establishment.....	241
14.2.5	Link maintenance.....	242
14.2.6	Link suspend and resume.....	242
14.2.6.1	Link suspend	242
14.2.6.2	Link resume.....	243
14.2.7	Link release.....	243
14.2.7.1	NLR notification without "partial release" as release reason	243
14.2.7.2	NLR notification with "partial release" as release reason	244
14.3	Connectionless link control procedures.....	244
14.3.1	Message routing.....	244
14.3.2	Broadcast announce procedure	244
14.3.3	LCE paging codes for connectionless service.....	245
14.4	Procedure for collective and group ringing	245

14.5	LCE paging procedures for DPRS	246
14.5.1	DPRS initial setup paging.....	246
14.5.1.1	Assumptions for Short paging format or for Full format with IPUI.....	246
14.5.1.2	Coding for Full paging format with TPUI.....	246
14.5.2	DPRS Resume paging.....	247
14.5.2.1	Assumptions for Short paging format or for Full format with IPUI.....	247
14.5.2.2	Coding for Full paging format with TPUI.....	247
14.5.2.3	LCE Resume Procedure description.....	247
14.5.3	Special cases	248
14.5.3.1	Rule for DPRS Class 1 devices.....	248
14.5.3.2	Rule for backcompatibility with former A/B 1 devices	248
15	Management procedures.....	248
15.1	Lower Layer Management Entity (LLME)	248
15.2	Service mapping and negotiation	249
15.2.1	General.....	249
15.2.2	Prioritized list negotiation.....	249
15.2.3	Exchanged attribute negotiation	249
15.2.4	Operating parameter negotiation.....	250
15.2.5	Peer attribute negotiation	250
15.3	Service modification procedures	251
15.4	Resource management.....	251
15.5	Management of MM procedures	251
15.6	Call ciphering management.....	252
15.7	External Handover.....	253
15.7.1	Handover candidate procedures.....	253
15.7.1.1	General.....	253
15.7.1.2	Handover candidate indication.....	253
15.7.1.3	Handover candidate retrieval	254
15.7.1.4	Target FP selection.....	254
15.7.2	Handover reference procedure.....	255
15.7.2.1	General.....	255
15.7.2.2	Handover reference indication.....	255
15.7.2.3	Handover reference retrieval.....	255
15.7.3	External handover suggested by FP	255
15.7.4	NWK layer set up procedure.....	256
15.7.4.1	Handover request	256
15.7.4.2	Handover confirm	256
15.7.4.3	Handover accept.....	256
15.7.4.4	Handover reject.....	256
15.7.4.5	Release of old connection	256
15.7.4.6	Handover Fall Back.....	257
15.7.5	U-plane handling	257
15.7.6	Ciphering procedure	258
15.7.7	Interaction with location registration	258
15.8	Test management procedures	258
15.8.1	Test call back procedure	259
15.8.2	Test hook control procedures.....	259
15.8.3	Upper tester procedure.....	259
15.9	Application assistance procedures.....	260
15.9.1	DECT Identity Resolution (Retrieval) Procedure.....	260
15.9.1.1	FT (or HyP) initiated Connectionless Identity Resolution procedure	260
15.9.1.2	PT initiated Connectionless Identity Resolution procedure	261
15.9.1.3	Connection oriented Identity Resolution procedure.....	261
15.9.2	Application Address Resolution (Retrieval) Procedure.....	261
15.9.3	Application Parameter Allocation Procedure.....	261
15.9.3.1	FT initiated application parameter allocation procedure.....	261
15.9.3.2	PT initiated application parameter allocation procedure.....	262
15.9.4	Application parameter information procedure	262
15.9.4.1	FT initiated connection oriented Application parameter information procedure	262
15.9.4.2	PT initiated connection oriented Application parameter information procedure	262
15.9.4.3	FT initiated connectionless Application parameter information procedure	263

15.9.4.4	PT initiated connectionless Application parameter information procedure	263
15.9.5	Application Parameter Indication procedure	263
16	Primitives	264
16.1	Primitive types.....	264
16.2	Primitives to lower layer (DLC layer).....	264
16.3	Primitives to IWU	264
16.3.1	Parameter definitions	264
16.3.2	MNCC primitives	265
16.3.2.1	MNCC_SETUP primitive	266
16.3.2.2	MNCC_SETUP_ACK primitive.....	266
16.3.2.3	MNCC_REJECT primitive	267
16.3.2.4	MNCC_CALL_PROC primitive.....	267
16.3.2.5	MNCC_ALERT primitive	268
16.3.2.6	MNCC_CONNECT primitive.....	268
16.3.2.7	MNCC_RELEASE primitive	269
16.3.2.8	MNCC_FACILITY primitive	269
16.3.2.9	MNCC_INFO primitive	270
16.3.2.10	MNCC_MODIFY primitive.....	270
16.3.2.11	MNCC_HOLD primitive	270
16.3.2.12	MNCC_RETRIEVE primitive	271
16.3.2.13	MNCC_IWU_INFO primitive	271
16.3.3	MNSS primitives	271
16.3.3.1	MNSS_SETUP primitive	271
16.3.3.2	MNSS_FACILITY primitive	272
16.3.3.3	MNSS_RELEASE primitive.....	272
16.3.4	MNCO primitives	272
16.3.4.1	MNCO_SETUP primitive	273
16.3.4.2	MNCO_CONNECT primitive	273
16.3.4.3	MNCO_INFO primitive.....	273
16.3.4.4	MNCO_ACK primitive.....	273
16.3.4.5	MNCO_RELEASE primitive.....	274
16.3.4.6	MNCO_REJECT primitive.....	274
16.3.5	MNCL primitives.....	274
16.3.5.1	MNCL_UNITDATA primitive.....	274
16.3.6	MM primitives	275
16.3.6.1	MM_IDENTITY primitive	275
16.3.6.2	MM_IDENTITY_ASSIGN primitive	275
16.3.6.3	MM_AUTHENTICATE primitive	276
16.3.6.4	MM_LOCATE primitive	276
16.3.6.5	MM_DETACH primitive.....	276
16.3.6.6	MM_ACCESS_RIGHTS primitive.....	277
16.3.6.7	MM_ACCESS_RIGHTS_TERMINATE primitive.....	277
16.3.6.8	MM_KEY_ALLOCATE primitive.....	277
16.3.6.9	MM_INFO primitive.....	278
16.3.6.10	MM_CIPHER primitive.....	278
16.3.6.11	MM_IWU primitive	278
17	Handling of error and exception conditions	279
17.1	Protocol discrimination error.....	279
17.2	Message too short.....	279
17.3	Transaction identifier error.....	279
17.3.1	Illegal and unsupported transaction identifier value	279
17.3.2	Transaction identifier procedural errors and exception conditions	279
17.3.2.1	Unknown active CC call	279
17.3.2.2	Unknown active CISS call	280
17.3.2.3	Unknown active COMS call	280
17.3.2.4	Unknown active CLMS call.....	280
17.3.2.5	Unknown active MM transaction.....	280
17.3.2.6	Unknown active LCE transaction	280
17.3.3	Call Resource Contention	280
17.4	Message type or message sequence errors	281

17.4.1	CC message error.....	281
17.4.2	CISS message error.....	281
17.4.3	COMS or CLMS message error.....	281
17.4.4	MM message error.....	281
17.4.5	LCE message error.....	281
17.5	General information element errors.....	281
17.5.1	Information element out of sequence.....	281
17.5.2	Duplicated information elements.....	282
17.6	Mandatory information element errors.....	282
17.6.1	Mandatory information element missing in CC messages.....	282
17.6.2	Mandatory information element content error in CC messages.....	282
17.6.3	Mandatory information element error in COMS or CLMS messages.....	282
17.6.4	Mandatory information element error in MM messages.....	283
17.6.5	Mandatory information element error in LCE messages.....	283
17.7	Non-mandatory information element errors.....	283
17.7.1	Unrecognized information element.....	283
17.7.2	Non-mandatory information element content error.....	283
17.8	Data link reset.....	284
17.9	Data link failure.....	284
Annex A (normative): System parameters.....		285
A.1	CC timers.....	285
A.2	SS timers.....	286
A.3	COMS timers.....	286
A.4	CLMS timer.....	287
A.5	MM timers.....	287
A.6	LCE timers.....	290
A.7	NWK layer constants.....	291
A.8	Restart.....	291
Annex B (normative): CC state transition tables.....		292
B.1	CC state transitions at PT side.....	292
B.1.1	CC state table at PT side.....	292
B.1.2	CC transition procedures at PT side.....	293
B.2	CC state transitions at FT side.....	295
B.2.1	CC state table at FT side.....	295
B.2.2	CC transition procedures at FT side.....	295
Annex C (informative): DLC states as viewed by the LCE.....		298
Annex D (normative): DECT standard character sets.....		299
D.1	General.....	299
D.2	DECT standard 8-bit characters.....	299
D.2.1	General.....	299
D.2.2	Control codes.....	300
D.2.3	Standard IA5 codes.....	301
D.2.4	extended codes and escape to alternative character sets.....	301
D.3	DECT standard 4-bit characters.....	301
Annex E (normative): Default coding of information elements.....		302
E.1	Default coding of <<IWU-ATTRIBUTES>> and <CALL-ATTRIBUTES>> information elements for basic speech.....	302

E.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES>> and <<CONNECTION-ATTRIBUTES>> information elements for wideband speech	302
E.2.1	Default setup attributes for basic service wideband speech	303
Annex F (normative): Broadcast attributes coding		304
F.1	Higher layer capabilities.....	304
F.2	Extended higher layer capabilities	305
F.3	Extended higher layer capabilities (part 2).....	305
Annex G (normative): Use of <<IWU-PACKET>> and <<IWU-TO-IWU>> information elements		307
G.1	General	307
G.2	Sending of <<IWU-PACKET>> elements.....	307
G.2.1	CC and MM use of <<IWU-PACKET>>	307
G.2.2	COMS and CLMS use of <<IWU-PACKET>>.....	307
G.2.3	Rejection of <<IWU-PACKET>> elements	307
G.3	Use of <<IWU-TO-IWU>> elements	308
G.3.1	Sending of <<IWU-TO-IWU>> elements.....	308
G.3.2	Rejection of <<IWU-TO-IWU>> elements	308
Annex H (normative): Transaction identifier flags (TIF) assignment in MM procedures.....		309
H.1	General	309
H.2	Nested procedures	309
H.3	Stand alone procedures.....	310
H.3.1	Location update procedure	310
H.3.2	Location registration procedure with temporary identity assignment	310
H.3.3	PT initiated cipher switching	311
H.3.4	Key allocation	311
H.4	External protocol information procedure	312
Annex I (normative): Distributed communications.....		313
I.1	Introduction	313
I.2	General requirements	313
I.2.1	DCDL-net.....	313
I.2.2	Subscription.....	313
I.2.3	Communication	314
I.3	Procedure description.....	315
I.3.1	HyP Identities	315
I.3.2	Membership Access Rights Allocation	315
I.3.3	Re-initialization of membership access rights	316
I.3.4	Members Data Transfer	316
I.3.5	Presence/Absence Indication.....	318
I.3.6	Bandwidth management	318
I.3.7	Direct Link Establishment.....	319
I.3.8	Indirect Link Establishment	320
I.3.9	MASTER management	321
I.3.9.1	MASTER assign	321
I.3.9.2	MASTER Change	321
I.3.9.3	DCDL-net System bearer management	321
I.3.10	Common Subscription Database management	322
I.3.10.1	IdN.....	322
I.3.10.2	RFPI, PARK and PLI.....	322
I.3.10.3	IPUI	323
I.3.10.4	TPUI and LAL	323