

**SLOVENSKI STANDARD
SIST EN 302 878-4 V1.1.1:2012
01-februar-2012**

**Dostop, priključki, prenos in multipleksiranje (ATTM) - Tretja generacija prenosnih sistemov za storitve interaktivne kabelske televizije - IP-kabelski modemi - 4. del:
MAC in protokoli zgornje plasti - DOCSIS 3.0**

Access, Terminals, Transmission and Multiplexing (ATTM) - Third Generation
Transmission Systems for Interactive Cable Television Services - IP Cable Modems -
Part 4: MAC and Upper Layer Protocols - DOCSIS 3.0

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 302 878-4 V1.1.1:2012](#)

[https://standards.iteh.ai/catalog/standards/sist/a4212e38-73b1-4d51-93b2-
253342aa1853/sist-en-302-878-4-v1-1-1-2012](https://standards.iteh.ai/catalog/standards/sist/a4212e38-73b1-4d51-93b2-253342aa1853/sist-en-302-878-4-v1-1-1-2012)

Ta slovenski standard je istoveten z: EN 302 878-4 Version 1.1.1

ICS:

| | | |
|--------|--|--|
| 35.180 | Terminalska in druga periferna oprema IT | IT Terminal and other peripheral equipment |
|--------|--|--|

SIST EN 302 878-4 V1.1.1:2012

en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 302 878-4 V1.1.1:2012

<https://standards.iteh.ai/catalog/standards/sist/a4212e38-73b1-4d51-93b2-253342aa1853/sist-en-302-878-4-v1-1-1-2012>

ETSI EN 302 878-4 V1.1.1 (2011-11)



**Access, Terminals, Transmission and Multiplexing (ATM);
Third Generation Transmission Systems for
Interactive Cable Television Services)- IP Cable Modems;
Part 4: MAC and Upper Layer Protocols;**

SIST EN 302 878-4 V1.1.1:2012
<https://standards.iteh.ai/callforstandard/standards/342/2e38-73b1-4d51-93b2-253342aa1853/sist-en-302-878-4-v1-1-1-2012>

Reference

DEN/ATTM-003006-4

Keywords

access, broadband, cable, data, IP, IPCable,
modem***ETSI***

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)[SIST EN 302 878-4 V1.1.1:2012](#)[https://standards.iteh.ai/catalog/standards/sist/a4212e38-73b1-4d51-93b2-
253342aa18](https://standards.iteh.ai/catalog/standards/sist/a4212e38-73b1-4d51-93b2-253342aa18) [Important notice](#)Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|----|
| Intellectual Property Rights | 22 |
| Foreword..... | 22 |
| 1 Scope | 23 |
| 1.1 Introduction and Purpose..... | 23 |
| 1.2 Requirements..... | 23 |
| 1.3 Conventions..... | 23 |
| 2 References | 23 |
| 2.1 Normative references | 24 |
| 2.2 Informative references..... | 27 |
| 3 Definitions and abbreviations..... | 27 |
| 3.1 Definitions | 27 |
| 3.2 Abbreviations | 37 |
| 4 Void..... | 41 |
| 5 Overview and Theory of Operations | 41 |
| 5.1 DOCSIS 3.0 MULPI Key Features | 41 |
| 5.2 Technical Overview | 42 |
| 5.2.1 CMTS and CM Models..... | 42 |
| 5.2.1.1 CMTS Model | 42 |
| 5.2.1.1.1 Types of CMTS..... | 42 |
| 5.2.1.1.2 CMTS Internal Forwarding Model..... | 44 |
| 5.2.1.1.3 CMTS MAC Domain..... | 45 |
| 5.2.1.2 CM Model | 46 |
| 5.2.2 DOCSIS MAC Operation | 46 |
| 5.2.2.1 QoS | 46 |
| 5.2.2.1.1 https://standards.iteh.ai/catalog/standards/sist-en-302-878-4-v1-1-2012 | 47 |
| 5.2.2.1.2 Individual and Group Service Flows | 47 |
| 5.2.2.2 Channel Bonding..... | 48 |
| 5.2.2.2.1 Downstream Channel Bonding..... | 48 |
| 5.2.2.2.2 Upstream Channel Bonding..... | 49 |
| 5.2.2.3 Autonomous Load Balancing..... | 51 |
| 5.2.3 Multicast Operation | 51 |
| 5.2.4 Network and Higher Layer Protocols | 52 |
| 5.2.5 CM and CPE Provisioning and Management | 52 |
| 5.2.5.1 Initialization, Provisioning and Management of CMs | 52 |
| 5.2.5.2 Initialization, Provisioning and Management of CPEs | 53 |
| 5.2.6 Relationship to the Physical HFC Plant Topology | 53 |
| 5.2.6.1 RF Topology Configuration | 53 |
| 5.2.6.2 Frequency Assignment | 55 |
| 5.2.7 Cable Modem Service Group (CM-SG) | 56 |
| 5.2.7.1 MAC Domain Channel Assignment..... | 57 |
| 5.2.7.2 Multiple MAC Domains per Fibre Node | 58 |
| 5.2.7.3 MAC Domain Downstream and Upstream Service Groups..... | 59 |
| 5.2.7.4 Channel Bonding Topology Considerations | 59 |
| 5.2.8 CMTS Downstream Service Model Example..... | 60 |
| 6 Media Access Control Specification | 61 |
| 6.1 Introduction | 61 |
| 6.1.1 Overview | 61 |
| 6.1.2 Definitions | 61 |
| 6.1.2.1 MAC-Sublayer Domain | 61 |
| 6.1.2.2 MAC Service Access Point | 62 |
| 6.1.2.3 Service Flows | 62 |
| 6.1.2.4 Upstream Intervals, Mini-Slots and 6,25-Microsecond Increments | 62 |
| 6.1.2.4.1 TDMA mode | 62 |
| 6.1.2.4.2 S-CDMA mode..... | 63 |

| | | |
|-----------|---|-----|
| 6.1.2.5 | MAC Frame | 63 |
| 6.1.2.6 | Logical Upstream Channels | 63 |
| 6.1.2.6.1 | Type 3 Logical Upstreams..... | 64 |
| 6.1.2.6.2 | Type 4 Logical Upstreams..... | 64 |
| 6.1.3 | Future Use..... | 65 |
| 6.2 | MAC Frame Formats..... | 65 |
| 6.2.1 | Generic MAC Frame Format..... | 65 |
| 6.2.1.1 | PMD Overhead | 65 |
| 6.2.1.2 | MAC Frame Transport..... | 66 |
| 6.2.1.3 | Ordering of Bits and Octets..... | 66 |
| 6.2.1.3.1 | Representing Negative Numbers | 67 |
| 6.2.1.3.2 | Type-Length-Value Fields..... | 67 |
| 6.2.1.4 | MAC Header Format..... | 67 |
| 6.2.1.5 | Data PDU | 68 |
| 6.2.2 | Packet-Based MAC Frames | 69 |
| 6.2.2.1 | Packet PDU and Isolation Packet PDU | 69 |
| 6.2.3 | ATM Cell MAC Frames | 70 |
| 6.2.4 | MAC-Specific Headers..... | 70 |
| 6.2.4.1 | Timing Header | 70 |
| 6.2.4.2 | MAC Management Header | 71 |
| 6.2.4.3 | Request Frame..... | 71 |
| 6.2.4.4 | Fragmentation Header | 72 |
| 6.2.4.5 | Queue-depth Based Request Frame | 73 |
| 6.2.4.6 | Concatenation Header | 73 |
| 6.2.5 | Extended MAC Headers | 74 |
| 6.2.5.1 | Piggyback Requests | 76 |
| 6.2.5.2 | Request Extended Header..... | 76 |
| 6.2.5.3 | Fragmentation Extended Header..... | 76 |
| 6.2.5.4 | Service Flow Extended Header..... | 77 |
| 6.2.5.4.1 | Payload Header Suppression Header..... | 77 |
| 6.2.5.4.2 | Unsolicited Grant Synchronization Header | 78 |
| 6.2.5.5 | BP_UP2 Extended Header | 78 |
| 6.2.5.6 | Downstream Service Extended Header | 78 |
| 6.2.5.7 | DPV Extended Header | 78 |
| 6.3 | Segment Header Format | 80 |
| 6.4 | MAC Management Messages..... | 81 |
| 6.4.1 | MAC Management Message Header | 81 |
| 6.4.2 | Time Synchronization (SYNC)..... | 84 |
| 6.4.3 | Upstream Channel Descriptor (UCD)..... | 84 |
| 6.4.3.1 | Example of UCD Encoded TLV Data..... | 92 |
| 6.4.4 | Upstream Bandwidth Allocation Map (MAP) | 93 |
| 6.4.5 | Ranging Request Messages | 95 |
| 6.4.5.1 | Ranging Request (RNG-REQ) | 97 |
| 6.4.5.2 | Initial Ranging Request (INIT-RNG-REQ) | 98 |
| 6.4.5.3 | Bonded Initial Ranging Request (B-INIT-RNG-REQ) | 99 |
| 6.4.5.3.1 | Capability Flags..... | 99 |
| 6.4.6 | Ranging Response (RNG-RSP) | 100 |
| 6.4.6.1 | Encodings..... | 101 |
| 6.4.6.2 | Example of TLV Data | 102 |
| 6.4.6.3 | Transmit Equalization Encodings | 103 |
| 6.4.6.4 | RNG-RSP Channel Overrides | 103 |
| 6.4.6.5 | Upstream Channel Adjustments | 104 |
| 6.4.6.6 | T4 Timeout Multiplier..... | 104 |
| 6.4.7 | Registration Request Messages..... | 105 |
| 6.4.7.1 | Registration Request (REG-REQ) | 106 |
| 6.4.7.2 | Multipart Registration Request (REG-REQ-MP) | 106 |
| 6.4.8 | Registration Response Messages | 107 |
| 6.4.8.1 | Registration Response (REG-RSP)..... | 109 |
| 6.4.8.2 | Multipart Registration Response (REG-RSP-MP) | 110 |
| 6.4.8.3 | Encodings..... | 111 |
| 6.4.8.3.1 | Modem Capabilities..... | 111 |
| 6.4.8.3.2 | DOCSIS 1.0 Service Class Data..... | 111 |

| | | |
|-------------|--|-----|
| 6.4.9 | Registration Acknowledge (REG-ACK) | 112 |
| 6.4.10 | Upstream Channel Change Request (UCC-REQ)..... | 113 |
| 6.4.11 | Upstream Channel Change Response (UCC-RSP)..... | 114 |
| 6.4.12 | Dynamic Service Addition - Request (DSA-REQ)..... | 114 |
| 6.4.12.1 | CM-Initiated Dynamic Service Addition | 115 |
| 6.4.12.2 | CMTS-Initiated Dynamic Service Addition..... | 115 |
| 6.4.13 | Dynamic Service Addition - Response (DSA-RSP) | 116 |
| 6.4.13.1 | CM-Initiated Dynamic Service Addition | 117 |
| 6.4.13.2 | CMTS-Initiated Dynamic Service Addition..... | 117 |
| 6.4.14 | Dynamic Service Addition - Acknowledge (DSA-ACK)..... | 117 |
| 6.4.15 | Dynamic Service Change - Request (DSC-REQ)..... | 118 |
| 6.4.16 | Dynamic Service Change - Response (DSC-RSP) | 120 |
| 6.4.17 | Dynamic Service Change - Acknowledge (DSC-ACK)..... | 121 |
| 6.4.18 | Dynamic Service Deletion - Request (DSD-REQ) | 122 |
| 6.4.19 | Dynamic Service Deletion - Response (DSD-RSP)..... | 122 |
| 6.4.20 | Dynamic Channel Change - Request (DCC-REQ) | 123 |
| 6.4.20.1 | Encodings..... | 124 |
| 6.4.20.1.1 | Upstream Channel ID | 124 |
| 6.4.20.1.2 | Downstream Parameters | 124 |
| 6.4.20.1.3 | Initialization Technique | 125 |
| 6.4.20.1.4 | UCD Substitution | 126 |
| 6.4.20.1.5 | Security Association Identifier (SAID) Substitution | 127 |
| 6.4.20.1.6 | Service Flow Substitutions | 127 |
| 6.4.20.1.7 | CMTS MAC Address | 128 |
| 6.4.21 | Dynamic Channel Change - Response (DCC-RSP)..... | 129 |
| 6.4.21.1 | Encodings..... | 129 |
| 6.4.21.1.1 | CM Jump Time | 130 |
| 6.4.22 | Dynamic Channel Change - Acknowledge (DCC-ACK) | 130 |
| 6.4.23 | Device Class Identification Request (DCI-REQ)..... | 131 |
| 6.4.24 | Device Class Identification Response (DCI-RSP)..... | 132 |
| 6.4.25 | Upstream Transmitter Disable (UP-DIS)..... | 132 |
| 6.4.26 | Test Request (TST-REQ)..... | 134 |
| 6.4.27 | Downstream Channel Descriptor (DCD)..... | 135 |
| 6.4.28 | MAC Domain Descriptor (MDD)..... | 135 |
| 6.4.28.1 | TLV Encodings | 136 |
| 6.4.28.1.1 | Downstream Active Channel List TLV | 136 |
| 6.4.28.1.2 | MAC Domain Downstream Service Group (MD-DS-SG) TLV | 137 |
| 6.4.28.1.3 | Downstream Ambiguity Resolution Frequency List TLV | 138 |
| 6.4.28.1.4 | Receive Channel Profile Reporting Control TLV | 138 |
| 6.4.28.1.5 | IP Initialization Parameters TLV..... | 139 |
| 6.4.28.1.6 | Early Authentication and Encryption (EAE) Enable/Disable TLV | 139 |
| 6.4.28.1.7 | Upstream Active Channel List TLV | 140 |
| 6.4.28.1.8 | Upstream Ambiguity Resolution Channel List TLV | 140 |
| 6.4.28.1.9 | Upstream Frequency Range TLV | 141 |
| 6.4.28.1.10 | Symbol Clock Locking Indicator | 141 |
| 6.4.28.1.11 | CM-STATUS Event Control | 141 |
| 6.4.28.1.12 | Upstream Transmit Power Reporting | 142 |
| 6.4.28.1.13 | DSG DA-to-DSID Association Entry | 142 |
| 6.4.28.1.14 | CM-STATUS Event Enable for Non-Channel-Specific Events | 142 |
| 6.4.28.1.15 | Extended Upstream Transmit Power Support | 143 |
| 6.4.29 | Dynamic Bonding Change Request (DBC-REQ) | 143 |
| 6.4.30 | Dynamic Bonding Change Response (DBC-RSP) | 144 |
| 6.4.31 | Dynamic Bonding Change Acknowledge (DBC-ACK) | 146 |
| 6.4.32 | DOCSIS Path Verify Request (DPV-REQ) | 146 |
| 6.4.33 | DOCSIS Path Verify Response (DPV-RSP) | 148 |
| 6.4.34 | Status Report (CM-STATUS)..... | 148 |
| 6.4.34.1 | TLV Encodings | 149 |
| 6.4.35 | CM Control Request (CM-CTRL-REQ)..... | 149 |
| 6.4.35.1 | TLV Encodings | 150 |
| 6.4.36 | CM Control Response (CM-CTRL-RSP)..... | 150 |
| 7 | Media Access Control Protocol Operation..... | 151 |

| | | |
|------------|---|-----|
| 7.1 | Timing and Synchronization | 151 |
| 7.1.1 | Global Timing Reference..... | 151 |
| 7.1.2 | CM Synchronization | 152 |
| 7.1.3 | Ranging..... | 152 |
| 7.1.3.1 | Broadcast Initial Ranging..... | 152 |
| 7.1.3.2 | Unicast Initial Ranging | 153 |
| 7.1.4 | Timing Units and Relationships..... | 153 |
| 7.1.4.1 | TDMA Timing Units and Relationships | 153 |
| 7.1.4.1.1 | Mini-Slot Capacity | 153 |
| 7.1.4.1.2 | Mini-Slot Numbering | 154 |
| 7.1.4.2 | S-CDMA Timing Units and Relationships | 154 |
| 7.1.4.2.1 | Mini-Slot Capacity | 154 |
| 7.1.4.2.2 | Mini-Slot Numbering | 154 |
| 7.2 | Upstream Data Transmission | 155 |
| 7.2.1 | Upstream Bandwidth Allocation..... | 155 |
| 7.2.1.1 | The Allocation MAP MAC Management Message | 156 |
| 7.2.1.2 | Information Elements..... | 156 |
| 7.2.1.2.1 | The Request IE | 156 |
| 7.2.1.2.2 | The Request/Data IE..... | 157 |
| 7.2.1.2.3 | The Initial Maintenance IE..... | 157 |
| 7.2.1.2.4 | The Station Maintenance IE | 157 |
| 7.2.1.2.5 | Short and Long Data Grant IEs | 157 |
| 7.2.1.2.6 | Data Acknowledge IE..... | 158 |
| 7.2.1.2.7 | Expansion IE | 158 |
| 7.2.1.2.8 | Null IE | 158 |
| 7.2.1.2.9 | Advanced PHY Short and Long Data Grant IEs | 158 |
| 7.2.1.2.10 | Advanced PHY Unsolicited Grant IE..... | 159 |
| 7.2.1.3 | Requesting with Multiple Transmit Channel Mode Disabled..... | 159 |
| 7.2.1.4 | Requesting with Multiple Transmit Channel Mode Enabled..... | 160 |
| 7.2.1.4.1 | Request Mechanisms for Segment Header OFF Service Flows | 160 |
| 7.2.1.4.2 | Request Mechanisms for Segment Header ON Service Flows..... | 160 |
| 7.2.1.5 | Information Element Feature Usage Summary SIST EN 302 878-4 V1.1.1:2012 | 165 |
| 7.2.1.6 | Map Transmission and Timing http://public.etsi.org/standards/sist/a4212e38-73b1-4d51-93b2-253342aa1853/sist-en-302-878-4-v1-1-2012 | 165 |
| 7.2.1.7 | Protocol Example ... 253342aa1853/sist-en-302-878-4-v1-1-2012 | 166 |
| 7.2.1.8 | MAP Generation Example - Two Logical Upstreams..... | 167 |
| 7.2.2 | Upstream Transmission and Contention Resolution..... | 168 |
| 7.2.2.1 | Contention Resolution Overview | 168 |
| 7.2.2.1.1 | Contention Resolution with Multiple Transmit Channel Mode Disabled | 168 |
| 7.2.2.1.2 | Contention Resolution with Multiple Transmit Channel Mode Enabled..... | 169 |
| 7.2.2.2 | Transmit Opportunities | 171 |
| 7.2.2.3 | CM Bandwidth Utilization..... | 172 |
| 7.2.3 | Upstream Service Flow Scheduling Services | 172 |
| 7.2.3.1 | Unsolicited Grant Service | 173 |
| 7.2.3.2 | Real-Time Polling Service | 173 |
| 7.2.3.3 | Unsolicited Grant Service with Activity Detection..... | 174 |
| 7.2.3.4 | Non-Real-Time Polling Service | 175 |
| 7.2.3.5 | Best Effort Service | 175 |
| 7.2.3.6 | Other Services | 175 |
| 7.2.3.6.1 | Committed Information Rate (CIR)..... | 175 |
| 7.2.3.7 | Parameter Applicability for Upstream Service Scheduling..... | 175 |
| 7.2.3.8 | CM Transmit Behavior | 176 |
| 7.2.4 | Continuous Concatenation and Fragmentation | 176 |
| 7.2.5 | Pre-3.0 DOCSIS Concatenation and Fragmentation..... | 177 |
| 7.2.5.1 | Concatenation..... | 177 |
| 7.2.5.2 | Fragmentation | 178 |
| 7.2.5.2.1 | CM Fragmentation Support..... | 180 |
| 7.2.5.2.2 | CMTS Fragmentation Support | 182 |
| 7.2.5.2.3 | Fragmentation Example..... | 183 |
| 7.2.5.2.4 | Pre-Registration Fragmentation..... | 185 |
| 7.2.5.2.5 | Considerations for Concatenated Packets and Fragmentation | 186 |
| 7.3 | Upstream - Downstream Channel Association within a MAC Domain..... | 186 |
| 7.3.1 | Primary Downstream Channels | 186 |

| | | |
|-----------|--|-----|
| 7.3.2 | MAP and UCD Messages | 187 |
| 7.3.3 | Multiple MAC Domains | 187 |
| 7.4 | DSID Definition | 187 |
| 7.5 | Quality of Service | 188 |
| 7.5.1 | Concepts | 188 |
| 7.5.1.1 | Service Flows | 188 |
| 7.5.1.2 | Classifiers | 190 |
| 7.5.1.2.1 | Upstream and Downstream QoS Classifiers | 190 |
| 7.5.1.2.2 | Upstream Drop Classifiers | 192 |
| 7.5.2 | Object Model | 192 |
| 7.5.3 | Service Classes | 194 |
| 7.5.4 | Authorization | 195 |
| 7.5.5 | States of Service Flows | 195 |
| 7.5.5.1 | Deferred Service Flows | 195 |
| 7.5.5.1.1 | Provisioned Service Flows | 196 |
| 7.5.5.1.2 | Authorized Service Flows | 196 |
| 7.5.5.2 | Admitted Service Flows | 196 |
| 7.5.5.3 | Active Service Flows | 197 |
| 7.5.6 | Service Flows and Classifiers | 197 |
| 7.5.6.1 | Policy-Based Classification and Service Classes | 198 |
| 7.5.7 | General Operation | 198 |
| 7.5.7.1 | Static Operation | 198 |
| 7.5.7.2 | Dynamic Service Flow Creation - CM Initiated | 199 |
| 7.5.7.3 | Dynamic Service Flow Creation - CMTS Initiated | 200 |
| 7.5.7.4 | Dynamic Service Flow Modification and Deletion | 200 |
| 7.5.8 | QoS Support for Joined IP Multicast Traffic | 201 |
| 7.5.8.1 | Overview | 202 |
| 7.5.8.2 | Group Configuration and Group QoS Configuration Tables | 203 |
| 7.5.8.3 | Instantiating Group Classifier Rules and Group Service Flows | 204 |
| 7.5.8.3.1 | Examples of GCR and GSF Instantiation | 206 |
| 7.5.8.4 | Default Group Service Flows | 212 |
| 7.5.8.5 | Service Class QoS Parameter Changes <small>SIST EN 302 878-4 V1.1.1:2012</small> | 212 |
| 7.5.8.6 | Group QoS Configuration Changes <small>SIST EN 302 878-4 V1.1.1:2012</small> | 212 |
| 7.5.9 | Other Multicast and Broadcast Traffic <small>SIST EN 302 878-4 V1.1.1:2012</small> | 213 |
| 7.6 | Downstream Traffic Priority | 213 |
| 7.6.1 | Traffic Priority Ordering and Mapping to CM Output Queues | 213 |
| 7.7 | Payload Header Suppression | 214 |
| 7.7.1 | Overview | 214 |
| 7.7.1.1 | PHSI-indexed PHS | 215 |
| 7.7.1.2 | DSID-indexed PHS | 215 |
| 7.7.2 | Example Applications | 216 |
| 7.7.3 | Operation | 216 |
| 7.7.4 | Signalling | 218 |
| 7.7.4.1 | Signalling PHSI-Indexed Payload Header Suppression | 218 |
| 7.7.4.2 | Signalling DSID-Indexed Payload Header Suppression | 219 |
| 7.7.5 | Payload Header Suppression Examples | 220 |
| 7.7.5.1 | Upstream Example | 220 |
| 7.7.5.2 | Downstream Example | 221 |
| 7.7.5.3 | DSID-Indexed Multicast Example | 222 |
| 7.8 | Data Link Encryption Support | 223 |
| 7.8.1 | MAC Messages | 223 |
| 7.8.2 | Framing | 223 |
| 7.8.3 | Multiple Transmit Channel Mode Operation and Packet Encryption | 223 |
| 8 | Channel Bonding | 223 |
| 8.1 | Upstream and Downstream Common Aspects | 224 |
| 8.1.1 | Service Flow Assignment | 224 |
| 8.1.2 | CMTS Bonding and Topology Requirements | 227 |
| 8.2 | Downstream Channel Bonding | 228 |
| 8.2.1 | Multiple Downstream Channel Overview | 228 |
| 8.2.2 | CMTS Downstream Bonding Operation | 229 |
| 8.2.3 | Sequenced Downstream Packets | 229 |

| | | |
|-----------|--|-----|
| 8.2.3.1 | Downstream Sequencing..... | 230 |
| 8.2.3.2 | Skew Requirements..... | 232 |
| 8.2.3.3 | Resequencing DSID Signalling..... | 233 |
| 8.2.4 | Cable Modem Physical Receive Channel Configuration..... | 233 |
| 8.2.4.1 | Receive Channels | 234 |
| 8.2.4.2 | Receive Modules..... | 234 |
| 8.2.4.2.1 | Receive Module Interconnection..... | 236 |
| 8.2.4.3 | Receive Channel Profile..... | 237 |
| 8.2.4.3.1 | Standard Receive Channel Profiles | 237 |
| 8.2.4.4 | Receive Channel Configuration | 238 |
| 8.2.4.4.1 | Static Receive Module Assignments | 239 |
| 8.2.4.5 | RCC Message Sequence Example | 240 |
| 8.2.5 | QoS for Downstream Channel Bonding | 241 |
| 8.3 | Upstream Channel Bonding | 241 |
| 8.3.1 | Granting Bandwidth..... | 241 |
| 8.3.2 | Upstream Transmissions with Upstream Channel Bonding | 241 |
| 8.3.2.1 | Segment Header ON Operation..... | 241 |
| 8.3.2.2 | Segment Header OFF Operation..... | 242 |
| 8.3.3 | Dynamic Range Window..... | 242 |
| 8.3.3.1 | Channels Added During Registration | 242 |
| 8.3.3.2 | Channels Added by a DBC-REQ | 243 |
| 8.3.3.3 | Channels Deleted by a DBC-REQ | 244 |
| 8.3.3.4 | UCD Changes Burst Profiles Resulting in New Value for P_{hi} | 244 |
| 8.3.3.5 | Power Offset in RNG-RSP Causing Dynamic Range Window Violation | 244 |
| 8.4 | Partial Service | 244 |
| 9 | Data Forwarding..... | 245 |
| 9.1 | General Forwarding Requirements..... | 245 |
| 9.1.1 | CMTS Forwarding Rules..... | 246 |
| 9.1.1.1 | General CMTS Forwarding..... | 246 |
| 9.1.1.2 | DSID Labeling | 247 |
| 9.1.2 | CM Address Acquisition, Filtering and Forwarding Rules..... | 247 |
| 9.1.2.1 | MAC Address Acquisition..... | 248 |
| 9.1.2.2 | CM Filtering Rules..... | 248 |
| 9.1.2.3 | CM Forwarding Rules | 249 |
| 9.1.2.3.1 | CM Pre-Operational Forwarding Behavior | 249 |
| 9.1.2.3.2 | CM Operational Forwarding Behavior | 249 |
| 9.2 | Multicast Forwarding | 251 |
| 9.2.1 | Introduction..... | 251 |
| 9.2.2 | Downstream Multicast Forwarding | 252 |
| 9.2.2.1 | Examples of Downstream Multicast Forwarding using DSIDs | 253 |
| 9.2.2.2 | Labeling Multicast Packets with DSIDs | 255 |
| 9.2.2.2.1 | Mixed CM environment | 256 |
| 9.2.2.2.2 | Pre-Registration DSID..... | 256 |
| 9.2.2.2.3 | Upstream Multicast Traffic from a Multicast Client | 256 |
| 9.2.2.3 | Communicating DSIDs and group forwarding attributes to a CM | 256 |
| 9.2.2.4 | DSID based Filtering and Forwarding by a Cable Modem | 257 |
| 9.2.2.5 | Individually Directed Multicast | 258 |
| 9.2.3 | Downstream Multicast Traffic Encryption | 258 |
| 9.2.3.1 | Multicast Encryption Overview | 258 |
| 9.2.3.2 | Dynamic Multicast Encryption | 259 |
| 9.2.3.3 | DSIDs and SAIDs | 259 |
| 9.2.3.4 | Pre-Registration Multicast Encryption | 259 |
| 9.2.4 | Static Multicast Session Encodings | 260 |
| 9.2.5 | IGMP and MLD Support | 260 |
| 9.2.5.1 | Motivation behind taking CM out of IGMP Control Plane..... | 260 |
| 9.2.5.2 | IP multicast service model support | 260 |
| 9.2.5.3 | IGMP and MLD membership handling..... | 261 |
| 9.2.5.4 | IGMPv2/MLDv1 Leave Processing | 262 |
| 9.2.5.5 | IGMP and MLD version and query support..... | 262 |
| 9.2.5.6 | Separation of Query Domains | 262 |
| 9.2.6 | Encrypted Multicast Downstream Forwarding Example | 263 |

| | | |
|------------|--|-----|
| 9.2.7 | IP Multicast Join Authorization | 266 |
| 9.2.7.1 | Maximum Multicast Sessions | 266 |
| 9.2.7.2 | Session Rules | 267 |
| 9.2.7.2.1 | IP Multicast Profiles | 267 |
| 9.2.7.2.2 | Static IP Multicast Join Authorization Rules | 268 |
| 9.2.7.3 | CM Configuration File | 268 |
| 9.2.7.3.1 | IP Multicast Profile Name Subtype | 268 |
| 9.2.7.3.2 | Static IP Multicast Session Rule Subtype | 268 |
| 9.2.7.4 | Matching Session Rules | 268 |
| 9.2.7.5 | IP Multicast Profile Changes | 269 |
| 10 | Cable Modem - CMTS Interaction | 269 |
| 10.1 | CMTS Initialization | 269 |
| 10.2 | Cable Modem Initialization and Reinitialization | 270 |
| 10.2.1 | Scan for Downstream Channel | 270 |
| 10.2.2 | Continue Downstream Scanning | 271 |
| 10.2.3 | Service Group Discovery and Initial Ranging | 271 |
| 10.2.3.1 | Read MAC Domain Descriptor (MDD) | 273 |
| 10.2.3.2 | MDDs Not Found on Primary Downstream | 274 |
| 10.2.3.3 | Determination of MD-DS-SG | 275 |
| 10.2.3.4 | Ranging Holdoff | 277 |
| 10.2.3.5 | Determination of MD-US-SG | 279 |
| 10.2.3.5.1 | Bonded Initial Ranging | 280 |
| 10.2.3.5.2 | Continue US Ambiguity Initial Ranging | 282 |
| 10.2.3.6 | Obtain Upstream Parameters / Try Next Upstream (DOCSIS 2.0 Initialization) | 284 |
| 10.2.3.6.1 | Message Flows During Scanning and Upstream Parameter Acquisition | 285 |
| 10.2.3.7 | Ranging and Automatic Adjustments | 286 |
| 10.2.3.7.1 | Adjust Transmit Parameters | 290 |
| 10.2.3.8 | CMTS Determination of Cable Modem Service Group and Initial Ranging | 291 |
| 10.2.4 | Authentication | 293 |
| 10.2.5 | Establishing IP Connectivity | 293 |
| 10.2.5.1 | Establish IPv4 Network Connectivity | 301 |
| 10.2.5.1.1 | DHCPv4 Fields Used by the CM | 302 |
| 10.2.5.1.2 | Use of T1 and T2 Timers | 303 |
| 10.2.5.1.3 | CMTS Requirements | 303 |
| 10.2.5.2 | Establish IPv6 Network Connectivity | 304 |
| 10.2.5.2.1 | Obtain Link-Local Address | 305 |
| 10.2.5.2.2 | Obtain default routers | 305 |
| 10.2.5.2.3 | Obtain IPv6 management address and other configuration parameters | 305 |
| 10.2.5.2.4 | Use of T1 and T2 Timers | 306 |
| 10.2.5.2.5 | CMTS Requirements | 307 |
| 10.2.5.3 | Alternate Provisioning Mode (APM) Operation | 307 |
| 10.2.5.4 | Dual-stack Provisioning Mode (DPM) | 308 |
| 10.2.5.5 | Establish Time of Day | 308 |
| 10.2.5.6 | Transfer Operational Parameters | 309 |
| 10.2.5.7 | Configuration File Processing | 310 |
| 10.2.5.8 | Post-registration Failures to Renew IP Addresses | 311 |
| 10.2.6 | Registration with the CMTS | 311 |
| 10.2.6.1 | Cable Modem Requirements | 311 |
| 10.2.6.2 | CMTS Requirements | 319 |
| 10.2.6.2.1 | Channel Assignment During Registration | 325 |
| 10.2.7 | Baseline Privacy Initialization | 327 |
| 10.2.8 | Service IDs During CM Initialization | 327 |
| 10.3 | Periodic Maintenance | 328 |
| 10.4 | Fault Detection and Recovery | 330 |
| 10.4.1 | CM Downstream Channel Interruptions | 331 |
| 10.4.2 | MAC Layer Error-Handling | 332 |
| 10.4.2.1 | Error Recovery During Pre-3.0 DOCSIS Fragmentation | 333 |
| 10.4.2.2 | Error Recovery During Segmentation with Segment Headers On | 333 |
| 10.4.3 | CM Status Report | 334 |
| 10.4.3.1 | Event Codes | 337 |
| 10.5 | DOCSIS Path Verification | 340 |

| | | |
|------------|---|-----|
| 10.5.1 | DPV Overview..... | 340 |
| 10.5.2 | DPV Reference Points | 340 |
| 10.5.3 | DPV Math..... | 342 |
| 10.5.4 | DPV Per Path Operation..... | 342 |
| 10.5.4.1 | DPV Ping | 343 |
| 10.5.5 | DPV Per Packet Operation | 343 |
| 11 | Dynamic Operations..... | 344 |
| 11.1 | Upstream Channel Descriptor Changes..... | 344 |
| 11.2 | Dynamic Service Flow Changes | 345 |
| 11.2.1 | Dynamic Service Flow State Transitions..... | 346 |
| 11.2.2 | Dynamic Service Addition..... | 354 |
| 11.2.2.1 | CM Initiated Dynamic Service Addition..... | 354 |
| 11.2.2.2 | CMTS Initiated Dynamic Service Addition..... | 355 |
| 11.2.2.3 | Dynamic Service Addition State Transition Diagrams | 356 |
| 11.2.3 | Dynamic Service Change..... | 364 |
| 11.2.3.1 | CM-Initiated Dynamic Service Change | 365 |
| 11.2.3.2 | CMTS-Initiated Dynamic Service Change..... | 365 |
| 11.2.3.3 | Dynamic Service Change State Transition Diagrams | 367 |
| 11.2.4 | Dynamic Service Deletion | 375 |
| 11.2.4.1 | CM Initiated Dynamic Service Deletion..... | 375 |
| 11.2.4.2 | CMTS Initiated Dynamic Service Deletion | 375 |
| 11.2.4.3 | Dynamic Service Deletion State Transition Diagrams..... | 376 |
| 11.3 | Pre-3.0 DOCSIS Upstream Channel Changes..... | 380 |
| 11.4 | Dynamic Downstream and/or Upstream Channel Changes | 383 |
| 11.4.1 | DCC General Operation..... | 383 |
| 11.4.1.1 | Derivation of T15 Timer..... | 385 |
| 11.4.1.2 | Initialization Technique | 386 |
| 11.4.1.2.1 | Initialization Technique Zero (0)..... | 386 |
| 11.4.1.2.2 | Initialization Technique One (1)..... | 387 |
| 11.4.1.2.3 | Initialization Technique Two (2)..... | 387 |
| 11.4.1.2.4 | Initialization Technique Three (3)..... | 387 |
| 11.4.1.2.5 | Initialization Technique Four (4)..... | 387 |
| 11.4.2 | DCC Exception Conditions..... | 388 |
| 11.4.3 | DCC State Transition Diagrams | 389 |
| 11.4.4 | DCC Performance..... | 396 |
| 11.5 | Dynamic Bonding Change (DBC)..... | 397 |
| 11.5.1 | DBC General Operation..... | 397 |
| 11.5.1.1 | Changes to the Receive Channel Set..... | 398 |
| 11.5.1.2 | Changes to a DSID | 399 |
| 11.5.1.2.1 | Changes to Resequencing Encodings | 399 |
| 11.5.1.2.2 | Changes to Multicast Encodings | 400 |
| 11.5.1.3 | Changes to the Security Association for encrypting downstream traffic | 402 |
| 11.5.1.4 | Changes to the Transmit Channel Set | 402 |
| 11.5.1.4.1 | Impact of TCS Changes on Periodic Ranging | 403 |
| 11.5.1.4.2 | Exception Conditions for TCS Changes | 403 |
| 11.5.1.5 | Changes to the Service Flow SID Cluster Assignments..... | 404 |
| 11.5.1.5.1 | Bandwidth Sufficiency | 405 |
| 11.5.1.6 | Initialization Technique | 405 |
| 11.5.1.6.1 | Initialization Technique One (1)..... | 405 |
| 11.5.1.6.2 | Initialization Technique Two (2)..... | 406 |
| 11.5.1.6.3 | Initialization Technique Three (3)..... | 406 |
| 11.5.1.6.4 | Initialization Technique Four (4)..... | 406 |
| 11.5.1.7 | Fragmentation of DBC-REQ Messages | 407 |
| 11.5.2 | Exception Conditions..... | 407 |
| 11.5.3 | DBC State Transition Diagrams | 408 |
| 11.5.3.1 | CMTS DBC State Transition Diagrams | 408 |
| 11.5.3.2 | CM DBC State Transition Diagrams | 413 |
| 11.6 | Autonomous Load Balancing | 418 |
| 11.6.1 | Load Balancing Groups | 419 |
| 11.6.1.1 | General Load Balancing Groups | 419 |
| 11.6.1.2 | Restricted Load Balancing Groups..... | 420 |

| | | |
|-----------------------------|---|------------|
| 11.6.2 | CMTS Load Balancing Operation | 420 |
| 11.6.3 | Multiple Channel Load Balancing | 421 |
| 11.6.4 | Initialization Techniques..... | 421 |
| 11.6.5 | Load Balancing Policies | 421 |
| 11.6.6 | Load Balancing Priorities | 422 |
| 11.6.7 | Load Balancing and Multicast | 422 |
| 11.6.8 | Externally-Directed Load Balancing | 423 |
| 12 | Supporting Future New Cable Modem Capabilities | 423 |
| 12.1 | Downloading Cable Modem Operating Software | 423 |
| 12.2 | Future Capabilities | 424 |
| Annex A (normative): | Well_know_addresses..... | 425 |
| A.1 | Addresses | 425 |
| A.1.1 | General MAC Addresses..... | 425 |
| A.1.2 | Well-known IPv6 Addresses | 425 |
| A.2 | MAC Service IDs | 425 |
| A.2.1 | All CMs and No CM Service IDs..... | 425 |
| A.2.2 | Well-Known Multicast Service IDs | 426 |
| A.2.3 | Priority Request Service IDs | 426 |
| A.3 | MPEG PID | 426 |
| Annex B (normative): | Parameters and Constants | 427 |
| Annex C (normative): | Common TLV Encodings..... | 430 |
| C.1 | Encodings for Configuration and MAC-Layer Messaging | 431 |
| C.1.1 | Configuration File and Registration Settings | 431 |
| C.1.1.1 | Downstream Frequency Configuration Setting..... | 431 |
| C.1.1.2 | Upstream Channel ID Configuration Setting..... | 432 |
| C.1.1.3 | Network Access Control Object..... | 432 |
| C.1.1.4 | DOCSIS 1.0 Class of Service Configuration Setting..... | 432 |
| C.1.1.4.1 | Class ID..... | 433 |
| C.1.1.4.2 | Maximum Downstream Rate Configuration Setting..... | 433 |
| C.1.1.4.3 | Maximum Upstream Rate Configuration Setting..... | 433 |
| C.1.1.4.4 | Upstream Channel Priority Configuration Setting | 434 |
| C.1.1.4.5 | Guaranteed Minimum Upstream Channel Data Rate Configuration Setting | 434 |
| C.1.1.4.6 | Maximum Upstream Channel Transmit Burst Configuration Setting | 434 |
| C.1.1.4.7 | Class-of-Service Privacy Enable | 434 |
| C.1.1.5 | CM Message Integrity Check (MIC) Configuration Setting..... | 435 |
| C.1.1.6 | CMTS Message Integrity Check (MIC) Configuration Setting | 435 |
| C.1.1.7 | Maximum Number of CPEs | 435 |
| C.1.1.8 | TFTP Server Timestamp..... | 435 |
| C.1.1.9 | TFTP Server Provisioned Modem IPv4 Address..... | 435 |
| C.1.1.10 | TFTP Server Provisioned Modem IPv6 Address..... | 436 |
| C.1.1.11 | Upstream Packet Classification Configuration Setting | 436 |
| C.1.1.12 | Downstream Packet Classification Configuration Setting | 436 |
| C.1.1.13 | Upstream Service Flow Encodings | 436 |
| C.1.1.14 | Downstream Service Flow Encodings | 436 |
| C.1.1.15 | Payload Header Suppression..... | 436 |
| C.1.1.16 | Maximum Number of Classifiers..... | 436 |
| C.1.1.17 | Privacy Enable | 437 |
| C.1.1.18 | DOCSIS Extension Field | 437 |
| C.1.1.18.1 | General Extension Information | 437 |
| C.1.1.18.1.1 | CM Load Balancing Policy ID | 438 |
| C.1.1.18.1.2 | CM Load Balancing Priority | 438 |
| C.1.1.18.1.3 | CM Load Balancing Group ID | 438 |
| C.1.1.18.1.4 | CM Ranging Class ID Extension..... | 438 |
| C.1.1.18.1.5 | L2VPN Encoding | 438 |
| C.1.1.18.1.6 | Extended CMTS MIC Configuration Setting | 439 |
| C.1.1.18.1.7 | Source Address Verification (SAV) Authorization Encoding | 440 |

| | | |
|---------------|---|-----|
| C.1.1.18.1.8 | Cable Modem Attribute Masks..... | 441 |
| C.1.1.18.1.9 | IP Multicast Join Authorization Encoding | 442 |
| C.1.1.18.1.10 | Service Type Identifier | 444 |
| C.1.1.18.2 | Vendor-Specific Information | 444 |
| C.1.1.19 | Subscriber Management TLVs | 445 |
| C.1.1.19.1 | Subscriber Management Control..... | 445 |
| C.1.1.19.2 | Subscriber Management CPE IPv4 List..... | 445 |
| C.1.1.19.3 | Subscriber Management CPE IPv6 Prefix List | 445 |
| C.1.1.19.4 | Subscriber Management Filter Groups..... | 445 |
| C.1.1.19.5 | Subscriber Management Control Max CPE IPv6 Addresses | 446 |
| C.1.1.19.6 | Subscriber Management CPE IPv6 List..... | 446 |
| C.1.1.20 | Enable 2.0 Mode..... | 446 |
| C.1.1.21 | Enable Test Modes..... | 446 |
| C.1.1.22 | Downstream Channel List | 447 |
| C.1.1.22.1 | Single Downstream Channel..... | 447 |
| C.1.1.22.1.1 | Single Downstream Channel Timeout..... | 448 |
| C.1.1.22.1.2 | Single Downstream Channel Frequency | 448 |
| C.1.1.22.2 | Downstream Frequency Range | 448 |
| C.1.1.22.2.1 | Downstream Frequency Range Timeout | 448 |
| C.1.1.22.2.2 | Downstream Frequency Range Start | 448 |
| C.1.1.22.2.3 | Downstream Frequency Range End | 449 |
| C.1.1.22.2.4 | Downstream Frequency Range Step Size..... | 449 |
| C.1.1.22.3 | Default Scanning..... | 449 |
| C.1.1.22.4 | Examples Illustrating Usage of the Downstream Channel List..... | 449 |
| C.1.1.23 | Static Multicast MAC Address | 450 |
| C.1.1.24 | Downstream Unencrypted Traffic (DUT) Filtering Encoding..... | 450 |
| C.1.1.25 | Channel Assignment Configuration Settings..... | 451 |
| C.1.1.25.1 | Transmit Channel Assignment Configuration Setting..... | 451 |
| C.1.1.25.2 | Receive Channel Assignment Configuration Setting..... | 451 |
| C.1.1.26 | Upstream Drop Classifier Group ID | 451 |
| C.1.1.27 | CMTS Static Multicast Session Encoding | 451 |
| C.1.1.27.1 | Static Multicast Group Encoding <small>SIST EN 302 878-4 V1.1.1:2012</small> | 452 |
| C.1.1.27.2 | Static Multicast Source Encoding <small>http://standards.etsi.org/standards/sist/a4212e38-73b1-4d51-93b2-000000000000/sist-en-302-878-4-v1-1-2012</small> | 452 |
| C.1.1.27.3 | Static Multicast CMIM Encoding <small>http://standards.etsi.org/standards/sist/a4212e38-73b1-4d51-93b2-000000000000/sist-en-302-878-4-v1-1-2012</small> | 452 |
| C.1.2 | Configuration-File-Specific Settings | 452 |
| C.1.2.1 | End-of-Data Marker..... | 452 |
| C.1.2.2 | Pad Configuration Setting | 452 |
| C.1.2.3 | Software Upgrade Filename | 453 |
| C.1.2.4 | SNMP Write-Access Control..... | 453 |
| C.1.2.5 | SNMP MIB Object | 453 |
| C.1.2.6 | CPE Ethernet MAC Address | 454 |
| C.1.2.7 | Software Upgrade IPv4 TFTP Server | 454 |
| C.1.2.8 | Software Upgrade IPv6 TFTP Server | 454 |
| C.1.2.9 | SnmpV3 Kickstart Value | 454 |
| C.1.2.9.1 | SnmpV3 Kickstart Security Name | 454 |
| C.1.2.9.2 | SnmpV3 Kickstart Manager Public Number..... | 455 |
| C.1.2.10 | Manufacturer Code Verification Certificate | 455 |
| C.1.2.11 | Co-signer Code Verification Certificate | 455 |
| C.1.2.12 | SNMPv3 Notification Receiver | 455 |
| C.1.2.12.1 | SNMPv3 Notification Receiver IPv4 Address..... | 455 |
| C.1.2.12.2 | SNMPv3 Notification Receiver UDP Port Number..... | 456 |
| C.1.2.12.3 | SNMPv3 Notification Receiver Trap Type..... | 456 |
| C.1.2.12.4 | SNMPv3 Notification Receiver Timeout..... | 456 |
| C.1.2.12.5 | SNMPv3 Notification Receiver Retries | 456 |
| C.1.2.12.6 | SNMPv3 Notification Receiver Filtering Parameters | 456 |
| C.1.2.12.7 | SNMPv3 Notification Receiver Security Name | 456 |
| C.1.2.12.8 | SNMPv3 Notification Receiver IPv6 Address | 457 |
| C.1.2.13 | SNMPv1v2c Coexistence Configuration | 457 |
| C.1.2.13.1 | SNMPv1v2c Community Name..... | 457 |
| C.1.2.13.2 | SNMPv1v2c Transport Address Access | 457 |
| C.1.2.13.2.1 | SNMPv1v2c Transport Address | 457 |
| C.1.2.13.2.2 | SNMPv1v2c Transport Address Mask | 458 |

| | | |
|------------|---|-----|
| C.1.2.13.3 | SNMPv1v2c Access View Type | 458 |
| C.1.2.13.4 | SNMPv1v2c Access View Name..... | 458 |
| C.1.2.14 | SNMPv3 Access View Configuration | 458 |
| C.1.2.14.1 | SNMPv3 Access View Name | 459 |
| C.1.2.14.2 | SNMPv3 Access View Subtree..... | 459 |
| C.1.2.14.3 | SNMPv3 Access View Mask | 459 |
| C.1.2.14.4 | SNMPv3 Access View Type..... | 459 |
| C.1.2.15 | SNMP CPE Access Control..... | 459 |
| C.1.2.16 | Management Event Control Encoding | 460 |
| C.1.3 | Registration-Request/Response-Specific Encodings..... | 460 |
| C.1.3.1 | Modem Capabilities Encoding..... | 460 |
| C.1.3.1.1 | Concatenation Support | 460 |
| C.1.3.1.2 | DOCSIS Version..... | 460 |
| C.1.3.1.3 | Fragmentation Support..... | 461 |
| C.1.3.1.4 | Payload Header Suppression Support | 461 |
| C.1.3.1.5 | IGMP Support..... | 461 |
| C.1.3.1.6 | Privacy Support..... | 461 |
| C.1.3.1.7 | Downstream SAID Support | 461 |
| C.1.3.1.8 | Upstream Service Flow Support | 461 |
| C.1.3.1.9 | Optional Filtering Support | 462 |
| C.1.3.1.10 | Transmit Pre-Equalizer Taps per Modulation Interval..... | 462 |
| C.1.3.1.11 | Number of Transmit Equalizer Taps..... | 462 |
| C.1.3.1.12 | DCC Support..... | 462 |
| C.1.3.1.13 | IP Filters Support | 463 |
| C.1.3.1.14 | LLC Filters Support | 463 |
| C.1.3.1.15 | Expanded Unicast SID Space..... | 463 |
| C.1.3.1.16 | Ranging Hold Off Support..... | 463 |
| C.1.3.1.17 | L2VPN Capability..... | 464 |
| C.1.3.1.18 | L2VPN eSAFE Host Capability | 464 |
| C.1.3.1.19 | Downstream Unencrypted Traffic (DUT) Filtering | 464 |
| C.1.3.1.20 | Upstream Frequency Range Support..... | 464 |
| C.1.3.1.21 | Upstream Symbol Rate Support SIST EN 302.878-4 V1.1.1:2012 | 464 |
| C.1.3.1.22 | Selectable Active Code Mode 2 Support SIST EN 302.878-4 V1.1.1:2012 | 465 |
| C.1.3.1.23 | Code Hopping Mode 2 Support SIST EN 302.878-4 V1.1.1:2012 | 465 |
| C.1.3.1.24 | Multiple Transmit Channel Support..... | 465 |
| C.1.3.1.25 | 5,12 Msps UpstreamTransmit Channel Support | 466 |
| C.1.3.1.26 | 2.56 Msps Upstream Transmit Channel Support | 466 |
| C.1.3.1.27 | Total SID Cluster Support..... | 466 |
| C.1.3.1.28 | SID Clusters per Service Flow Support | 466 |
| C.1.3.1.29 | Multiple Receive Channel Support | 466 |
| C.1.3.1.30 | Total Downstream Service ID (DSID) Support | 467 |
| C.1.3.1.31 | Resequencing Downstream Service ID (DSID) Support | 467 |
| C.1.3.1.32 | Multicast Downstream Service ID (DSID) Support..... | 467 |
| C.1.3.1.33 | Multicast DSID Forwarding..... | 467 |
| C.1.3.1.34 | Frame Control Type Forwarding Capability | 468 |
| C.1.3.1.35 | DPV Capability | 468 |
| C.1.3.1.36 | Unsolicited Grant Service/Upstream Service Flow Support | 468 |
| C.1.3.1.37 | MAP and UCD Receipt Support | 468 |
| C.1.3.1.38 | Upstream Drop Classifier Support | 469 |
| C.1.3.1.39 | IPv6 Support | 469 |
| C.1.3.1.40 | Extended Upstream Transmit Power Capability | 469 |
| C.1.3.2 | Vendor ID Encoding..... | 470 |
| C.1.3.3 | Modem IP Address | 470 |
| C.1.3.4 | Service(s) Not Available Response | 470 |
| C.1.3.5 | Vendor-Specific Capabilities | 470 |
| C.1.3.6 | CM Initialization Reason | 471 |
| C.1.4 | Dynamic-Message-Specific Encodings | 471 |
| C.1.4.1 | HMAC-Digest..... | 471 |
| C.1.4.2 | Authorization Block..... | 472 |
| C.1.4.3 | Key Sequence Number | 472 |
| C.1.5 | Registration, Dynamic Service and Dynamic Bonding Settings | 472 |
| C.1.5.1 | Transmit Channel Configuration (TCC)..... | 472 |